



Modelling the impact of retention-detention units on sewer surcharge and peak and annual runoff reduction

Locatelli, Luca; Søren, Gabriel; Mark, Ole; Mikkelsen, Peter Steen; Arnbjerg-Nielsen, Karsten; Taylor, Heidi; Bockhorn, Britta; Larsen, Hauge; Just Kjølby, Morten; Steensen Blicher, Anne

Total number of authors:

11

Published in:

13th International Conference on Urban Drainage (ICUD 2014)

Publication date:

2014

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Locatelli, L., Søren, G., Mark, O., Mikkelsen, P. S., Arnbjerg-Nielsen, K., Taylor, H., Bockhorn, B., Larsen, H., Just Kjølby, M., Steensen Blicher, A., & Binning, P. J. (2014). Modelling the impact of retention-detention units on sewer surcharge and peak and annual runoff reduction. In *13th International Conference on Urban Drainage (ICUD 2014): Abstract Book* (pp. 16). Article 2518343 IWA Publishing.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Oral Presentations

flood problems in major cities can be eliminated. The study area, Sungai Kedah ungauged catchment, is located at the northern region of Malaysia. The Kota Setar subcatchment is located downstream of Sungai Kedah with the newly completed development of a control barrage at the upper Kota Setar. This paper describes the analyses of the infiltration curves at Kota Setar. The resulting infiltration maps have been developed based on the infiltration capacities.

Keywords

Sungai Kedah ungauged catchment, type of soil, infiltration curve, infiltration map

2518343

Modelling the Impact of Retention-Detention Units on Sewer Surcharge and Peak and Annual Runoff Reduction

Luca LOCATELLI¹, Søren GABRIEL², Ole MARK³, Peter Steen MIKKELSEN¹, Karsten ARNBJERG-NIELSEN¹, Heidi TAYLOR², Britta BOCKHORN⁴, Hauge LARSEN², Morten Just KJØLBY³, Anne Steensen BLICHER², Philip John BINNING¹

- ¹Technical University of Denmark, 2800 Kgs Lyngby, Denmark
- ²Orbicon, 4000 Roskilde, Denmark
- ³Danish Hydraulic Institute, 2970 Hørsholm, Denmark
- ⁴University of Copenhagen, 1017 Copenhagen, Denmark

*Corresponding author

Email: lulo@env.dtu.dk

Abstract

Stormwater management using water-sensitive urban design (WSUD) is expected to be part of future drainage systems. The novelty of this paper is in the combination of local retention units, such as soakaways, with subsurface detention units. Soakaways aim at reducing (by infiltration) peak and volume stormwater runoff; however, significantly high retention volumes are required for peak reduction. Peak runoff is therefore handled by detention units coupled to soakaways. This article aims at modelling the impact of retrofitting retention–detention units at a small catchment scale.

The impact of retention-detention units on sewer surcharge was simulated for a small catchment in Copenhagen (Denmark) for a single design event. The software Mike Urban with an integrated soakaway model was used. Results showed that a retention–detention unit of 3.2 m³/100 m² (volume/impervious area) could avoid sewer surcharge during a 10-year design event. The initial water content for the single event simulation and annual water balance of storage units was estimated by 22 years of continuous simulation and the effect of several retention-detention volume combinations on peak and annual runoff reduction was determined. Results show that for a given storage volume, combining detention and retention improve the overall performance.

Keywords

Soakaways, water-sensitive urban design, stormwater runoff, modelling, detention units

2518643

Simulation of Green Roof Impact at Basin Scale by Using a Distributed Rainfall-Runoff Model

Pierre-Antoine VERSINI^{*}, Auguste GIRES, Jean-Baptiste ABBES, Agathe GIANGOLA-MURZYN, Ioulia TCHINGUIRINSKAIA, Daniel SCHERTZER

- Laboratoire Eau Environnement et Systèmes Urbains—Ecole des Ponts et Chaussées, 77455 Champs-sur-Marne, France

*Corresponding author

Email: pierre-antoine.versini@leesu.enpc.fr

Abstract

Currently widespread in new urban projects, green roofs have shown a positive impact on urban runoff at the building scale, that is, decreased and slow peak discharge and decreases runoff volume. The aim was to study the possible impact of green roof at the catchment scale, more compatible with stormwater management issues. For this purpose, a distributed rainfall-runoff model (Multi-Hydro) devoted to urban environment and able to simulate the hydrological behaviour of green roof has been used to assess the green roof impact at such a scale.

It has been applied on an urban catchment (Loup basin located in the Seine-Saint-Denis county, East of Paris, France) where most of the building roofs are flat and assumed to easily accept the implementation of green roof. Catchment responses to several rainfall events covering a wide range of meteorological situation have been simulated. The simulation results show that green roof can significantly reduce runoff volume and the magnitude of peak discharge (up to 80%) depending on the rainfall event and the initial saturation of the substrate.

Keywords

Green roof, source control, hydrological modelling, multi-hydro

2518795

A Study on Hydrograph Design in Ungauged Basins Using Digital Elevation Models

Joan Nathalie SUÁREZ HINCAPIÉ^{1,*}, Victor Mauricio ARISTIZAL MURILLO^{1,**}, Jorge Julián VÉLEZ UPEGUI^{1,***}

- ¹National University of Colombia, Manizales, Colombia
- ²Institute of Environmental Studies — IDEA

Corresponding authors

*Email: jnsuarez@unal.edu.co

**Email: vmaristizabalm@unal.edu.co

***Email: jjvelezu@unal.edu.co

Abstract

A hydrologic design of hydraulic structures in tropical Andean zones is normally affected by the challenge of the estimation of discharges in ungauged basins or basins with short time series information. Therefore, a synthetic unit hydrograph, empirical approaches and regressions among other gross methodologies are widely used to estimate the transformation of precipitation into runoff. The main inconvenience of all these methodologies is that they were created for other latitudes, climates, soil characteristics and geomorphometry, which are quite different to the mountain areas located in tropical Andes where non-linearity is highly present. This paper tackles this problem using the promising tools available in the geographical information systems (GISs). The case study area is located in Manizales city of Colombia (South America), where three small basins were studied: the San Luis creek, the Olivares-El Popal creek and the Manizales-Tesorito creek. All of them have been monitored with a temporal resolution of 5 minutes since 5 to 10 years ago, so the flow levels of main events were extracted and the dimensionless observed unit hydrograph (OUH) for each basin was obtained. The OUH was then compared with the unit hydrograph extracted from DEM through the width function (WF) and topographic index (TI) strategies.

Keywords

Hydrological design, urban drainage, unit hydrograph, GIS, DEM

2528455

Identifying Changes in Rainfall Extremes in South Australia

Mohammad KAMRUZZAMAN^{1,*}, Simon BEECHAM¹, Andrew V. METCALFE²

- ¹Centre for Water Management and Reuse, School of Natural and Built Environments, University of South Australia, Australia