

Utilization of CO, fixating bacterium Actinobacillus succinogenes 130Z for simultaneous biogas upgrading and bio-succinic acid production

Gunnarsson, Ingólfur Bragi; Alvarado-Morales, Merlin; Angelidaki, Irini

Published in: Environmental Science and Technology

Link to article, DOI: 10.1021/es504000h

Publication date: 2014

Document Version Publisher's PDF, also known as Version of record

Link back to DTU Orbit

Citation (APA):

Gunnarsson, Í. B., Alvarado-Morales, M., & Angelidaki, I. (2014). Utilization of CO fixating bacterium Actinobacillus succinogenes 130Z for simultaneous biogas upgrading and bio-succinic acid production. *Environmental Science and Technology*, *48*(20), 12464-12468. https://doi.org/10.1021/es504000h

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Environmental Science & Technology

Utilization of CO₂ Fixating Bacterium *Actinobacillus succinogenes* 130Z for Simultaneous Biogas Upgrading and Biosuccinic Acid Production

Ingólfur B. Gunnarsson, Merlin Alvarado-Morales, and Irini Angelidaki*

Department of Environmental Engineering, Technical University of Denmark, DK-2800 Kongens Lyngby, Denmark

Supporting Information



ABSTRACT: Biogas is an attractive renewable energy carrier. However, it contains CO_2 which limits its use for certain applications. Here we report a novel approach for removing CO_2 from biogas and capturing it as a biochemical through a biological process. This approach entails converting CO_2 into biosuccinic acid using the bacterial strain *Actinobacillus succinogenes* 130Z, and simultaneously producing high-purity CH_4 (> 95%). Results showed that when pressure during fermentation was increased from 101.325 to 140 kPa, higher CO_2 solubility was achieved, thereby positively affecting final succinic acid yield and titer, CO_2 consumption rate, and CH_4 purity. When using biogas as the only CO_2 source at 140 kPa, the CO_2 consumption rate corresponded to 2.59 L CO_2 L⁻¹ d⁻¹ with a final succinic acid titer of 14.4 g L⁻¹. Under this pressure condition, the highest succinic acid yield and biogas quality reached corresponded to 0.635 g g⁻¹ and 95.4% (v v⁻¹) CH_4 content, respectively, after 24 h fermentation. This work represents the first successful attempt to develop a system capable of upgrading biogas to vehicle fuel/ gas grid quality and simultaneously produce biosuccinic acid, a valuable building block with large market potential in the near term.

■ INTRODUCTION

The EU Renewable Energy Source (RES) directive states that EU members should increase RES share of final energy consumption to an EU average of 20% and reduce CO_2 emissions 15-30% by 2020. With the EU commission trying to implement its emissions trading system (EU ETS),¹ firms are likely to be charged a carbon tax of $\in 10$ per metric tonne of CO₂ emissions by the end of 2014 (predicted to reach €13 by the end of 2015).² In the context of the EU directive framework, increased biofuel production and consumption should be complemented by increased production and use of biobased chemicals and should be preferred over their petrochemical derived equivalents.³ Gaseous biofuels, mainly biogas, are increasingly becoming an important renewable energy source for combined heat and power (CHP) generation, while their role as transport fuel is also expected to increase in the coming years.⁴ Biogas, produced through anaerobic digestion of organic material, is generally composed of 50-75% CH₄ and 25-50% CO₂. Depending on the final use, different processing steps are necessary. For instance, where it is important to have high energy

content in the gas, as in vehicle fuel or for grid injection, the CH_4 needs to be purified (upgrading).⁵ By removing CO_2 from the biogas in the upgrading process the energy content of the gas increases. Current upgrading technologies such as absorption make use of the physical/chemical properties of CO_2 where it is captured from the biogas (thereby increasing the CH_4 purity) and then released into the atmosphere, contributing to the global warming effect.⁵ The necessity for reducing CO_2 emissions has never been greater, as recently the amount of CO_2 in earth's atmosphere was observed to exceed 400 ppm for the first time since measurements started 55 years ago,⁶ also the fact that current technologies for CO_2 capturing and storage are costly, therefore processes that use CO_2 as a raw material are likely to become increasingly important.⁷ An example of such a process is biological production of succinic acid through bacterial

Received:	August 15, 2014
Revised:	September 23, 2014
Accepted:	October 2, 2014
Published:	October 2, 2014

Article



Figure 1. Experimental setup.

fermentation, where CO₂ fixation is performed by Actinobacillus succinogenes or any other bacterium capable of producing succinic acid.⁸ Succinic acid is a four-carbon diacid with the chemical formula $C_4H_6O_4$ and is a precursor in the chemical synthesis of numerous commodities in agricultural, food, chemical, and pharmaceutical industries (e.g., solvents (1,4-butanediol, tetrahydrofuran, 2-pyrrolidinone, and gamma-butyrolactone) and biodegradable polymers (polybutylene succinate (PBS) and polyamides)).^{8,9} Producing succinic acid biologically through fermentation has the advantage of consuming 1 mol of CO₂ per 1 mol of succinic acid produced, opposed to producing it chemically through hydrogenation of maleic acid as most of it is currently produced.¹⁰ Substantial CO₂ emission savings in the range of 4.5-5 t per t biosuccinic acid produced have been estimated compared to emissions of petrochemical-derived succinic acid, therefore, it is evident that biosuccinic acid production could contribute to the abatement of CO₂ emissions.¹¹ A number of bacterial strains are able to produce succinic acid through fermentation, including Actinobacillus succinogenes,¹² Mannheimia succiniciproducens,¹³ Anaerobiospirillum succiniciproducens,¹⁴ Corynebacterium glutamicum,¹⁵ and recombinant Escherichia coli.¹⁶ A. succinogenes is recognized as one of the most promising microorganisms utilized for biosuccinic acid production, as it is a facultative anaerobe with high tolerance to initial sugar concentrations (≤ 158 g L⁻¹ Dglucose), but also tolerates high levels of succinic acid (> 70 g L^{-1}).^{12,17} Additionally A. succinogenes has a broad preference of carbon sources such as glucose, xylose, arabinose, galactose, maltose, fructose, sucrose, cellobiose, lactose, mannitol, arabitol, sorbitol, and glycerol. This makes it possible to utilize a large variety of residual biomasses, such as carbohydrate-rich wastes or crude glycerol, a byproduct from biodiesel industry, for succinic acid production.¹⁸⁻²² The fermentation end products of A. *succinogenes* are succinic acid as the main metabolite, in addition to formate, acetate, and ethanol.^{12,23} The supply of CO_2 is a key factor in the production of succinic acid by A. succinogenes. A higher concentration of dissolved CO₂ in the fermentation broth could result in increasing the ratio of succinic acid to the other metabolites, the ratio of carbon recovery, and the succinic acid yield.²⁴ When using biogas as the only CO₂ source, the maximum dissolved CO₂ concentration in the culture broth corresponds to its solubility at the corresponding CO₂ partial pressure in the biogas $(25-50\% (v v^{-1}))$. However, one way to make CO₂ more available to the bacterium in the culture broth is to increase its solubility by means of increasing its partial pressure. This can be

predicted by means of Henry's law. More complex models can also be used; the choice of model will strongly depend on what system operation conditions are imposed. A mathematical model was used together with experimental measurements to predict the dissolved CO_2 in culture broth. The model and parameters used in this work were retrieved from an earlier study unless otherwise stated (see Supporting Information (SI)).²⁵ In this study we demonstrate a new biogas upgrading technology, which makes use of bacterial fermentation to simultaneously produce high-purity CH_4 and biosuccinic acid. The benefits of integrating both processes—succinic acid production via bacterial fermentation and biogas upgrading—would potentially overcome the cost of CO_2 capture and storage and the cost of biogas upgrading, thereby promoting biobased economy.

EXPERIMENTAL SECTION

Chemicals and Gases. All chemicals used in this study were of analytical grade and purchased from Sigma-Aldrich ApS (Brøndby, Denmark); gases were supplied by AGA A/S (Copenhagen, Denmark).

System Setup and Operation. Two identical 3-L bioreactors (Sartorius BIOSTAT Aplus, Germany) with an initial liquid working volume of 1.5 L were used. The bioreactors were equipped with EASYFERM PLUS K8 200 pH probes (Hamilton Bonaduz AG, Switzerland), temperature probes (Sartorius, Germany) and InPro 5000i dissolved CO₂ sensors (Mettler Toledo, Switzerland). Flow rate of gas mixtures was controlled through a peristaltic pump (Watson-Marlow, United Kingdom). For monitoring and controlling pressure inside bioreactors a pressure gauge (Cewai, Italy) was mounted with a relief valve (Hy-Lok, USA) set to the experimental pressure. Gas-liquid ratio is defined in this study as initial volume of gas per liquid working volume. Experiments were conducted using different gas-liquid ratios (8.3:1 and 5:1). As shown in Figure 1 the gas was recirculated through the system during fermentation, allowing changes in biogas composition to be observed. Under anaerobic conditions, the biogas was injected through the sparger at the bottom of the reactor. As the biogas bubbles go through the reactor some of the gaseous CO₂ gets solubilized in the culture broth. As fermentation progresses, CO₂ decreases in the liquid phase (due to consumption by bacterial fermentation) which, according to Henry's law, forces more CO₂ to the gas phase to be dissolved into the culture broth. In this way the CH₄ content of the biogas is increased.

Environmental Science & Technology

Microorganisms, Medium, and Succinic Fermentation. The strain of Actinobacillus succinogenes 130Z (DSM 22257) was obtained from DSMZ. The culture stock was stored in glycerol at -80 °C until used. Seed culture medium was composed of (g/L) glucose (10.0), yeast extract (5.0), NaHCO₃ (10.0), NaH₂PO₄. $2H_2O$ (9.6), and $K_2HPO_4 \cdot 3H_2O$ (20.3). Medium was sterilized at 121 °C for 20 min. Seed culture was cultivated at 37 °C and 150 rpm in 50-mL sealed anaerobic bottles containing 30 mL of medium and inoculated with 1 mL of -80 glycerol stock culture. Biogas upgrading and succinic acid production batch experiments were conducted in duplicates. Fermentation experiments were conducted using biogas (60% CH₄, 40% CO₂) or 100% CO_2 as only source of CO_2 for succinic acid production. Fermentations were carried out at either 101.325 or 160 kPa pressure. Experimental medium for biogas upgrading and fermentation was composed of (g/L) yeast extract (10.0), K₂HPO₄ (3.0), MgCl₂ (0.2), CaCl₂ (0.2), and NaCl (1.0). Medium was sterilized at 121 °C for 20 min. Sterile glucose solution was added separately to the bioreactors to get a glucose concentration of 30-32 g L^{-1} . All batch fermentations in 3-L bioreactors were carried out at 37 °C, pH 6.75, and 200 rpm for 24 h, and inoculated with 5% (v v^{-1}) of exponentially growing inoculum. Prior to start of fermentation, pH was adjusted to 6.75 using 50% (w v⁻¹) phosphoric acid, and 0.05 mL of sterile Antifoam 204 (Sigma-Aldrich) was added. NaOH (8 M) was added automatically to maintain the pH at 6.75 during fermentation. N₂ gas was used in all cases to create anaerobic conditions prior to start of fermentation.

Analytical Methods. Dissolved CO₂ in fermentation broth was determined experimentally using an InPro 5000i (Mettler Toledo, Switzerland) CO₂ sensor controlled by M400 transmitter (Mettler Toledo, Switzerland). Gas containing 100, 40, and 20% (v/v) CO_2 was used to determine the dissolved CO_2 in fermentation broth at 101.325, 120, and 140 kPa pressure with temperature and pH fixed at 37 °C and 6.8, respectively. Cell growth was monitored by measuring the optical density at 660 $nm(OD_{660})$ using a spectrophotometer (Jenway Buch and Holm A/S 64050UV/vis). At OD₆₆₀ of 1.0, A. succinogenes 130Z has a concentration of 0.626 g dry cell weight (DCW) L^{-1} (data no shown). Glucose, succinic acid, lactic acid, formic acid, acetic acid, and ethanol were all detected and quantified using highperformance liquid chromatography (HPLC). The HPLC (Agilent 1100 series) had a refractive index detector (detection of sugars, VFAs, and ethanol) and a Bio-Rad Aminex HPX-87H column (300 mm \times 7.8 mm) with 4 mM H₂SO₄ as an eluent at a flow rate of 0.6 mL min⁻¹ with column oven temperature set to 63.5 °C. To protect the HPX-87H column from contamination and foreign particles a guard column was fitted to the system. The yield of succinic acid, expressed as a percentage, was defined as the amount of final succinic acid produced from 1 g of reduced sugar consumed.

Model Description and Calculation. From low to moderate pressures at supercritical temperature, the solubility of a gas (e.g., CO_2) in a pure solvent (e.g., water) can be calculated by Henry's law:

$$p_{\rm CO_2} = H_{\rm o}C_{\rm CO_2}$$

where p_{CO_2} is the CO₂ partial pressure in a gas mixture (kPa), H_0 is the Henry's constant for CO₂ in a pure solvent (kPa L mol⁻¹), and C_{CO_2} is the concentration of dissolved CO₂ in the liquid phase (mol L⁻¹). However, in a culture broth different kinds of organic substances and salts are always present which affects the

solubility of CO_2 . The effect of pH, temperature, and the organic substances and salts on CO_2 solubility has been taken into account through an empirical model for further predictions. For details see the Supporting Information.

Statistical Analysis. An ANOVA analysis followed by Fisher's Least Significant Difference test (LSD, p < 0.05) was used to evaluate if any significant differences were observed between model predictions and experimental measurements. All statistical analyses mentioned above were carried out using OriginPro software, version 9.0.0 (OriginLab Corporation, Northampton, MA).

RESULTS AND DISCUSSION

Proof of Concept. In this experiment, biogas (60% CH_4 , 40% CO_2) was used as the only source of CO_2 for succinic acid fermentation (Figure 2a) using a gas-liquid ratio of 8.3:1. At



Figure 2. Fermentation (a) and biogas upgrading (b) profiles of *A. succinogenes* at 101.325 kPa and gas-liquid ratio of 8.3:1. Error bars represent the standard deviation of duplicates.

atmospheric pressure (CO₂ partial pressure of 40 kPa), the maximum solubility of CO₂ corresponds to 9.15 mM. As shown in Figure 2b at 101.325 kPa, the final biogas composition at the end of the fermentation corresponded to 76.4% CH₄, 24.6% CO₂. The CO₂ partial pressure lessens as CO₂ is consumed during the course of the fermentation. This resulted in a decrease of the solubility of CO₂ (5.4 mM) in the culture broth at the end of the fermentation. In terms of succinic acid production, the final titer was 12.85 g L⁻¹ with a yield of 0.60 g g⁻¹. When fermentation was performed at 101.325 kPa, the overall CO₂ consumption rate during 24 h fermentation corresponded to 1.35 L CO₂ L⁻¹ d⁻¹. Succinic acid yield and productivity were in agreement with those reported in previous studies.²⁶ To our

	CO ₂ partial pressure (kPa)						
	biogas (40% CO ₂ /60% CH ₄)				CO ₂ gas		
	40	56	40	56	101.325	140	
CO ₂ solubility (mM)	9.15	16.7	9.15	16.7	23.16	31.97	
gas—liquid ratio	8.3:1	8.3:1	5:1	5:1			
CO_2 fixation rate (L CO_2 L ⁻¹ d ⁻¹)	1.35	2.59	1.52	1.77			
final CH_4 content in biogas (% v v ⁻¹)	76.4	91.1	85.2	95.4			
succinic acid yield (g g^{-1})	0.60	0.62	0.56	0.63	0.62	0.69	
succinic acid productivity (g $L^{-1} h^{-1}$)	0.53	0.60	0.53	0.56	0.73	0.80	
succinic acid titer (g $L^{-1} \pm SD$)	12.85 ± 0.01	14.39 ± 0.09	12.74 ± 0.22	13.53 ± 0.09	17.53 ± 0.22	19.28 ± 0.24	
acetic acid titer (g $L^{-1} \pm SD$)	5.64 ± 0.09	5.10 ± 0.04	6.47 ± 0.45	5.61 ± 0.50	6.13 ± 0.14	5.58 ± 0.13	
formic acid titer (g $L^{-1} \pm SD$)	3.86 ± 0.22	3.55 ± 0.02	5.16 ± 0.34	4.35 ± 0.48	4.32 ± 0.27	3.93 ± 0.24	

knowledge, this is the first study reporting simultaneous biogas upgrading and succinic acid production by means of this novel concept.

Improving Process Performance. It was investigated if increasing pressure in the system (therefore increasing CO_2) solubility) could significantly increase final CH4 content in biogas. To study the effect of pressure, the gas-liquid ratio of the system was first kept constant (8.3:1). When total pressure was increased to 140 kPa (CO₂ partial pressure of 56 kPa) the final methane content in biogas was increased to fixation, thereby increasing CH₄ purity in biogas and favorably affecting the succinic acid production. Gas-liquid ratio in the system was reduced to 5:1 in order to investigate its effect on the process performance, especially if CH₄ content could be increased further. At the end of fermentation, CH₄ content was increased from 85.2% at 101.325 kPa to 95.4% at 140 kPa (see Table 1). When comparing the overall CO₂ consumption rate during 24 h fermentation, a 16.4% increase (from 1.52 to 1.77 L CO₂ L⁻¹ d^{-1}) was achieved. The final succinic acid titer increased by 6.2% (p < 0.05) from 101.325 to 140 kPa (see Table 1).

Additionally, there was a positive effect on the succinic acid yield when pressure was increased, improving it by 13.8% (from 0.56 to 0.63 g g⁻¹). Increased pressure appears to favor succinic acid metabolism in relation to other fermentation products. Increase of the CO₂ pressure from 101.325 to 140 kPa resulted in decrease of the final formic acid titer by 15.7% (p < 0.05) compared to that at 101.325 kPa. However, in this case the final acetic acid titer was not found to be significantly different. By reaching 95.4% CH₄ content, the system (gas–liquid ratio 5:1) was able to upgrade the biogas (60% CH₄, 40% CO₂) to a purity similar to that of commercial biogas upgrading technologies (95–98% CH₄ content).⁵ Although countries have different standards for purity of natural gas used for gas grid injection and vehicle fuel, purity of 95–98% CH₄ is a common target.²⁷

System Performance at Different CO₂ Partial Pressures. One of the key factors in succinic acid fermentation is the availability of CO₂.^{25,26} Many studies focusing on succinic acid production have increased the CO₂ availability by addition of salts such as MgCO₃, NaHCO₃, or CaCO₃. Through addition of such salts the CO₂ solubility is greatly increased.²⁵ Nevertheless, from an industrial perspective the addition of these salts will likely increase the cost of the fermentation process and certainly any solid residue left will increase the cost of downstream processing. Many studies have investigated the use of CO₂ gas in succinic acid production up to 101.325 kPa, while few or no studies have investigated the effect of raising the total pressure (> 101.325 kPa) in the system. For this reason, experiments were conducted using CO₂ gas as the only CO₂ source to study the effect of increasing pressure in the system. The first approach was to predict the effect of increasing pressure in the system (from 101.325 to 140 kPa) by means of an empirical model (SI) together with our experimental conditions (pH, temperature, and culture broth composition). Model prediction showed an increase of 38.1% in CO₂ solubility, which was confirmed later by experimental determination (Figure 3).

Article



Figure 3. Calculated dissolved $CO_2(-)$ and $CH_4(--)$ concentrations in culture broth as a function of CO_2 and CH_4 partial pressure using the model and dissolved CO_2 concentration in the culture broth determined experimentally at different CO_2 partial pressures (\blacklozenge).

As observed in Table 1, the increment of pressure favorably affected the succinic acid production. Comparing the two experimental conditions, the succinic acid titer was observed to be 10.0% higher (p < 0.05) at 140 kPa compared to 101.325 kPa. At 140 kPa the succinic acid yield was calculated to be 0.69 g g⁻¹, which represents an increase of 11.5%. Additionally the productivity at 24 h increased from 0.73 to 0.80 g L⁻¹ h⁻¹. When comparing results obtained at 101.325 kPa to similar studies, the yield and productivity were 12.7% and 35.4% lower.²⁶ However, these differences are mainly due to the higher initial glucose concentration used in that study.²⁶ The final acetic and formic acid titers after 24 h were found not to be significantly different (p < 0.05) when comparing both pressure conditions.

In summary, the system described in this work was able to simultaneously upgrade biogas to CH_4 purity of 95.4% and produce succinic acid. To the best of our knowledge this study represents the first investigation of biosuccinic acid production

Environmental Science & Technology

along with CH_4 purification through utilization of CO_2 fixating bacterium *A. succinogenes* 130Z. By increasing pressure in the system, higher CO_2 solubility was achieved, thereby positively affecting succinic acid yield and titer, CO_2 consumption rate, and CH_4 purity. This work serves as a state-of-the-art study about the integration of production of a biobased bulk chemical and purification of a gaseous energy carrier. Further studies involving the optimization of the system are necessary to fully demonstrate its economic feasibility. Finally, the implementation of this concept on a larger scale may promote its practical application thereby contributing to a worldwide biobased economy.

ASSOCIATED CONTENT

S Supporting Information

Model description and details, as well as additional fermentation data. This material is available free of charge via the Internet at http://pubs.acs.org.

AUTHOR INFORMATION

Corresponding Author

*Phone: +45 45251429; e-mail: iria@env.dtu.dk.

Notes

The authors declare no competing financial interest.

ACKNOWLEDGMENTS

This study is the result of work done in the Biorefinery Øresund project. We thank Interreg IVA for the financial support given.

REFERENCES

(1) European Commission.. Directive 2009/28/EC of the European Parliament and of the Council of 23 April 2009 on the promotion of the use of energy from renewable sources and amending and subsequently repealing Directives 2001/77/EC and 2003/30/EC. *Off. J. Eur. Union* 2009, *52*, 16–62.

(2) Szabo, M. UBS slashes EU carbon price forecast on weak backloading effect. www.reuters.com/article/2014/05/20/ubs-ag-carbontrading-idUSL6N0O622M20140520.

(3) Bioeconomy strategy. http://ec.europa.eu/research/bioeconomy/ policy/strategy_en.htm.

(4) Holm-Nielsen, J. B.; Al Seadi, T.; Oleskowicz-Popiel, P. The future of anaerobic digestion and biogas utilization. *Bioresour. Technol.* 2009, 100, 5478–5484.

(5) Ryckebosch, E.; Drouillon, M.; Vervaeren, H. Techniques for transformation of biogas to biomethane. *Biomass Bioenergy* **2011**, 35 (5), 1633–1645.

(6) Kunzig, R. Climate Milestone: Earth's CO_2 Level Passes 400 ppm. http://news.nationalgeographic.com/news/energy/2013/05/130510-earth-co2-milestone-400-ppm.

(7) Aresta, M.; Dibenedetto, A.; Angelini, A. Catalysis for the valorization of exhaust carbon: From CO_2 to chemicals, materials, and fuels. Technological use of CO_2 . *Chem. Rev.* **2014**, *114* (3), 1709–1742.

(8) Zeikus, J. G.; Jain, M. K.; Elankovan, P. Biotechnology of succinic acid production and markets for derived industrial products. *Appl. Microbiol. Biotechnol.* **1999**, *51* (5), 545–552.

(9) Cukalovic, A.; Stevens, C. V. Feasibility of production methods for succinic acid derivatives: A marriage of renewable resources and chemical technology. *Biofuels, Bioprod. Biorefin.* **2008**, *2* (6), 505–529.

(10) Song, H.; Lee, S. Y. Production of succinic acid by bacterial fermentation. *Enzyme Microb. Technol.* **2006**, *39* (3), 352–361.

(11) Hermann, B. G.; Blok, K.; Patel, M. K. Producing bio-based bulk chemicals using industrial biotechnology saves energy and combats climate change. *Environ. Sci. Technol.* **2007**, *41* (22), 7915–7921.

(12) Guettler, M.; Rumler, D.; Jain, M. *Actinobacillus succinogenes* sp. nov., a novel succinic-acid-producing strain from the bovine rumen. *Int. J. Syst. Bacteriol.* **1999**, 49 (1), 207–216.

(13) Lee, P.; Lee, S.; Hong, S.; Chang, H. Isolation and characterization of a new succinic acid-producing bacterium, *Mannheimia succiniciproducens* MBEL5SE, from bovine rumen. *Appl. Microbiol. Biotechnol.* **2002**, *58* (5), 663–668.

(14) Nghiem, N.; Davison, B.; Suttle, B.; Richardson, G. Production of succinic acid by *Anaerobiospirillum succiniciproducens*. *Appl. Biochem. Biotechnol.* **1997**, 63–65 (1), 565–576.

(15) Okino, S.; Inui, M.; Yukawa, H. Production of organic acids by *Corynebacterium glutamicum* under oxygen deprivation. *Appl. Microbiol. Biotechnol.* **2005**, *68* (4), 475–480.

(16) Wu, H.; Li, Z.; Zhou, L.; Ye, Q. Improved succinic acid production in the anaerobic culture of an *Escherichia coli* pflB ldhA double mutant as a result of enhanced anaplerotic activities in the preceding aerobic culture. *Appl. Environ. Microbiol.* **2007**, 73 (24), 7837–7843.

(17) Lin, S. K. C.; Du, C.; Koutinas, A.; Wang, R.; Webb, C. Substrate and product inhibition kinetics in succinic acid production by *Actinobacillus succinogenes. Biochem. Eng. J.* **2008**, *41* (2), 128–135.

(18) Vlysidis, A.; Binns, M.; Webb, C.; Theodoropoulos, C. Glycerol utilisation for the production of chemicals: Conversion to succinic acid, a combined experimental and computational study. *Biochem. Eng. J.* **2011**, 58–59, 1–11.

(19) Chen, K.-Q.; Li, J.; Ma, J.-F.; Jiang, M.; Wei, P.; Liu, Z.-M.; Ying, H.-J. Succinic acid production by *Actinobacillus succinogenes* using hydrolysates of spent yeast cells and corn fiber. *Bioresour. Technol.* **2011**, *102* (2), 1704–1708.

(20) Zheng, P.; Dong, J.-J.; Sun, Z.-H.; Ni, Y.; Fang, L. Fermentative production of succinic acid from straw hydrolysate by *Actinobacillus succinogenes*. *Bioresour. Technol.* **2009**, *100* (8), 2425–2429.

(21) McKinlay, J. B.; Laivenieks, M.; Schindler, B. D.; McKinlay, A. a; Siddaramappa, S.; Challacombe, J. F.; Lowry, S. R.; Clum, A.; Lapidus, A. L.; Burkhart, K. B.; et al. A genomic perspective on the potential of *Actinobacillus succinogenes* for industrial succinate production. *BMC Genomics* **2010**, *11* (1), 680.

(22) Borges, E. R.; Pereira, N. Succinic acid production from sugarcane bagasse hemicellulose hydrolysate by *Actinobacillus succinogenes. J. Ind. Microbiol. Biotechnol.* **2011**, *38* (8), 1001–1011.

(23) Der Werf, M. J. Van; Guettler, M. V.; Jain, M. K.; Zeikus, J. G. Environmental and physiological factors affecting the succinate product ratio during carbohydrate fermentation by Actinobacillus sp. 130Z. *Arch. Microbiol.* **1997**, *167* (6), 332–342.

(24) Zou, W.; Zhu, L.-W.; Li, H.-M.; Tang, Y.-J. Significance of CO_2 donor on the production of succinic acid by *Actinobacillus succinogenes* ATCC 55618. *Microb. Cell Fact.* **2011**, 10 (1), 87.

(25) Song, H.; Lee, J. W.; Choi, S.; You, J. K.; Hong, W. H.; Lee, S. Y. Effects of dissolved CO_2 levels on the growth of *Mannheimia succiniciproducens* and succinic acid production. *Biotechnol. Bioeng.* **2007**, *98*, 1296–1304.

(26) Xi, Y.; Chen, K.; Li, J.; Fang, X.; Zheng, X.; Sui, S.; Jiang, M.; Wei, P. Optimization of culture conditions in CO₂ fixation for succinic acid production using *Actinobacillus succinogenes*. J. Ind. Microbiol. Biotechnol. **2011**, 38 (9), 1605–1612.

(27) Basu, S.; Khan, A. L.; Cano-Odena, A.; Liu, C.; Vankelecom, I. F. J. Membrane-based technologies for biogas separations. *Chem. Soc. Rev.* **2010**, *39*, 750–768.