



Use of glaciogenic marine clays for brick production in the Arctic

Belmonte, Louise Josefine; Ottosen, Lisbeth M.

Published in:
Proceedings of Euroclay 2015

Publication date:
2015

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Belmonte, L. J., & Ottosen, L. M. (2015). Use of glaciogenic marine clays for brick production in the Arctic. In *Proceedings of Euroclay 2015*

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Use of glaciogene marine clays for brick production in the Arctic

Louise Josefine Belmonte¹

Lisbeth Ottosen¹

¹ DTU Civil Engineering (Arctic Technology Centre), Brovej bygn. 118, 2800 Kgs. Lyngby, Denmark

(email: lojon@byg.dtu.dk)

Large occurrences of fine-grained glaciogene marine sediments (clays and silts) were deposited after the last glaciation and some later uplifted above sea level due to isostatic movements. Today, they are found all over the formerly glaciated regions of the northern hemisphere, such as Canada, northern Scandinavia and Greenland (Belmonte et al., in prep.; Foged, 1979; Gillott, 1979; Locat et al., 1984; Ramesh and d'Angeljan, 1995; Roaldset, 1972). Research world-wide has established that marine sediments can be suitable as primary and secondary resources in the production of clay ceramics, such as bricks (Baruzzo et al., 2006; Hamer and Karius, 2002; Mezencevova et al., 2012).

Today, bricks are not commonly used nor produced in Greenland, where building materials such as wood and concrete are favoured (Bjarløv and Vladykova, 2011; Garcia; 2012). However, as most of the construction materials used in the country, are imported, it is of great importance to investigate the potential for local production.

In this study, a representative clay occurrence from Ilulissat, West Greenland was investigated as a potential resource for local brick production. The study comprised of three parts: 1) raw material characterisation based on grain size distribution, major element chemistry including total carbon, sulphur and chloride concentrations, mineralogy, morphology and Atterberg limits 2) production of test bricks and 3) testing of the bricks based on total shrinkage, water absorption, hygroscopic adsorption, open porosity, bulk density, compression strength, freeze-thaw resistance and mineralogy. The bricks produced proved to have excellent compression strengths, low open porosity and low water absorption. In conjunction with some of the other investigated properties, this indicates that this type of clay is highly suitable as a resource for bricks, which could be used in the arctic climate.

Baruzzo, D., Minichelli, D., Bruckner, S., Fedrizzi, L., Bachiorrini, A. and Maschio, S. (2006) Possible production of ceramic tiles from marine dredging spoils alone and mixed with other waste materials. *Journal of hazardous materials*, B134, pp. 202-210.

Belmonte, L.J., Foged, N.N. and Ingeman-Nielsen, T. (in prep) Characterisation and weathering properties of fine-grained marine sediments from West Greenland.

Bentley, S.P. and Smalley, I.J. (1978) Mineralogy of sensitive clays from Quebec. *Canadian Mineralogist*, 16, pp. 103-112.

Bjarløv, S. P. and Vladykova, P. (2011) The potential need for energy saving in standard family detached and semi-detached wooden houses in arctic Greenland. *Building and Environment*, 46, pp. 1525-1536.

Foged, N. (1979) Ingeniørgeologiske undersøgelser af kvartære marine leraflejringer på Vestgrønland, Licentiate (Ph.d.) dissertation, Technical University of Denmark, Lyngby, Denmark (in Danish).

Garcia, D. (2012) View from Nuuk, Greenland. *The Architectural Review*, 27th March.

Gillott, J.E. (1979) Fabric, composition and properties of sensitive soils from Canada, Alaska and Norway. *Engineering geology*, 14, pp. 149-172.

Hamer, K. and Karius, V. (2002) Brick production with dredged harbour sediments. An industrial-scale experiment. *Waste Management*, 22, pp. 521-530.

Locat, J., Lefebvre, G. and Ballivy, G. (1984) Mineralogy, chemistry, and physical properties interrelationships of some sensitive clays from Eastern Canada. *Canadian Geotechnical Journal*, 21, pp. 530-540.

Mezencevova, A., Yeboah, N. N., Burns, S. E., Kahn, L. F. and Kurtis, K. E. (2012) Utilization of Savannah Harbor river sediments as the primary raw material in production of bricks. *Journal of Environmental Management*, 113, pp. 128-136.

Ramesh, R., d'Anglejan, B. (1995) Mineralogy, Chemistry and particle size interrelationships in some Post-Glacial Marine Deposits of the St. Lawrence Lowlands. *Journal of Coastal Research*, 11 (4), pp. 1167-1179.

Roaldset, E. (1972) Mineralogy and geochemistry of Quaternary clays in the Numedal area, southern Norway, *Norsk Geologisk Tidsskrift* 52 (4), pp. 335-369.