



Accounting for nearfield exposure to chemicals in consumer products in LCA

Jolliet, Olivier; Fantke, Peter; Huang, Lei; Ernstoff, Alexi

Published in:
Abstract book - LCA XV Conference

Publication date:
2015

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Jolliet, O., Fantke, P., Huang, L., & Ernstoff, A. (2015). Accounting for nearfield exposure to chemicals in consumer products in LCA. In *Abstract book - LCA XV Conference*

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Studentlitteratur AB, Lund (Sweden).

[3] Seider W.D., Seader J.D., Lewin D.R., Widagdo S.: Product and Process Design Principles: Synthesis, Analysis and Design. 3rd edition, John Wiley & Sons Inc., Hoboken, 2008.

[4] Kemp I.C. (2011): Pinch Analysis and Process Integration: A User Guide on Process Integration for the Efficient Use of Energy. Butterworth-Heinemann.

[5] Tachikawa H. (2014): Manual on Material Flow Cost Accounting ISO 14051. ISBN 978-92-833-2450-8, Asian Productivity Organization, Tokyo (Japan).

[6] Nickel S., Stein O., Waldmann K.-H. (2014): Operations Research. 2nd edition, Springer / Gabler, Berlin / Heidelberg, ISBN 978-3-642-54367-8.

[7] Viere, T. et al. (2014): Integrated Resource Efficiency Analysis for Reducing Climate Impacts in the Chemical Industry. In: Journal of Business Chemistry, June 2014. <http://www.businesschemistry.org/article/?article=192>, last visit 2015-4-30.

[8] Denz N., Ausberg L., Bruns M., Viere T. (2014): Supporting resource efficiency in chemical industries - IT-based integration of flow sheet simulation and material flow analysis. Proceedings of the 21st CIRP Conference on Life Cycle Engineering, Trondheim (Norway), June.

[9] Zschieschang E., Lambrecht H., Denz N., Viere T. (2014): Resource efficiency-oriented optimization of material flow networks in chemical process engineering, in: Proceedings of the 21st CIRP Conference on Life Cycle Engineering, Trondheim (Norway), June.

[11] Brandt C., Fieg G., Luo X., Liu X. (2011): Improving genetic algorithms for the synthesis of heat exchanger networks. World Congress on Engineering and Technology (CET), Shanghai.

[12] <http://www.umberto.de/en>, last visit 2015-4-30.

[13] <http://pinch-analyse.ch/index.php/en>, last visit 2015-4-30.

[14] <http://www.xrg-simulation.de/en/products/xrg-applications/synthex>, last visit 2015-4-30.

14:15 [Olivier Jolliet](#), [Peter Fantke](#), [Lei Huang](#) and [Alexi Ernstoff](#)

Accounting for near-field exposure to chemicals in consumer products in LCA

SPEAKER: [Olivier Jolliet](#)

ABSTRACT. Every consumer product has the potential to expose humans to chemical ingredients during use, via multiple exposure pathways. However, many product oriented exposure assessment accounts mostly for indirect environmental exposure and not direct exposure of consumer to product during use. We therefore aim to a) Identify the most efficient interface between LCI and LCIA for the use and disposal stage of consumer products, b) determine the chemical concentration in product as an LCI input, c) define and calculate the Product Intake Fraction (PiF), a metric that accounts for near field exposure in LCA, d) demonstrate the framework and models through examples from various consumer products. We propose to first determine the mass of chemical in product per functional unit (FU) as inventory flow and point of departure to then calculate intake and impact. This inventory flow is the amount of product used per FU multiplied by the chemical content in product. This content is either based on measured data, derived from household product databases, or determined based on chemical-product specific function and frame formulations. Intakes are then determined using the product intake fractions - the fraction of the chemical in product that is taken in via each exposure pathway, considering the specific point of entry (cosmetics, chemical in article, indoor air, etc.). We propose a new near & far field multi-media matrix of transfer fractions, with one column and row for each point of entry, for each environmental compartment and for each exposure pathway. The multiple transfer and product intake fraction (e.g from chemical in article to inhalation of indoor air) is obtained by inverting the transfer fraction matrix, yielding the infinite multi-media transfer fractions. Product intake fraction range from 10e-7 for an SVOC in a thick flooring, to 5e-3 for an indoor air emission up to 96% for a leave-on cosmetic ingredient.

14:30 [Susan A. Csiszar](#), [Alexi S. Ernstoff](#), [Peter Fantke](#), [Olivier Jolliet](#), [Jane Bare](#) and [David Meyer](#)

Near-field exposure factor modeling of chemicals in personal care products

SPEAKER: [Susan A. Csiszar](#)

ABSTRACT. It has been estimated that there are thousands of chemicals used in personal care products (PCPs) and human exposure to these