



Implementation of fully coupled heat and mass transport model to determine the behaviour of timber elements in fire

Pečenko, Robert; Huč, Sabina; Turk, Goran; Svensson, Staffan; Hozjan, Tomaž

Published in:
World Conference on Timber Engineering, Proceedings — 2014

Publication date:
2014

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Pečenko, R., Huč, S., Turk, G., Svensson, S., & Hozjan, T. (2014). Implementation of fully coupled heat and mass transport model to determine the behaviour of timber elements in fire. In World Conference on Timber Engineering, Proceedings — 2014 WCTE 2014 Secretariat.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

IMPLEMENTATION OF FULLY COUPLED HEAT AND MASS TRANSPORT MODEL TO DETERMINE THE BEHAVIOUR OF TIMBER ELEMENTS IN FIRE

Robert Pečenko¹, Sabina Huč², Goran Turk³, Staffan Svensson⁴, Tomaž Hozjan⁵

ABSTRACT: In this paper we present results of numerical analysis of timber beam exposed to fire. The numerical procedure is divided into two physically separated but closely related phases. In the first phase coupled problem of moisture and heat transfer over the timber beam is numerically solved using the enhanced finite element method. The results of the first computational stage were used as the input data for the numerical analysis of mechanical response of timber element.

KEYWORDS: fire, fire resistance, timber beam, heat and mass transfer model

1 INTRODUCTION

From the fire safety point of view timber is relatively favourable material. The behaviour of timber in fire depends on a large number of phenomena that occur when it is exposed to elevated temperatures. The behaviour of timber in fire depends on a large number of phenomena. In an accurate model, for estimating the response of timber elements in fire, these, must be accounted for. A major problem is the pyrolysis associated with charring of timber. At temperatures above 300°C timber starts to char which leads to changed thermal and mechanical properties. In addition it is necessary to carry out temperature-moisture analysis of timber element exposed to fire in order to determine its response.

In an open porous hygroscopic material such as wood heat and moisture transport is a complex system of coupled processes. Inside timber, different phases of water can be

observed, i.e., free water, bound water and gas phase of water (water vapour and air). Conservation equations for each phase with the exchange of mass between the different phases have to be considered. Different transfer phenomenon's can be applied for each phase. The equations describing the conservation of mass must also be supplemented with an equation describing the conservation of enthalpy [2].

2 NUMERICAL ANALYSIS

Mechanical behaviour of timber elements in fire is very complex phenomenon where the temporal and spatial distributions of temperature and water content of wood play a decisive role. The deformation of the structure does not significantly affect the moisture and heat transfer. Therefore, the numerical procedure is divided into two phases. In the first phase the time development of the moisture and temperature state of the timber element is calculated. The results of the first computational stage are used as the input data for the numerical analysis of mechanical response of timber elements.

2.1 THERMAL ANALYSIS

The bound water transfer model is assumed to follow Fick's law [1]. More complex is the transfer of gaseous mixture. Transfer of water vapour and air has to be combined by a convective and diffusive model of transport. For the convective part Darcy's law is usually applied and for the diffusive part Fick's law is used [2]. The free water constitutive relation is usually assumed to follow the generalized Darcy's law [3]. All three processes are connected with each other through the exchange of mass between the different phases, i.e., the phase change

¹ University of Ljubljana, Faculty of Civil and Geodetic Engineering, Jamova 2, 1000 Ljubljana, Slovenia. Email: robert.pecenko@fgg.uni-lj.si

² GIIP d.o.o., Dobja vas 200, 2390 Ravne na Koroškem, Slovenia. Email: sabina.huc@gmail.com

³ University of Ljubljana, Faculty of Civil and Geodetic Engineering, Jamova 2, 1000 Ljubljana, Slovenia. Email: goran.turk@fgg.uni-lj.si

⁴ Technical University of Denmark, Department of Civil Engineering, Brovej 118, 2800 Kgs. Lyngby, Denmark. Email: nss@byg.dtu.dk

⁵ University of Ljubljana, Faculty of Civil and Geodetic Engineering, Jamova 2, 1000 Ljubljana, Slovenia. Email: tomaz.hozjan@fgg.uni-lj.si

of vapour to free water and vice versa (condensation and evaporation), the phase change of vapour to bound water and vice versa (sorption) and the phase change of free water to bound water and vice versa. Thermal interaction on mass transfer is seen as temperature dependent diffusion coefficients where Fick's law is applied and temperature dependent mass velocity where Darcy's law is used as well as the Soret effect. The energy conservation equation takes three phenomena into account. Firstly, the usual conduction of heat thru solid, described by Fourier's law. Secondly, the changes in enthalpy resulting from change of phase, i.e. sorption, evaporation and condensation. And finally, the convective transfer of heat, i.e. the effect that heat is carried by the mass flux. These equations with corresponding initial and boundary conditions are generally non-linear and can rarely be if at all solved analytically. Therefore, numerical methods have to be employed.

2.2 MECHANICAL ANALYSIS

The presented finite element formulation is based on Reissner's kinematically exact model of beam where large membrane and flexural deformations are allowed [3]. The geometric extensional strain is a function of extensional strain of centroidal axis ε and its pseudocurvature κ . The Bernoulli hypothesis is considered. An important assumption in this model is the additive decomposition of the increment of geometric extensional strain. The system of equations for finite element method is written based on modified principle of virtual work where quantities ε and κ are interpolated over finite element by Lagrangian polynomials. A more detailed description of the finite element formulation is presented in [4].

3 PARAMETRIC STUDY

With the presented numerical model impact of parameters such as the effect of bound water diffusion, water vapour diffusion and temperature dependent sorption on mechanical response is investigated. Particular attention is focused on the impact of diffusion of bound water on the mechanical response. We analyze if, in certain cases, diffusion of bound water can be omitted. Therefore in this context, the numerical model can be simplified with only one diffusion equation.

ACKNOWLEDGMENT

The work of R. Pecenko was partly financially supported by the Slovenian Research agency under contract No. 1000-11-310126. The support is gratefully acknowledged. The work of S. Huč was partly financially supported by Slovenian Ministry of Economic Development and Technology and by the European Social Fund. The support is gratefully acknowledged.

REFERENCES

- [1] Frandsen H.L. Selected Constitutive models for simulating the hygromechanical response of wood. Department of Civil Engineering Aalborg University (PhD Thesis), 2007.
- [2] R.T. Tenchev, L.Y. Li and J.A Purkiss. Finite element analysis of coupled heat and moisture transfer in concrete subjected to fire. *Numerical Heat Transfer, Part A*, 39: 685-710, 2001.
- [3] P. Perre and I.W. Turner. A 3-D version of Transpore: a comprehensive heat and mass transfer computational model for simulating the drying of porous media. *International Journal of Heat and Mass Transfer*, 42:4501-4521, 1999.
- [4] Bratina S., Planinc I., Saje M., Turk G. Non-linear fire-resistance of reinforced concrete beams. *Structural engineering and mechanics*, 16(6):695-712, 2003.
- [5] Reissner E. On one-dimensional finite-strain beam theory: the plane problem. *J. Appl. Math. Phys.* (ZAMP) 23:795-804, 1972.