

Using Numerical Weather Prediction Ensembles to Anticipate Flows in Urban Area

Courdent, Vianney; Grum, Morten; Mikkelsen, Peter Steen

Published in: Book of Abstracts. DTU's Sustain Conference 2015

Publication date: 2015

Document Version Publisher's PDF, also known as Version of record

Link back to DTU Orbit

Citation (APA): Courdent, V., Grum, M., & Mikkelsen, P. S. (2015). Using Numerical Weather Prediction Ensembles to Anticipate Flows in Urban Area. In *Book of Abstracts. DTU's Sustain Conference 2015* Article L-18 Technical University of Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



Using Numerical Weather Prediction Ensembles to Anticipate Flows in Urban Area

<u>Vianney Courdent</u>^{1,2}, Morten Grum², Peter S. Mikkelsen¹ 1: DTU Environment; 2: Kruger A/S *Corresponding author email: <u>vatc@env.dtu.dk</u>

Weather forecasts can provide valuable information to improve the operational performance of urban drainage systems (UDS) and wastewater treatment plants (WWTPs). For example, radar-based rainfall forecast are increasingly being used within real-time control (RTC) concepts (Vezzaro et al. 2014). Numerical weather prediction (NWP) models can also contribute to forecasting rainfall with the advantage of an increased lead-time. For example Meneses et al. (2015) use NWPs to generate operational flood warnings, and Bjerg et al. (2015) described the potential of flow domain forecasting using NWP to optimise energy consumption: The UDS can be used as buffer when no rain is expected to control the timing of energy consumption which, enables coupling with the electrical smart grid system optimizing expenses and CO_2 footprint.

Using uncertain information, such as NWP, to optimize storm- and wastewater systems in real time is generally challenging. Indeed, NWP is embedded with a significant uncertainty. Therefore Ensemble Prediction Systems (EPS) are generated and prediction strategies using multiple ensemble members are implemented e.g. (Courdent et al. 2015), Figure 1 illustrates the principal.



Figure 1: Flow prediction at Damhuså catchment generated the 11th of May 2015 at 18:00 using the DMI-HIRLAM-S05 NWP model

- Bjerg, J.E. et al., 2015. Coupling of Weather Forecasts and Smart Grid-Control of Wastewater inlet to Kolding WWTP (Denmark). In 10th International Urban Drainge Modelling Conference. Mont Sainte-Anne, Québec, Canada, pp. 47–59.
- Courdent, V., Grum, M. & Mikkelsen, P.S., 2015. Using numerical weather prediction ensembles to dstinguish urban drainage flow domains 2 days ahead. In *10th International Urban Drainge Modelling Conference*. Mont Sainte-Anne, Québec, Canada, pp. 123–126.
- Meneses, E.J. et al., 2015. SURFF Operational flood warnings for cities based on hydraulic 1D-2D simulations and NWP. In *10th* International Urban Drainge Modelling Conference. Mont Sainte-Anne, Québec, Canada, pp. 97–104.
- Vezzaro, L. et al., 2014. Water Quality-based Real Time Control of Integrated Urban Drainage Systems: A Preliminary Study from Copenhagen, Denmark. *Procedia Engineering*, 70, pp.1707–1716. Available at: http://linkinghub.elsevier.com/retrieve/pii/S1877705814001908.

Sustain DTU Abstract: L-18