An Ultra-Efficient Nonlinear Platform: AlGaAs-On-Insulator

Pu, Minhao; Ottaviano, Luisa; Semenova, Elizaveta; Hu, Hao; Oxenløwe, Leif Katsuo; Yvind, Kresten

Link to article, DOI:

[10.1109/PIERS.2016.7735233](https://doi.org/10.1109/PIERS.2016.7735233)

Publication date:

2016

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Pu, M., Ottaviano, L., Semenova, E., Hu, H., Oxenløwe, L. K., & Yvind, K. (2016). *An Ultra-Efficient Nonlinear Platform: AlGaAs-On-Insulator*. Abstract from Progress In Electromagnetics Research Symposium 2016, Shanghai, China. <https://doi.org/10.1109/PIERS.2016.7735233>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

An Ultra-efficient Nonlinear Platform: AlGaAs-on-Insulator

Minhao Pu, Luisa Ottaviano, Elizaveta Semenova, Hao Hu,
Leif K. Oxenløwe, and Kresten Yvind

DTU Fotonik, Department of Photonics Engineering, Technical University of Denmark
Building 343, DK-2800 Lyngby, Denmark

Abstract— The combination of nonlinear and integrated photonics enables applications including optical signal processing, multi-wavelength lasers, metrology, spectroscopy, and quantum information science. Silicon-on-insulator (SOI) has emerged as a promising platform [1, 2] due to its high material nonlinearity and its compatibility with the CMOS industry. However, silicon suffers two-photon absorption (TPA) in the telecommunication wavelength band around $1.55\ \mu\text{m}$, which hampers its applications. Different platforms have been proposed to avoid TPA in the telecom wavelength range such as Si_3N_4 and Hydrex [3]. Though tremendous technological work in those platforms have greatly improved device performances, the relatively low intrinsic material nonlinearities of those materials limit device performances concerning efficiency. Therefore, an integrated nonlinear platform that combines a high material nonlinearity, a high-index contrast as SOI, and low linear and nonlinear losses is highly desired.

Aluminium gallium arsenide (AlGaAs) was early identified as a promising candidate and even nominated as “the silicon of nonlinear optical material” [4] when operated just below half its bandgap energy. It offers a nonlinear index (n_2) on the order of $10^{-17}\ \text{W}/\text{m}^2$ and a high refractive index ($n \approx 3.3$), a large transparency window (from near- to mid-infrared), and the ability to engineer the material bandgap to mitigate TPA [5]. In this presentation, we introduce AlGaAs-on-insulator (AlGaAsOI) platform which combines both strong nonlinear light-matter interaction induced by high-index contrast layout and the potential to fabricate complex designs similar to what is done in silicon-on-insulator photonics. We demonstrate low loss ($\sim 1.4\ \text{dB}/\text{cm}$) nanowaveguides with an ultra-high nonlinear coefficient ($\sim 660\ \text{W}^{-1}\text{m}^{-1}$) and microring resonators with quality factors on the order of 10^5 [6]. The large effective nonlinearity of such platform enables efficient nonlinear processes such as high-speed optical signal processing [7], supercontinuum generation, and Kerr frequency comb generation [8]. Moreover, the required operation power for signal generation processes such as optical parametric oscillation in the AlGaAsOI platform is well within the range of standard on-chip light sources. In line with the fast-growing hybrid integration trend to combine different materials in multiple levels on a single CMOS compatible chip, the AlGaAsOI platform is very promising for realizing a compact fully-integrated multi-wavelength light source for high bandwidth optical interconnects.

ACKNOWLEDGMENT

The authors acknowledge financial support from the Danish Research Council and Villum Fonden via the SPOC (DNR123) and NATEC centers, and SiMOF project (FTP 11-117031).

REFERENCES

1. Leuthold, J., et al., “Nonlinear silicon photonics,” *Nat. Photon.*, Vol. 4 535–544, 2010.
2. Oxenløwe, L. K., et al., “Silicon photonics for signal processing of Tbit/s serial data signals,” *Journal of Selected Topics in Quantum Electronics*, Vol. 18, No. 2, 996–1005, 2012.
3. Moss, D. J., et al., “New CMOS-compatible platforms based on silicon nitride and Hydrex for nonlinear optics,” *Nat. Photon.*, Vol. 7 597–607, 2014.
4. Stegeman, G. I., et al., “AlGaAs below half bandgap: the silicon of nonlinear optical materials,” *Int. J. Nonlinear Opt. Phys.*, Vol. 3, No. 3, 347–371, 1994.
5. Wathen, J. J., et al., “Efficient continuous-wave four-wave mixing in bandgap-engineered AlGaAs waveguides,” *Opt. Lett.*, Vol. 39, No. 11, 3161–3164, 2014.
6. Pu, M., et al., “AlGaAs-on-insulator nonlinear photonics,” arXiv:1509.03620 [physics.optics], 2015.
7. Pu, M., et al., “AlGaAs-on-insulator nanowire with 750 nm FWM bandwidth, $-9\ \text{dB}$ CW conversion efficiency, and ultrafast operation enabling record Tbaud wavelength conversion,” *Optical Fiber Communication Conference Post Deadline Papers*, Th5A.3, 2015.
8. Pu, M., et al., “Ultra-low threshold power on-chip optical parametric oscillation in algaas-on-insulator microresonator,” *CLEO: 2015 Postdeadline Paper Digest*, JTh5A.9, 2015.