



## Amphiphilic copolymers for fouling-release coatings

Noguer, Albert Camós; Olsen, Stefan Møller; Hvilsted, Søren; Kiil, Søren

*Publication date:*  
2016

*Document Version*  
Peer reviewed version

[Link back to DTU Orbit](#)

*Citation (APA):*

Noguer, A. C., Olsen, S. M., Hvilsted, S., & Kiil, S. (2016). *Amphiphilic copolymers for fouling-release coatings*. Abstract from 18th International Congress on Marine Corrosion and Fouling, Toulon, France.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

## Amphiphilic copolymers for fouling-release coatings

Albert CAMÓS NOGUER<sup>1</sup>, Stefan M. OLSEN<sup>2</sup>, Søren HVILSTED<sup>1</sup>, Søren KIIL<sup>1,\*</sup>

<sup>1</sup>Department of Chemical and Biochemical Engineering, Technical University of Denmark (DTU), Kgs. Lyngby, Denmark

<sup>2</sup>Department of Fouling Release Systems, Hempel A/S, Kgs. Lyngby, Denmark  
\*sk@kt.dtu.dk

Polydimethylsiloxane (PDMS) resins are extensively used as binder in fouling-release coatings due to the low critical surface energy and low elastic modulus of PDMS. These properties result in poor adhesion of the fouling organisms, which are therefore detached by hydrodynamic forces during navigation [1,2,3]. Other compounds are usually mixed together with the binder (e.g. silica and pigments) in order to improve the mechanical, thixotropic and visual properties of the coatings. It has been shown, however, that these ingredients have a negative effect on the fouling-release properties of the coatings [1,2,4].

Together with the PDMS-system, non-reactive polymers have been used to improve the fouling-release properties of the coatings. Initially, hydrophobic siloxane-based polymers were used, which aimed to increase the hydrophobicity of the PDMS surface [5,6]. However, copolymers comprising hydrophilic, amphiphilic and zwitterionic chemistries have been recently introduced due to their resistance to protein adsorption [7,8]. As a result, most of the current commercial fouling-release coatings contain either amphiphilic or hydrophilic copolymers to improve the fouling release properties of the coatings [9,10,11].

This work shows the effect of an amphiphilic copolymer that induces hydrophilicity on the surface of the silicone-based fouling release coatings. The behaviour of these copolymers within the coating upon immersion and the interaction of these surface-active additives with other compounds of the coatings are addressed.

- [1] R. F. Brady, I. L. Singer, *Biofouling* **2000**, 15, 73-81.
- [2] M. Lejars, A. Margaillan, C. Bressy, *Chem. Rev.* **2012**, 112, 4347-4390.
- [3] A. G. Nurioglu, A. Catarina C. Esteves, G. de With, *J. Mater. Chem. B* **2015**, 3, 6547-6570.
- [4] J. Stein, K. Truby, C. D. Wood, M. Takemori, M. Vallance, G. Swain, C. Kavanagh, B. Kovach, M. Schultz, D. Wiebe, E. Holm, J. Montemarano, D. Wendt, C. Smith, A. Meyer, *Biofouling* **2003**, 19, 87-94.
- [5] K. Truby, C. Wood, J. Stein, J. Cella, J. Carpenter, C. Kavanagh, G. Swain, D. Wiebe, D. Lapota, A. Meyer, E. Holm, D. Wendt, C. Smith, J. Montemarano, *Biofouling* **2002**, 15, 141-150.
- [6] A. Milne, *US Patent* 4,025,693, **1977**
- [7] R. G. Chapman, E. Ostuni, S. Takayama, R. E. Holmlin, L. Yan, G. M Whitesides, *J. Am. Chem. Soc.* **2000**, 8303-8304
- [8] C. J. Kavanagh, G. W. Swain, B. S. Kovach, J. Stein, C. Darkangelo-Wood, K. Truby, E. Holm, J. Montemarano, A. Meyer, D. Wiebe, *Biofouling* **2003**, 19, 381-390.
- [9] P. C. W. Thorlaksen, A. Blom, U. Bork, *WO Patent* 076856A1, **2011**.
- [10] D. C. Webster, R. B. Bodkhe, *WO Patent* 052181A2, **2013**.
- [11] K. J. Reynolds, B. V. Tyson, *WO Patent* 131695A1, **2014**.