



Dynamic tracer dispersion method: A tool for measuring the total methane emission from individual Danish landfills

Mønster, Jacob; Fuglsang, Karsten; Scheutz, Charlotte

Publication date:
2016

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Mønster, J. (Author), Fuglsang, K. (Author), & Scheutz, C. (Author). (2016). Dynamic tracer dispersion method: A tool for measuring the total methane emission from individual Danish landfills. Sound/Visual production (digital), Technical University of Denmark, DTU Environment.


General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.


A tool for measuring the total methane emission from individual Danish landfills




Jacob Mønster, FORCE Technology & DTU Environment
Karsten Fuglsang, FORCE Technology
Charlotte Scheutz, DTU DTU Environment

- Theory
- In practice
- Uncertainties
- Possibilities
- Results & Conclusion

$$E_{\text{gas}} = Q_{\text{tracer}} \cdot \frac{\int_{\text{Plume end 1}}^{\text{Plume end 2}} C_{\text{gas}} dx}{\int_{\text{Plume end 1}}^{\text{Plume end 2}} C_{\text{tracer}} dx} \cdot \frac{MW_{\text{gas}}}{MW_{\text{tracer}}}$$





$$E_{gas} = Q_{tracer} \cdot \frac{\int_{Plume\ end\ 1}^{Plume\ end\ 2} C_{gas} dx}{\int_{Plume\ end\ 1}^{Plume\ end\ 2} C_{tracer} dx} \cdot \frac{MW_{gas}}{MW_{tracer}}$$


- Tracer gas with long atmospheric lifetime
- Good/stable wind & road conditions
- Sensitive analytical instrument



Tracer gas (C_2H_2)




1) Screening for methan



2) Tracer gas placement





3) Measurements of the downwind plumes



Time (hh:mm)	Methane mission (kg h ⁻¹)
12:32	10.2
12:44	10.7
12:53	10.6
12:56	12.8
13:01	11.0
13:03	13.6
13:06	10.7
13:09	11.7
13:13	12.9
13:19	11.9
13:21	11.5
13:23	11.7
13:26	11.2
13:32	12.7
13:34	13.9
13:36	13.6
13:38	12.8
13:43	10.6
13:46	11.7
Average	11.9
Std. Dev.	1.1
95% Conf. Int.	0.6

Interfering sources





Measurement uncertainties:

Other sources*

Tracer gas release (flow & placement*)


Elevated sources*

Variation of background concentration*

Too low concentrations*

Sudden change in atmospheric conditions*


*) site specific




Landfill emission variation

Atmospheric pressure (absolute & change)


- Wind
- Precipitation
- Temperature




Leachate well in the middle of a
composting area: $0.6 \text{ kg CH}_4 \text{ h}^{-1}$




Leachate well :
 $5.3 \text{ kg CH}_4 \text{ h}^{-1}$
Whole landfill:
 $6.9 \text{ kg CH}_4 \text{ h}^{-1}$




Whole site/area




Single process






3 tracer gas configurations



Seperated plumes for quantification



Dynamic tracer dispersion method

Results

Landfill	CH ₄ emission measured		CH ₄ emission reported
	(kg CH ₄ h ⁻¹)	(tons CH ₄ y ⁻¹)	(tons CH ₄ y ⁻¹)
Audebo	16.0	140	664
AV Miljø	32.4	284	28
Eskelund	6.1	53	NR
Fakse	42.2	370	129
Feltengård	3.9	34	298
Frederiksværk	8.9	78	17
Glatved	60.8	533	3490
Hedeland	3.1	27	3390
Klintholm	15.0	131	1490
Odense	33.1	290	487
Skovsted	2.6	23	500
Skårup	11.9	104	24
Uggeløse	9.5	83	NR
Viborg	11.1	97	1260
Ærø	6.9	60	118
Average	17.6	154	793

X 5

- + Emission of methane (real time)
- + Locate and quantify emission hotspots
- + Quantify emission areas e.g. single landfill cell or biocover)

Measure down to 1 kg methane h⁻¹
Point source down to 10 g methane h⁻¹

Both depends on many factors

- Relative small time window
- Other sources
- Emission variation



Dynamic tracer dispersion method

Future work



Further validation of the method and instrumentation

- + Additional controlled release campaigns
- + Instrumentation intercomparison
- + Additional method intercomparison



Thank you for your attention

Further information: jmn@force.dk

References in presentation

Mønster, et al., 2014. Quantifying methane emission from fugitive sources by combining tracer release and downwind measurements - a sensitivity analysis based on multiple field surveys. *Waste Management* 34, 1416–1428.

Mønster, et al., 2015. Quantification of methane emissions from 15 Danish landfills using the mobile tracer dispersion method. *Waste Management* 35, 177–186.

Spørgsmål?

Artikler og anden dokumentation/information:

Jacob Mønster

jmn@force.dk