Time Lens based Optical Fourier Transformation for All-Optical Signal Processing of Spectrally-Efficient Data

Guan, Pengyu; Røge, Kasper Meldgaard; Lillieholm, Mads; Galili, Michael; Hu, Hao; Morioka, Toshio; Oxenløwe, Leif Katsuo

Published in:
Journal of Lightwave Technology

Link to article, DOI:
[10.1109/JLT.2016.2614186](https://doi.org/10.1109/JLT.2016.2614186)

Publication date:
2017

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Guan, P., Røge, K. M., Lillieholm, M., Galili, M., Hu, H., Morioka, T., & Oxenløwe, L. K. (2017). Time Lens based Optical Fourier Transformation for All-Optical Signal Processing of Spectrally-Efficient Data. *Journal of Lightwave Technology*, 35(4), 799 - 806. [7579624]. <https://doi.org/10.1109/JLT.2016.2614186>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Time Lens based Optical Fourier Transformation for All-Optical Signal Processing of Spectrally-Efficient Data

P. Guan, Member, IEEE, K. M. Røge, M. Lillieholm, M. Galili, Member, OSA, H. Hu, T. Morioka, Member, IEEE, Fellow, OSA, and L. K. Oxenløwe, Member, OSA

Abstract— We review recent progress in the use of time lens based optical Fourier transformation for advanced all-optical signal processing. A novel time lens based complete optical Fourier transformation (OFT) technique is introduced. This complete OFT is based on two quadratic phase-modulation stages using four-wave mixing (FWM), separated by a dispersive medium, which enables time-to-frequency and frequency-to-time conversions simultaneously, thus performing an exchange between the temporal and spectral profiles of the input signal. Using the proposed complete OFT, several advanced all-optical signal processing schemes for spectrally-efficient systems and networks have been achieved, including all-optical generation, detection and format conversion of spectrally-efficient signals. The spectrally-efficient signals in this paper mainly refer to efficiently multiplexed signals with a high symbol rate per Hz, such as orthogonal frequency division multiplexing (OFDM), Nyquist wavelength-division multiplexing (Nyquist-WDM) and Nyquist optical time division multiplexing (Nyquist-OTDM) signals.

Index Terms— All-optical OFDM, optical Fourier transformation, OTDM, Nyquist-WDM, optical signal processing.

I. INTRODUCTION

Due to the rapid traffic growth in optical communication networks, current infrastructures and technologies may not be able to handle the coming increase in data traffic and associated energy requirements [1-2]. Thus, it has become increasingly important to develop energy- and spectrally-efficient communication systems and the associated enabling technologies. One possible solution is the combination of several lower-rate channels with high spectral efficiency (SE) using orthogonal frequency division

Fig. 1. Spectrum and corresponding waveform of: (a) OFDM, (b) Nyquist-WDM and (c) Nyquist-OTDM signals.

multiplexing (OFDM) [3], Nyquist wavelength division multiplexing (Nyquist-WDM) [4] and Nyquist optical time division multiplexing (Nyquist-OTDM) [5], which all take advantage of the orthogonality to enable a channel bandwidth close or equal to the symbol rate. Fig. 1(a) illustrates the spectrum of an OFDM signal and the waveform of a selected OFDM subcarrier. It consists of closely spaced and overlapping sinc-shaped subcarriers in the frequency domain. The waveforms for each subcarrier are square-shaped and closely spaced. Fig. 1(b) illustrates the spectrum of a Nyquist-WDM signal and the waveform of a selected Nyquist WDM channel. It consists of closely spaced but non-overlapping individual channels in the frequency domain. For each Nyquist-WDM channel, the waveforms are sinc-shaped and overlap in time domain. Fig. 1(c) illustrates the spectrum and waveform of a Nyquist-OTDM signal. It consists of a single square-shaped channel with broad bandwidth in the frequency domain. Its waveforms are sinc-shaped and overlap in time domain as the Nyquist-WDM signal, but usually with a higher symbol rate (achieved by OTDM). All the three multiplexing techniques have the same performance in terms of spectrum efficiency. In particular, OFDM has a large tolerance to fiber dispersion, Nyquist-WDM is more robust to practical implementation constraints [4], and Nyquist-OTDM can offer ultrahigh symbol rate beyond electronic limitation, but with less network flexibility due to its inseparable broad spectrum. With the help

Manuscript received xx-xx-xxxx; revised xx; accepted xx. Date of publication xx; date of current version xx. This work was funded by the Danish Research Council FTP project LENS-COM (ref. DFF-5054-00184), FTP-TOR project (ref.no. 0602-02398B), the DFF Sap. Aude Adv. Grant NANO-SPECS (DFF-4005-00558B) and the DNRF Research Centre, SPOC (ref. DNRF123).

P. Guan, K. M. Røge, M. Galili, H. Hu, M. Lillieholm, T. Morioka and L. K. Oxenløwe are with DTU Fotonik, Department of Photonics Engineering, Technical University of Denmark, Ørstedes Plads 343, DK-2800 Kgs. Lyngby, Denmark (e-mail: pengu@fotonik.dtu.dk).

Color versions of one or more of the figures in this paper are available online at <http://ieeexplore.ieee.org>.

Copyright (c) 2016 IEEE

of advanced coherent detection and electronic digital signal processing (DSP) technologies, OFDM, Nyquist-WDM and Nyquist-OTDM have been used to demonstrate high SE super-channels with more than 1 Tbit/s capacity [6]-[8]. However, due to the bandwidth limitation of electronics, scaling the bandwidth of the DSP based system will also scale the number of components and their combined power consumption. On the other hand, optical signal processing (OSP) that can avoid optical to electrical to optical (OEO) conversion, has the potential to realize energy-efficient systems [9]. In addition, OSP explores nonlinear optical phenomena which have a response time on the order of femtoseconds, thus allowing for a processing bandwidth beyond one THz. In general, OSP is considered suitable only for relatively simple functionalities, and complex digital logic for spectrally-efficient signals may turn out to be too challenging to implement all-optically.

In this paper, we describe a novel time lens based complete optical Fourier transformation (OFT) technique for advanced optical signal processing of OFDM, Nyquist-OTDM and Nyquist-WDM signals. A number of recent demonstrations of complex high-speed optical signal processing using complete OFT will also be reviewed, including generation, detection and format conversion of OFDM, Nyquist-WDM and Nyquist-OTDM signals. These demonstrations show that the simple OFT implementations can be used to achieve relatively complex signal processing operations.

In section II, the principle of time lens based complete OFT is described and discussed. In section III, recent experimental demonstrations and results are presented. In section IV, we discuss the potential and the future implications and finally conclude this paper.

II. PRINCIPLE OF TIME LENS BASED COMPLETE OFT

The time lens is based on the space-time duality of light, which states that a quadratic phase modulation (PM) of a temporal waveform is analogous to the action of a thin lens on a spatial beam, hence the expression “time lens” [10]. By combining a time lens with suitable dispersion media both before and after the lens, an OFT can be realized as shown in Fig. 2(a) [11]. Recently, the time lens based OFT has been shown to be a very versatile and powerful tool for ultrafast optical signal processing. It can be applied to transfer the temporal profile of an optical signal into the frequency domain and vice-versa. This has led to demonstrations of e.g. distortion-less transmission [12], an ultrafast optical oscilloscope [13] and optical time division multiplexing (OTDM) to WDM conversion [14]. One common feature of these demonstrations is that they are all realized by a “partial” OFT, where only one-way conversion can be achieved, either from the time- to the frequency-domain, or from the frequency- to the time-domain. A partial OFT scheme is not sufficient for processing of OFDM, Nyquist-WDM and Nyquist-OTDM signals, especially at the transmitter, since it introduces a residual chirp or dispersion which will impact the orthogonality of OFDM and Nyquist-WDM signals. To overcome this challenge, we proposed a new time lens based

Fig. 2. Schematic diagrams of a time lens based OFT: (a) a traditional D-K-D configuration and (b) a proposed K-D-K configuration for signal processing of spectrally-efficient signals.

complete OFT, cf. Fig. 2(b) [15]. The proposed OFT is based on two quadratic phase-modulation stages ($\delta\phi = Kt^2/2$) with chirp rate K , separated by a dispersive medium with $D = \beta_2 L$ (where β_2 is the 2nd order dispersion and L is the length), which satisfies the condition $K = 1/D$ (a K-D-K configuration). Consider an input signal waveform $u(t)$. The output waveform $v(t)$ after the first phase modulation stage and the dispersive medium is given by:

$$v(t) = \sqrt{\frac{i}{2\pi D}} \int_{-\infty}^{\infty} u(t') \exp\left(i \frac{K}{2} t'^2\right) \exp\left[-\frac{i}{2D}(t-t')^2\right] dt'. \quad (1)$$

When $K = 1/D$, the expression can be simplified to the following form that contains the Fourier transform of the input signal,

$$v(t) = \sqrt{\frac{i}{2\pi D}} \exp\left(-i \frac{K}{2} t^2\right) \int_{-\infty}^{\infty} u(t') \exp\left[i \left(\frac{t}{D}\right) t'\right] dt'. \quad (2)$$

After chirp compensation in the second phase modulation stage, the temporal output becomes a scaled version of the spectral input:

$$v(t) = \sqrt{\frac{i}{2\pi D}} U\left(\frac{t}{D}\right) \quad (3)$$

Taking the Fourier transform of (3) then yields the output spectrum $V(\omega)$:

$$V(\omega) = \sqrt{i 2\pi D} u(-\omega D), \quad (4)$$

which is a scaled version of the temporal input. Unlike the partial OFT schemes, this configuration enables

TABLE I
COMPARISON OF DIFFERENT OFT CONFIGURATIONS

OFT Configurations	Achievable conversion(s)	Residual chirp or dispersion	Guard interval requirement
D-K	Time→Frequency	Dispersion	Large
K-D	Frequency→Time	Chirp	small
D-K-D	Time→Frequency Frequency→Time	No	Large
K-D-K	Frequency→Time Time→Frequency	No	small

Fig. 5. (a) The waveform of the 160 Gbit/s OTDM DPSK signal, (b) and the waveform of the chirped rectangular pump pulses for FWM.

blue path. The experimental setup is shown in Fig. 4. An SC signal is generated by a 10 GHz mode-locked laser and a 400 m dispersion-flattened highly non-linear fiber (DF-HNLF). The SC signal is filtered into 1.7 ps wide pulses with a flat-top spectrum using a WSS, which then undergoes DPSK modulation and OTDM multiplexing, resulting in a 160 Gbit/s OTDM-DPSK signal centered at 1551 nm with a guard interval of 44 ps between each group of the 16 tributaries. The guard interval is generated optically as part of the OTDM multiplexing. The waveform of the 160 Gbit/s OTDM DPSK signal is shown in Fig. 5(a). The generated OTDM data signal is launched into a complete OFT for OTDM to OFDM conversion. A simple D-K configuration is used for complete OFT as the

input pulse width is narrow enough to satisfy the condition $|\delta t_0^2/2D| \ll 1$. The quadratic phase modulation is implemented based on a four-wave mixing (FWM) process in a highly nonlinear fiber (HNLF) using linearly chirped rectangular pump pulses [13]. As the first step of the OFT process, the 160 Gbit/s OTDM signal is dispersed in 2 km SSMF, resulting in overlapping 160 ps flat-top linearly-chirped pulses. The quadratic phase modulation and pulse shaping are simultaneously achieved in a FWM process (HNLF1) using 80-ps linearly chirped rectangular pump pulses (1561 nm), obtained through filtering by a WSS and propagation in 4 km SSMF. Fig. 5(b) shows the waveform of the chirped rectangular pump pulses. Fig. 6(a) shows the spectrum after FWM. The center part of the idler is the 16-subcarrier OFDM spectrum with 12.5 GHz channel spacing. The empty bands in the idler spectrum originate from the 44 ps guard-intervals in the OTDM signal. A zoom-in of the obtained OFDM spectrum is shown in Fig. 6(b). Spectra obtained for individual OFDM subcarrier are also shown in Fig. 6(b), where the characteristic sinc-shape can be observed. The spectrum of a single 12.5 GHz sinc subcarrier is shown in Fig. 6(c). To compare with one of the most proven all-optical approaches [19], a subcarrier generated by a WSS (Finisar Waveshaper) that has been used for 28×10 Gbit/s all optical OFDM generation [24] is shown, in addition to an ideal sinc profile with roll-off $\alpha=0.3$. It can be seen that the spectrum out of the WSS is distorted due to the limited frequency resolution, whereas a close to ideal 12.5 GHz OFDM subcarrier is obtained using OFT, indicating a better performance for the generation of narrow OFDM subcarriers.

In addition, it has been proposed that an OFDM signal can also be generated all-optically from a WDM signal [21]. The principle is shown in Fig. 7. As described above, an OFDM signal can be generated from either a Nyquist-OTDM signal (S21) or an OTDM signal with a flat-top spectrum (S22). These two kinds of signals (S21, S22) can in turn be generated from a WDM signal (S02) using an extra OFT, and thus two additional approaches to generate an OFDM signal are obtained. One (indicated by red arrows) is intermediately converting a WDM signal to a Nyquist-OTDM signal (S21) using a rectangular temporal waveform shaper followed by a complete OFT, and then converted to an OFDM signal using another OFT. This

Fig. 6. Results of all-optical OFDM generation: (a) output spectrum of the FWM, (b) obtained OFDM spectrum and individual sinc-shaped subcarriers for different input OTDM tributaries, (c) spectrum of a single 12.5 GHz sinc subcarrier, a subcarrier generated by WSS and an ideal sinc shape with $\alpha=0.3$.

Fig. 7. Principle of OFDM signal generation based on time-domain OFT from a WDM signal using two equivalent approaches (red and blue).

Fig. 8. (a) Principle of all-optical OFDM demultiplexing using time-lens based OFT, (b) experimental setup of a 160 Gbaud all-optical OFDM receiver using time lens based OFT.

approach can also be described as rectangular temporal waveform shaper followed by a spectral compressor. The other one (indicated by blue arrows) is intermediately converting a WDM signal to an OTDM signal with a flat-top spectrum (S22) using a complete OFT, and then converted to an OFDM signal using another OFT, followed by a rectangular temporal waveform shaper. This approach can also be described as a spectral compressor followed by a rectangular temporal waveform shaper. These schemes may provide simple approaches that can greatly enhance the spectral efficiency of existing commercial WDM systems.

B. All-optical OFDM receivers

The subcarriers of the OFDM signal are equidistantly spaced, thus overlapping with a frequency null-point at all other subcarriers as shown in Fig. 1(a). For the demultiplexing, it is important to note that the individual OFDM subcarrier cannot simply be extracted by optical bandpass filtering as in traditional WDM systems, since this would imply a large penalty due to the crosstalk from the spectrally overlapping neighbor subcarriers. Previously the OFDM subcarriers were demultiplexed either in the electrical domain using DSP [3], or in the optical domain using ODFT based on various structures of optical splitters, delays, phase-shifters and time-gates

Fig. 9. Results of all-optical OFDM demultiplexing, (a) output FWM spectrum of HNL2, (b) obtained Nyquist-OTDM like signal, (c) and the waveform of a single Nyquist tributary.

Fig. 10. (a) BER measurements of 16 OFDM subcarriers (10 Gbit/s DPSK) after 100 km transmission, (b) Receiver power sensitivities at $\text{BER} = 10^{-9}$ B2B and after 100 km.

[17]–[19]. In this section, we introduce a new all-optical OFDM demultiplexing scheme using time lens based OFT [20]. The principle is shown in Fig. 8(a). To receive an OFDM signal, a partial time lens based OFT is sufficient to frequency-to-time convert the OFDM signal into a Nyquist-OTDM like signal, which has sinc-shaped waveforms and non-square spectrum. The Nyquist-OTDM like signal is subsequently time-demultiplexed by sampling each subcarrier at the intersymbol interference (ISI) free point using a narrow optical sampling gate [5]. Finally, the demultiplexed signal is detected using a base rate receiver.

In the experimental demonstration, a 16-subcarrier 160 Gbit/s OFDM signal is obtained from an OFT based all optical OFDM transmitter that has been introduced in section 3A. The experimental setup is shown in Fig. 8(b). The generated 160 Gbit/s OFDM signal was transmitted over a 100 km dispersion-managed fiber-link consisting of super large area fiber (SLA) and inverse dispersion fiber (IDF). In the receiver, a time lens based OFT, achieved in a FWM process (HNL2), is used for the OFDM to Nyquist-OTDM conversion, and a nonlinear optical loop mirror (NOLM) is employed for the 10 GHz optical sampling using 1.1 ps wide control pulses. The FWM pump pulses (1561 nm) and NOLM control-pulses (1566 nm) are obtained via spectral broadening in DF-HNLs and spectral filtering. The output FWM spectrum of HNL2 is shown in Fig. 9(a). The idler at 1551 nm is extracted by an OBF and propagated through 3.6 km SSMF, resulting in the 160 Gbaud Nyquist-OTDM like signal as shown in Fig. 9(b). The tributary spacing is 6 ps, and the sinc-shaped waveform of a single tributary can be observed in Fig. 9(c). The ISI-free position of each tributary is sampled out using the NOLM, and the BER of each tributary (subcarrier) is measured in a 10-Gbit/s pre-amplified DPSK receiver. The BER performance is shown in Fig. 10(a). The 100-km 160 Gbit/s OFDM transmission is successful with $\text{BER} < 10^{-9}$ performance for all 16 subcarriers. Fig. 10(b) shows the receiver sensitivities of all channels at $\text{BER} = 10^{-9}$ for the 100-km transmission, and for the back-to-back (B2B) system. The average transmission penalty is 1.6 dB, which is mainly attributed to additional jitter in the clock recovery from the OFDM signal.

Fig. 11. Principle of an all-optical OFDM receiver using time lens based spectral magnification and optical bandpass filtering.

Furthermore, another all-optical OFDM demultiplexing scheme using time lens based spectral magnification has been demonstrated [23], which allows for the direct detection of all subcarriers without using temporal sampling gates, further reducing the complexity of the system. The principle is shown in Fig. 11. The first OFT converts the OFDM spectrum to a Nyquist-OTDM like signal (frequency-to-time conversion), and the second OFT converts it back to the spectral domain (time-to-frequency conversion). The magnification factor is determined by the ratio of the two employed chirp rates K . The magnified spectrum enables reduced intercarrier interference when using OBFs to extract the subcarriers. This scheme has been used for all-optical demultiplexing of a 28-subcarrier, 280 Gbit/s OFDM signal [24].

C. Conversion from DWDM to Nyquist-OTDM

The Nyquist-OTDM technique takes advantage of time domain orthogonality, allowing the signal bandwidth to be reduced to the symbol rate without ISI, enabling terabit-per-second transmission with high SE [8]. Recently, a novel dense WDM (DWDM) to a single Nyquist channel (Nyquist-OTDM) conversion scheme based on complete OFT and optical Nyquist filtering has been proposed [25]. The principle is shown in Fig. 12(a). The DWDM channels with flat-top temporal waveforms are bit-wise synchronized. A complete OFT using a K-D-K configuration is then applied to exchange the temporal and spectral profiles of the input DWDM signal, resulting in an OTDM signal with tributary spacing of $\Delta T = 2\pi\Delta f/K$. To achieve maximum SE, the OTDM

Fig. 12. (a) Principle of DWDM signal to a single Nyquist channel conversion, (b) conversion from a 16x10 Gbit/s DPSK, 50-GHz spacing DWDM signal to a 160 Gbit/s Nyquist channel with 166 GHz total bandwidth, inset is the temporal waveform, (c) BER measurements for all 16 demultiplexed Nyquist-OTDM tributaries.

channel spacing ΔT is set equal to $1/f_s$, where f_s is the OTDM symbol rate. A rectangular OBF (Nyquist filtering) with bandwidth $BW = 1/\Delta T$ is then used to filter the center of the overlapping spectra, resulting in a Nyquist-OTDM signal with sinc-shaped tributaries. In the experimental demonstration, a 16x10 Gbit/s DPSK, 50-GHz spacing DWDM signal was successfully converted to a 160 Gbit/s Nyquist-OTDM signal with 166 GHz total bandwidth as shown in Fig. 12(b), thus increasing the SE from 0.2 to 0.96 symbol/s/Hz. This indicates

Fig. 13. (a) The principle of all-optical OFDM to Nyquist-WDM conversion, (b) and experimental setup for conversion of an 8-subcarrier 640 Gbit/s OFDM super-channel to eight 80-Gbit/s Nyquist-WDM channels.

that the total transmission capacity can be improved by a factor of ~ 5 . The Nyquist-OTDM signal is subsequently received by optical sampling using a NOLM based narrow time-gate. Fig. 12(c) shows the BER measurements for all 16 demultiplexed Nyquist-OTDM tributaries, where error-free operation ($BER < 10^{-9}$) is achieved for all tributaries. The average power penalty was only 1.4 dB for the full system. This technique has the potential to provide a simple and economical solution to upgrade commercial DWDM systems.

D. Conversion from OFDM to Nyquist-WDM

Spectrally-efficient signals such as OFDM, Nyquist-WDM and Nyquist-OTDM have been intensely investigated for next generation commercial communication systems. If employed side by side, it may be very important to have an efficient tool for converting signals between these systems. However, such functionality has not previously been possible unless complex OEO conversion and DSP are used, which may further increase the complexity, power-consumption and cost. Recently, a novel all-optical ultra-high-speed OFDM to Nyquist-WDM conversion scheme based on complete OFT has been proposed [15]. This scheme is essentially simple, and the implementation complexity does not scale with the number of OFDM subcarriers. The principle is shown in Fig. 13(a). As the OFDM and Nyquist-WDM are equivalent when exchanging the temporal and spectral profiles, they are the ideal candidates for complete OFT processing. The experimental setup is shown in Fig. 13(b). An 8-subcarrier 640 Gbit/s differential phase-shift keying (DPSK) OFDM super-channel is generated by an all-optical OFDM transmitter, based on rectangular temporal gating and OTDM technique. A complete OFT with a K-D-K configuration is used for the OFDM to Nyquist-WDM conversion. In the receiver, the eight converted 80-Gbit/s

Fig. 14. (a) Optical spectra of the original OFDM signal and individual subcarriers (top) and of the output Nyquist WDM signal (bottom), (b) receiver sensitivities at $\text{BER}=10^{-9}$ of all converted Nyquist-WDM channels. Nyquist-WDM channels are received by WDM demultiplexing using a rectangular filter, followed by optical sampling using a NOLM. The experimental results are shown in Fig. 14. A 640 Gbit/s OFDM signal was successfully converted to eight Nyquist-WDM channels as shown in Fig. 14(a), achieving $\text{BER} < 10^{-9}$ performance for all channels. Fig. 14(b) shows the corresponding receiver sensitivities at $\text{BER} = 10^{-9}$. The SE remains unchanged at 0.8 symbol/s/Hz after conversion. To the best of our knowledge, this is the first and only demonstration of OFDM to Nyquist-WDM conversion. In principle, such an OFT-based technique can also be employed for Nyquist-WDM to OFDM conversion. It could therefore provide a simple and energy-efficient link between spectrally-efficient OFDM and Nyquist-WDM systems.

IV. DISCUSSIONS AND CONCLUSION

Time lens based optical Fourier transformation has a wide range of applications, including distortion-less transmission, ultrafast optical oscilloscopes and optical format conversion between the time and frequency domains. In this paper, we have reviewed our recent progress in advanced all-optical processing of spectrally-efficient signals using time lens based OFT. A novel time lens based complete OFT technique for advanced processing of OFDM, Nyquist-WDM and Nyquist-OTDM signals has been introduced, and various demonstrations have been reviewed. Time lens based OFT has the benefit of enabling broadband ultrafast advanced OSP, which allows for the handling of a much larger number of channels, and also higher channel symbol rates in real-time. The implementation complexity does not increase with the number of channels, as opposed to the DSP approach. The same set-up can be used for any number of channels, as long as the total signal bandwidth can be accommodated by the time lenses.

This technique might enable even more complex signal processing applications, and become a very important enabling technology for future energy- and spectrally- efficient optical communication systems.

To realize higher spectrally-efficient communication system and networks, the capability to adapt the higher-level modulation format is very important. As the time lens based OFT in principle only exchanges the signal temporal and frequency profiles, the phase and amplitude information is preserved. Hence, the time lens is transparent to the data format. For example, a FWM-based OFT has been used to demonstrate OTDM-to-WDM conversion of a 320-GBd 16QAM signal [26]. Previously, time lenses have been demonstrated based on electro-optic phase modulation or nonlinear effects such as cross-phase modulation (XPM) or FWM [27]. The electro-optic approach provides a simpler configuration with lower loss, but the low PM index and the impurely quadratic phase modulation limits the performance of such a scheme. Using XPM based on parabolic pump pulses is the most straightforward all-optical approach to quadratic phase modulation, but the parabolic pump shape may become distorted due to self-phase modulation. The most suitable approach for spectrally efficient applications is FWM based on chirped pump pulses, which can achieve a large and purely quadratic phase-modulation. However, the phase noise of the pump is transferred to the signal in the FWM process, potentially limiting the performance for advanced signal modulation formats. Additionally, as a platform for time lens based OSP, nonlinear silicon photonics becomes more appealing, due to its integration potential with electronics, low cost, broad operation bandwidth and high space- and energy-efficiency. Silicon photonic integration will make time lens based all-optical signal processing more attractive for the future energy- and spectrally-efficient communication systems.

ACKNOWLEDGMENT

The authors would like to thank OFS Denmark for supplying the nonlinear fibers and H. C. Hansen Mulvad for his great contributions. This work is supported by FTP project LENS-COM (ref. DFF-5054-00184), FTP-TOR project (ref.no. 0602-02398B), the DFF Sap. Aude Adv. Grant NANO-SPECs (DFF-4005-00558B) and the DNRF Research Centre, SPOC (ref. DNRF123).

REFERENCES

- [1] Peter J. Winzer, "Scaling optical fiber networks: challenges and solutions," *Optics & Photonics News*, vol. 26, no. 3, pp. 28-35, March 2015.
- [2] T. Morioka, "New generation optical infrastructure technologies: "EXAT initiative" towards 2020 and beyond," in *Proc. Opto Electronics and Communications Conference (OECC2009)*, paper FT4, July 2009.
- [3] A. Lowery and J. Armstrong, "Orthogonal-frequency-division multiplexing for dispersion compensation of long-haul optical systems," *Opt. Express*, vol. 14, no. 6, pp. 2079-2084, March 2006.
- [4] G. Bosco, V. Curri, A. Carena, P. Poggiolini, and F. Forghieri, "On the performance of Nyquist-WDM terabit superchannels based on

- PM-BPSK, PM-QPSK, PM-8QAM or PM-16QAM subcarriers," *J. Lightwave Technol.*, vol. 29, no. 1, pp. 53-61, January 2011.
- [5] M. Nakazawa, T. Hirooka, P. Ruan, and P. Guan, "Ultrahigh-speed "orthogonal" TDM transmission with an optical Nyquist pulse train," *Opt. Express*, vol. 20, no. 2, pp. 1129-1140, January 2012.
- [6] X. Liu, S. Chandrasekhar, P. J. Winzer, T. Lotz, J. Carlson, J. Yang, G. Cheren, and S. Zederbaum, "1.5-Tb/s guard-banded superchannel transmission over 56x 100-km (5600-km) ULAF using 30-Gbaud pilot-free OFDM-16QAM signals with 5.75-b/s/Hz net spectral efficiency," in *Proc. European Conf. Optical Communication (ECOC2012)*, PDP, Th.3.C.5, September 2012.
- [7] R. Cigliutti, A. Nespola, D. Zeolla, G. Bosco, A. Carena, V. Curri, F. Forghieri, Y. Yamamoto, T. Sasaki, and P. Poggiolini, "Ultra-long-haul transmission of 16x112 Gb/s spectrally-engineered DAC-generated Nyquist-WDM PM-16QAM channels with 1.05x(symbol-rate) frequency spacing," in *Proc. Optical Fiber Communication Conference, (OFC 2012)*, paper OTh3A3, March 2012.
- [8] D. O. Otuya, K. Kasai, T. Hirooka, and M. Nakazawa, "Single-channel 1.92 Tbit/s, 64 QAM coherent Nyquist orthogonal TDM transmission with a spectral efficiency of 10.6 bit/s/Hz," *J. Lightwave Technol.*, vol. 34, no. 2, pp. 768-775, January 2016.
- [9] H. C. H. Mulvad, E. Palushani, H. Hu, H. Ji, M. Galili, A. T. Clausen, P. Jeppesen, and L. K. Oxenløwe, "Recent advances in ultra-high-speed optical signal processing," in *Proc. European Conf. Optical Communication (ECOC2012)*, paper Tu1A5, September 2012.
- [10] B. H. Kolner and M. Nazarathy, "Temporal imaging with a time lens," *Opt. Lett.*, vol. 14, no. 12, pp. 630-632, June 1989.
- [11] A. W. Lohmann and D. Mendlovic, "Temporal filtering with time lenses," *Appl. Opt.*, vol. 31, no. 29, pp. 6212-6219, October 1992.
- [12] M. Nakazawa, T. Hirooka, F. Futami and S. Watanabe, "Ideal distortion-free transmission using optical Fourier transformation and Fourier transform-limited optical pulses", *IEEE Photon. Technol. Lett.*, vol. 16, no. 4, pp. 1059-1061, April 2004.
- [13] M. A. Foster, R. Salem, D. F. Geraghty, A. C. Turner-Foster, M. Lipson, and A. L. Gaeta, "Silicon-chip-based ultrafast optical oscilloscope," *Nature*, vol. 456, pp. 81-84 September 2008.
- [14] H. C. H. Mulvad, E. Palushani, M. Galili, J. Xu, H. Hu, A. Clausen, L. Oxenløwe, and P. Jeppesen, "OTDM-WDM conversion based on timedomain optical Fourier transformation with spectral compression", *Optical Fiber Communication Conference, (OFC 2011)*, paper OThN2, March 2011.
- [15] P. Guan, K. M. Røge, H. C. H. Mulvad, M. Galili, H. Hu, M. Lillieholm, T. Morioka, and L. K. Oxenløwe, "All-optical ultra-high-speed OFDM to Nyquist-WDM conversion based on complete optical Fourier transformation," *J. Lightwave Technol.*, vol. 34, no. 2, pp. 626-632, January 2016.
- [16] D. Hillerkuss, R. Schmogrow, T. Schellinger, M. Jordan, M. Winter, G. Huber, T. Vallaitis, R. Bonk, P. Kleinow, F. Frey, M. Roeger, S. Koenig, A. Ludwig, A. Marculescu, J. Li, M. Hoh, M. Dreschmann, J. Meyer, S. Ben Ezra, N. Narkiss, B. Nebendahl, F. Parmigiani, P. Petropoulos, B. Resan, A. Oehler, K. Weingarten, T. Ellermeyer, J. Lutz, M. Moeller, M. Huebner, J. Becker, C. Koos, W. Freude, and J. Leuthold, "26 Tbit/s line-rate super-channel transmission utilizing all-optical fast Fourier transform processing," *Nat. Photon.*, vol. 5, pp. 364-371, May 2011.
- [17] D. Hillerkuss, M. Winter, M. Teschke, A. Marculescu, J. Li, G. Sigurdsson, K. Worms, S. Ben Ezra, N. Narkiss, W. Freude, and J. Leuthold, "Simple all-optical FFT scheme enabling Tbit/s real-time signal processing," *Opt. Express*, vol. 18, no. 9, pp. 9324-9340 April 2010.
- [18] A. J. Lowery, and L. Du, "All-optical OFDM transmitter design using AWGRs and low-bandwidth modulators," *Opt. Express* vol. 19, no. 17, pp. 15696-15704, August 2011.
- [19] J. Schröder, L. B. Du, J. Carpenter, B. J. Eggleton, and A. J. Lowery, "All-optical OFDM with cyclic prefix insertion using flexible wavelength selective switch optical processing," *J. Lightwave Technol.*, vol. 32, no. 4, pp. 752-759, Feb. 2014.
- [20] P. Guan, D. Kong, K. M. Røge, H. C. Hansen Mulvad, M. Galili, and L. K. Oxenløwe, "Real-time all-optical OFDM transmission system based on time-domain optical Fourier transformation." *Optical Fiber Communication Conference (OFC 2014)*, paper W4F.1, March 2014.
- [21] P. Guan, H.C. H. Mulvad, L. K. Oxenlowe, "All-optical orthogonal frequency division multiplexing (OFDM) transmitter" IPC No. H04J 14/00 A I. Patent No. EP2916472.
- [22] E. Palushani, L. K. Oxenlowe, M. Galili, H. Mulvad, A. T. Clausen, and P. Jeppesen, "Flat-top pulse generation by the optical Fourier transform technique for ultrahigh speed signal processing," *IEEE J. Quantum Electron.* vol. 45, no. 11, pp. 1317-1324, November 2009.
- [23] E. Palushani, H. C. Hansen Mulvad, D. Kong, P. Guan, M. Galili, and L.K. Oxenløwe, "All-optical OFDM demultiplexing by spectral magnification and band-pass filtering," *Opt. Express* vol. 22, no. 1, pp. 136-144 December 2014.
- [24] P. Guan, S. Lefrancois, M. Lillieholm, H. C. Hansen Mulvad, K. M. Røge, H. Hu, J. Schroeder, B. J. Eggleton, Z. Geng, A. J. Lowery, T. Morioka, L. K. Oxenløwe, "All-optical OFDM system using a wavelength selective switch based transmitter and a spectral magnification based receiver." *European Conference and Exhibition on Optical Communication (ECOC 2014)*, paper Tu.3.6.2, September 2014.
- [25] P. Guan, K. M. Røge, H. C. Hansen Mulvad, H. Hu, T. Morioka, L. K. Oxenløwe, "Conversion of a DWDM signal to a single Nyquist channel based on a complete optical Fourier transformation." *European Conference and Exhibition on Optical Communication (ECOC 2014)*, paper We.2.5.5, September 2014.
- [26] E. Palushani, T. Richter, R. Ludwig, C. Schubert, H. C. H. Mulvad, A. Clausen, and L. Oxenløwe, "OTDM-to-WDM conversion of complex modulation formats by time-domain optical Fourier transformation," *Optical Fiber Communication Conference, (OFC 2012)*, paper OTh3H.2, March 2012.
- [27] R. Salem, M. A. Foster, and A. L. Gaeta, "Application of space-time duality to ultrahigh-speed optical signal processing," *Adv. Opt. Photon.*, Vol. 5, no. 3, pp. 274-317, August 2013.

Pengyu Guan

Kasper Meldgaard Røge

Mads Lillieholm

Michael Galili

Hao Hu

Toshio Morioka

Leif Katsuo Oxenløwe