

# Full-shipload tramp ship routing and scheduling with variable speeds

Wen, M.; Røpke, Stefan; Petersen, Hanne Løhmann; Larsen, Rune; Madsen, Oli B.G.

Published in: Computers and Operations Research

Link to article, DOI: 10.1016/j.cor.2015.10.002

Publication date: 2016

Document Version Peer reviewed version

Link back to DTU Orbit

*Citation (APA):* Wen, M., Røpke, S., Petersen, H. L., Larsen, R., & Madsen, O. B. G. (2016). Full-shipload tramp ship routing and scheduling with variable speeds. *Computers and Operations Research*, *70*, 1-8. https://doi.org/10.1016/j.cor.2015.10.002

#### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- · You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Full-Shipload Tramp Ship Routing and Scheduling with Variable Speeds

M. Wen<sup>a,\*</sup>, S. Ropke<sup>b</sup>, H. L. Petersen<sup>c</sup>, R. Larsen<sup>c</sup>, O. B.G. Madsen<sup>c</sup>

<sup>a</sup>Xi'an Jiaotong–Liverpool University, 111 Ren Ai Road, Suzhou Industrial Park, Suzhou, Jiangsu, 215123, China <sup>b</sup>Department of Management Engineering, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark <sup>c</sup>Department of Transport, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark

# Abstract

This paper investigates the simultaneous optimization problem of routing and sailing speed in the context of full-shipload tramp shipping. In this problem, a set of cargoes can be transported from their load to discharge ports by a fleet of heterogeneous ships of different speed ranges and load-dependent fuel consumption. The objective is to determine which orders to serve and to find the optimal route for each ship and the optimal sailing speed on each leg of the route so that the total profit is maximized. The problem originated from a real-life challenge faced by a Danish tramp shipping company in the tanker business. To solve the problem, a three-index mixed integer linear programming formulation as well as a set packing formulation are presented. A novel Branch-and-Price algorithm with efficient data preprocessing and heuristic column generation is proposed. The computational results on the test instances generated from real-life data show that the heuristic provides optimal solutions for small test instances and near-optimal solutions for larger test instances in a short running time. The effects of speed optimization can improve the total profit by 16% on average and the fuel price has a significant effect on the average sailing speed and total profit.

Keywords: tramp shipping, speed optimization, heuristic column generation

# 1 1. Introduction

Sea shipping is one of the most important transportation modes especially for large-volume goods
 between continents. It is estimated that sea cargo is responsible for around 80% of global trade by
 volume and over 70% by value, and these percentages are even higher in most developing countries
 (UNCTAD 2013). Among the various operational costs of sea shipping, fuel cost accounts for a large
 proportion. For example, in a liner shipping company, bunker cost can be around 50% (Notteboom 2006)

Preprint submitted to Elsevier

<sup>\*</sup>Corresponding author

Email address: min.wen@xjtlu.edu.cn (M. Wen)

or even above 60% (Golias et al. 2009) of the total operational cost. In addition, the large consumption of fuel results in significant  $CO_2$  and  $NO_x$  emissions, which have recently attracted media attention for their negative impacts on climate change and air pollution. According to the International Maritime Organization (Buhaug et al. 2009),  $CO_2$  emissions from the maritime sector in 2007 has increased by 86% compared to 1990 and accounted for 3.3% of the world's total emissions. These emissions are expected to continue to increase by 150-250% in 2050 if no action is taken.

The fuel cost, and consequently CO<sub>2</sub> emissions, are strongly dependent on the sailing speed. Ryder and Chappell (1980) and Ronen (1982) showed that a cubic function can describe the relationship between fuel consumption and speed. The ocean conservation group OCEANA states: "Reducing commercial ship speeds, by only a few knots, yields salutary results for both shipping companies and the environment." (OCEANA 2008). Therefore optimizing sailing speed in order to reduce fuel cost and CO<sub>2</sub> emissions is an important issue to investigate.

Speed optimization for shipping routes has attracted some attention recently. For liner shipping, most 19 of the previous work focuses on optimizing the speed for one or several fixed route(s) (Corbett et al. 2009, 20 Ronen 2011, Lindstad et al. 2011 and Wang and Meng 2012). In these studies, the sailing speed is treated 21 as a variable, which not only determines the fuel consumption but also determines the required ship 22 and/or fleet size to maintain the given service frequency. The yearly profit is expressed as a function of 23 sailing speed, and the optimal sailing speed is obtained when the marginal profit equals zero. Both Ronen 24 (2011) and Corbett et al. (2009) concluded that when the fuel price is increased, the optimal speed is 25 likely to be reduced when maximizing the profit. This reduction of speed also leads to a reduction of  $CO_2$ 26 emissions. Wang and Meng (2012) dealt with the problem of finding the optimal route for containers and 27 the optimal speed for the ships given fixed shipping routes and origin-destination pair of each container. 28 They proposed an outer-approximation method, which uses piecewise-linear functions to approximate 29 the fuel consumption as a function of speed within a predetermined tolerance level. 30

In contrast to liner shipping, tramp shipping does not consider service frequency. A ship can sail at 31 different speeds on different sailing legs of a route. The objective of tramp shipping is to minimize the 32 total cost or maximize the total profit for transporting cargoes. Fagerholt et al. (2010) considered the 33 problem of optimizing the speed on each leg of a single fixed route. Gatica and Miranda (2011) and 34 Norstad et al. (2011) studied simultaneous routing and speed optimization for a full-shipload problem 35 and a less-than-shipload problem respectively. In Fagerholt et al. (2010), the sequence of ports and the 36 time window of visiting each port on a given route are fixed. Three models were presented for solving the 37 problem. The first two models are non-linear models, where the speed is a continuous variable between 38 a minimum and a maximum, and the fuel consumption per distance unit is expressed as a quadratic 39

function of speed. The third model discretizes the time window and converts the problem into a shortest 40 path problem on an acyclic graph. These models were tested on data with up to 16 ports and 10-day 41 time window. It was shown that, compared to the continuous model, the discrete model is able to provide 42 quality solution within short computational time. Gatica and Miranda (2011) applied the same idea of 43 discretized time window to the solution of a full-shipload routing and speed optimization problem. They 44 tested their method on generated data instances with up to 15 discretized time-window points, 50 cargoes 45 and 9 ships. Norstad et al. (2011) formulated the less-than-shipload routing and speed optimization 46 problem as a pickup and delivery problem with an extra continuous decision variable for the speed on 47 each leg. They proposed a recursive smoothing algorithm for determining the optimal speed for a given 48 route, which is shown to be superior to the discretization of arrival time presented in Fagerholt et al. 49 (2010). To solve the routing and speed optimization simultaneously, they proposed a multi-start local 50 search heuristic and tested it on data with up to 10-day time windows. 51

The problem of routing and scheduling for tramp shipping is very similar to the well-know vehicle 52 routing problem (Eksioglu et al. (2009), Laporte et al. (2013)), which has been studied intensively in the 53 literature. Christiansen et al. (2007) and Christiansen et al. (2013) gave a good overview of maritime 54 transportation and present different models for routing and scheduling of both tramp and liner ships. A 55 few variations of tramp shipping problems have also been addressed in the previous work. Gatica and 56 Miranda (2011) studied a full-shipload problem, where each cargo corresponds to a full-shipload and a 57 ship can only carry one cargo at a time as mentioned above. Brønmo et al. (2007a), Korsvik et al. (2010), 58 Lin and Liu (2011) and Norstad et al. (2011) studied the less-than-shipload problem, in which several 59 cargoes are allowed to be onboard at the same time. The cargo size is fixed in their studies. Brønmo 60 et al. (2007b), Korsvik and Fagerholt (2010) and Brønmo et al. (2010) allowed the shipping company to 61 choose the quantity of each cargo to be transported, and therefore the delivery quantity becomes a variable 62 between given upper and lower bounds. In Henrik et al. (2011), Korsvik et al. (2011) and Stålhane et al. 63 (2012), a single cargo can be split between multiple ships. 64

The work described in this paper originated from a routing and scheduling problem encountered 65 by a large Danish product tanker shipping operator, who transports oil products in full-shipload mode. 66 The shipping operator has a fleet of heterogeneous ships with different sizes and fuel consumptions. It 67 receives cargo orders from the customers, each of which has a specific pickup port, a delivery port and a 68 time window within which the cargo should be picked up. The operater needs to decide whether to accept 69 the cargo, which ship should pickup the cargo at what time, and at which speed each ship should sail 70 on each leg in order to maximize the overall profit. This problem is similar to the full-shipload routing 71 and speed optimization problem considered in Gatica and Miranda (2011). The difference is that, in 72

our problem, the fuel consumption of each ship depends individually on the sailing speed and the load 73 of the ship, i.e., whether the ship is loaded (laden) or empty (ballast); whereas, in Gatica and Miranda 74 (2011), the fuel consumption only depends on the speed. To the best of the authors' knowledge, the load 75 dependent fuel consumption has not been considered in the literature. In addition, Gatica and Miranda 76 (2011) did not propose any tailored solution method but relied on solving the models using an IP solver. 77 We have formulated two mathematical models for the problem, developed a Branch-and-Price (B&P) 78 algorithm with heuristic column generation, and tested the proposed algorithm on instances generated 79 from real-life data. The computational results show that the branch-and-price heuristic produces optimal 80 or near-optimal solutions in relatively short time. 81

The main contribution of this paper is the proposed heuristic. The heuristic is able to find high quality solutions in short computation time. It clearly outperforms a commercial IP solver when it comes to computation time and size of the instances that can be handled. In terms of modeling, the present paper is one of the first to consider variable speeds in a tramp shipping planning context and it is the first to consider a load dependent fuel consumption. Although the modeling is greatly simplified by the assumption of full-vessel loads, the assumption itself is realistic. The company used as a case in this project does not carry multiple orders simultaneously on a single ship.

The remainder of the paper is organized as follows. Two mathematical formulations are presented in Section 2 and the heuristic B&P algorithm is described in Section 3. The computational results are given in Section 4, followed by conclusions in Section 5.

# 92 2. Mathematical Model

Our problem can be defined on the graph G = (N, A), where N is the set of all the nodes and A is the 93 set of feasible arcs in the graph. Let S denote the set of ships. Each ship  $s \in S$  starts from node o(s) and 94 ends at dummy node d(s). Let O and D denote the set of all origins and destinations of the ships. Let 95  $N_0$  denote the set of cargoes. As this is a full-shipload problem, each node  $i \in N_0$  corresponds to a cargo, 96 which is transported directly from its load port to discharge port, and is associated with a sailing distance 97  $g_i$  from the load port to the discharge port, a port service time  $t_i$  for loading and unloading the cargo and a 98 time window  $[a_i, b_i]$ , within which the cargo should start being loaded. For  $i \in O \cup D$ , we set  $g_i = 0, t_i = 0$ , 99  $a_i = 0$  and  $b_i = \max_{j \in N_0} \{b_j\}$ . The set of all the nodes is  $N = N_0 \cup O \cup D$ . Let  $N_i^+ = \{j : (i, j) \in A\}$  and 100  $N_i^- = \{j : (j,i) \in A\}$  be the set of nodes that can be reached from node *i* and can reach node *i* respectively. 101 The distance between two nodes i and j is denoted as  $d_{ij}$ , which is the distance from the discharge port 102 of cargo *i*, or the location of *i* if  $i \in O$ , to the load port of cargo *j*. For the dummy nodes  $j \in D$ , we set 103  $d_{ij} = 0$ , since we do not decide in advance where the ship should end its journey. The ships can sail at 104

different speeds. Let V denote the set of speeds and  $l^{v}$  the time of sailing one distance unit at speed  $v \in V$ . 105 The fuel consumption depends on the ship, the sailing speed and the load of the ship. Let  $e_s^{\nu}$  denote the 106 ballast fuel cost of ship s sailing one distance unit at speed v. Let  $c_{is}^{v}$  be the cost of ship s sailing one 107 distance unit at speed v with cargo i. It should be noted that  $c_{is}^{v}$  is determined by the light weight of the 108 ship s, the weight of cargo i and the speed. Examples of approximation functions of  $c_{is}^{v}$  can be found in 109 Psaraftis and Kontovas (2013). Due to the fact that the ships are different, not all the ships can serve all 110 the cargoes. For example, a small ship cannot carry a large cargo, and a large ship with deep draft cannot 111 serve a cargo with a shallow load or discharge port. Let binary variable  $p_{is}$  be 1 if is feasible for ship s to 112 serve cargo *i* and 0 otherwise. Let  $r_i^v$  be the reward of cargo *i* when served at speed *v*. 113

# 114 2.1. A Three-Index Formulation

Let binary variable  $x_{ijs}^{\nu}$  be 1 iff ship *s* sails from cargo node *i* to cargo node *j* at speed *v*, and let binary variable  $y_{is}^{\nu}$  be 1 iff ship *s* serves cargo *i* at speed *v*. Let variable  $z_{is}$  denote the time when ship *s* starts loading cargo *i*, and auxiliary variable  $w_{ijs}$  denote the time span of ship *s* from arriving at the loading port of cargo *i* to arriving at the loading port of cargo *j*. The mathematical model can be presented as follows:

$$\min \sum_{i \in N_0} \sum_{s \in S} \sum_{v \in V} c_{is}^v g_i y_{is}^v + \sum_{(i,j) \in A} \sum_{s \in S} \sum_{v \in V} e_s^v d_{ij} x_{ijs}^v - \sum_{i \in N_0} \sum_{s \in S} \sum_{v \in V} r_i^v y_{is}^v$$
(1)

120

subject to:

$$\sum_{j \in N_i^+} \sum_{s \in S} \sum_{v \in V} x_{ijs}^v \le 1 \qquad \qquad \forall i \in N_0$$
(2)

$$\sum_{j \in N_{o(s)}^+} \sum_{v \in V} x_{o(s)js}^v = 1 \qquad \forall s \in S$$
(3)

$$\sum_{j \in N_i^+} \sum_{\nu \in V} x_{ijs}^{\nu} - \sum_{j \in N_i^-} \sum_{\nu \in V} x_{jis}^{\nu} = 0 \qquad \qquad \forall i \in N_0, s \in S$$

$$(4)$$

$$\sum_{j \in N_{d(s)}^-} \sum_{v \in V} x_{jd(s)s}^v = 1 \qquad \qquad \forall s \in S$$
(5)

$$t_i + \sum_{v \in V} g_i l^v y_{is}^v + \sum_{v \in V} d_{ij} l^v x_{ijs}^v = w_{ijs} \qquad \forall (i,j) \in A, s \in S$$
(6)

$$z_{is} + w_{ijs} - M(1 - \sum_{v \in V} x_{ijs}^v) \le z_{js} \qquad \forall (i,j) \in A, s \in S$$

$$(7)$$

$$a_i \leq z_{is} \leq b_i \qquad \forall i \in N, s \in S$$
 (8)

$$\sum_{v \in V} y_{is}^v \le p_{is} \qquad \qquad \forall i \in N_0, s \in S \tag{9}$$

$$\sum_{j \in N_i^+} \sum_{\nu \in V} x_{ijs}^{\nu} = \sum_{\nu \in V} y_{is}^{\nu} \qquad \forall i \in N_0, s \in S$$
(10)

$$x_{ijs}^{\nu}, y_{is}^{\nu} \in \{0, 1\} \qquad \forall i, j \in N, \nu \in V, s \in S$$

$$(11)$$

$$z_{is} \ge 0 \qquad \qquad \forall i \in N, s \in S \tag{12}$$

$$w_{ijs} \ge 0 \qquad \qquad \forall i, j \in N, s \in S \tag{13}$$

122

The objective function (1) minimizes the sum of the transportation cost minus the total reward of the 123 served cargoes. It can also be reformulated as maximization of the total profit. It should be noted that 124 other ship costs, such as maintainance costs and crew salaries, are not considered in this work. Constraints 125 (2) ensure that each cargo is served by at most one ship at one speed. If a subset of the cargoes is 126 mandatory, we need to change the inequality in this constraint to an equality for those mandatory cargoes. 127 Constraints (3) to (5) are flow conservation constraints. Constraints (6) calculate the time span  $w_{iis}$ 128 of ship  $s \in S$  from the arrival at the loading port of cargo i to the arrival at the loading port of cargo 129 j, which is the sum of the loading and unloading time of cargo i, the sailing time between the load 130 and discharge ports of cargo i and the sailing time from cargo i to cargo j. Constraint (7) imposes 131 that if ship s sails from i to j, then  $z_{is} \ge z_{is} + w_{ijs}$ . Parameter M is a sufficiently large number, and 132 is set to  $b_i + (t_i + \max_{v \in V} g_i l^v + \max_{v \in V} d_{ij} l^v) - a_i$ . Constraints (8) are the time window constraints. 133 Constraints (9) ensure that each cargo can only be served by a compatible ship. Constraints (10) enforce 134 the relationship between x and y variables. Constraints (11), (12) and (13) define the variables. 135

In order to tighten and simplify the model, it is advantageous to only generate variables corresponding to arcs that are feasible. An arc (i, j) is infeasible, if  $b_j < a_i + t_i + (g_i + d_{ij}) \cdot l^{\nu_{\text{max}}}$ , where  $\nu_{\text{max}}$  corresponds to the highest possible speed.

This model is solved by CPLEX 12.5. The tests show that removing infeasible arcs reduces computational time significantly. For an instance with 100 cargoes, 20 ships and a 60-day planning horizon, the number of arcs in the graph and the computational time is reduced by 78% and 66% respectively. This is because our problem is a full-shipload problem and the service time of a cargo, including the loading time, transportation time from pickup to delivery and unloading time, is relatively long compared to the pickup time window. Further computational results will be presented in Section 4.

# 145 2.2. Set Packing Formulation

This problem can also be formulated as a Set Packing problem. Let  $P^s$  be the set of feasible routes for ship  $s \in S$ . Let  $c_p^s$  denote the cost of route p for ship s, calculated as the transportation cost minus the total reward of the cargoes served on the route. Let  $a_{ip}$  equal 1 if route p covers cargo i, and 0 otherwise. Let the binary variable  $y_p^s$  be 1 if route p is taken by ship s, and 0 otherwise. The problem can be formulated as follows:

151

$$\min \sum_{s \in S} \sum_{p \in P^s} c_p^s y_p^s \tag{14}$$

152

153 subject to

$$\sum_{s \in S} \sum_{p \in P^s} a_{ip} y_p^s \le 1 \qquad \forall i \in N_0$$
(15)

$$\sum_{p \in P^s} y_p^s \le 1 \qquad \qquad \forall s \in S \tag{16}$$

$$y_p^s \in \{0,1\} \qquad \forall p \in P^s, s \in S \tag{17}$$

154

The objective is to minimize the cost of the selected routes in such way that each cargo is covered by at most one ship and each ship is assigned to at most one route.

The LP relaxation of the set packing formulation will always provide the same or better lower bound compared to the LP relaxation of the three-index formulation.

#### 159 **3. Solution Method**

Solving the set packing model (14)–(17) by listing all possible ship routes in  $P^s$  for all  $s \in S$  and passing this problem to an IP solver seems impossible given the many possible routes for each ship and the many choices of sailing speeds for a single route. As a consequence, the model is solved using a heuristic branch-and-price algorithm (see e.g. Barnhart et al. 1998). The branch-and-price algorithm solves the linear programming (LP) relaxation of the problem (denoted as LP-SP in the following text), where (17) is replaced by

$$y_p^s \ge 0 \qquad \forall p \in P^s, s \in S.$$

This problem can be solved by column generation, where only a subset of the ship routes are firstly considered in the model and the rest of the routes that have the potential to improve the objective function are gradually generated and added to the model. Let  $\bar{P}^s$  be the restricted set of routes for ship *s*, which can be initialized by single-cargo routes. The restricted LP with the restricted sets  $\bar{P}^s$  is called *the master problem*. Solving the master problem gives dual variables  $\pi_i$  and  $\lambda^s$  corresponding to constraints (15) and (16), respectively. Using these dual variables, we can calculate the reduced cost of a path *p* for ship *s* as

 $\hat{c}_p^s = c_p^s - \sum_{i \in N_0} a_{ip} \pi_i - \lambda^s$ . If  $\hat{c}_p^s \ge 0$  for all  $s \in S$  and all  $p \in P^s$  (that is, considering all feasible routes), 172 then the current LP solution to the restricted problem is optimal for the full LP model. If there exist an 173  $s \in S$  and a  $p \in P^s$  such that  $\hat{c}_p^s < 0$  then the corresponding variable has a chance of producing improved 174 LP solution. It should be added to  $\bar{P}^s$  and the LP should be resolved to obtain new dual variables. Finding 175 the  $s \in S$  and  $p \in P^s$  that results in the lowest  $\hat{c}_p^s$  is done by solving a *pricing problem*. In our case the 176 pricing problem is an elementary shortest path problem with time windows and variable speeds. We solve 177 a problem for each ship  $s \in S$ , aiming at finding the cheapest path from o(s) to d(s) satisfying the time 178 windows. The information given by the dual variables is encoded in the arc costs of the shortest path 179 problem. More precisely, in the shortest path problem related to ship s, the cost  $\bar{c}_{ij}^{\nu_1\nu_2}$  of an arc (i, j) with 180 a traverse speed  $v_1$  on the laden part of the journey, i.e. the sailing distance between cargo i's load and 181 discharge ports, and speed  $v_2$  on the ballast part of the travel (from node *i* to node *j*) is set to 182

$$\bar{c}_{ij}^{\nu_1\nu_2} = \begin{cases} c_{is}^{\nu_1}g_i + e_s^{\nu_2} \cdot d_{ij} - \pi_i & \text{if } i \in N_0 \\ e_s^{\nu_2} \cdot d_{ij} - \lambda^s & \text{if } i = o(s) \end{cases}$$

By using these arc costs, it is easy to show that the cost of a path will equal the reduced cost of 184 the corresponding variable. The resource constrained shortest path problem is usually solved by using 185 labeling algorithms (Irnich and Desaulniers 2005). However, in this paper, we use a simple heuristic to 186 ensure that the computational time of the pricing problem is short even for large instances. The heuristic 187 is described in Section 3.2. Using a heuristic for solving the pricing problem implies that we do not know 188 if the algorithm has solved LP-SP to optimality. Even if the heuristic cannot find a path with negative cost, 189 we cannot rule out the existence of a path that could improve the current solution to LP-SP. However, the 190 algorithm proceeds as if we had solved the LP to optimality. If the LP relaxation only takes integer values, 191 the algorithm stops and outputs the solution. If some variables take fractional values, the algorithm will 192 branch in order to find an integer solution. We choose to branch on the arcs used in the subproblem, i.e., 193 whether the ships should use an arc or not. From an implementation point of view, it is handled in the 194 way described by Desrochers et al. (1992). 195

The algorithm uses strong branching in order to decide which arc to branch on. A number,  $\beta$ , of branching candidates are evaluated by enforcing the branch and computing the resultant improvement in the lower bounds ( $\Delta_1$  and  $\Delta_2$ ) in the two child nodes. Following Linderoth and Savelsbergh (1999), the algorithm chooses the branch that maximizes

$$\alpha \min{\{\Delta_1, \Delta_2\}} + (1 - \alpha) \max{\{\Delta_1, \Delta_2\}}$$

where  $0 \le \alpha \le 1$  is a parameter.

If the pricing problem were solved to optimality and the branch-and-bound algorithm were allowed to run until all relevant nodes in the search tree had been explored, it would either return the optimal solution or state that no feasible solution exists. Since the implemented algorithm only solves the pricing problem using a heuristic, we cannot guarantee that the optimal solution is found, but the solution quality is in general good as will be seen in Section 4.2.

After finishing the branch-and-bound search, the algorithm uses a generic IP solver to solve (14)– (17) using the generated columns. This can give improved solutions even when the branch-and-bound search has run to the end. This is because the heuristic branch-and-price algorithm can fathom a node erroneously due to the missing of an important column. If this column is generated at a later stage then solving the model with these additional generated columns may yield an improved solution.

#### 211 3.1. Preprocessing

The purpose of the preprocessing is to reduce the solution space by identifying incompatibilities between the cargoes. Two cargoes are incompatible if it is infeasible to serve them on the same route without violating their time windows, i.e.,  $a_i + T_{ij}^{\min} > b_j$  or  $a_j + T_{ji}^{\min} > b_i$ , where  $T_{ij}^{\min}$  denotes the minimum time required to serve cargo *i* and to travel from cargo *i* to cargo *j*. The first inequality states that cargo *j* can not be reached before the end of its time window even if a ship starts serving cargo *i* at the beginning of its time window, uses the minimum time to service cargo *i* and sail to cargo *j*. The second inequality describes the opposite. Any route that contains two incompatible cargoes is infeasible.

Let  $N_i^{\text{INF}}$  denote the set of cargoes that are incompatible with cargo *i* and  $|N_i^{\text{INF}}|$  the number of cargoes incompatible with *i*. Figure 1 shows  $|N_i^{\text{INF}}|$  for each cargo in an instance with 160 cargoes in a 90-day planning horizon. The cargoes (x-axis) are sorted by their  $|N_i^{\text{INF}}|$  in a non-decreasing order. As can be seen from the figure, for most of the cargoes, the number of incompatible cargoes is larger than 60, and there are 11 cargoes, with more than 100 incompatible cargoes. These cargoes are characterized by a long distance between the load and discharge port and long service time, which makes it difficult for other cargoes to fit in the same route.

The result of the preprocessing is used in solving the pricing problem. The pricing heuristic will never try to put two incompatible cargoes into the same route. This helps to reduce the solution space and shorten the computational time of solving the pricing problem. The tests show that, for an instance with 100 cargoes and 20 ships within a 60-day planning horizon, the proposed preprocessing can reduce the computational time by more than 80% (from 46 seconds to 9 seconds).

232



Figure 1: The number of incompatible cargoes for each cargo.

#### 233 3.2. Heuristic algorithm for solving the pricing problem

Our pricing heuristic method is described in Algorithm 1. It initially makes a random permutation of the ships, which determines the order of processing.

For each ship s, the algorithm tries to find a list of routes, R, with negative reduced cost by means 236 of an insertion heuristic. The insertion heuristic first initializes the route r with a seed cargo i (every 237 cargo is treated as a seed node). Let the set of nodes N' denote the remaining candidate cargoes to be 238 inserted,  $N' = N_0 \setminus \{\{i\} \cup N_i^{\text{INF}}\}$ . At each iteration, the algorithm attempts to insert every cargo  $j \in N'$  into 239 every possible position on route r at every possible speed on the sailing legs from the precedent cargo 240 to j, between the load and discharge ports of j, and from j to the successor cargo. The best cargo  $j^*$ 241 with the minimum insertion cost is selected for insertion and N' is updated by removing cargo  $j^*$  and its 242 incompatible cargoes. Whenever a node is inserted, the reduced cost of the resultant route r is updated. 243 If it is negative, then the route is added to R. Node insertion and updating of N' and R are repeated until 244 there are no nodes left in N'. The same insertion heuristic is repeated for every feasible seed cargo. If 245 the resultant route list R for ship s is not empty, the pricing heuristic stops, filters R by removing the 246 dominated routes in a heuristic way. Otherwise, the algorithm proceeds with the next ship, and repeats 247 the same procedure until it finds a ship, for which the route list R is not empty, or until all ships have been 248 tried. 249

Algorithm 1 Heuristic algorithm for the pricing problem.

1:	S: the set of ships sorted in a random order;							
2:	<i>R</i> : the list of routes to be added into the master problem;							
3:	$N_0$ : the set of all the cargoes							
4:	$N_i^{INF}$ : the set of cargoes that are incompatible with cargo <i>i</i> ;							
5:	$R \leftarrow \emptyset$							
6:	for (ship $s \in S$ ) do							
7:	for (seed cargo $i \in N_0$ ) do							
8:	Create an empty route $r$ for ship $s$							
9:	$N' \leftarrow N_0;$							
10:	if ( <i>i</i> can be inserted to <i>r</i> ) then							
11:	Insert <i>i</i> into route <i>r</i> ;							
12:	$N' \leftarrow N' ackslash \{i\} \cup N_i^{INF}\};$							
13:	if (r has negative reduced cost) then							
14:	Update <i>R</i> ;							
15:	while $N'$ is not empty <b>do</b>							
16:	$j^* \leftarrow$ Find the best node in $N'$ that can be inserted into r							
17:	if $j^*$ is empty then							
18:	$N' \leftarrow 0$							
19:	else							
20:	Insert <i>j</i> into route <i>r</i> ;							
21:	$N' \leftarrow N' ackslash \{ \{ j^* \} \cup N_{j^*}^{INF} \}$							
22:	if (r has negative reduced cost) then							
23:	Update <i>R</i> ;							
24:	if <i>R</i> is not empty <b>then</b>							
25:	Return <i>R</i> ;							
26:	Return <i>R</i> ;							

## **4.** Computational experiments

Our algorithm is implemented in C++ and executed on a computer with a 2.90GHz Intel Core i7-3520M processor that has two cores (and doubles the amount of virtual cores through the *hyper threading* feature). The computer has 8 GB of RAM. The model (1)–(13) is solved by CPLEX 12.5 on the same computer. CPLEX takes advantage of all available cores while our heuristic only uses one core. The data used for testing the algorithm is described in Section 4.1 and the computational results are presented in Section 4.2. The parameters  $\alpha$  and  $\beta$  in strong branching were set to  $\frac{3}{4}$  and 15, respectively, the same values as in Dabia et al. (2013) and Ropke (2013).

# 258 4.1. Data

The test instances are generated from real-life data provided by the tanker shipping operator. The 259 distributions of the generated cargoes in the test instances approximate the observed distributions in the 260 real-life dataset in terms of traveling distance, geographical location of the load and discharge ports, load 261 and discharge times, and time windows. In practice, a preferred service (laden) speed, at which the cargo 262 should be shipped, and the corresponding reward are fixed after a business negotiation between the cargo 263 owner and the shipping company. In this work, in order to investigate the effect of variable speeds, we 264 allow the cargoes to be served at different speeds and the corresponding rewards to be dependent on the 265 selected sailing speeds. Let  $v_i^{\text{pref}} \in V$  denote the preferred service speed of cargo *i*. The reward of cargo *i* at 266 speed  $v \in V$ ,  $r_i^v$ , is determined by the fuel consumption over the total sailing distance of the cargo and the 267 deviation from the cargo's preferred speed, i.e.  $|v - v_i^{\text{pref}}|$ , multiplied by a random element for variation. 268 The sailing speed is discretized in the real-life data and the set of speeds is  $V = \{10, 10.5, ..., 16\}$  knots 269 (1 knot equals 1.852 km per hour). As the fleet of ships is heterogeneous, the feasible sailing speeds and 270 the corresponding fuel consumptions vary between ships. For example, a heavy and slow ships can sail 271 between 12 and 15.5 knots, with a fuel consumption at 14 knots of 39.5 and 41.5 tons per day for ballast 272 and laden sailing respectively, while a lighter ship consumes 29.5 and 34 tons per day at the same speed. 273 Thus, the test data are generated by approximating the long-term statistics of the cargoes and using the 274

same practical sailing speed options and fuel consumption functions as in the real-life data. The dataset consists of twenty instances involving up to 250 cargoes and 32 ships in a 135-day planning horizon. The number of cargoes, the number of ships and the length of the planning horizon of each instance are given in Table 1.

	Number of cargoes	Planning horizon (days)	Number of ships
c40_d30_s20	40	30	20
c40_d30_s32	40	30	32
c70_d45_s20	70	45	20
c70_d45_s32	70	45	32
c100_d60_s20	100	60	20
c100_d60_s32	100	60	32
c130_d75_s20	130	75	20
c130_d75_s32	130	75	32
c160_d90_s20	160	90	20
c160_d90_s32	160	90	32

Table 1: The ten instances generated from real-life data.

# 279 4.2. Results

We test our algorithm on the generated instances, and compare the heuristic solutions to the optimal solutions. We also investigate the effects of allowing variable speeds and analyze how the fuel price affects the solutions.

# 283 The performance of the proposed heuristic method

The problem of simultaneously optimizing routing and sailing speed is solved by the proposed heuristic approach and by solving model (1)–(13) using CPLEX 12.5. A comparison between the two solution approaches is given in Table 2. Columns  $Z^H$  and  $Z^*$  are the profits obtained by the heuristic method and CPLEX respectively. The computational time in seconds and the number of served cargoes are given in columns *T* and  $n_s$ . The last column shows the optimality gap in percentage, which is calculated as  $\frac{Z^H - Z^*}{Z^*} \cdot 100$ . The instances of which CPLEX runs out of memory are indicated by "–" in the table. The limit on the computational time for the heursitc is set to 3600 seconds and for CPLEX 24 hours.

As can be seen from the table, CPLEX managed to find the optimal solutions for all the instances with up to 160 cargoes. Larger instances can be solved directly by CPLEX for our problem than for the vehicle routing problems. This is because, as mentioned earlier, our problem is a full-shipload shipping problem and the service time of a cargo, including the loading time, transportation time from pickup to delivery and unloading time, is relatively long compared to the pickup time window. Therefore the solution space is not as large as for a vehicle routing problem of the same size.

Our heuristic is able to find optimal solutions to three small instances and near-optimal solutions to the remaining instances. The optimality gap is consistently below 4.08% for the instances that CPLEX succeeded in finding the optimal solutions. In terms of computational time, the heuristic approach outperforms the exact method significantly. The average running time of the heuristic is less than 5% of that of CPLEX, and the heuristic managed to find solutions to all the instances. The numbers of served cargoes given by the two solution approaches are very close. In both heuristic and exact solutions, the ship's waiting time is approximately 15% of the entire planning horizon on average.

	Heuristic solution			Exa			
	$Z^H$	<i>T</i> (s)	$n_s$	$Z^*$	<i>T</i> (s)	$n_s$	Gap (%)
c40_d30_s20	5,497,357	0.2	20	5,497,357	3.0	20	0.00
c40_d30_s32	7,455,752	0.5	31	7,455,752	7.9	31	0.00
c70_d45_s20	8,222,284	2.5	33	8,222,892	52.8	33	-0.01
c70_d45_s32	11,735,410	3.3	49	11,735,410	117.6	49	0.00
c100_d60_s20	13,132,563	9.0	43	13,135,308	34.2	43	-0.02
c100_d60_s32	15,706,468	41.6	58	15,746,738	176.7	57	-0.26
c130_d75_s20	15,615,057	25.0	53	15,651,603	131.9	53	-0.23
c130_d75_s32	16,876,775	74.8	77	16,905,159	502.6	78	-0.17
c160_d90_s20	16,683,846	303.3	56	16,765,250	2,958.6	57	-0.49
c160_d90_s32	24,237,644	843.0	92	24,366,858	53,509.7	91	-0.53
Average	13,516,315	130.3	51.2	13,548,232	5,747.5	51.2	-0.17

Table 2: The results obtained by the heuristic method and CPLEX for the ten test instances.

In Table 3, we show detailed statistics for the heuristic. The first column shows the instance name. 304 The second column shows the total time spent by the heuristic. The third column shows if the branch 305 and bound search finished (X) or if it was stopped prematurely (-). The fourth column shows the number 306 of branch-and-bound nodes explored. The fifth column shows the number of columns generated. And 307 the last column shows the time spent in the pricing heuristic. It is obvious that most of the time is spent 308 on the pricing problem, which means that only a small fraction of time is spent on solving LP and the 309 necessary bookkeeping within the algorithm. It is also interesting to note that only a small number of 310 branch-and-bound nodes have been searched. 311

#### 312 The effect of speed optimization

In order to evaluate the effects of speed optimization, we compared the solutions to the multiple-speed case with those to the single-speed case. In the single-speed case, the laden sailing speed of a ship is equal to the preferred service speed of the cargo, and the ballast sailing speed is set to a constant speed, which is the smaller value of 12 knots (a realistic choice according to the company's statistic) and the ship's

Instance	$T_{tot}$ (s)	Fin.	#BB Nodes	#Columns	$T_{pricing}$ (s)
c40_d30_w1_s20	0.2	Х	0	235	0.2
c40_d30_w1_s32	0.5	Х	0	339	0.4
c70_d45_w1_s20	2.3	Х	0	550	2.3
c70_d45_w1_s32	3.3	Х	0	946	3.2
c100_d60_w1_s20	9.0	Х	0	1112	8.9
c100_d60_w1_s32	41.6	Х	2	1734	41.3
c130_d75_w1_s20	25.0	Х	0	1810	24.9
c130_d75_w1_s32	74.8	Х	0	2690	74.5
c160_d90_w1_s20	303.3	Х	2	2185	302.8
c160_d90_w1_s32	843.0	Х	2	3542	841.7

Table 3: Detailed results for the heuristic

lowest feasible ballast speed, whereas in the multiple-speed case, both the laden and ballast speeds are
variables. The profit, computational time and number of served cargoes for both cases are provided in
Table 4.

For the multiple-speed case, column  $\overline{v}_{\text{diff}}$  shows the average difference in knots between the actual service speed and the preferred speed over all the served cargoes. It is calculated as  $\frac{\sum_{i \in N_S} |v_i - v_i^{\text{pref}}|}{n_s}$ , where  $N_S$  is the set of served cargoes,  $n_s$  is the number of served cargoes, and  $v_i$  is the actual service speed of cargo *i*. The column  $Gap_1$  presents the optimality gap of the single-speed case, which is calculated as  $\frac{Z_S^H - Z_S^*}{Z_S^*} \cdot 100$ . The column  $Gap_2$  shows the gap between the heuristic solution to the multiple-speed case and that to the single-speed case, which is calculated as  $\frac{Z_M^H - Z_S^H}{Z_U^H} \cdot 100$ .

For the single-speed case, the heuristic finds the optimal solution for ten instances using on average 326 7% of the computational time used by CPLEX. By allowing speed variation, we gained a profit improve-327 ment ranging from 9.82% to 21.80% and an average improvement of 16%. We can also see that adding 328 multiple speeds makes the problem significantly harder both for the MIP model and the heuristic branch-329 and-price method. Although the running time of the multi-speed heuristic approach increases compared 330 to the single-speed heuristic method, it is still within an acceptable range, and shorter than that of CPLEX 331 for the single-speed case for almost all the instances. In addition, the multiple-speed solutions yield on 332 average 13% more served cargoes. 333

	Heuristic solution			Heuristic solution			Exact solution					
	(multiple-speed)			(single-speed)			(single-speed)					
	$Z_M^H$	<i>T</i> (s)	$n_s$	$\overline{v}_{diff}$	$Z_S^H$	T (s)	$n_s$	$Z_S^*$	T (s)	$n_s$	Gap <sub>1</sub>	Gap <sub>2</sub>
c40_d30_s20	5,497,357	0.2	20	1.35	4,636,034	0.03	18	4,636,034	2.4	18	0.00	18.58
c40_d30_s32	7,455,752	0.5	31	1.13	6,789,020	0.03	28	6,789,020	6.3	28	0.00	9.82
c70_d45_s20	8,222,284	2.5	33	2.00	6,750,725	0.05	26	6,750,725	22.1	26	0.00	21.80
c70_d45_s32	11,735,410 3.3 49 1.40		9,796,283	0.08	43	9,796,283	25.0	43	0.00	19.79		
c100_d60_s20	13,132,563 9.0 43 1.30		11,438,435	0.09	40	11,438,435	31.7	40	0.00	14.81		
c100_d60_s32	15,706,468	41.6	58	1.46	13,640,487	0.41	51	13,640,487	84.4	51	0.00	15.15
c130_d75_s20	15,615,057	25.0	53	1.35	13,554,505	0.19	49	13,554,505	167.9	49	0.00	15.20
c130_d75_s32	16,876,775	74.8	77	1.19	14,762,244	3.74	69	14,762,244	371.1	69	0.00	14.32
c160_d90_s20	16,683,846	303.3	56	1.46	14,139,457	0.44	51	14,139,457	372.4	51	0.00	18.00
c160_d90_s32	24,237,644	843.0	92	1.51	20,752,350	5.66	79	20,769,526	1,188.5	80	-0.08	16.79
Average	13,516,315 130.3 51.2 1.41		11,625,953	1.07	45.4	11,627,671	227.1	45.5	-0.01	16.43		

Table 4: A comparison between the multiple-speed case and the single-speed case.

#### 334 Sensitivity to the fuel price

The price of fuel oil fluctuates in real life. Here we investigate how this affects the speed selection and profit by running the instance c130\_d75\_s32 with different fuel prices, ranging from 50% to 200% of the current price. The detailed results are illustrated in Table 5. The first column shows the price factor in percentage relative to the price used in the previous simulations. Column  $n_s^>$  gives the number of cargoes served at a higher speed than preferred and column  $n_s^<$  provides the number of cargoes served at a lower speed than preferred. The last column  $\bar{\nu}$  is the average speed in knots for all served cargoes.

Figure 2 shows how the number of served cargoes, the number of cargoes served at a higher speed 341 than preferred, and the number of cargoes served at a lower speed than preferred change as the fuel price 342 increases from 50% to 200% of the current price. It can be seen that, as fuel price goes up, the number of 343 served cargoes  $n_s$  generally drops because some cargoes are no longer profitable given the high fuel price. 344 The tendency of serving the cargoes at lower speeds, as fuel price increases, is also clearly seen in the 345 figure. The number of served cargoes is especially sensitive when the fuel price goes beyond the current 346 price, whereas the number of cargoes served at a higher speed is very sensitive to fuel price throughout 347 the whole range. The number of cargoes served at a lower speed keeps increasing until the fuel price 348 reaches 160% of the current price and then drops. This is because in the beginning, it is preferred to serve 349

the cargoes at lower speeds but when the fuel price reaches a high level, it is more desirable to ignore the unprofitable cargoes. The results in Table 5 show that when the price increases from 50% to 200% of the current price, the number of served cargoes drops by 72.6%, the percentage of cargoes served at a higher-than-preferred speed decreases from 86.90% to 8.70% and the percentage of cargoes served at a lower-than-preferred speed increases from 0 to 86.93%.

Figure 3 depicts the profit and the average speed as a function of fuel price. The average speed decreases approximately linearly as a function of the fuel price increases. The profit decreases very fast as the fuel price increases and the decrease rate gradually slows down. When the price increases from 50% to 200% of the current price, the profit is decreased by 96.8% and the average speed is decreased by 30.1%.

In summary, the fuel price has significant effects on the profit and the average sailing speed, which shows the importance and benefit of applying speed optimization in a market with changing fuel prices. However, in practice, if the fuel price increases significantly, the reward for serving each cargo is expected to increase as well, and thus, the increased cost will be shared with the cargo owners.

Price factor (%)	$Z^H$	$n_s$	$n_s^>$	$\frac{n_s^>}{n_s} \cdot 100$	$n_s^<$	$\frac{n_s^<}{n_s} \cdot 100$	$\overline{v}$ (knot)
50	34,375,102	84	73	86.90	0	0.00	15.23
60	30,418,937	84	66	78.57	0	0.00	14.79
70	26,691,163	83	63	75.90	1	1.20	14.47
80	23,193,509	81	50	61.73	5	6.17	14.04
90	19,976,088	80	49	61.25	7	8.75	13.93
100	16,876,775	77	45	58.44	12	15.58	13.66
110	14,119,083	68	33	48.53	19	27.94	13.39
120	11,887,260	63	25	39.68	22	34.92	13.12
130	9,901,069	57	22	38.60	22	38.60	12.85
140	8,059,775	54	19	35.19	25	46.30	12.42
150	6,339,031	55	19	34.55	27	49.09	12.31
160	4,823,284	47	12	25.53	30	63.83	11.93
170	3,594,923	41	10	24.39	27	65.85	11.50
180	2,591,039	33	7	21.21	24	72.73	11.29
190	1,785,860	30	4	13.33	23	76.67	11.07
200	1,090,434	23	2	8.70	20	86.96	10.64

Table 5: The results of instance c130\_d75\_s32 with different fuel prices.



Figure 2: The number of served cargoes, the number of cargoes served at a higher-than-preferred speed and the number of cargoes served at a lower-than-preferred speed for different fuel prices.



Figure 3: The profit and average speed in knots for different fuel prices.

## 364 5. Conclusion

In this paper, we have considered the simultaneous optimization of routing and sailing speed in the 365 context of full-shipload tramp shipping encountered by a large Danish product tanker shipping operator. 366 A number of cargoes with specified pick-up time windows can be transported from load to discharge ports 367 using a fleet of heterogeneous ships of different speed ranges and fuel consumption. The ships can sail at 368 certain discretized speeds. For each ship, the fuel consumption depends on the shipload and sailing speed, 369 and is obtained from real-life data. This practical consideration is different from previous studies, where 370 fuel consumption is load independent. The objective of the problem is to find the optimal route for each 371 ship and the optimal sailing speed for each leg on the route to maximize the total profit of transportation. 372 We have presented a three-index formulation and a set packing formulation for this problem, and pro-373 posed a B&P algorithm with heuristic column generation and efficient data preprocessing. The algorithm 374 is implemented and tested on instances generated by approximating long-term statistics and using the 375 practical speed options and fuel consumption functions from real-life data. The computational results 376 show that our heuristic algorithm is able to find optimal solutions to the small instances and near-optimal 377 solutions to the large instances with optimality gaps consistently below 4.08%. The running time of the 378 heuristic method is significantly shorter than that of CPLEX (on average around 5% of the latter). We 379 have compared the solutions with speed optimization to those to a single-speed case, in which the cargoes 380 can only be served at individual fixed speeds, and found that by allowing speed variation, we can gain on 381 average 16% more profit and serve on average 13% more cargoes. We have also tested the algorithm with 382 different fuel prices, ranging from 50% to 200% of the current fuel price, and observed that the solution is 383 sensitive to fuel price changes. A higher fuel price leads to lower profit, fewer served cargoes and slower 384 average sailing speed. 385

#### 386 Acknowledgments

This work was supported by the Danish Maritime Fund. This support is gratefully acknowledged. The authors also thank the anonymous referee for the valuable comments that contributed to improve the quality of the paper.

# 390 Bibliography

C. Barnhart, E.L. Johnson, G.L.Nemhauser, M.W.P. Savelsbergh, and P.H. Vance. Branch-and-price: column gener ation for solving huge integer programs. 46(3):316–329, 1998.

393 G. Brønmo, B. Nygreen, and J. Lysgaard. Column generation approaches to ship scheduling with flexible cargo sizes.

<sup>394</sup> European Journal of Operational Research, 200:139–150, 2010.

- G. Brønmo, M. Christiansen, K. Fagerholt, and B. Nygreen. A multi-start local search heuristic for ship scheduling
   a computational study. *Computers & Operations Research*, 34(3):900–917, MAR 2007a. ISSN 0305-0548.
   doi: {10.1016/j.cor.2005.05.017}.
- G. Brønmo, M. Christiansen, and B. Nygreen. Ship routing and scheduling with flexible cargo sizes. *Journal of the Operational Research Society*, 58(9):1167–1177, SEP 2007b. ISSN 0160-5682. doi: {10.1057/palgrave.jors.
   2602263}.
- Ø. Buhaug, J. J. Corbett, Ø. Endresen, V. Eyring, J. Faber, S. Hanayama, D. S. Lee, D. Lee, H. Lindstad, A. Z.
   Markowska, A. Mjelde, D. Nelissen, J. Nilsen, C. Pålsson, J. J. Winebrake, W-Q Wu, and K. Yoshida, April
   2009. Second IMO GHG study, International Maritime Organization (IMO) London, UK.
- M. Christiansen, K. Fagerholt, B. Nygreen, and D. Ronen. Maritime transportation. In Cynthia Barnhart and Gilbert
   Laporte, editors, *Transportation*, volume 14 of *Handbooks in operations research and management science*,
   chapter 4, pages 189–284. Elsevier, 2007.
- M. Christiansen, K. Fagerholt, B. Nygreen, and D. Ronen. Ship routing and scheduling in the new millennium.
   *European Journal of Operational Research*, 228:467–483, 2013.
- J. J. Corbett, H. Wang, and J. J. Winebrake. The effectiveness and costs of speed reductions on emissions from
   international shipping. *Transportation Research Part D-Transportation and Environment*, 14(8):593–598,
   DEC 2009. ISSN 1361-9209. doi: {10.1016/j.trd.2009.08.005}.
- S. Dabia, S. Ropke, T. van Woensel, and T. De Kok. Branch and cut and price for the time dependent vehicle routing
   problem with time windows. 2013. Forthcoming.
- M. Desrochers, J. Desrosiers, and M. Solomon. A new optimization algorithm for the vehicle routing problem with time windows. 40(2):342–354, 1992.
- B. Eksioglu, A. V. Vural, and A. Reisman. The vehicle routing problem: A taxonomic review. *Computers & Industrial Engineering*, 57(4):1472–1483, 2009.
- K. Fagerholt, G. Laporte, and I. Norstad. Reducing fuel emissions by optimizing speed on shipping routes. *Journal* of the Operational Research Society, 61(3, SI):523–529, MAR 2010. ISSN 0160-5682. doi: {10.1057/jors.
   2009.77}.
- 421 R. A. Gatica and P. A. Miranda. Special Issue on Latin-American Research: A Time Based Discretization Approach
- for Ship Routing and Scheduling with Variable Speed. *Networks & Spatial Economics*, 11(3, SI):465–485,
   SEP 2011. ISSN 1566-113X. doi: {10.1007/s11067-010-9132-9}.
- M. M. Golias, G. K. Saharidis, M. Boile, S. Theofanis, and M. G. Ierapetritou. The berth allocation problem:
   optimizing vessel arrival time. *Maritime Economics and Logistics*, 11:358–377, 2009.

- A. Henrik, M. Christiansen, and K. Fagerholt. The maritime pickup and delivery problem with time windows and
   split loads. *Information Systems and Operational Research*, 49(2):79–91, 2011.
- 428 S. Irnich and G. Desaulniers. Shortest path problems with resource constraints. Springer US, 2005.
- J. E. Korsvik and K. Fagerholt. A tabu search heuristic for ship routing and scheduling with flexible cargo quantities.
   *Journal of Heuristics*, 16(2):117–137, APR 2010. ISSN 1381-1231. doi: {10.1007/s10732-008-9092-0}.
- J. E. Korsvik, K. Fagerholt, and G. Laporte. A tabu search heuristic for ship routing and scheduling. *Journal of the Operational Research Society*, 61(4):594–603, APR 2010. ISSN 0160-5682. doi: {10.1057/jors.2008.192}.
- J. E. Korsvik, K. Fagerholt, and G. Laporte. A large neighbourhood search heuristic for ship routing and scheduling
   with split loads. *Computers & Operations Research*, 38(2):474–483, FEB 2011. ISSN 0305-0548. doi:
   {10.1016/j.cor.2010.07.005}.
- G. Laporte, P. Toth, and D. Vigo. Vehicle routing: historical perspective and recent contributions. *EURO Journal on Transportation and Logistics*, 2(1-2):1–4, 2013.
- D.-Y. Lin and H.-Y. Liu. Combined ship allocation, routing and freight assignment in tramp shipping. *Transportation Research Part E-Logistics and Transportation Review*, 47(4):414–431, JUL 2011. ISSN 1366-5545. doi:
   {10.1016/j.tre.2010.12.003}.
- J.T. Linderoth and M.W.P. Savelsbergh. A computational study of search strategies for mixed integer programming. 11(2):173–187, 1999.
- H. Lindstad, B. E. Asbjørnslett, and A. H. Strømman. Reductions in greenhouse gas emissions and cost by shipping
  at lower speeds. *Energy Policy*, 39(6):3456–3464, JUN 2011. ISSN 0301-4215. doi: {10.1016/j.enpol.2011.
  03.044}.
- I. Norstad, K. Fagerholt, and G. Laporte. Tramp ship routing and scheduling with speed optimization. *Trans- portation Research Part C-Emerging Technologies*, 19(5, SI):853–865, AUG 2011. ISSN 0968-090X. doi:
   {10.1016/j.trc.2010.05.001}. 4th International Workshop on Freight Transportation and Logistics, Cesme
- 448 {10.1016/j.trc.2010.05.001}. 4th International Workshop on Freight Transportation and Log
   449 Izmir, TURKEY, MAY 26-29, 2009.
- 450 T. E. Notteboom. The time factor in liner shipping services. *Maritime Economics and Logistics*, 8:19–39, 2006.
- 451 OCEANA. Shipping industry on benefits of slower steaming. http://oceana.org/sites/default/ 452 files/o/fileadmin/oceana/uploads/Climate\_Change/Shipping\_Industry\_on\_
- 453 Benefits\_of\_Slower\_Steaming\_July\_2008.pdf, July 2008. Accessed on June 29, 2013.
- H. N. Psaraftis and Kontovas. Speed models for energy-efficient maritime transportation: A taxonomy and
   survey. *Transportation Research Part C: Emerging Technologies*, 26(0):331 351, 2013. ISSN 0968 090X. doi: http://dx.doi.org/10.1016/j.trc.2012.09.012. URL http://www.sciencedirect.com/
   science/article/pii/S0968090X12001246.
- D. Ronen. The effect of oil price on the optimal speed of ships. *Journal of the Operational Research Society*, 33(11):
   1035–1040, 1982.

- D. Ronen. The effect of oil price on containership speed and fleet size. *Journal of the Operational Research Society*,
   62(1):211–216, JAN 2011. ISSN 0160-5682. doi: {10.1057/jors.2009.169}.
- 462 S Ropke. Strong branching in branch-and-price-and-cut algorithms for vehicle routing problems. Technical report,
   463 DTU Management Science, 2013. Working paper.
- 464 S. C. Ryder and D. Chappell. Optimal speed and ship size for the liner trades. *Maritime Policy and Management*, 7
   (1):55–57, 1980.
- M. Stålhane, H. Andersson, M. Christiansen, J.-F. Cordeau, and G. Desaulniers. A branch-price-and-cut method for
   a ship routing and scheduling problem with split loads. *Computers & Operations Research*, 39:3361–3375,
   2012.
- 469 UNCTAD. *Review of Maritime Transport 2012*. United Nations, 2013.
- 470 S. Wang and Q. Meng. Sailing speed optimization for container ships in a liner shipping network. *Transportation*
- 471 Research Part E-Logistics and Transportation review, 48(3):701–714, MAY 2012. ISSN 1366-5545. doi:
- 472 {10.1016/j.tre.2011.12.003}.