The impact of CO₂-costs on biogas usage

Jensen, Ida Græsted; Nielsen, Lise Skovsgaard

Published in:
Energy

Link to article, DOI:
[10.1016/j.energy.2017.06.019](https://doi.org/10.1016/j.energy.2017.06.019)

Publication date:
2017

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Jensen, I. G., & Nielsen, L. S. (2017). The impact of CO₂-costs on biogas usage. *Energy*, 134, 289-300.
<https://doi.org/10.1016/j.energy.2017.06.019>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

The impact of CO₂-costs on biogas usage

Ida Græsted Jensen^{a,*}, Lise Skovsgaard^a

^a*Technical University of Denmark, DTU Management Engineering, Produktionstorvet, Building 426, DK – 2800 Kongens Lyngby, Denmark*

Abstract

The Danish government has set a target of being fossil fuel independent by 2050 implying that a high degree of inflexible renewable energy will be included in the energy system; biogas can add flexibility and potentially has a negative CO₂-emission. In this paper, we investigate the socio-economic system costs of reaching a Danish biogas target of 3.8 PJ in the energy system, and how CO₂-costs affect the system costs and biogas usage.

We perform our analysis using the energy systems model, Balmorel, and expand the model with a common target for raw biogas and upgraded biogas (biomethane). Raw biogas can be used directly in heat and power production, while biomethane has the same properties as natural gas. Balmorel is altered such that natural gas and biomethane can be used in the same technologies.

Several CO₂-cost estimates are investigated; hereunder a high estimate for the expected CO₂-externality costs. We find that system costs increase with CO₂-costs in most cases, while the biogas target becomes socio-economically cheaper. In the case of a very high CO₂-cost, system costs decrease and biomethane becomes the primary fuel. Furthermore, biomethane functions as regulating power and the Danish fuel consumption increases due to a higher electricity export.

Keywords: Energy systems modelling, Biogas, Biomethane, Renewable energy, Balmorel, CO₂-externality costs

1. Introduction

The Danish climate strategy is shaped around a goal of being independent of fossil fuels in all energy consuming sectors by 2050, and one tool among many is biogas. First focus point have been the heat and power sector (from now on called the energy system) in which there has already

*Corresponding author: idje@dtu.dk

been a large development in energy savings and implementation of renewable energy. Therefore, an energy system independent of fossil fuels by 2035 has been determined as a stepping stone towards the 2050 goal [1].

Biogas production have been developed in Denmark since the late 1970's with varying focus points [2]. Biogas is a renewable fuel that can be produced from a large variety of inputs such as manure, waste water and other wet substrates, which are expensive to use in other technologies. In Denmark, biogas is primarily based on manure of which there is an abundant supply from the large Danish agricultural industry. The degassed manure from the biogas process has an improved fertiliser value and can potentially improve the water environment as less nutrients are washed out from the fields. Furthermore emissions from the far more potent greenhouse gasses: methane (CH_4) and laughing gas (N_2O) are converted into CO_2 -emissions—making biogas one of the few fuels that potentially can reduce greenhouse gas emission effects.

In Denmark, biogas has primarily been used in local, combined heat and power plants (CHPs). As biogas is produced constantly all over the year and it is expensive to store, it is also *used* constantly, i.e. producing a constant stream of heat and power. With an increase in volatile renewable power production, this is not necessarily the optimal usage of biogas. In 2014 new regulation was ratified, such that biogas is now also subsidised when it is upgraded to natural gas quality (biomethane). Biomethane can be transported in the natural gas grid, which allows it to be used *where* it is needed, *when* it is needed.

Biogas has been applied in other analyses on systems optimisation—in particular on the issue of waste as a fuel [3, 4, 5]. Biogas is often one fuel out of many and seldom turn out to be the preferred fuel as seen in e.g. [3] and the national biomass value chain model [6]. In our analysis, we turn our attention to biogas (hereunder biomethane) by including a separate target of biogas usage.

There is a variety of literature on energy systems optimisation using different optimisation models, e.g. Balmorel [7, 8, 9], MARKAL/TIMES [10, 11, 12], and EnergyPLAN [13, 14, 15]. An overview of existing energy systems models can be found in [16]. With the choice of model, it becomes necessary to assess whether the model can include varying properties of the two types of biogas and the target of biogas usage.

In this paper, we consider the year 2025 for which the Danish Energy Agency (DEA) has a

prognosis of the biogas production [17], which seems to be aligned with the goal of being fossil fuel independent by 2035. We model biomethane as a substitute fuel for natural gas in an energy systems optimisation model and include a common goal on the use of biogas in the energy system. We allow the model to use biomethane as well as raw biogas and thereby we can compare the two options for the energy system. To our knowledge no other articles have included both raw biogas and biomethane in an energy systems optimisation model to evaluate their usage. The optimisation model is minimising the socio-economic cost of the energy system. From the model, the use of raw biogas and biomethane can be evaluated to find the socio-economic cost of a biogas target in the energy system both as a system cost and a marginal cost of the target. Furthermore, scenarios for different settings of the CO₂-cost is introduced to evaluate the effect on the system cost and the marginal cost of the target.

2. Biogas in Denmark

Biogas production has been developed in Denmark since the late 1970s [2], primarily based on manure and co-substrates from a large agricultural industry; and due to regulation biogas plants have primarily supplied heat and power locally.

As Denmark moves towards being fossil independent by 2050, it becomes necessary to find replacements for particularly coal and natural gas in the energy system. There is already by 2017 a massive development in Denmark where coal to a large extent has been replaced by biomass and wind power. However, the lack of flexibility and predictability among renewable energy sources such as wind and solar power [18] has become a repeated concern, when renewable energy is integrated into the energy system. One suggested benefit from biogas is the potential to add this needed flexibility. The traditionally, Danish biogas usage where biogas is sent directly through a dedicated pipeline to a nearby CHP-plant, can however not be expected to add much flexibility—in some cases it might even work against flexibility, since an effective production of raw biogas only can vary a little and due to high costs with local storing [19] it has to be used gradually while it is produced.

Raw biogas can also be upgraded to natural gas quality and sent as biomethane into the national gas grid. Raw biogas is made of approximately 65% methane and 35% CO₂, and the upgrading process consists essentially in removing this CO₂-surplus, converting the raw biogas

into biomethane (98% methane and 2% CO₂). Alternatively, hydrogen from electrolysis could be added to raw biogas, converting the CO₂-surplus into additional methane[20]. This process would increase the biomethane production with roughly 70%. The biomethane can be transported in the gas grid, stored and used with the same flexibility as natural gas in the heat and power sector, in industry or in heavy transport.

2.1. Biogas targets

There is no particular target for Danish biogas usage in 2025. However, a target of using 50% of all manure for biogas production by 2020 was set in the Green Growth Agreement [21]. This is an extensive increase in the biogas production, as currently only 7-10% of the Danish manure is used for biogas production. If 50% of the manure were to be used for biogas production it would correspond to approximately 11 PJ.

The energy consumption prognosis from the Danish Energy Agency (DEA) [17], predicts a 7 PJ increase in total biogas consumption from 10 PJ in 2015 to 17 PJ in 2025. In figure 1 the latest and expected development in biogas consumption are depicted (left y-axis) and for comparison the natural gas consumption is also depicted (right y-axis). From this it is clear, that even with a high percentage increase in biogas consumption, it will still be far from the current natural gas consumption.

[Figure 1 about here.]

The latest calculations on future biogas potentials for Denmark corresponds to approximately 60-85 PJ [22, 23]. But even with such high production it only corresponds to roughly 10% of the current total energy demand in Denmark, which is around 750 PJ. Furthermore, biogas is considered relatively expensive compared to other renewable technologies. The expected Danish energy consumption is depicted in figure 2 together with the energy consumption for the energy system for 2015 and a prognosis for 2025 from the Danish Energy Agency (DEA).

[Figure 2 about here.]

From the 2025 prognosis it becomes clear that an increased biogas production is not expected to be used in the heat and power sector. An increase in biogas consumption is most likely to happen in the transport and industrial sectors according to the Danish biogas task force analysis [24].

2.2. Regulation

As already mentioned, support for biogas was until recently only given indirectly to electricity produced on raw biogas in a local CHP. With the new regulation support is also given to upgraded biogas. The support for 2015 can be seen in table 1 together with an approximation for the support in 2025. Since the support is dependent on both the natural gas price and the net price index, it is uncertain what the exact support will be in 2025.

[Table 1 about here.]

With the current regulation, the support for raw and upgraded biogas is in many ways similar and since costs for upgrading are high, a private economic analysis could point to direct use as the preferred usage. According to [25], this is also the preferred choice as long as the plant is small. Following the inflexible production of biogas and the support design, when raw biogas is used in a local CHP, CHP is incentivised to produce constantly, independently of the electricity market. Support for biomethane is given before the biomethane is used and—except for a reduced CO₂-cost—biomethane is expected to have the same properties as natural gas and is taxed the same way. Therefore, the private economic competitiveness of biomethane can already be determined at the gate into the gas system: if the fuel costs including CO₂-costs are sufficiently low, biomethane could compete with natural gas, which may favour upgrading [26, 27].

In conclusion, it is reasonable to expect that biogas will be used both raw and upgraded in the future energy system depending on the local conditions, e.g. the local district heating demand.

3. Biogas in the energy system

Based on the above, we find it reasonable to include both raw biogas and biomethane when we model biogas within a Danish energy system context. The raw biogas and biomethane should be included in the energy systems model with different properties, e.g. cost and efficiency, and the common target should be handled by the model.

3.1. Balmorel

We choose to use the energy system model, Balmorel [28], for analysing the use of raw biogas and biomethane. Balmorel is a bottom-up model in which the energy system can be optimised

using an economic dispatch model, i.e. assuming all energy generating units are always online. The general economic dispatch model for electricity generation without investments can be written as:

$$\text{Min. } z = \sum_{t \in \mathcal{T}} \sum_{a \in \mathcal{A}} \sum_{g \in \mathcal{G}} \sum_{s \in \mathcal{S}} cost_g vge_{a,g,s,t} \quad (1)$$

$$\text{S.t. } vge_g^{min} \leq vge_{a,g,s,t} \leq vge_g^{max} \quad \forall a \in \mathcal{A}, g \in \mathcal{G}, s \in \mathcal{S}, t \in \mathcal{T} \quad (2)$$

$$\sum_{g \in \mathcal{G}} vge_{a,g,s,t} = d_{a,s,t} \quad \forall a \in \mathcal{A}, s \in \mathcal{S}, t \in \mathcal{T} \quad (3)$$

$$vge_{a,g,s,t} \geq 0 \quad \forall a \in \mathcal{A}, g \in \mathcal{G}, s \in \mathcal{S}, t \in \mathcal{T} \quad (4)$$

Line 1 is the total cost of producing on the installed technology type g . Here $cost_g$ is the cost of producing one unit of power on technology g and $vge_{a,g,s,t}$ is the amount of electricity produced on technology g in area a in all time periods given by season s and time t . Equation 2 ensures that each technology produces within its limits given by a minimum production limit, vge_g^{min} , and a maximum production limit, vge_g^{max} , in all areas and time periods. Equation 3 ensures that the electricity demand is met in all areas and time periods. Equation 4 ensures that the production is non-negative for all technologies in each area at all time periods. All used nomenclature can be seen in Appendix A. The economic dispatch problem can be extended to include heat-only technologies as well as combined heat and power technologies. This extension is not covered here, however, Balmorel includes both power and heat generation, as well as transmission within countries and between countries. The reader can refer to [28] for more details on modelling in Balmorel.

Balmorel is adoptable to any choice of geography, however it is used mostly in the Nordic and Baltic countries. Balmorel can be extended using several different add-ons, e.g. a unit commitment add-on, a policy add-on, and a time aggregation add-on. In this paper we use the economic dispatch model with optimisation of investments, and the combination technology add-on (Combtech) described in section 3.3.

Balmorel performs an economic optimisation with a simplistic representation of a socio-economic analysis, which do not include all externalities. The socio-economic optimisation is a cost-based analysis, using neither national taxes nor subsidies, and costs used in the model are expected market prices.

3.2. Modelling of biogas in the energy system: limitations and delimitations

Balmorel is run using economic dispatch, meaning that the fuel with the lowest cost for the system is used first and the most expensive fuels are used as regulating power. Given the inflexibilities of biogas production and expensive local storage [19], raw biogas cannot be used as regulating power in the system. This could be included in the model by forcing the model to use the raw biogas constantly. This addition would make the model an integer programming model and would increase running time significantly. With a long running time already before this addition, it is not considered a viable solution and the model is kept linear. Alternatively, the model could be forced to flare a certain percentage of the raw biogas. This, however, would require that the raw biogas is used as base load and, as described in section 6.2, the main investments for biogas are made in regulating power technologies. We therefore address this issue manually in the result analysis; and to avoid an extensive usage of raw biogas as regulating power—giving raw biogas an incorrect competitive advantage compared to biomethane—we do not allow the model to invest in new plants using raw biogas as fuel.

Aggregation is widely applied in Balmorel to make the model both faster and—as in the case of fuel usage—more specific. Time aggregation is applied by using a number of weeks during the year with a number of hours per weeks specified by the user. These choices will make the model faster than running the full year and—with a clever choice of weeks over the year—the results will be close to the full year model.

Fuel usage aggregation means that each technology has a specific fuel assigned to it with specific properties, hereunder efficiencies. One plant in the real world with different fuel inputs, would therefore be displayed in Balmorel as a number of technologies corresponding to the number of fuel inputs. Balmorel then optimises the fuel usage considering fuel costs, technology properties, capacity availability and so forth. At the same time, many plants in a given area are aggregated into one representative plant, meaning that in each area in Balmorel there can only be one plant of each technology.

A combined heat and power plant (CHP) using raw biogas cannot easily substitute the biogas with another fuel. A CHP using natural gas can however substitute the natural gas with biomethane, as this is essentially the same.

3.3. Combtech: combination of two technologies

The relevant add-on for combining two technologies is called Combtech. To our knowledge, Combtech has only been used in one paper, [5], where it is used to evaluate how waste should be used in the energy system. Combtech can combine two technologies, a primary technology and a secondary technology, with similar characteristics, e.g. efficiencies, lifetime, and fuel type. In our case, the only characteristic biomethane and natural gas technologies do not share is the fuel type, which results in different CO₂-emissions and fuel costs.

To allow substitution of fuels in a specific plant, the following constraints must be revised in Balmorel:

- Capacity constraints for existing and new energy conversion capacities
- Loss of electricity generation per unit of heat generated on extraction units for existing and new capacities

The capacity constraint is defined for existing electricity units, existing heat units, new electricity units, and new heat units. For the sake of simplicity, this constraint is only given for the existing electricity units but can easily be transferred to the other types by a name change in variables and sets. The existing electricity units g are in the set $\mathcal{G}^{elec,1}$ and $\mathcal{G}^{elec,2}$, where the first set is for the primary technologies and the second for secondary technologies. $vge_{a,g,s,t}$ is the production of electricity in area a , on technology g , season s and time t . The primary and secondary technologies are given from g by $\mathcal{G}^1(g)$ and $\mathcal{G}^2(g)$, respectively. The capacity of technology g in area a is given by $c_{a,g}$ and the combination of areas and technologies where capacity exists is given by the set $\mathcal{AGK}$. The capacity constraint is:

$$vge_{a,g,s,t} + \sum_{g_2 \in \mathcal{G}^2(g)} vge_{a,g_2,s,t} \leq c_{a,g} \quad \forall a \in \mathcal{A}, g \in \mathcal{G}^{elec,1}, \{a, g\} \in \mathcal{AGK}, s \in \mathcal{S}, t \in \mathcal{T} \quad (5)$$

Here the generation on the primary technology and all related secondary technologies are added and can not exceed the installed capacity.

An extraction unit can generate both heat and power, but in contrast to a back-pressure unit, the ratio between heat and power is not fixed. Instead the extraction unit will have a loss of electricity produced per unit of heat generated. The loss, which is given by the so-called Cv-line, is defined for both existing units and new units and is given here for the existing units. As for

the capacity constraint, the constraint for the new units is similar and can be derived by a name change in variables and sets. The electricity loss of the extraction unit $g \in \mathcal{G}^{ext,1}$, is modelled using the parameter, C_g^v , which is assumed constant. The loss of electricity generation per unit of heat generated by extraction units is given by:

$$\begin{aligned} vge_{a,g,s,t} + \sum_{g_2 \in \mathcal{G}^2(g)} vge_{a,g_2,s,t} &\leq c_{a,g} - C_g^v vgh_{a,g,s,t} - \sum_{g_2 \in \mathcal{G}^2(g)} C_{g_2}^v vgh_{a,g_2,s,t} \\ \forall a \in \mathcal{A}, g \in \mathcal{G}^{ext,1}, \{a, g\} \in \mathcal{AGK}, s \in \mathcal{S}, t \in \mathcal{T} \end{aligned} \quad (6)$$

When optimising, Balmorel can then decide whether to use natural gas or biomethane in the production—taking fuel prices and restrictions into consideration.

3.4. Modelling the biogas target

The common biogas target for raw biogas and biomethane is included by a new constraint. The model is based on the abbreviations used above and the following is added. $\mathcal{A}(c)$ is the areas related to country c . $vgf_{a,g,s,t}$ is the used fuel in area a on technology g in season s in time t on installed capacity and $vgfn_{a,g,s,t}$ is the same for new capacity. $fuel(g)$ is the fuel type used on technology g . The parameter called $GMIN2F_{c,f,f'}$ is added to the model with the target described in section 4 and represents the target for fuel f and f' in the country c . The target should be given in GJ.

The common target can be handled by the following constraint:

$$\begin{aligned} &3.6 \cdot \sum_{a \in \mathcal{A}(c)} \left(\sum_{\substack{g \in \mathcal{G} \\ fuel(g)=f}} \sum_{s \in \mathcal{S}} \sum_{t \in \mathcal{T}} (vgf_{a,g,s,t} + vgfn_{a,g,s,t}) \right. \\ &+ \sum_{\substack{g \in \mathcal{G} \\ fuel(g)=f'}} \sum_{s \in \mathcal{S}} \sum_{t \in \mathcal{T}} (vgf_{a,g,s,t} + vgfn_{a,g,s,t})) \\ &\geq GMIN2F_{c,f,f'} \quad \forall c \in \mathcal{C}, f \in \mathcal{F}, f' \in \mathcal{F} \end{aligned} \quad (7)$$

The first line represents the amount of fuel type f that is used and the second line represents the amount of fuel type f' used in the model. As the amount of fuel used is given in MWh and the target in GJ, the left hand side is multiplied by 3.6. Only the countries and fuels for which there are a specified target are bound by the constraint.

4. Assumptions and data

For this analysis we simulate the Nordic countries and Northern Germany with a focus on Denmark, i.e. only a Danish target of biogas consumption. The countries are further divided on a regional level corresponding to the regions on Nordpool—except for Northern Germany, which is divided into three regions. The regions are further divided in up to 10 areas based on the demand, size and geography.

We model one year, 2025, using four full weeks, one in each season. Furthermore, we perform a simple socio-economic analysis, i.e. cost prices from a Danish viewpoint together with no taxes nor subsidies. CO₂-emission is the only externality included in the optimisation and is represented by a socio-economic cost of CO₂. Focus is on climate targets, as this is where biogas has a competitive advantage due to a negative CO₂-emission in CO₂-equivalents. This assumed negative emission is based on avoided methane and N₂O-emissions when manure is treated and thereby converted into biogas and digestate instead of being distributed directly on the fields. The CO₂-emission value has been calculated by using the data from [29, 30].

[Table 2 about here.]

Fuel costs are mainly international market prices, following the assumption that most fuel prices will not be affected significantly by Danish fuel consumption. The primary source for fuel costs is the Danish Energy Agency (DEA) 2016-prognosis for socio-economic analysis, which is estimated on the basis of IEA prices [31]. The natural gas price is for example based on IEA prices adjusted to Danish price levels.

Fuels with high transportation costs, which do not enter the international markets, such as some biomasses, have an estimated cost which follows the closest substitute [31]. In the case of for example straw, the closest substitute is wood chips. Biogas costs are estimated on the basis of production costs found by using a profit optimising plant model with an input combination of manure and straw [27]. The straw price is the same as used in the energy systems analysis. The plant is large, using as input 600.000 t/y and generating a biogas yield of approximately 34 Mm³/y. Costs are found both in relation to raw biogas and when upgrading costs for the biomethane are included. The upgrading to biomethane is done by water scrubbing.

Type of fuel cost method, fuel costs and CO₂-emissions are listed in table 2. All costs are in €2015 prices.

4.1. The significance of price changes

The Danish Energy Agency (DEA) assumes that fixed fuel prices will increase over the years, however, not extraordinarily [31]. There is a possibility that particularly biomass prices will increase more rapidly than expected, which could change the overall system results significantly. As we use the straw price as input to the biogas production, higher biomass prices will have an effect on the biogas costs and thereby an effect on the biogas target. However, higher biomass costs would improve the competitiveness of biogas compared to biomasses, as straw is a minor part of the biogas costs. The most important factor in relation to price changes is expected to be price changes for the nearest substitute, in this case natural gas.

4.2. Targets and maximum consumption

As mentioned in section 2.1 there are currently no biogas targets, so we set the biogas target following the biogas consumption prognosis for biogas in the heat and power sector from DEA [17], where biogas consumption in the energy system is expected to decline from 4.3 PJ to approximately 3.8 PJ. This assumption follows the conclusions from the Biogas Taskforce as well as the general development in the Danish energy system, where natural gas based combined heat and power production is crowded out by primarily wind power [32].

[Table 3 about here.]

We do not use a target for natural gas consumption, however we set a limit following the DEA estimated use by 2025. In this estimation, it seems that the goal of a renewable founded heat and power production by 2035 is taken into account. Furthermore, there is a fixed usage of waste which is based on calculations using the FRIDA model [33] using the recycling targets from [34]. Last, an upper bound on wind potential is used, which is based on the IEA report [35].

4.3. Production capacity

We apply the existing generation capacity in the model by 2025, which for the Danish capacities are based on data from the Danish counting of energy production capacity by 2016 [36]. These capacities have been projected up to 2025 following expected remaining lifetimes and efficiencies. We allow the model to invest in further capacity in order to fill the gaps from existing, depreciated capacity and new demand. The given technology costs are found in the technology catalogues from

DEA [37] and new investments are depreciated with a 4% interest rate following the instructions for socio-economic analysis in Denmark [38, 39]. Furthermore, it is assumed that all investments have a 20 year lifetime.

In table 4 the existing capacities for technologies using biogas are shown along with their average efficiencies.

[Table 4 about here.]

The model is allowed to invest in new capacity using natural gas/biomethane, but it is not allowed to invest in capacity using raw biogas. This is due to the challenges with raw biogas, where it is difficult to resemble reality and force the model to use the same amount of biogas all over the year, as explained in section 3.3. As it turns out, this will only be an issue in one scenario.

5. Scenarios

In order to understand the socio-economic costs from setting a target for biogas usage in the Danish Energy System, two primary scenarios are considered. A Base-scenario with no biogas target and a Target-scenario, with a target for biogas. A determining factor for the result is the socio-economic cost of CO₂. When the socio-economic cost of CO₂ is high, fossil fuels becomes relatively less competitive. In the case of biogas, this becomes even more relevant, as biogas is assumed to have a negative CO₂-emission. Therefore three secondary scenarios are added investigating the importance of the CO₂-cost. The settings used can be seen in table 5.

[Table 5 about here.]

[Figure 3 about here.]

In figure 3, the CO₂-cost is added to the fuel cost to illustrate the significance of the CO₂-cost. It becomes clear that the closest substitute to biogas, natural gas, continue to be cheaper than biogas—even in the high CO₂-cost scenario, given the expected development in natural gas prices.

The actual socio-economic cost of CO₂-emissions from the Danish energy production is difficult to estimate correctly. Therefore, we followed the recommendation from DEA [31] to use different prognoses for the CO₂-quota price, assuming, that this to some extent corresponds to the socio-economic cost. We used the DEA 2015-prognosis for the high and low CO₂-quota price which is

based on current CO₂-quota prices and the IEA World Economic outlook prognosis from 2015. Finally, we used the average of the two scenarios. All scenarios are shown in table 5.

5.1. CO₂-externality cost scenarios

The European CO₂-quota prices are based on the expected marginal costs of CO₂-emission reduction given the political decided cap on CO₂-emissions within the CO₂-quota affected sectors. As the cap is politically decided it is not necessarily related to any expectations for the actual CO₂-externality costs, and compared to the literature, these costs also seem rather low. In [40] several estimations for the CO₂-externality costs from the literature are collected and evaluated, and from this a lower bound for the social cost of CO₂ is formed. This bound is high compared to other cost estimates in the literature [40].

To see what happens to the biogas consumption when a higher CO₂-cost is used in the model, we include this lower bound as the Van den Bergh CO₂-cost in the CO2Bergh/Target scenario. Further, we use the lower estimate from [41] in the CO2Dice/Target scenario to compare the results from the DEA estimates on marginal CO₂-emission reduction costs to the estimated CO₂-externality costs from [40] and [41]. The used CO₂-costs and the resulting fuel costs for natural gas, biomethane, and biogas can be seen in table 6 for the scenarios with high CO₂-cost.

[Table 6 about here.]

It is noticeable that the Dice CO₂-externality costs are quite close to the estimated high CO₂-quota price from the DEA.

6. Results

Seven scenarios have been run: two primary and three secondary, as well as two sensitivity analysis scenarios of the CO₂-costs.

6.1. System cost

Five parameters are presented in Table 7 giving the overall results from the scenario runs. The objective function value, OBJ, constitute the total system costs of the given scenario in Million Euro. Whereas Δ OBJ shows the additional system cost of a scenario in relation to the base scenario. The system cost increases when a biogas target is added, as the model would otherwise

have used the biogas already. However, the results show, that the system cost increase is low, compared to a high CO₂-cost. This makes sense as biogas corresponds to approximately 1.6% of the fuel usage in the target scenario while fossil fuel usage corresponds to approximately 36% of the fuel usage in all scenarios. Furthermore, we find that it becomes relatively less costly to add a biogas target as the CO₂-cost increases, which is due to the negative CO₂-emissions from biogas.

[Table 7 about here.]

The marginal cost of forcing a biogas target of 3.8PJ on the system is between 1.23-3.36€/GJ depending on the CO₂-cost. In order to make biogas socio-economically worthwhile, the actual CO₂-externality cost should prove to be even higher in order to call the biogas target socio-economic beneficial. Alternatively, other benefits from biogas production could be considered, such as positive externalities from e.g. reduced smell, increased quality of agricultural fertilisers, possible reduced nutrient releases to groundwater, or job creation in rural areas.

The last parameters, CO₂-total and CO₂-DK, show the amount of CO₂-emissions for the scenarios. Here it shows that a biogas target changes the CO₂-emissions in Denmark more than the high CO₂-cost. The Danish biogas target has an effect on the total CO₂-emission. This can be seen by the total CO₂-emission in the target scenarios being reduced more than the Danish CO₂-emissions and can be explained by an increase of electricity transmission to Germany, which reduces the use of coal in Germany and therefore a decrease in the CO₂-emissions.

6.2. Fuel and capacity usage

In table 8 it shows that the upper bound on natural gas usage is binding through all the scenarios. In all scenarios, however, only approximately 11-12% of the installed capacity is used, and only a small fraction of the used capacity is using biomethane. An explanation of this low usage combined with new investments could be that gas primarily is used for regulating power. This is substantiated by 80-98% of the new investments in combination technologies are in power producing capacity. Both raw biogas and biomethane are used in the target-scenarios, however, raw biogas is preferred to biomethane due to the lower fuel costs. The model does not distinguish between raw biogas and combination technologies as we have not included the problems with flexible usage of raw biogas in the model, see section 3.2. These observations emphasise the need of not allowing the model to invest in new capacity using raw biogas.

[Table 8 about here.]

[Figure 4 about here.]

Figure 4 displays the normalised fuel usage in the base and target scenarios in order to compare how fuel consumption differs. As the biogas target represent a small share of the total energy consumption it is no surprise, that the overall fuel consumption is quite similar. However, it can be seen that the additional biogas usage is substituting use of oil and heat pumps, but also biomass.

[Figure 5 about here.]

Figure 5 presents the three target scenarios and displays the significance of the CO₂-costs on fuel usage. The figure shows, that the usage of coal, natural gas, waste, wind, and sun does not change through the scenarios. Relating this to figure 3, an explaining factor can be that neither coal, natural gas nor waste changes position in the ranking of fuel costs with these changes in the CO₂-costs. When the CO₂-cost is low, it is preferred to use heat pumps, oil, and surplus heat in the system, whereas biomass and biogas is preferred when the CO₂-cost is high.

For the CO₂Low/Target scenario, the usage of biomethane is higher than in any other scenario. This is due to the fact that when comparing raw biogas and biomethane, the fuel costs become relatively closer to each other when the CO₂-cost is low compared to when the CO₂-cost is high. Biomethane is still more expensive, but when the costs are relatively closer, other factors become more determining for the result. These factors are e.g. technology efficiency, investment and operational costs, and the relative demand between heat and power.

Waste, wind, and sun are used equally across all scenarios. This is due to the fact that the maximum restrictions on these energy sources are binding in all scenarios. It is out of the scope of this paper to evaluate further on the restrictions. The results, however, indicate that the restrictions have an influence on the final results.

6.3. Usage of raw biogas in the system

Raw biogas is preferred to biomethane in all scenarios due to the lower fuel costs of raw biogas while not all inefficiencies from the real world are implemented in the model, as e.g. the need for an almost constant use of raw biogas. Figure 6 represents the usage of raw biogas in the CO₂High/Target scenario, where the biogas usage in GJ for CHP-units relates to the right y-axis

and boilers plus electricity-only units relates to the right y-axis. It is clear, that raw biogas primarily is used in CHP-units and mostly during winter and autumn (first and last period) and as regulating power during spring and summer. If a real world biogas based CHP had this consumption pattern, it would result in approximately 30% of the gas being flared, which would increase the cost of using raw biogas considerably. More likely, the plant would produce constantly, thus decreasing the value of the output for the system and thereby also the value of the raw biogas.

[Figure 6 about here.]

6.4. When the CO₂-externality costs are implemented

While the first scenarios presented in this paper relate to estimated CO₂-cost from a CO₂-quota system, the CO₂-costs in the last two scenarios are related to estimations of the actual CO₂-damage costs: a low and a high estimate. As given in table 6, the estimated CO₂-costs in the CO2Dice/Target scenario are quite close to CO2High/Target scenario, which is also reflected in the result summary in table 9. However, the interpretation of the costs is not the same. Total system costs increase slightly from the CO2High/Target to the CO2Dice/Target scenario, while the marginal costs of having a target for biogas usage approaches zero, so it seems that the CO₂-costs approaches a breaking point where the needed biogas would be used without a target.

[Table 9 about here.]

Total system costs are low in the CO2Bergh/Target scenario compared to the other high CO₂-cost scenarios. This decrease in system costs is based on fuel costs of raw biogas and biomethane, which are low due to their negative CO₂-emission. This also result in a high use of biomethane, which by far exceeds the target and thereby reduces the marginal cost of the biogas target to zero.

[Figure 7 about here.]

In table 9 we see a small decrease in both usage and installation of combination technologies in the CO2Dice/Target scenario, and in figure 7, we see that biomass seems to have become relatively more attractive in the CO2Dice/Target scenario. In the CO2Bergh/Target scenario on the other hand, both the degree of capacity usage and investments increase, which could also be expected considering the increased usage of biomethane—reflected in figure 7.

The CO₂-emissions show to be negative for both Denmark and the total energy system for the CO2Bergh/Target scenario as shown in table 9. The negative CO₂-emission in Denmark is explained by the excessive usage of biomethane in Denmark as shown in figure 7. For the total system, the important contributor to negative CO₂-emissions is Germany where biomethane is also used to a large extent—resulting in negative CO₂-emissions for the whole system.

The accumulated amount of fuels used in the CO2Bergh/Target scenario exceeds the fuel usage in any of the other scenarios. This can be explained by electricity based on biomethane becoming cheap enough to substitute a large amount of electricity production in Germany, resulting in an increased electricity export and a higher fuel usage in Denmark.

The natural gas consumption in this scenario has been replaced completely with biomethane, which then function as a base load provider during winter and autumn, and provider of regulating power during the summer period. This underlines, that biomethane can indeed function as a fuel for regulating power, using the gas transmission net as energy storage—in a scenario where CO₂-costs are very high.

The suggested biomethane consumption in CO2Bergh/Target scenario exceeds by far the sketched biogas potential in section 2.1, which means that more biogas would have to be produced. This could be through the addition of imported biomasses or e.g. grown algae, which are not considered in the current prognosis for biogas potentials[22, 23]. Furthermore, biogas could be upgraded by methanation where hydrogen is added to the raw biogas, such that excess CO₂ and hydrogen are converted into CH₄ and thereby increase the biomethane production by approximately 70% [42]. The hydrogen could be produced when electricity prices are low. Potentially, this can help even-out the electricity price and give an effective way to store electricity when there is an over-supply. How the additional biomethane is produced and interacts with the energy system is out of scope of this paper. It can, however, be expected that biomethane made by methanation will affect the assumed CO₂-emission related to biomethane such that less CO₂ will be reduced per GJ biomethane produced. When fed into the calculation, this should make the model less eager to use the large amount of biomethane.

7. Conclusion

In this paper we investigated the socio economic system costs of having a biogas target in Denmark, and how CO₂-costs affect the system costs and biogas usage. To do this, we used the energy system model Balmorel with the possibility to combine natural gas with biomethane in one technology. Furthermore, we set a target for raw biogas and biomethane corresponding to the predicted amount used in the heat and power sector in 2025. First, the model was applied using predictions of CO₂-costs from the Danish Energy Association. Then, we added two sensitivity analysis scenarios where we applied higher CO₂-costs corresponding to estimates for the actual CO₂-externality costs found in the literature.

From our analysis, we see that we need a very high CO₂-cost estimate in the area of the CO₂-costs estimated by Van den Bergh [40] before biogas or biomethane is worthwhile using in large amounts. When increasing the CO₂-costs, the biogas target becomes less costly while the total system cost increases. First when CO₂-costs are very high, biogas becomes worthwhile and used to such an extent, that total system costs decline. Even though the very high CO₂-cost might not be justified, there could still be arguments for forcing the system to use biogas, as there are other positive externalities from biogas than CO₂-reductions. This has, however, not been investigated further in this paper.

There are investments in combination technologies in all scenarios, but the usage of the natural gas technologies is relatively low, and the existing combination technologies are not used much. This suggests that gas primarily is used as regulating power. However, with very high CO₂-costs, combination technologies are used as base-load during winter and regulating power during summer. Furthermore, there is an increase in export of electricity in this scenario, which can be explained by the fact that the high CO₂-cost reduces the biomethane cost, and thereby increases biomethane's competitiveness compared to other electricity sources in the surrounding countries.

The scenario with the CO₂-cost estimate by [40] leads to an extensive usage of biogas that exceeds the potentials described in [22]. The lack of biogas resources could partly be overcome by biogas upgrading through methanation where hydrogen is used to upgrade the biogas. This could be investigated further in an energy system where the upgrading of biogas is included. This requires new estimates of the biogas CO₂-emissions, since upgraded biogas through methanation contains a lower share of manure per GJ and thereby also another level of CO₂-emissions.

Acknowledgement

This article is part of the project “Optimisation of value chains for biogas production in Denmark (BioChain)” funded by the Danish Council for Strategic Research (DSF), under the “Strategic Research in Sustainable Energy and Environment” research programme (Grant number: 12-132631). The authors are responsible for the content of this publication.

References

- [1] Danish Energy Agency, Energiscenarier frem mod 2020, 2035 og 2050 (Energy scenarios towards 2020, 2035, and 2050) (2014). doi:ISBN:978-87-93071-64-3.
URL https://ens.dk/sites/ens.dk/files/EnergiKlimapolitik/energiscenarier_-_analyse_2014_web.pdf
- [2] R. Lybæk, T. B. Christensen, T. Kjær, Governing innovation for sustainable development in the danish biogas sector - a historical overview and analysis of innovation, Sustainable Development (2013) 171–182doi:10.1002/sd.1548.
- [3] M. Münster, H. Lund, Use of waste for heat, electricity and transport-Challenges when performing energy system analysis, Energy 34 (5) (2009) 636–644. doi:10.1016/j.energy.2008.09.001.
- [4] M. Münster, P. Meibom, Long-term affected energy production of waste to energy technologies identified by use of energy system analysis, Waste Management 30 (12) (2010) 2510–2519. doi:10.1016/j.wasman.2010.04.015.
- [5] M. Münster, P. Meibom, Optimization of use of waste in the future energy system, Energy 36 (3) (2011) 1612–1622. doi:10.1016/j.energy.2010.12.070.
- [6] S. Samsatli, N. J. Samsatli, N. Shah, BVCM: A comprehensive and flexible toolkit for whole system biomass value chain analysis and optimisation - Mathematical formulation, Applied Energy 147 (2015) 131–160. doi:10.1016/j.apenergy.2015.01.078.
- [7] K. Karlsson, P. Meibom, Optimal investment paths for future renewable based energy systems—Using the optimisation model Balmorel, International Journal of Hydrogen Energy 33 (7) (2008) 1777–1787. doi:10.1016/j.ijhydene.2008.01.031.
- [8] L. Kitzing, H. Ravn, Support mechanisms and risk: Implications on the Nordic electricity system, in: 2013 10th International Conference on the European Energy Market (EEM), IEEE, 2013, pp. 1–7. doi:10.1109/EEM.2013.6607341.
- [9] K. Hedegaard, O. Balyk, Energy system investment model incorporating heat pumps with thermal storage in buildings and buffer tanks, Energy 63 (2013) 356–365. doi:10.1016/j.energy.2013.09.061.
- [10] K. Q. Nguyen, Impacts of wind power generation and CO2 emission constraints on the future choice of fuels and technologies in the power sector of Vietnam, Energy Policy 35 (4) (2007) 2305–2312. doi:10.1016/j.enpol.2006.06.023.
- [11] K. Vaillancourt, M. Labriet, R. Loulou, J. P. Waaub, The role of nuclear energy in long-term climate scenarios: An analysis with the World-TIMES model, Energy Policy 36 (7) (2008) 2296–2307. doi:10.1016/j.enpol.2008.01.015.

- [12] A. Elobeid, S. Tokgoz, R. Dodder, T. Johnson, O. Kaplan, L. Kurkalova, S. Secchi, Integration of agricultural and energy system models for biofuel assessment, *Environmental Modelling & Software* 48 (2013) 1–16. doi: 10.1016/j.envsoft.2013.05.007.
- [13] K. Hedegaard, B. V. Mathiesen, H. Lund, P. Heiselberg, Wind power integration using individual heat pumps - Analysis of different heat storage options, *Energy* 47 (1) (2012) 284–293. doi:10.1016/j.energy.2012.09.030.
- [14] P. S. Kwon, P. A. Østergaard, Priority order in using biomass resources - Energy systems analyses of future scenarios for Denmark, *Energy* 63 (2013) 86–94. doi:10.1016/j.energy.2013.10.005.
- [15] D. A. Hagos, A. Gebremedhin, T. Folsland Bolkesjø, Comparing the value of bioenergy in the heating and transport sectors of an electricity-intensive energy system in Norway, *Energy Policy* 85 (2015) 386–396. doi: 10.1016/j.enpol.2015.06.021.
- [16] D. Connolly, H. Lund, B. V. Mathiesen, M. Leahy, A review of computer tools for analysing the integration of renewable energy into various energy systems, *Applied Energy* 87 (4) (2010) 1059–1082. doi:10.1016/j.apenergy.2009.09.026.
- [17] Danish Energy Agency, Baseline Projections from DEA.
URL <https://ens.dk/en/our-services/projections-and-models/danish-climate-and-energy-outlook>
- [18] International Energy Agency, Empowering Variable Renewables - Options for Flexible Electricity Systems, OECD/IEA.
URL [https : / / www.iea.org / publications / freepublications / publication / Empowering_Variable_Renewables.pdf](https://www.iea.org/publications/freepublications/publication/Empowering_Variable_Renewables.pdf)
- [19] NIRAS, Biogas drifts- og samfundsøkonomisk analyse (Biogas private and socioeconomic analysis) (2010).
URL <http://energinet.dk/SiteCollectionDocuments/Danske%20dokumenter/Gas/Biogas%20drifts-%20og%20samfunds%C3%B8konomisk%20analyse%20-%20S%C3%A6sonvariation.pdf>
- [20] L. Jürgensen, E. A. Ehimen, J. Born, J. B. Holm-Nielsen, Utilization of surplus electricity from wind power for dynamic biogas upgrading: Northern Germany case study, *Biomass and Bioenergy* (2014) 126–132doi: 10.1016/j.biombioe.2014.02.032.
- [21] Danish Government, Aftale om Grøn Vækst (Green Growth Agreement) (2009).
URL https://www.danskfolkeparti.dk/pictures.org/Grn%20Vkst-aftale_final.pdf
- [22] T. Birkmose, K. Hjort-Gregersen, K. Stefanek, Biomasse til biogasanlæg i Danmark - på kort og langt sigt (Biomass to biogas plants on the long and short term), Tech. Rep. april (2013).
URL https://ens.dk/sites/ens.dk/files/Bioenergi/biomasser_til_biogasanlaeg.pdf
- [23] EA Energi Analyses, Anvendelse af biogas til el- og varmeproduktion (Usage of biogas to electricity and heat production), Tech. rep. (2014).
URL https://ens.dk/sites/ens.dk/files/Bioenergi/anvendelse_af_biogas_til_el_og_varme_2.pdf
- [24] Danish Energy Agency, Biogas i Danmark—status, barrierer og perspektiver (Biogas in Denmark—status, barriers, and perspectives), Tech. rep. (2014).
URL https://ens.dk/sites/ens.dk/files/Bioenergi/biogas_i_danmark_-_analyse.2014-final.pdf
- [25] M. Pöschl, S. Ward, P. Owende, Evaluation of energy efficiency of various biogas production and utilization pathways, *Applied Energy* 87 (11) (2010) 3305–3321. doi:10.1016/j.apenergy.2010.05.011.

- [26] L. Skovsgaard, H. K. Jacobsen, Economies of scale in biogas production and the significance of flexible regulation, *Energy Policy* 101 (2017) 77–89. doi:10.1016/j.enpol.2016.11.021.
- [27] I. G. Jensen, M. Münster, D. Pisinger, Optimizing the supply chain of biomass and biogas for a single plant considering mass and energy losses, *European Journal of Operational Research* (2017) –doi:<https://doi.org/10.1016/j.ejor.2017.03.071>.
- [28] H. Ravn, M. Hindsberger, R. Schmidt, R. Bøg, P. E. Grohnheit, M. Petersen, H. V. Larsen, J. Munksgaard, J. Ramskov, M.-R. Esop, G. Klavs, A. Galinis, R. Paprocki, M. Wawrzyszczuk, A. Gloukhov, Balmorel: A model for analyses of the electricity and CHP markets in the Baltic Sea Region, ElkraftSystem, 2001.
URL <http://eabalmorel.dk/files/download/Balmorel%20A%20Model%20for%20Analyses%20of%20the%20Electricity%20and%20CHP%20Markets%20in%20the%20Baltic%20Sea%20Region.pdf>
- [29] H. Wenzel, L. Højbye, R. Duban Grandal, L. Hamelin, D. N. Bird, A. Olesen, Carbon footprint of bioenergy pathways for the future Danish energy system, Tech. Rep. March (2014).
URL https://ens.dk/sites/ens.dk/files/Bioenergi/carbon_footprint_of_bioenergy_pathways_for_the_future_danish_energy_system_final_210314.1.pdf
- [30] H. Wenzel, L. Hamelin, Identifying marginal biomass supply and its carbon footprint under varying future framework conditions (2015).
URL http://www.sdu.dk/-/media/files/om_sdu/centre/lifecycleengineering/reports/wenzel_et_al_2015_global_biomass_marginals.pdf
- [31] Danish Energy Agency, Forudsætninger for samfundsøkonomiske analyser på energiområdet (Assumptions for socio-economic analyses within energy) (april) (2016) 1–22.
URL https://ens.dk/sites/ens.dk/files/Analyser/samfundsøkonomiske_beregningsforudsætninger_2016_v3.pdf
- [32] EA Energy Analyses, Afsætning af biogas til industri (Industrial purchase of biogas), Tech. rep. (2014).
URL https://ens.dk/sites/ens.dk/files/Bioenergi/afsaetning_af_biogas_til_industri_-_final.pdf
- [33] F. M. Andersen, H. V. Larsen, FRIDA: A model for the generation and handling of solid waste in Denmark, *Resources, Conservation and Recycling* 65 (2012) 47–56. doi:10.1016/j.resconrec.2012.04.004.
- [34] A. L. Hill, O. L. Dall, F. M. Andersen, Modelling Recycling Targets : Achieving a 50 % Recycling Rate for Household Waste in Denmark, *Journal of Environmental Protection* (May) (2014) 627–636. doi:10.4236/jep.2014.57064.
- [35] IEA, Nordic Energy Technology Perspectives 2016doi:10.1787/9789264257665-en.
- [36] Danish Energy Agency, Energiproducenttællingen (Energy producer count) (2016).
- [37] Danish Energy Agency, Technology data for energy plants, no. August, 2016.
URL https://ens.dk/sites/ens.dk/files/Analyser/teknologikatalog_august_2016_08082016.pdf
- [38] Danish Energy Agency, Vejledning i samfundsøkonomiske analyser på energiområdet (Guidance for socio-economic analyses within energy), Tech. Rep. April 2005, rev. 2007 (2005).
URL https://ens.dk/sites/ens.dk/files/Analyser/vejledning_2005-rev2007.pdf
- [39] Danish Energy Agency, Opdateret tillægsblad om kalkulationsrente, levetid og reference (Updated sheet on calculation rate, life time, and reference) (2013).
URL https://ens.dk/sites/ens.dk/files/Analyser/notat_om_kalkulationsrenten_juni_2013.pdf

- [40] J. C. J. M. van den Bergh, W. J. W. Botzen, A lower bound to the social cost of CO₂ emissions, *Nature Climate Change* 4 (4) (2014) 253–258. doi:10.1038/nclimate2135.
- [41] A. L. Marten, S. C. Newbold, Estimating the social cost of non-CO₂ GHG emissions: Methane and nitrous oxide, *Energy Policy* 51 (2012) 957–972. doi:10.1016/j.enpol.2012.09.073.
- [42] A. Evald, G. Hu, M. T. Hansen, Technology data for advanced bioenergy fuels, Tech. rep. (2013).
URL https://ens.dk/sites/ens.dk/files/Analyser/1.teknologikatalog_for_konvertering_af_biomasse_til_biobraendsle

Appendix A. Nomenclature

Sets

$\mathcal{AK}$ Combination of areas and technologies where capacity exists

$\mathcal{A}(c)$ All areas in country c

$\mathcal{A}$ All areas

$\mathcal{G}^2(g)$ Secondary technologies for primary technology

g

$\mathcal{G}^{elec,1}$ Primary technologies producing electricity

$\mathcal{G}^{ext,1}$ Primary technologies that are extraction units

$\mathcal{S}$ All seasons

$\mathcal{T}$ All time periods

Variables

$ve_{a,g,s,t}$ production of electricity in area a , on technology g , season s and time t

$vgf_{a,g,s,t}$ usage of fuel in area a , on existing technology g , season s and time t

$vgfn_{a,g,s,t}$ usage of fuel in area a , on new technology g , season s and time t

$vgh_{a,g,s,t}$ production of heat in area a , on technology g , season s and time t

Parameters

C_g^v Amount of electricity generation reduction per unit of heat generated on technology g

$GMIN2F_{c,f,f'}$ Common target in country c for fuel type f and f'

$c_{a,g}$ Capacity of technology g in area a

$cost_g$ The cost of producing electricity on technology g

$de_{a,s,t}$ The demand of electricity in area a in season s and time t

$fuel(g)$ Fuel type used on technology g

vg_e^{max} The maximum electricity production on technology type g

vg_e^{min} The minimum electricity production on technology type g

Tables

Regulation type	2015	2025
Electricity feed-in tariff, CHP - raw biogas	16.8 Eurocent/kWh	12.8 Eurocent/kWh
Avoided fuel tax on heat, CHP - raw biogas	3.1 Eurocent/kWh	3.1 Eurocent/kWh
Biogas feed-in premium, biomethane	16.8 Euro/GJ	12.8 Euro/GJ

Table 1: Direct and indirect support for biogas, in 2015-prices

	Type of price	Price, €/GJ	CO ₂ -emissions, kg/GJ
Fossil Fuels	Market prices [31]	Predicted avg. prices	Standard figures [31]
Biomasses	Comb. of market and cost prices [31]	Predicted avg. prices	Avg. figures calculated on expected usage [30]
Raw biogas	Cost calculated [27]	10.2	-77 [30]
Biomethane	Cost calculated [27]	12.1	-77 [30]
Natural gas	Market prices	6.7 [31]	56.8 [31]
Straw	Comb. of market and cost prices	6.3 [31]	11 [29]

Table 2: Fuel data

	Actual, Energy system, 2015	Forecasted, Energy System, 2025	Target or Maximum
Biogas	4.3 PJ	3.8 PJ	Target
Natural gas	34.5 PJ	28 PJ	Maximum

Table 3: Forecasts and targets, [17]

	Existing capacity		Efficiency	
	Raw biogas	Combination technology	Raw biogas	Combination technology
Heat Only	19 MW	3,161 MW	80.7%	95.6%
CHP	107 MW	934 MW	89.9%	90.5%
Electricity Only	0.3 MW	0.8 MW	31.7%	44.0%

Table 4: Technology data, [36, 37]

Scenario	Target	CO ₂ -cost level	CO ₂ -cost, €/ton
Base	-	Average	15.3
Target	+	Average	15.3
CO ₂ High/Base	-	High	23.1
CO ₂ High/Target	+	High	23.1
CO ₂ Low/Target	+	Low	7.5

Table 5: Settings for the scenarios

Scenario	CO2-cost	Natural gas	Biomethane	Biogas
CO2High/Target	23.1	8.0	11.8	9.7
CO2Dice/Target	30.3	8.4	11.3	9.2
CO2Bergh/Target	99.2	12.4	6.0	3.8

Table 6: CO₂-costs for the high CO₂-cost scenarios, €2015/ton

	Base	Target	CO2High/Base	CO2High/Target	CO2Low/Target
OBJ, M€	35,798	35,804	37,928	37,931	33,385
ΔOBJ, M€	-	6	2,130	2,133	-2,414
MTE, €/GJ	-	2.22	-	1.23	3.36
CO ₂ -total, MT	296.7	296.3	253.1	252.7	320.7
CO ₂ -DK, MT	8.0	7.8	8.1	7.8	7.8

Table 7: Results of the five scenarios. OBJ is the objective function value, ΔOBJ is the change in the objective function from the Base scenario, MTE is the marginal value of the biogas target constraint (Equation 7), and CO₂-total and CO₂-DK are the CO₂-emissions from the total energy system and for the Danish energy system

	Base	Target	CO2High/Base	CO2High/Target	CO2Low/Target
Biogas usage, GJ	485,731	2,083,290	776,758	2,517,432	1,964,166
Biomethane usage, GJ	-	1,716,710	-	1,282,568	1,835,834
Natural gas usage, GJ	28,000,000	28,000,000	28,000,000	28,000,000	28,000,000
BM-COMB	0%	5.8%	0%	4.5%	6.1%
%-COMB	11.7%	12.1%	11.0%	11.3%	11.8%
New COMB-capacity, MW	525	568	352	389	735

Table 8: Fuel usage, basic results. BM-COMB represents the percentage usage of biomethane in the combination technologies and %-COMB represents the percentage that the combination technologies are used

	CO2High/Target	CO2Dice/Target	CO2Bergh/Target
OBJ, M€	37,931	39,685	36,437
MTE, €/GJ	1.23	0.13	-
%-COMB	11.3 %	10.7%	44.3%
New COMB-capacity, MW	389	352	3,443
CO ₂ -total, MT	252.7	232.4	-178.4
CO ₂ -DK, MT	7.8	7.7	-13.3

Table 9: Results of the high CO₂-scenarios. MTE is the marginal value of the biogas target constraint (Equation 7) and %-COMB represents the percentage that the combination technologies are used. The capacity installed on the combination technologies are given by New COMB-capacity, and the CO₂-emissions for the system and for Denmark is given by CO₂-total and CO₂-DK.

Figures

Figure 1: Biogas target shown on the left y-axis compared to the natural gas demand on the right y-axis

Figure 2: Danish fuel consumption

Figure 3: Fuel costs, when the CO₂-cost is added; for average, low, and high CO₂-costs

Figure 4: Normalised fuel usage for Denmark in the base and target scenario

Figure 5: Normalised fuel usage for Denmark in the target scenarios

Figure 6: Usage distribution of raw biogas in the CO₂High/Target scenario

Figure 7: Fuel usage in Denmark for the scenarios with high CO₂-cost