Impact of KCl impregnation on single particle combustion of wood and torrefied wood

Lu, Zhimin; Jian, Jie; Jensen, Peter Arendt; Wu, Hao; Glarborg, Peter

Published in:
Fuel

Link to article, DOI:
[10.1016/j.fuel.2017.05.082](https://doi.org/10.1016/j.fuel.2017.05.082)

Publication date:
2017

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Lu, Z., Jian, J., Jensen, P. A., Wu, H., & Glarborg, P. (2017). Impact of KCl impregnation on single particle combustion of wood and torrefied wood. *Fuel*, 206, 684-689. <https://doi.org/10.1016/j.fuel.2017.05.082>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

**Impact of KCl Impregnation on Single Particle Combustion of Wood and
Torrefied Wood**

Zhimin Lu^{1*}, Jie Jian¹, Peter Arendt Jensen², Hao Wu^{2*}, Peter Glarborg²

¹ *School of Electric Power, Guangdong Province Key Laboratory of Efficient and Clean Energy
Utilization, South China University of Technology, No. 381, Wushan Road, Tianhe District,
Guangzhou 510640, China.*

² *Department of Chemical and Biochemical Engineering, Technical University of Denmark,
Søltofts Plads 229, 2800 Kgs. Lyngby, Denmark*

* *zhmlu@scut.edu.cn (Z. Lu); haw@kt.dtu.dk (H. Wu)*

12 **Highlights**

- 13 ● We study combustion of raw and torrefied wood spheres with varying K content.
- 14 ● Ignition time and devolatilization time depend mostly on fuel particle mass.
- 15 ● Both char yield and reactivity influence char conversion time.
- 16 ● Potassium promotes char yield and char reactivity of raw and torrefied wood.
- 17 ● Torrefaction increases char yield but does not influence char reactivity.

18 **Abstract**

19 In this work, single particle combustion of raw and torrefied 4mm wood particles with different
20 potassium content obtained by KCl impregnation and washing was studied experimentally under a
21 condition of 1225°C, 3.1% O₂ and 26.1% H₂O. The ignition time and devolatilization time
22 depended almost linearly on the fuel particle mass. The char conversion time was influenced by
23 both the char mass and char reactivity. Both KCl impregnation and torrefaction promoted char
24 yield, while washing slightly inhibited char formation. The char reactivity was increased by KCl
25 impregnation, decreased by washing, and unchanged by torrefaction. Compared to the raw wood
26 particle, the char conversion time was increased by torrefaction, decreased by washing, and almost
27 unchanged by KCl impregnation due to its promoting effect on both char yield and reactivity.

28 **Keywords:** Biomass; Torrefaction; Potassium; Combustion; Char yield; Char Reactivity

29 **1. Introduction**

30 Over the last decade, there has been an increasing interest in using torrefaction as pretreatment of
31 biomass because of its ability to increase hydrophobicity, grindability and energy density of biomass
32 [1-3]. Torrefied biomass, also known as bio-coal, is a suitable coal substitute with lower SO_x and net
33 CO₂ emissions [4]. It can be handled and combusted in a similar way as coal in pulverized-fuel power
34 plants without additional modifications of the plants [5]. Its potential of application in pulverized-
35 fuel power plants and metallurgical processes has been evaluated [5-7]. However, unlike the
36 torrefaction process and its effect on upgrading of biomass fuels which have been extensively
37 investigated, studies on the combustion or gasification characteristics of torrefied biomass are still
38 limited [8-20].

39 Char conversion is usually the rate limiting step in biomass combustion and gasification. It is
40 generally agreed that torrefaction can increase the char yield of biomass [9,13,14,21]. However, the
41 effect of torrefaction on the char reactivity is still in discussion. Using a thermogravimetric analyzer
42 (TGA), Jones and coworkers reported that torrefaction reduced the reactivity of willow and
43 Eucalyptus chars produced in a drop tube reactor [9,22,23], with the chars produced from the torrefied
44 biomass less reactive than the chars produced from the untreated biomass. Karlström et al. [21]
45 showed that after torrefaction, the char reactivity was increased, decreased and unchanged for straw,
46 olive stones and pine shell, respectively. Our previous work [13] revealed that the chars from raw and
47 torrefied Schima wood had almost the same reactivity.

48 The observed discrepancy of the effect of torrefaction on char reactivity may be related to the ash
49 content and composition in biomass. The existing studies indicate that torrefaction does not influence
50 the char reactivity of biomass with low ash content [13, 21], while for biomass with high ash content,
51 it may either reduce or promote the char reactivity [9,21-23]. Among the ash forming species in
52 biomass, potassium species, such as KCl, can effectively increase both char reactivity [24,25] and
53 char yield [26,27-39]. In order to better understand the effect of torrefaction on char reactivity, it is
54 therefore of interest to evaluate how torrefaction can influence the char reactivity of biomass with
55 different potassium content. In addition, since potassium promotes both char yield and char reactivity,
56 it is of interest to investigate the effect of potassium on char conversion time under high temperature
57 conditions relevant for pulverized fuel combustion.

58 In the present work, we prepared wood particles with different potassium content by water washing,
59 impregnation with KCl, impregnation with KCl after washing, and washing after impregnation. The
60 raw and the torrefied wood particles with different potassium content were combusted in a single
61 particle reactor to evaluate the time for ignition, devolatilization and char conversion. In addition,
62 selected char particles were extracted from the single particle reactor to determine the char yield and
63 to analyze the char reactivity by thermogravimetric analysis.

64 **2. Experimental**

65 **2.1 Feedstock**

66 Spherical Schima wood particles with a diameter of ~4mm were used as feedstock. The particle size
67 was chosen to represent the largest particles used in pulverized fired biomass boilers [13,30]. The
68 gross calorific value, proximate analysis and ultimate analysis of the fuel are listed in Table 1. As can
69 be seen, Schima wood is low in ash and alkali and alkaline earth metal content.

70 The wood particles were machine-produced to ensure uniformity. Each particle was drilled with a
71 0.4mm driller, and then weighed on a microbalance (± 0.01 mg). The weight of the particles was
72 averaging out at 20.0mg with a standard deviation of 1.5mg. The dimensions in three principal axes
73 were measured using a handheld micrometer (± 0.05 mm) and the mean diameter was 3.94 mm with
74 a standard deviation of 0.04 mm.

75 **2.2 Sample pretreatment and torrefaction**

76 Four ways of pretreatment consisting of washing, impregnation and their different combinations were
77 applied to the Schima wood particles: (a) washing by deionized water at 333K for 3h under stirring;
78 (b) impregnation with 1.07 % (weight basis) KCl solution at room temperature for 3h; (c) washing
79 by deionized water at 333K for 3h under stirring, followed by impregnation with 1.07% KCl solution
80 at room temperature for 3h; (d) impregnation with 1.07 % KCl solution at room temperature for 3h,
81 followed by washing by deionized water at 333K for 3h under stirring. For all the treatments, less
82 than 0.3g wood sample was soaked in 150ml water or KCl solution. After washing/impregnation, all
83 pretreated samples were dried in an oven at 333 K for about 12h.

84 Part of the raw and pretreated samples were torrefied in a tube oven in the presence of nitrogen at
85 290°C or 350°C for 1h, following the procedures described in [13].

86 All prepared particles were stored in sample bags before being tested in the single particle combustion
87 reactor. The samples, which were washed but not torrefied, were denoted as “washed raw”. Similarly,
88 the sample “KCl+washed 290°C” denotes the Schima wood particles that were first impregnated by
89 KCl solution, and then washed and torrefied at 290°C for 1h, and so on.

90 **2.3 Single particle combustion experiments**

91 The combustion experiments were conducted in a single particle combustion (SPC) reactor shown in
92 Figure 1. The SPC reactor was designed to simulate the combustion conditions in a pulverized fuel-
93 fired boiler. The setup mainly consists of a tube reactor, a burner, a gas supply system and a video
94 recording system. A burner with ninety-four injection nozzles were used to achieve good gas mixing
95 and led to a uniform flow distribution and a flat temperature profile in the center of the reactor, where
96 the biomass particles were placed. Four mass flow controllers (MFCs) controlled the flow to the
97 burner, maintaining flow rates of 8.45 NL/min, 5.20 NL/min and 22.80 NL/min for hydrogen, oxygen
98 and nitrogen, respectively. Before and after the experiment, the temperature and the oxygen
99 concentration (dry basis) in the center of the reactor were measured by a suction pyrometer and a
100 NGA2000 gas analyzer to be $1225\pm30^{\circ}\text{C}$ and $4.1\pm0.05\%$ O_2 , respectively. Based on the stoichiometry,
101 the average O_2 concentration in the flue gas before and after water condensation were calculated to
102 be 3.1% and 4.2%, respectively. The difference between the calculated O_2 concentration (4.2%) and
103 the measured value (4.1%) is small. Thus the atmosphere that the particles were exposed to was then
104 taken to be the calculated 3.1% O_2 and 26.1% H_2O . A detailed description of the reactor and the
105 experimental procedures can be found elsewhere [13,31].

106 To start the combustion experiment, a ceramic protection tube was placed in the SPC reactor. Then a
107 single fuel particle held by a small Al_2O_3 rod (0.3mm in diameter) was inserted coaxially into the
108 ceramic protection tube. The video recording was initiated, and the protection tube was rapidly
109 withdrawn, exposing the particle to combustion environment. The combustion process was recorded
110 by a camera with a speed of 67 frames/second.

111 The time-interval between the withdrawal of the protective tube and the first visible light flash is
112 taken to be the ignition time, which is believed to be governed by the time required for moisture
113 evaporation and heating up of the particle to start devolatilization and produce a visible volatile flame
114 [32]. The devolatilization time is defined as the time duration of the visible volatile flame. After the
115 devolatilization stage, the remaining char was combusted until complete burnout, indicated by the
116 end of the shrinkage and a brightness change of the remaining residue. This time period is defined as
117 the char burnout time. We neglected a possible overlap of the devolatilization and char combustion
118 stages, as the video images in the present study and previous studies [13,32] show a clear separation
119 between these two processes. For selected experiments, after the extinction of the volatile flame, the
120 char particle was quickly removed to the water cooled chamber of the SPC reactor and quenched by
121 1 Nl/min nitrogen. The char particles were weighted to determine the char yield.

122 **2.4 Thermogravimetric analysis (TGA)**

123 The char reactivity was analyzed in a TGA instrument (Netzsch STA 449F1 Jupiter). A small amount
124 of pulverized char sample (~2 mg) was first dried at 110°C for 10 minutes and then heated at
125 10°C/min to 800°C in an atmosphere of 5% O_2 and 95% N_2 .

126 **3. Results and discussion**

127 **3.1 Ignition time**

128 Figure 2 shows the ignition time versus the fuel particle mass. The considerable scatter in ignition
129 time is attributed mainly to the experimental uncertainties. Nevertheless, there seems to be a
130 correlation between the ignition time and the sample mass, i.e. torrefied particles with smaller mass
131 appear to ignite more rapidly than raw particles. We believe this is primarily due to the higher heating
132 rate of the particles with smaller mass. In addition, compared to the raw wood particles, the torrefied
133 samples have a darker surface and a lower moisture content, which would further shorten the ignition
134 time through promoting the radiation heat transfer and reducing the drying time. The impact of KCl
135 addition on ignition time is not obvious. However, for the raw wood particles, it seems that the
136 ignition time is slightly shortened by the addition of KCl, possibly because devolatilization starts at
137 lower temperatures when KCl is added to biomass [27].

138 **3.2 Devolatilization time**

139 Figure 3 shows that the devolatilization time increases nearly linearly with increasing fuel particle
140 mass, similar to our earlier findings in the same reactor [13]. The KCl impregnated particles seem to
141 have slightly shorter devolatilization time, independent of whether they are washed or not before the
142 impregnation. For the raw fuel, the effect of washing is insignificant on the devolatilization time,
143 probably due to the low potassium content in the raw fuel. However, washing after impregnation is
144 effective for restoring the devolatilization behavior to that observed for the raw and washed samples.

145 In a previous study on single particle combustion, Jones et al. [32] concluded that the devolatilization
146 time followed the sequence of K-impregnated <raw< water-washed. The present study shows that the
147 catalytic effect of KCl remains even after the torrefaction pretreatment. However, samples with a
148 high torrefaction degree, such as the “KCl 350C”, “350C” and “washed 350C” samples, have similar
149 devolatilization time for particles with similar masses.

150 **3.3 Char yield**

151 The char particles extracted from the SPC reactor were weighed, and the mass ratio of the residue
152 over the untreated raw fuel particle was taken as the char yield and plotted in Figure 4. Based on the
153 TGA results, the ash content in the residues is generally below 10 wt%. Thus, the tendencies shown
154 in Figure 4 would be the same if the char yield was determined on ash-free basis.

155 Figure 4 indicates that the char yield of raw and KCl doped raw particles follows the expected order
156 and increases with the potassium content in the samples, i.e., “KCl” (13.2%) > “washed+KCl”
157 (12.8%) > “raw” (9.6%) > “KCl+washed” (8.8%) > “washed” (6.9%). This finding is in agreement
158 with previous studies on biomass char formation [33-36], showing the promotion effect of potassium
159 on char formation. For samples torrefied at 290°C, the char yield follows the same order, i.e. KCl
160 (20.7%) > “washed+KCl” (18.5%) > “raw” (12.7%) > “KCl+washed” (12.3%) > “washed” (10.2%).

161 The char yield increased significantly after torrefaction, which is in agreement with our previous
162 study [13] and a number of other studies on low-temperature thermal treatment [37-39]. Compared
163 to the non-torrefied samples, the increases of char yield after torrefaction at 290°C are 3.3%, 3.5%,
164 3.2%, 5.6%, 7.6% for the “Washed”, “KCl+washed”, “raw”, “washed +KCl”, and “KCl” samples,

165 respectively, correlating well with the expected order of potassium content in the samples. This
166 indicates a synergistic effect of KCl addition and torrefaction on cross-linking and charring reactions
167 to increase the char yield. In other words, increased torrefaction severity and increased potassium
168 content would both lead to increased char yield. This synergistic effect resulted in a significant
169 increase of char yield from 6.9% for washed raw sample to 25.4% for KCl impregnated sample
170 torrefied at 350°C.

171 **3.5 Char reactivity**

172 Figure 5 shows the TG results of oxidation of selected chars. The results are given in dry ash free
173 (daf) basis in order to facilitate a direct comparison of the char reactivity. The reactivities of KCl
174 doped chars, i.e. “Washed KCl 290C”, “Washed KCl” and “KCl 290C”, are quite similar, implying
175 that the effect of torrefaction and initial washing on char reactivity, compared to the effect of
176 potassium doping, is small. The reactivities of the “raw” char and “290C” char are almost identical,
177 in agreement with our previous finding that torrefaction does not influence the char reactivity of
178 Schima wood [13]. This trend is also observed from the chars doped with KCl. Compared to the KCl
179 doped chars, the reactivities of the “raw” char and “290C” char are much lower, supporting the
180 significant catalytic effect of potassium on char oxidation, as reported extensively in literature
181 [32,40,41].

182 The washed samples, i.e. “Washed”, “Washed 290C” and “KCl washed 290C”, also exhibit similar
183 char reactivities. However, their char reactivities are considerably lower than those of “raw” char and
184 “290C” char. A possible explanation is that washing removes ash forming elements (e.g. potassium)

185 in biomass that can catalyze char oxidation, resulting in lower char reactivity. Similar results have
186 been observed for straw and washed straw [27].

187 **3.6 Char burnout time**

188 Figure 6 provides an overview of the char burnout time versus the char mass for different samples.
189 To facilitate the evaluation of the results, the samples are grouped into: 1) samples produced from
190 raw Schima wood, including “raw”, “290C”, “350C”; 2) samples produced from KCl impregnated
191 Schima wood, including “KCl raw”, “KCl 290C”, “KCl 350C” , “washed+KCl”, “washed+KCl
192 290C”; 3) samples produced from washed Schima wood, including “washed raw”, “washed 290C”,
193 “washed 350C”, “KCl+washed”, “KCl+washed 290C”.

194 For each group of samples, it is observed that the char oxidation time increases with the degree
195 torrefaction, i.e. in the order of non-torrefied sample, sample torrefied at 290°C, and sample torrefied
196 at 350°C. This is primarily because torrefaction can promote the char yield, resulting in heavier char
197 particle that requires longer combustion times. A similar tendency has been observed in our earlier
198 work [13].

199 Comparing different groups of samples with similar char mass, it is observed that the char burnout
200 time generally increases in an order of group 2, group 1 and group 3. This tendency is consistent with
201 the expected char reactivity in these groups, as illustrated in Figure 5. For char samples with similar
202 mass, the burnout time decreases with increasing char reactivity, indicating that the char conversion
203 is kinetically influenced under the experimental condition (1225°C, 3.1% O₂ and 26.1% H₂O). This

204 further suggests that gasification by H_2O would play an important role, as the $\text{char}+\text{O}_2$ reaction is
205 expected to be diffusion controlled under the experimental condition.

206 Comparing the group 1 and group 2 samples, it can be seen that although KCl impregnation increases
207 the char mass considerably both for raw samples and torrefied samples, the char conversion time is
208 almost unchanged due to the increased char reactivity. On the other hand, a comparison of group 1
209 and group 3 implies that although washing reduces slightly the char mass/yield, the conversion time
210 is considerably increased due to the reduced char reactivity.

211 **4. Conclusion**

212 Single particle combustion of wood particles pretreated by KCl impregnation, washing, torrefaction
213 and their different combinations was studied experimentally under a condition of 1225°C , 3.1% O_2
214 and 26.1% H_2O . The ignition time and devolatilization time depend almost linearly on the fuel particle
215 mass. The char conversion time is influenced both by the mass and the reactivity of char particles.
216 The char yield is promoted by KCl impregnation and torrefaction, while slightly inhibited by washing.
217 The char reactivity is increased by KCl impregnation, decreased by washing, and almost unchanged
218 by torrefaction. Compared to the raw wood particle, the char conversion time under the current
219 experimental condition is increased by torrefaction, decreased by washing, and almost unchanged by
220 KCl doping due to the combined effect of promoting both char yield and reactivity.

221

222 **Acknowledgements**

223 The first author was supported by the China Scholarship Council and Key Laboratory of Efficient
224 and Clean Energy Utilization of Guangdong Higher Education Institutes (KLB10004) for 1 year
225 study at the Technical University of Denmark. The work was also supported by the Danish Strategic
226 Research Council, DONG Energy, and Vattenfall.

227 **References**

- 228 [1] Nhuchhen D, Basu P, Acharya B. A Comprehensive Review on Biomass Torrefaction. *Int J*
229 *Renew Energy Biofuels* 2014;2014:1–56.
- 230 [2] Chen W-H, Peng J, Bi XT. A state-of-the-art review of biomass torrefaction, densification and
231 applications. *Renew Sustain Energy Rev* 2015;44:847–66.
- 232 [3] Tumuluru JS, Sokhansanj S, Hess JR, Wright CT, Boardman RD. A review on biomass
233 torrefaction process and product properties for energy applications. *Ind Biotechnol* 2011.
- 234 [4] Agar D, Wihersaari M. Bio-coal, torrefied lignocellulosic resources – Key properties for its use
235 in co-firing with fossil coal – Their status. *Biomass and Bioenergy* 2012;44:107–11.
- 236 [5] Li J, Zhang X, Pawlak-Kruczek H, Yang W, Kruczek P, Blasiak W. Process simulation of co-
237 firing torrefied biomass in a 220MWe coal-fired power plant. *Energy Convers Manag* 2014;84:503–
238 11.
- 239 [6] Li J, Brzdekiewicz A, Yang W, Blasiak W. Co-firing based on biomass torrefaction in a
240 pulverized coal boiler with aim of 100% fuel switching. *Appl Energy* 2012;99:344–54.
- 241 [7] Du S-W, Chen W-H, Lucas J a. Pretreatment of biomass by torrefaction and carbonization for
242 coal blend used in pulverized coal injection. *Bioresour Technol* 2014;161:333–9.
- 243 [8] Broström M, Nordin A, Pommer L, Branca C, Di Blasi C. Influence of torrefaction on the
244 devolatilization and oxidation kinetics of wood. *J Anal Appl Pyrolysis* 2012;96:100–9.

245 [9] Jones JM, Bridgeman TG, Darvell LI, Gudka B, Saddawi A, Williams A. Combustion
 246 properties of torrefied willow compared with bituminous coals. *Fuel Process Technol* 2012;101:1–
 247 9.

248 [10] Goldfarb JL, Liu C. Impact of blend ratio on the co-firing of a commercial torrefied biomass
 249 and coal via analysis of oxidation kinetics. *Bioresour Technol* 2013;149:208–15.

250 [11] Li J, Bonvicini G, Biagini E, Yang W, Tognotti L. Characterization of high-temperature rapid
 251 char oxidation of raw and torrefied biomass fuels. *Fuel* 2015;143:492–8.

252 [12] Costa FF, Wang G, Costa M. Combustion kinetics and particle fragmentation of raw and
 253 torrefied pine shells and olive stones in a drop tube furnace. *Proc Combust Inst* 2015;35:3591–9.

254 [13] Lu Z, Jian J, Jensen PA, Wu H, Glarborg P. The Influence of Torrefaction on Single Particle
 255 Combustion of Wood. *Energy & Fuels* 2016;30:5772-9.

256 [14] Li J, Bonvicini G, Tognotti L, Yang W, Blasiak W. High-temperature rapid devolatilization of
 257 biomasses with varying degrees of torrefaction. *Fuel* 2014;122:261–9.

258 [15] Couhert C, Salvador S, Commandré JM. Impact of torrefaction on syngas production from
 259 wood. *Fuel* 2009;88:2286–90.

260 [16] Weiland F, Nordwaeger M, Olofsson I, Wiinikka H, Nordin A. Entrained flow gasification of
 261 torrefied wood residues. *Fuel Process Technol* 2014;125:51–8.

262 [17] Li T, Geier M, Wang L, Ku X, Güell BM, Løvås T, et al. Effect of torrefaction on physical
 263 properties and conversion behavior of high heating rate char of forest residue. *Energy & Fuels*
 264 2015;29:177–84.

265 [18] Li T, Wang L, Ku X, Güell BM, Løvås T, Shaddix CR. Experimental and modeling study of
 266 the effect of torrefaction on the rapid devolatilization of biomass. *Energy & Fuels* 2015;29:4328–
 267 38.

268 [19] Riaza J, Khatami R, Levendis Y a., Álvarez L, Gil M V., Pevida C, et al. Combustion of single
 269 biomass particles in air and in oxy-fuel conditions. *Biomass and Bioenergy* 2014;64:162–74..

270 [20] Bridgeman TG, Jones JM, Shield I, Williams PT. Torrefaction of reed canary grass, wheat
 271 straw and willow to enhance solid fuel qualities and combustion properties. *Fuel* 2008;87:844–56.

272 [21] Karlström O, Costa M, Brink A, Hupa M. CO₂ gasification rates of char particles from
 273 torrefied pine shell, olive stones and straw. *Fuel* 2015;158:753–63.

274 [22] Fisher EM, Dupont C, Darvell LI, Commandré JM, Saddawi A, Jones JM, et al. Combustion
 275 and gasification characteristics of chars from raw and torrefied biomass. *Bioresour Technol*
 276 2012;119:157–65.

277 [23] McNamee P, Darvell LI, Jones JM, Williams A. The combustion characteristics of high-
 278 heating-rate chars from untreated and torrefied biomass fuels. *Biomass and Bioenergy* 2015;82:63–
 279 72.

280 [24] Blasi C Di, Galgano A, Branca C. Effects of potassium hydroxide impregnation on wood
 281 pyrolysis. *Energy & Fuels* 2009;23:1045–54.

282 [25] Saddawi A, Jones JM, Williams A. Influence of alkali metals on the kinetics of the thermal
 283 decomposition of biomass. *Fuel Process Technol* 2012;104:189–97.

284 [26]Cetin E, Moghtaderi B, Gupta R, Wall T. Influence of pyrolysis conditions on the structure and
 285 gasification reactivity of biomass chars. *Fuel* 2004;83:2139–50.

286 [27]Jensen A, Dam-Johansen K, Wójtowicz M a., Serio M a. TG-FTIR Study of the Influence of
 287 Potassium Chloride on Wheat Straw Pyrolysis. *Energy & Fuels* 1998;12:929–38.

288 [28]Saleh SB, Hansen BB, Jensen PA, Dam-Johansen K. Influence of biomass chemical properties
 289 on torrefaction characteristics. *Energy & Fuels* 2013;27:7541–8.

290 [29]Trubetskaya A, Jensen PA, Jensen AD, Steibel M, Spliethoff H, Glarborg P. Influence of fast
 291 pyrolysis conditions on yield and structural transformation of biomass chars. *Fuel Process Technol*
 292 2015;140:205–14.

293 [30]Baxter L, Ip L, Lu H, Tree D. Distinguishing biomass combustion characteristics and their
 294 implications for sustainable energy. *5th Asia-Pacific Conf Combust* 2005:469–74.

295 [31]Momeni M, Yin C, Kær SK, Hansen TB, Jensen PA, Glarborg P. Experimental Study on
 296 Effects of Particle Shape and Operating Conditions on Combustion Characteristics of Single
 297 Biomass Particles. *Energy & Fuels* 2013;27:507–14.

298 [32]Jones JM, Darvell LI, Bridgeman TG, Pourkashanian M, Williams A. An investigation of the
 299 thermal and catalytic behaviour of potassium in biomass combustion. *Proc Combust Inst*
 300 2007;31:1955–63.

301 [33]Antal MJ, Gronli M. The Art , Science , and Technology of Charcoal Production. *Ind Eng*
 302 *Chem Res* 2003;42:1619–40.

303 [34]Fahmi R, Bridgwater AV., Darvell LI, Jones JM, Yates N, Thain S, et al. The effect of alkali
304 metals on combustion and pyrolysis of Lolium and Festuca grasses, switchgrass and willow. Fuel
305 2007;86:1560–9.

306 [35]Perander M, DeMartini N, Brink A., Kramb J, . Karlström O, Hemming J, et al. Catalytic effect
307 of Ca and K on CO₂ gasification of spruce wood char. Fuel 2015;150:464–72.

308 [36]Zhang S, Dong Q, Zhang L, Xiong Y, Liu X, Zhu S. Effects of water washing and torrefaction
309 pretreatments on rice husk pyrolysis by microwave heating. Bioresour Technol 2015;193:442–8.

310 [37]Broido A, Nelson MA. Char yield on pyrolysis of cellulose. Combust Flame 1975;24:263–8.

311 [38]Kilzer FJ, Broido A. Speculations on nature of cellulose pyrolysis. Pyrodynamic 1965;2:151.

312 [39]Wannapeera J, Fungtammasan B, Worasuwanarak N. Effects of temperature and holding time
313 during torrefaction on the pyrolysis of woody biomass. 19th Eur Biomass Conf Exhib 2011;92:99–
314 105.

315 [40]Wu X, Tang J, Wang J. A new active site/intermediate kinetic model for K₂CO₃-catalyzed
316 steam gasification of ash-free coal char. Fuel 2016;165:59–67.

317 [41]Tang J, Wang J. Catalytic steam gasification of coal char with alkali carbonates: A study on
318 their synergic effects with calcium hydroxide. Fuel Process Technol 2016;142:34–41.

319

320

321

322 Table 1. Gross calorific value, proximate and ultimate analysis of Schima wood.

Parameter	Unit	value
Gross calorific value	MJ/kg (as received)	18.7
Moisture	wt% (as received)	5.6
Ash	wt% (as received)	1.2
Volatiles	wt% (as received)	75.6
Fixed carbon	wt% (as received)	17.7
Carbon (C)	wt% (dry basis)	49.6
Hydrogen (H)	wt% (dry basis)	6.1
Nitrogen (N)	wt% (dry basis)	< 0.2
Sulphur (S)	wt% (dry basis)	< 0.1
Chlorine (Cl)	wt% (dry basis)	< 0.2
Aluminum (Al)	mg/kg(dry basis)	260
Calcium (Ca)	mg/kg(dry basis)	590
Iron (Fe)	mg/kg(dry basis)	110
Potassium (K)	mg/kg(dry basis)	850
Magnesium (Mg)	mg/kg(dry basis)	210
Sodium (Na)	mg/kg(dry basis)	< 10
Phosphorus (P)	mg/kg(dry basis)	2500
Silicon (Si)	mg/kg(dry basis)	1100

Figure 1. Schematic diagram of the SPC reactor.

325

326 Figure 2. Ignition time of raw and pretreated particles as a function of the fuel particle mass in the

327 SPC reactor (1225°C, 3.1% O₂ and 26.1% H₂O). Red, blue and black symbols denote the washed

328 samples, KCl impregnated samples, and sample without these two pretreatment, respectively.

329

330 Figure 3. Devolatilization time of raw and pretreated particles as a function of the fuel particle mass

331 in the SPC reactor (1225°C, 3.1% O₂ and 26.1% H₂O). Red, blue and black symbols denote the

332 washed samples, KCl impregnated samples, and sample without these two pretreatment, respectively.

333

334

335 Figure 4. The char yield of pretreated and untreated fuel particles. Each value is the mean of five
 336 individual experiments in the SPC reactor (1225°C, 3.1% O₂ and 26.1% H₂O), and error bars
 337 indicate standard deviation.

338

339

340 Figure 5. TG results of the oxidation of selected chars obtained from the SPC reactor. The results

341 are dry ash free (daf) basis, obtained with a heating rate of 10 °C/min and 5% O₂ in N₂.

342

343 Figure 6. Char burnout times versus the char mass obtained in the SPC reactor (1225°C, 3.1% O₂

344 and 26.1% H₂O). Red, blue and black symbols denote the washed samples, KCl impregnated

345 samples, and sample without these two pretreatment, respectively.