



Reaction to fire of glass/ hemp/ furan composites

Markert, Frank

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Markert, F. (Author). (2017). Reaction to fire of glass/ hemp/ furan composites. Sound/Visual production (digital)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.


Reaction to fire of glass/ hemp/ furan composites

Frank Markert

Section for Building Design

Fire Safety Group

fram@byg.dtu.dk



Scope of the presentation

- Furfuryl alcohol is used for wood coatings and many other purposes in industries
- The paper is investigating the reaction to fire for composites using:
 - resin of **furfuryl alcohol** & **glass fibers** or **hemp fibers**.
- The composites are made at DTU wind energy using a compression moulding technique
- The samples used for the fire tests had been stored for some years under ambient conditions inside a laboratory environment.
- TGA results are reported and compared to literature data

Production path of the PFA resin

Sugar cane
or
agricultural wastes



Sugar extraction



BAGASSE

Lignin, Cellulose

Hemicellulose






Figure 5. Example of hemicellulose structure: L-arabino-D-xylane according to Ebringerova et al.^[44]

Hemicellulose



Furfural



Furfuryl alcohol

Oligomerisation



Source: TransFurans Chemicals (TFC)

Furfuryl alcohol


- **Thermoset composites using renewable resources:**

- **Furanic resins**


- **Possible fibres:**

- **Hemp**
 - **Flax**
 - **Wood**
 - **Glass**
 - **...**

PyMOL for evaluation only.
Contact sales@delsci.com.




Furfuryl alcohol



Production of (bio-)composites


- Composites made of glass or hemp fibers and furfuryl-alcohol are an alternative for fossil fuel based conventional materials
- Such composites have excellent strength and furfuryl alcohol is manufactured from agricultural residues
- In general, many different sustainable bio-composites are developed in many different areas as they are seen as excellent alternatives to conventional materials with regard to their weight-strength ratio.



Reaction to fire





before




after

- Both, the glass fiber furan and the hemp fiber furan composites were found to be difficult to ignite
- The furfuryl alcohol resin burns away leaving intact woven mat.

TGA of furan hemp composite



TGA results for PFA



Kandola, B. & Krishnan, L., 2014. Fire performance evaluation of different resins for potential application in fire resistant structural marine composites. Fire Safety Science, 11, pp.769–780.

PFA –lit: Guadalupe Rivero, Sara Villanueva, L.B.M., 2014. Furan resin as a replacement of phenolics: influence of the clay addition on its thermal degradation and fire behaviour. Fire and Materials, 38, pp.683–694.

conclusions

- Hemp and glassfibre PFA composites are investigated using TGA
- PFA degrades at high temperatures and has high residue yield
 - Black crystalline powder
- Degradation under oxidizing conditions are faster less residue yields
- Better performance compared to cellulose
- Co-polymerization as in PFA-phenolic resin may give improvements

THAT'S ALL FOR NOW

THANK YOU


QUESTIONS ?

fram@byg.dtu.dk

abstract

Composites made of glass or hemp fibers and furfuryl-alcohol are an alternative for fossil fuel based conventional materials [1]–[3]. Such composites have excellent strength and furfuryl alcohol is manufactured from agricultural residues [4]. In general, many different sustainable bio-composites are developed in many different areas as they are seen as excellent alternatives to conventional materials with regard to their weight-strength ratio. Nevertheless, biomaterials are combustible and therefore their application depends on the actual fire performance of these compounds. These have to follow the fire safety regulations. The paper is investigating the reaction to fire for two composites using a resin of furfuryl alcohol and glass fibers as well as hemp fibers. The composites are made at DTU wind energy using vacuum compression moulding and are tested for their mechanical strength. The samples used for the fire tests had been stored for some years under ambient conditions inside a laboratory environment. Different methods are used to investigate the reaction to fire: Vertical upward flame spread; Bomb calorimeter, Mass loss cone calorimeter, STA tests under inert atmosphere.

Both, the glass fiber furan and the hemp fiber furan composites were found to be difficult to ignite, as no ignition occurred in the flame spread tests using a normal lighter. It needed a gas burner to ignite the samples. The flame spread was moderate, but no self-extinction occurred in the case of glass fiber furan composite. This is also reflected by the preliminary results of the STA analysis showing that the degradation under nitrogen atmosphere is giving a residue of above 50% of the sample mass both for a literature example measured by Rivero et al [5] and by DTU. Changing the atmosphere to air the main combustion is taking place at about 700 K leading to complete degradation [6].



The findings will be more detailed presented and it will be argued about the benefits and constraints using these types of composites in applications, as e.g. as materials for wind mills or marine applications.

References

- [1] Y. Dong, "Wood/Polymer Nanocomposites Prepared by Impregnation with Furfuryl Alcohol and Nano-SiO₂," *Bioresources*, vol. 9, no. 4, pp. 6028–6040, 2014.
- [2] D. R. Arnold and J. L. Buzzard, "A novel process for furfural production," in *South African Chemical Engineering Congress 3-5th September 2003*, 2003.
- [3] F. Gao, Q. Lu, H. Pang, and S. Komarneni, "Sandwich-type polymer nanofiber structure of poly(furfuryl alcohol): an effective template for ordered porous films.," *J. Phys. Chem. B*, vol. 113, no. 37, pp. 12477–81, Sep. 2009.
- [4] EMPA, "LCA overview of furan and lignin based ecobinders," 2008.
- [5] L. B. M. Guadalupe Rivero, Sara Villanueva, "Furan resin as a replacement of phenolics: influence of the clay addition on its thermal degradation and fire behaviour," *Fire Mater.*, vol. 38, pp. 683–694, 2014.
- [6] B. Kandola and L. Krishnan, "Fire performance evaluation of different resins for potential application in fire resistant structural marine composites," *Fire Saf. Sci.*, vol. 11, pp. 769–780, 2014.