



Optical measuring system with an interrogator and a polymer-based single-mode fibre optic sensor system

Nielsen,, Kristian; Bang, Ole

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Nielsen, K., & Bang, O. (2017). Optical measuring system with an interrogator and a polymer-based single-mode fibre optic sensor system. (Patent No. WO2017093458).

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



- (51) International Patent Classification:
G01D 5/353 (2006.01)
- (21) International Application Number:
PCT/EP2016/079541
- (22) International Filing Date:
2 December 2016 (02.12.2016)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
15197578.6 2 December 2015 (02.12.2015) EP
- (71) Applicant: DANMARKS TEKNISKE UNIVERSITET [DK/DK]; Anker Engelunds Vej 101 A, DK-2800 Kgs. Lyngby (DK).
- (72) Inventors: NIELSEN, Kristian; Virumgade 27B, DK-2830 Virum (DK). BANG, Ole; Kongevejen 215, DK-2830 Virum (DK).
- (74) Agent: INSPICOS P/S; Kogle Allé 2, 2970 Hørsholm (DK).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))



WO 2017/093458 A1

(54) Title: OPTICAL MEASURING SYSTEM WITH AN INTERROGATOR AND A POLYMER-BASED SINGLE-MODE FIBRE OPTIC SENSOR SYSTEM




Fig. 1

(57) Abstract: The present invention relates to an optical measuring system comprising a polymer-based single-mode fibre-optic sensor system (102), an optical interrogator (101), and an optical arrangement (103) interconnecting the optical interrogator (101) and the polymer-based single-mode fibre-optic sensor system (102). The invention further relates to an optical interrogator adapted to be connected to a polymer-based single-mode fibre-optic sensor system via an optical arrangement. The interrogator comprises a broadband light source arrangement (104) and a spectrum analysing arrangement which receives and analyses light reflected from the polymer-based single-mode fibre-optic sensor system.

OPTICAL MEASURING SYSTEM WITH AN INTERROGATOR AND A POLYMER-BASED SINGLE-MODE FIBRE-OPTIC SENSOR SYSTEM

FIELD OF THE INVENTION

The present invention relates to an optical measuring system and an optical interrogator
5 comprised in the system. In particular, the invention relates to an optical measuring system with a large bandwidth covering more than 2000 nm.

BACKGROUND OF THE INVENTION

Various optical sensor interrogation systems for measuring different physical parameters have been suggested over the years.

10 For example, WO 2013/169098 discloses an optical sensor interrogation system comprising a light source, optical arrangements for connecting the source and sensor(s), a detector for receiving optical response from the sensor(s) and a data processing system. More precisely, the system comprises two optical arrangements, one to guide the light from the source and another one to guide the light reflected from the sensor. These arrangements are described
15 mainly to comprise free-space optics connecting a fibre-based source and a fibre sensor what is a disadvantage of the system since it cannot be installed with sensors at one location and the interrogator at another.

US 2014/0233020 relates to an interrogator for a plurality of sensor fibre-optic gratings. The interrogator comprises a broadband optical source, at least one beam-splitter directing
20 output of the source to an array of sensors, and at least one optical receiver.

None of the aforementioned references disclose sensors as polymer-based single-mode fibre sensors comprising fibre-Bragg gratings.

It is an object of embodiments of the present invention to provide an optical measuring system which combines a polymer-based single-mode fibre-optic sensor system with an
25 interrogator.

It is a further object of embodiments of the present invention to provide an optical measuring system suitable for being mounted in for example off-shore constructions and remote locations.

DESCRIPTION OF THE INVENTION

- 5 The above-mentioned objects are complied with by providing, in a first aspect, to an optical measuring system comprising
- 1) a polymer-based single-mode fibre-optic sensor system, comprising at least one fibre-Bragg grating;
 - 10 2) an optical interrogator comprising a broadband light source arrangement for emitting light at a plurality of wavelengths within a wavelength range, and a spectrum analysing arrangement for receiving and analysing light reflected from the polymer-based single-mode fibre-optic sensor system; and
 - 15 3) an optical arrangement interconnecting the optical interrogator and the polymer-based single-mode fibre-optic sensor system.

The polymer-based single-mode fibre-optic sensor system may comprise a plurality of polymer single-mode optical fibres. The polymer single-mode optical fibres may be micro-structured fibre. Multi-mode polymer fibres may optionally constitute part of the the sensor system as well.

In the present context, "polymer-based" fibre should be understood as a fibre having a polymer core with or without dopants. Such dopants may increase the sensitivity in relation to specific materials surrounding the optical sensor or may target the sensitivity of the sensor. Possible dopants may include any chemical compounds and even particles. The polymer base material of the core may be polymethylmethacrylate (PMMA). The cladding as well as the cap of the optical fibre structure may comprise polymer materials as well as materials like metal, semiconductors, ceramics etc.

30 In a preferred embodiment, the polymer-based single-mode fibre-optic sensor system comprises a plurality of single-mode polymer optical fibres where each of the polymer optical fibres comprises one or more fibre-Bragg gratings (FBGs) being arranged therein. The FBG may be placed only at a sensing point of the sensor. Each FBG is adapted to measure at least one physical parameter. The parameter may be any physical parameter, such as strain, 35 temperature, pressure, humidity, and/or any other parameter. The FBG is a structure

imprinted in a short segment of polymer-based single-mode optical fibre, at a sensing point, as mentioned above, so that the index of refraction varies in a periodic manner along the grating causing a particular wavelength of light to be reflected while all the others are transmitted. The physical parameter to be measured causes changes in the refractive index or the periodicity of the grating and therefore a shift in the reflected wavelength. By 5 determining this wavelength shift, the physical parameter can be determined. Typically, the FBGs may reflect light in the range from 400 to 2500 nm, such as in the wavelength range from 400 to 2000 nm, such as in the wavelength range from 400 to 1500 nm, such as in the wavelength range from 400 to 1200 nm, such as in the wavelength range from 400 to 1000 10 nm, such as in the wavelength range from 500 to 900 nm, or such as within the wavelength range from 600 to 650 nm. However, other wavelength ranges are applicable as well.

In one embodiment, the polymer-based single-mode fibre-optic sensor system may comprise three FBGs being adapted to measure strain, temperature and humidity at essentially the same time. These FBGs may be imprinted into a single polymer fibre being spatially displaced 15 along the fibre. In another embodiment, the plurality of FBGs of at least one single-mode polymer optical fibre may be imprinted into essentially the same spot. The FBGs arranged in this manner form a compact structure. In this case, the periods of the gratings are slightly different in order to reflect different wavelengths, thereby enabling measurement of different physical parameters.

20 The optical measuring system further includes an optical interrogator for interrogation of the polymer-based single-mode fibre-optic sensor system. The interrogator comprises a broadband light source arrangement and a spectrum analysing arrangement.

The broadband light source arrangement is configured to emit light at a plurality of wavelengths within a broad wavelength range. It may in principle involve any type of a single 25 broadband light source, such as superluminescent diodes, semiconductor optical amplifiers (SOAs), amplified spontaneous emission (ASE) source, super continuum fibre lasers or white light lasers, such as SuperK light sources. In another embodiment, it may also involve an array of single-wavelength lasers covering broad bandwidth. In a preferred embodiment of the invention, the broadband light source arrangement is adapted to emit light in the 30 wavelength range from 400 to 2500 nm, such as in the wavelength range from 400 to 2000 nm, such as in the wavelength range from 400 to 1500 nm, such as in the wavelength range from 400 to 1200 nm, such as in the wavelength range from 400 to 1000 nm, such as in the wavelength range from 500 to 900 nm, or such as in the wavelength range from 600 to 650 nm. However, other wavelength ranges are applicable as well. The bandwidth of the 35 broadband light source defines the bandwidth of the optical interrogator.

The spectrum analysing arrangement is configured to receive and analyse light reflected from the polymer-based single-mode fibre-optic sensor system. According to the invention, the spectrum analysing arrangement may comprise a single fibre-based broadband photodetector, charge-coupled device (CCD) spectrometer, or one or more discrete
5 photodetectors for detecting different wavelength ranges. The bandwidth of the spectrum analysing arrangement may be at least matched, if not larger than the bandwidth of the broadband light source arrangement. Naturally, the spectrum analysing arrangement may further comprise a digital signal processor for processing the detected light beam.

The optical measuring system may further include an optical arrangement interconnecting
10 the optical interrogator and the polymer-based single-mode fibre-optic sensor system. In one embodiment, the optical arrangement may form a silica-based fibre-optic distribution network. The silica-based fibre-optic distribution network may comprise one or more silica-based single-mode optical fibres, one or more silica-based optical splitters and couplers and/or one or more silica-based fibre multiplexers. All the components comprised in the
15 distribution network must support the entire bandwidth of the optical interrogator. Optical splitters make the optical measuring system suitable for installation in large areas, in which the optical interrogator may be located in one room while all the sensors are distributed elsewhere.

According to one embodiment of the invention, an optical measuring system in its most basic
20 implementation has a distribution network comprised of only a single fibre-optic circulator. In another embodiment, where the optical measuring system comprises N optical sensors, the optical distribution network may be represented by a fibre-optic circulator and 1-to-N splitter/coupler. In an embodiment in which $N=2$, the optical distribution network may be represented by a fibre-optic circulator and a silica-based fibre coupler. The connection
25 between the silica-based optical network and polymer-based single-mode optical fibre sensors may be established by appropriate mechanical connectors. The optical distribution network may support bi-directional light path, i.e. both the light sent from the broadband light source and the light reflected from the sensor system may be guided by the same components.

30 In another embodiment, the optical measuring system may comprise an optical distribution network formed by free-space optics. Such a network may comprise lenses, beam-splitters, prisms, mirrors, diffractive elements, etc. which guide/collimate/direct the light beam to/from the interrogator to the polymer-based single-mode fibre-optic sensor system through free-space.

The optical measuring system can be deployed in different environments, such as houses, tall buildings, large ships or even off-shore constructions. Depending on the application, a single-parameter sensor may be placed in the environment in which only one physical parameter needs to be measured, while a multi-parameter sensor will be placed in the environment requiring knowledge about a plurality of physical parameters such as strain, temperature, pressure, humidity, or/and other requiring parameters. When installed in remote locations, the optical measuring system may need to be remotely monitored and controlled. Therefore, the invention may further comprise a wireless communication system adapted to provide data to and/or from the optical measuring system.

10 According to a further embodiment, the optical measuring system may comprise a power supply system which can be a standard supply obtaining the energy from an electrical source, or alternatively it can be powered by a renewable power source, including solar panels, wind power systems etc. The latter examples would be of particular importance when the optical measuring system is installed on a ship or an off-shore construction.

15 In a second aspect, the present invention relates to an optical interrogator adapted to be connected to a polymer-based single-mode fibre-optic sensor system via an optical arrangement. The optical interrogator according to the second aspect comprises:

- 20 1) a broadband light source arrangement for emitting light at a plurality of wavelengths within a wavelength range; and
- 2) a spectrum analysing arrangement for receiving and analysing light reflected from the polymer-based single-mode fibre-optic sensor system.

25 The broadband light source arrangement of the optical interrogator is adapted to emit light at a plurality of wavelengths in the wavelength range from 400 to 2500 nm, such as in the wavelength range from 400 to 2000 nm, such as in the wavelength range from 400 to 1500 nm, such as in the wavelength range from 400 to 1200 nm, such as in the wavelength range from 400 to 1000 nm, such as in the wavelength range from 500 to 900 nm, or such as in the wavelength range from 600 to 650 nm.

30 The spectrum analysing arrangement of the optical interrogator may comprise charge-coupled device (CCD) spectrometer or a plurality of discrete detectors.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described in further details with reference to the accompanying drawings, in which:

5 Fig. 1 illustrates an optical measuring system with N sensors, where each sensor is adapted to measure three physical parameters.

Fig. 2 illustrates an optical measuring system with N sensors, where each sensor is adapted to measure one physical parameter.

Fig. 3 illustrates an optical measuring system adapted to measure one physical parameter.

Fig. 4 illustrates an optical measuring system comprising a wireless communication system.

10 Fig. 5 illustrates an optical measuring system with free space optics as a distribution network.

While the invention is susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and will be described in detail herein. It should be understood, however, that the following description relates to examples of embodiments, and the invention is not intended to be limited to the particular
15 forms disclosed. Rather, the invention covers all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION OF THE INVENTION

In its most general aspect, the present invention relates to an optical measuring system and an optical interrogator for measuring a plurality of physical parameters at essentially the
20 same time. The optical measuring system comprises an optical interrogator and a polymer-based single-mode fibre-optic sensor system being interconnected via an optical arrangement, such as an optical distribution network. The optical measuring system according to the present invention may advantageously be used in a wide variety of applications due to its large bandwidth.

25 The present invention further relates to an optical interrogator comprising a broadband light source arrangement and a corresponding detection system, i.e. spectrum analysing arrangement, in which the interrogator is adapted to be connected to a polymer-based single-mode fibre-optic sensor system via an optical arrangement.

In Fig. 1, the optical measuring system 100 of the present invention is shown. The system comprises an optical interrogator 101 and a fibre-optic sensor system 102 connected via an optical arrangement 103.

The optical interrogator 101, which is a single unit, comprises a broadband light source arrangement 104 and a spectrum analysing arrangement 105. It further comprises an output 5 104' connected to the source. Typically, the output 104' is a silica-based optical fibre which outputs the light from the interrogator. An optical input to the interrogator 105' can also be implemented by the use of a silica-based optical fibre connecting the optical arrangement and the spectrum analysing arrangement 105. In some embodiments, the interrogator may 10 comprise a plurality of input and output ports 105' and 104' for a direct connection to the polymer-based single-mode fibre-optic sensor system. A number of additional components such as different electronic circuits, signal processing units, and various connections therein are not shown in the figure. Furthermore, the interrogator comprises a power supply (also not shown in the figure) which can be a standard supply obtaining the energy from an electrical 15 source, or it can be powered by a solar panel. The latter example would be of particular importance when the optical measuring system is installed on a ship or an off-shore construction. Additionally, the interrogator may comprise a number of optical components, such as filters, beam-splitters, gratings, amplifiers, etc. which interconnect the source and spectrum analysing arrangement and create a feed-back loop to provide a stable system 20 without any wavelength errors.

The broadband light source arrangement 104 may comprise a single broadband source, such as a white light laser, supercontinuum laser, superluminescent diode, semiconductor optical amplifiers, an amplified spontaneous emission source, or an array of single-wavelength lasers covering broad bandwidth. In a preferred embodiment of the invention, the broadband light 25 source arrangement is adapted to emit light in the wavelength range from 400 to 2500 nm, such as in the wavelength range from 400 to 2000 nm, such as in the wavelength range from 400 to 1500 nm, such as in the wavelength range from 400 to 1200 nm, such as in the wavelength range from 400 to 1000 nm, such as in the wavelength range from 500 to 900 nm, or such as in the wavelength range from 600 to 650 nm. The bandwidth of the 30 broadband light source defines the bandwidth of the optical interrogator 101.

The spectrum analysing arrangement 105 for receiving and analysing light reflected from the fibre-optic sensor system may comprise a single fibre-based broadband photodetector, a charge-coupled device spectrometer or one or more photodetectors for detecting different 35 wavelength ranges. The bandwidth of the spectrum analysing arrangement 105 is preferably at least matched, if not larger than the bandwidth of the broadband light source arrangement

104. Naturally, the spectrum analysing arrangement 105 may further comprise processor means for processing the detected light beam.

In a preferred embodiment of the invention, the fibre-optic sensor system 102 comprises N polymer-based single-mode optical fibres 106⁽¹⁾, 106⁽²⁾, and 106^(N), where N can be any

5 positive integer. Typically, the polymer-based single-mode optical fibre can be a micro-structured fibre. Multimode polymer-based fibres may also serve as sensors and may be included in the system. The polymer-based single-mode fibre-optic sensor 106⁽¹⁾, 106⁽²⁾, and 106^(N) may comprise a plurality of FBGs. As an example, a sensor with three spatially overlapping FBGs, 107, 108, and 109 is illustrated in Fig. 1. The FBGs arranged in this

10 manner form a compact structure. In another implementation, FBGs may also be spatially displaced. Each FBG is adapted to measure at least one physical parameter. The parameter may be any physical parameter, such as strain, temperature, pressure, humidity, or/and other parameter. Typically, the FBGs 107, 108, and 109 may reflect light in the range from 400 to 2500 nm, such as in the wavelength range from 400 to 2000 nm, such as in the

15 wavelength range from 400 to 1500 nm, such as in the wavelength range from 400 to 1200 nm, such as in the wavelength range from 400 to 1000 nm or such as in the wavelength range from 500 to 900 nm, or such as in the wavelength range from 600 to 650 nm.

However, other wavelength ranges are applicable as well. In the case where the sensor comprises a number of spatially overlapped FBG, the periods of the gratings are slightly

20 different in order to reflect different wavelengths enabling measurement of different physical parameters.

The optical arrangement 103 may form a silica-based fibre-optic distribution network which comprises one or more silica-based single-mode optical fibres, one or more silica-based optical splitters and couplers, one or more silica-based fibre multiplexers or free-space optical

25 lens systems. All the components comprised in the optical distribution network must support the entire bandwidth of the optical interrogator 101. Optical splitters provide a point to multipoint topology, making the optical distribution network suitable for installation in large areas, such as tall buildings, large ships or off-shore constructions where the optical interrogator is located in one room while all the sensors are distributed elsewhere. In such

30 arrangements the optical fibres connecting the optical arrangement 103 and fibre-optic sensor system 102 may be very long.

The splitters also provide an easy upgrade with minimal change of the existing network. In the embodiment illustrated in Fig. 1, the optical distribution network is represented by a single fibre-optic circulator 110 and 1-to-N splitter/coupler 111, since it may be sufficient to

35 ensure the connection with N optical sensors. In an embodiment in which N=2, coupler 111 will be implemented by a simple 1-to-2 coupler. The connection between the silica-based

optical network and polymer-based single-mode optical fibre sensors may be established by appropriate mechanical connectors. Arrows in the optical arrangement 103 show the directions of the light waves traveling through the optical measuring system. It should be noted that the optical distribution network supports bi-directional light path, i.e. both the light sent from the broadband light source and the light reflected from the sensor system may be guided by the same components. Although the fibre-optic circulator 110 is likely to provide the best signals a conventional 2x2 coupler will be sufficient in many cases.

Fig. 2 illustrates another embodiment of an optical measuring system 200 which comprises the same optical interrogator 201 as that of embodiment of Fig. 1 and a fibre-optic sensor system 202 connected to the interrogator 201 via the optical distribution network 203. In this embodiment, the sensor system comprises N polymer-based single-mode fibre-optic sensors, $206^{(1)}$, $206^{(2)}$, and $206^{(N)}$. These sensors comprise only one FBG 207 so that each sensor may be used for measuring only one physical parameter. Sensors $206^{(1)}$, $206^{(2)}$, and $206^{(N)}$ can, however, measure different physical parameters. In another embodiment, the optical measuring system may comprise a combination of single-parameter sensors (sensors comprising one FBG) and multi-parameter sensors (sensors comprising plurality of FBGs). Depending on the application, a single-parameter sensor may be placed in the environment in which only one physical parameter needs to be measured, while a multi-parameter sensor will be placed in the environment requiring knowledge about a plurality of physical parameters such as strain, temperature, pressure, humidity, or/and other requiring parameters.

Yet another embodiment of the invention is illustrated in Fig. 3 which shows an optical measuring system 300 in its most basic implementation, comprising only the essential parts of the present invention. The system comprises an optical interrogator 301 and a polymer-based single-mode fibre-optic sensor 303 connected via an optical distribution network, which, in this embodiment, is represented by a single fibre-optic circulator 302. The sensor 303 is shown with only one FBG 306 for measuring one physical parameter, however, it may be replaced by a sensor having a plurality of spatially displaced FBGs, or even a plurality of spatially overlapping gratings, so that the optical measuring system comprising only one sensor may provide information of more than one physical parameter at essentially the same time.

Additionally, the optical measuring system 400 illustrated in Fig. 4 may further comprise a wireless communication system 408 adapted to provide data to and/or from the optical measuring system. This can be implemented in different monitoring systems installed in large areas, such as tall buildings, large ships or even off-shore constructions, so that these can be monitored and possibly controlled remotely.

Alternatively, the optical measuring system may comprise an optical arrangement built from free-space optic components. Such a system is illustrated in Fig. 5. The optical measuring system 500 is depicted comprising an optical interrogator 501 with the broadband light source arrangement 504 and the spectrum analysing arrangement 505. In the illustrated embodiment, the system 500 comprises only one polymer-based single-mode fibre-optic sensor 503 having only one FBG. The optical arrangement 502 comprises a plurality of optical lenses 506, 507, 508 and an optical prism 509 guiding the light beam through free space. Optical lenses 506, 507, 508 collimate a light beam propagating through free space, ensuring good coupling with fibre-based sensor 503 as well as with the input to the interrogator, i.e. the spectrum analysing arrangement 505. The optical prism 509 directs the light beam, ensuring that the light reflected from the sensor 503, i.e. its FBG, does not travel towards the broadband source 504. In another embodiment, sensor 503 with only one FBG 511 may be replaced by a sensor comprising multiple spatially overlapping, spatially displaced gratings, or alternatively, it may be replaced by a plurality of sensors. In that case, the optical arrangement would need to be modified to accommodate for more sensors. In one embodiment, the optical prism 509 may be replaced by a diffractive optical element configured to direct the light beam at different angles of incidence onto a plurality of sensors.

CLAIMS

1. An optical measuring system comprising

1) a polymer-based single-mode fibre-optic sensor system, comprising at least one fibre-Bragg grating;

5

2) an optical interrogator comprising a broadband light source arrangement for emitting light at a plurality of wavelengths within a wavelength range, and a spectrum analysing arrangement for receiving and analysing light reflected from the polymer-based single-mode fibre-optic sensor system; and

10

3) an optical arrangement interconnecting the optical interrogator and the polymer-based single-mode fibre-optic sensor system.

2. An optical measuring system according to claim 1, wherein the broadband light source arrangement is adapted to emit a plurality of wavelengths within the wavelength range 400-2500 nm, such as within the wavelength range 400-2000 nm, such as within the wavelength range 400-1500 nm, such as within the wavelength range 400-1200 nm, such as within the wavelength range 400-1000 nm, such as within the wavelength range 500-900 nm, such as within the wavelength range 600-650 nm.

15

3. An optical measuring system according to claim 1 or 2, wherein the spectrum analysing arrangement comprises a spectrum analyser, said spectrum analyser comprising a charge-coupled device (CCD) spectrometer or a plurality of discrete detectors.

20

4. An optical measuring system according to any of the preceding claims, wherein the optical arrangement interconnecting the optical interrogator and the polymer-based single-mode fibre-optic sensor system comprises a silica-based fibre-optic arrangement.

25

5. An optical measuring system according to claim 4, wherein the silica-based fibre-optic arrangement forms a silica-based fibre-optic distribution network.

6. An optical measuring system according to claim 5, wherein the silica-based fibre-optic distribution network comprises one or more silica-based fibre circulators and/or one or more silica-based fibre couplers.

7. An optical measuring system according to any of claims 1-3, wherein the optical arrangement interconnecting the optical interrogator and the polymer-based single-mode fibre-optic sensor system comprises a free-space optical lens systems.

5 8. An optical measuring system according to any of the preceding claims, wherein the polymer-based single-mode fibre-optic sensor system comprises one or more polymer-based single-mode optical fibres, and wherein each of the one or more polymer-based single-mode optical fibres comprises one or more fibre Bragg gratings being arranged therein.

9. An optical measuring system according to claim 8, wherein the one or more fibre Bragg gratings are adapted to measure at least one physical parameter.

10 10. An optical measuring system according to claim 9, wherein at least one of the one or more polymer-based single-mode optical fibres comprise three fibre Bragg gratings being adapted to measure strain, temperature and humidity at essentially the same time.

11. An optical measuring system according to claim 10, wherein the three fibre Bragg gratings of the at least one polymer-based single-mode optical fibre are located at essentially
15 the same spot.

12. An optical measuring system according to any of the preceding claims, further comprising

1) a wireless communication system adapted to provide data to and/or from the optical measuring system, and

20 2) a power supply system.

13. An optical measuring system according to any of the preceding claims, wherein the broadband light source arrangement comprises a broadband laser source, such as a supercontinuum laser source.

14. An optical interrogator being adapted to be connected to a polymer-based single-mode
25 fibre-optic sensor system via an optical arrangement, the optical interrogator comprising:

1) a broadband light source arrangement for emitting light at a plurality of wavelengths within a wavelength range; and

2) a spectrum analysing arrangement for receiving and analysing light reflected from the polymer-based single-mode fibre-optic sensor system.

15. An optical interrogator according to claim 14, wherein the broadband light source arrangement is adapted to emit light at a plurality of wavelengths within the wavelength
5 range 400-2500 nm, such as within the wavelength range 400-2000 nm, such as within the wavelength range 400-1500 nm, such as within the wavelength range 400-1200 nm, such as within the wavelength range 400-1000 nm, such as within the wavelength range 500-900 nm, or such as within 600-650 nm..

16. An optical interrogator according to claim 14 or 15, wherein the spectrum analysing
10 arrangement comprises a spectrum analyser comprising a charge-coupled device (CCD) spectrometer or a plurality of discrete detectors.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2016/079541

A. CLASSIFICATION OF SUBJECT MATTER
INV. G01D5/353
ADD.
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
Minimum documentation searched (classification system followed by classification symbols)
G01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	US 2014/203783 A1 (KIESEL PETER [US] ET AL) 24 July 2014 (2014-07-24) abstract paragraphs [0009], [0034], [0037], [0049], [0056], [0057]; figures 1(A), 3, 7	1-4,8,9, 14-16 5-7, 10-13
Y	EP 0 146 522 A2 (MONSANTO CO [US]) 26 June 1985 (1985-06-26) abstract; figure 2 page 5, line 22 - page 6, line 24 page 8, line 29 - page 9, line 3	5-7, 10-13
Y	US 2006/045412 A1 (XIAO GAOZHI [CA] ET AL) 2 March 2006 (2006-03-02)	5-7
A	paragraphs [0006] - [0009]; figures 3-6 ----- -/--	1-4,8-16

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search 30 January 2017	Date of mailing of the international search report 09/02/2017
--	--

Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Thomas, Judith
--	--

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2016/079541

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2013/052932 A1 (OFS FITEL LLC; DI GIOVANNI DAVID J [US]; SUMETSKY MIKHAIL [US]) 11 April 2013 (2013-04-11) abstract page 3, lines 10-19 page 4, lines 3-6 page 5, lines 3-21 page 9, lines 21-25; figures 1, 2 -----	1,14
A	WO 2007/137429 A1 (ITF LAB INC [CA]; DU XIN MING [CA]) 6 December 2007 (2007-12-06) abstract paragraphs [0005], [0016], [0022] -----	1-16
A	CN 102 507 074 A (UNIV ZHEJIANG NORMAL) 20 June 2012 (2012-06-20) figure 1 -----	1-16

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/EP2016/079541

Patent document cited in search report	Publication date	Publication date	Patent family member(s)	Publication date
US 2014203783	A1	24-07-2014	NONE	

EP 0146522	A2	26-06-1985	AU 3637384 A	13-06-1985
			EP 0146522 A2	26-06-1985
			JP S60141761 A	26-07-1985

US 2006045412	A1	02-03-2006	CA 2518173 A1	02-03-2006
			US 2006045412 A1	02-03-2006

WO 2013052932	A1	11-04-2013	JP 5856307 B2	09-02-2016
			JP 2014532182 A	04-12-2014
			US 2014247453 A1	04-09-2014
			WO 2013052932 A1	11-04-2013

WO 2007137429	A1	06-12-2007	CA 2549084 A1	30-11-2007
			WO 2007137429 A1	06-12-2007

CN 102507074	A	20-06-2012	NONE	
