



Effective stresses and shear failure pressure from in situ Biot's coefficient, Hejre Field, North Sea

Stresses and shear failure pressure

Regel, Jeppe Bendix; Orozova-Bekkevold, Ivanka; Andreassen, Katrine Alling; van Gilse, N. C. Hoegh; Fabricius, Ida Lykke

Published in:
Geophysical Prospecting

Link to article, DOI:
[10.1111/1365-2478.12442](https://doi.org/10.1111/1365-2478.12442)

Publication date:
2017

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Regel, J. B., Orozova-Bekkevold, I., Andreassen, K. A., van Gilse, N. C. H., & Fabricius, I. L. (2017). Effective stresses and shear failure pressure from in situ Biot's coefficient, Hejre Field, North Sea: Stresses and shear failure pressure. *Geophysical Prospecting*, 65(3), 808-822. <https://doi.org/10.1111/1365-2478.12442>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Effective stresses and shear failure pressure from in-situ Biot's coefficient, Hejre Field, North Sea.

J.B. Regel⁺, I. Orozova-Bekkevold[#], K.A. Andreassen, and I.L. Fabricius^{*}, Technical University of Denmark, and **N.C. Høegh van Gilse**, DONG Energy

^{*}corresponding author: ilfa@byg.dtu.dk , ⁺ Present affiliation: Danish Geotechnical Institute (GEO),

[#]Present affiliation: Eni S.p.A.

Summary

We propose a combination of Biot's equations for effective stress and the expression for shear failure in a rock to obtain an expression for minimum pore pressure in a stable vertical well bore. We show that a Biot's coefficient calculated from logging data in the Hejre field, North Sea, is significantly different from 1. The log derived Biot's coefficient is above 0.8 in the Shetland chalk Group and in the Tyne Group, and 0.6 to 0.8 in the Heno sandstone Formation. We show that the effective vertical and horizontal stresses obtained using the log derived Biot's coefficient result in a drilling window for a vertical well larger than if approximating Biot's coefficient by 1. The estimation of the Biot's coefficient is straightforward in formations with a stiff frame, whereas in formations such as shales caution has to be taken. We discuss the consequence of assumptions made on the mineral composition of shales, as unphysical results could be obtained when choosing inappropriate mineral moduli.

Keywords

Borehole geophysics, Petrophysics, Rock physics.

Introduction

The Hejre field is situated in the Danish sector of the North Sea. Two wells were drilled in the field, one exploration well (Hejre-1) in 2001 and one appraisal well (Hejre-2) in 2004/05. The objective of both wells was to reach and investigate the sandstone reservoir in the Heno Formation. This is a deep (more than 5400 m) HPHT reservoir with formation pressure above 100 MPa and temperature above 160°C.

An accurate determination of the pre-production in-situ effective stresses is essential to better understand possible deformations, which might compromise borehole integrity during drilling and production (Zoback, 2007; Fjaer et al., 2008). The effective stresses are used to calculate the shear failure pressure (*SFP*) at the borehole wall (Yew and Liu, 1992; Zoback, 2007; Fjaer et al., 2008). *SFP* is one of the most important parameters when analyzing wellbore stability (Lang et al., 2011). *SFP* is a function of the effective principal stresses acting on the borehole wall, the rock properties and, in case of a deviated well, the well geometry (deviation from the vertical and, in case of horizontal stress anisotropy, azimuth with respect to the maximum horizontal stress). In the cases where *SFP* is larger than the pore pressure, *SFP* is used to determine the optimal well pressure of the drilling fluid (Yew and Liu, 1992; Fjaer et al., 2008), which mitigates the risk of borehole instabilities. The lower limit of the pressure exercised by the drilling fluid must be above *SFP*. The upper pressure limit is determined by the formations tensile strength or its ability to withstand the hydraulic fracturing. The onset of a fracture is noticed by a loss in circulated mud and the pressure level is called the leak off pressure (*LOP*). The lower limit (*SFP*) and the upper limit (*LOP*) define the “drilling window” or “drilling margins” which constitute the stable pressure interval when drilling.

The purpose of this study is to investigate the lower limit of the drilling window, the shear failure pressure from the data obtained from the drilling campaign of the two Hejre wells. As seen from the final well reports, the drilling window was estimated from experience and empirical relations (ConocoPhillips AS 2005) and no attempt was made to estimate shear failure pressure. The result was a narrow drilling window.

Background Theory

Effective stresses and principal stresses at the wall of a vertical well

The effective stresses in horizontal (h) and vertical (v) directions for an isotropic medium at a given depth were defined by (Biot 1941):

$$\begin{aligned} \sigma_{h,eff} &= \sigma_h \frac{(1-\nu)}{(1-2\nu)} - \sigma_v \frac{\nu}{(1-2\nu)} - \alpha P_p, \dots\dots\dots (1) \\ \sigma_{v,eff} &= \sigma_v \frac{1}{(1-2\nu)} - \sigma_h \frac{2\nu}{(1-2\nu)} - \alpha P_p \end{aligned}$$

where ν is the drained Poisson’s ratio and α is Biot’s coefficient. By introducing a total horizontal and vertical stress at given depth as:

$$\begin{aligned} \sigma_{h,TOT} &= \sigma_h \frac{(1-\nu)}{(1-2\nu)} - \sigma_v \frac{\nu}{(1-2\nu)} \\ \sigma_{v,TOT} &= \sigma_v \frac{1}{(1-2\nu)} - \sigma_h \frac{2\nu}{(1-2\nu)} \end{aligned}$$

Equation (1) can be generalized to the familiar expression:

$$\sigma_{i,eff} = \sigma_{i,TOT} - \alpha P_p, \dots\dots\dots (1a)$$

Please note that both σ_h and σ_v (the overburden) are contributing to the estimate of each of the total stresses.

On the wall of a vertical wellbore, we define the axial stress, σ_a , and split the horizontal stress field into a radial, σ_r , and tangential, σ_t , contribution (Fjær *et al.* 2008):

$$\sigma_a = \sigma_v \qquad \sigma_r = P_w \qquad \sigma_t = 2\sigma_h - P_w, \dots\dots\dots (2)$$

where P_w is the pressure inside the well.

Estimating rock strength

The set of Mohr-Coulomb failure parameters that define the strength of a rock, the failure angle β , and the uniaxial compressive strength, C_o , are normally obtained by compression tests in the laboratory.

Here defined as (Fjær *et al.* 2008):

$$2\beta = \frac{\pi}{2} + \phi; \quad C_o = 2S_c \tan \beta \dots\dots\dots (3)$$

In the absence of laboratory results, the angle of internal friction ϕ , and the cohesion, S_c in MPa, can be estimated from the compressive sonic log using Lal's empirical correlations (Lal 1999):

$$\sin \phi = \frac{V_p - 1}{V_p + 1}; \quad S_c = \frac{5(V_p - 1)}{\sqrt{V_p}} \dots\dots\dots (4)$$

where V_p is the elastic p-wave velocity, in km/s with units removed.

Estimating Shear failure pressure in a vertical well

The Mohr-Coloumb failure criterion is used to estimate the critical pressure at which, if exceeded, shear failure occurs:

$$\sigma_{1,eff} = C_o + \sigma_{3,eff} \cdot \tan^2(\beta) \dots\dots\dots (5)$$

where $\sigma_{1,eff}$ and $\sigma_{3,eff}$ are the effective maximum and minimum principal stresses,

The maximum and minimum among the principal stresses at the borehole wall σ_r , σ_t and σ_a are found as:

$$\sigma_1 = \max \{ \sigma_r, \sigma_t, \sigma_a \}; \sigma_3 = \min \{ \sigma_r, \sigma_t, \sigma_a \}, \dots \dots \dots (6)$$

Were σ_r , σ_t and σ_a are the radial, tangential and vertical stress and the respective effective principal stresses are approximated as (Fjær *et al.* 2009):

$$\sigma_{i,eff} = \sigma_i - \alpha P_p \dots \dots \dots (7)$$

By finding the principal stresses by equation (2), the rock strength from equation (4) and determining the minimum and maximum effective stresses by equations (6) and (7), we can solve equation (5) in order to find the minimum well pressure P_w needed to avoid shear failure collapse of the borehole. This minimum well pressure is the Shear Failure Pressure, *SFP*. For example, if $\sigma_1 = \sigma_t$ and $\sigma_3 = \sigma_r$ then from (2), (3), (5), (6) and (7):

$$P_w \equiv SFP = \frac{2\sigma_h - c_o - \alpha P_p (1 - \tan^2(\beta))}{(1 + \tan^2(\beta))}, \dots \dots \dots (8)$$

Method for calculating Biot’s coefficient and elastic moduli from log data

Biot’s coefficient can be calculated from bulk moduli (Biot 1941, Zimmermann 1991) as

$$\alpha = 1 - \frac{K_{dry}}{K_{min}}, \dots \dots \dots (9)$$

where K_{dry} is the bulk modulus of the dry rock frame and K_{min} is the bulk modulus of the mineral composing the rock frame. The saturated bulk modulus K_{sat} can be calculated from sonic log P-wave and shear velocities (V_p respectively V_s) and the bulk density as:

$$K_{sat} = \rho_b \left(V_p^2 - \frac{4}{3} V_s^2 \right), \dots\dots\dots (10)$$

and the dry rock frame modulus is calculated from the saturated modulus by the Gassmann's fluid substitution (Gassmann 1951) as given in (Mavko *et al.* 2009):

$$K_{dry} = \frac{K_{sat} \left(\frac{\varphi \cdot K_{min}}{K_{fl}} + 1 + \varphi \right) - K_{min}}{\frac{\varphi \cdot K_{min}}{K_{fl}} + \frac{K_{sat}}{K_{min}} + 1 + \varphi}, \dots\dots\dots (11)$$

where K_{fl} is the modulus of the pore fluid and φ is porosity. This method only works where shear velocity data are available. In the case where only V_p is available, an estimate of α is possible because Biot's coefficient can be estimated from the P-wave modulus of the rock frame, M_{dry} and P-wave modulus of the mineral, M_{min} (Fabricius 2014):

$$\alpha \approx 1 - \frac{M_{dry}}{M_{min}}, \dots\dots\dots (12)$$

and the P-wave modulus of the rock frame can be derived by an approximation of the Gassmann's fluid substitution as suggested by (Mavko *et al.* 2009):

$$M_{dry} \approx \frac{M_{sat} \left(\frac{\varphi \cdot M_{min}}{M_{fl}} + 1 + \varphi \right) - M_{min}}{\frac{\varphi \cdot M_{min}}{M_{fl}} + \frac{M_{sat}}{M_{min}} + 1 + \varphi}, \dots\dots\dots (13)$$

The P-wave modulus and the bulk modulus are related through:

$$K_{min} = M_{min} - \frac{4}{3} G_{min}, \quad K_{sat} = M_{sat} - \frac{4}{3} G \quad \text{and} \quad K_{dry} = M_{dry} - \frac{4}{3} G, \dots\dots\dots (14)$$

where G is the shear modulus, given as $G = \rho_b \cdot V_s^2$. Fluids have no shear component so the bulk modulus, K_{fl} is equal to the P-wave modulus, M_{fl} :

$$K_{fl} = M_{fl} , \dots\dots\dots (15)$$

The parameters to be estimated or determined are: M_{sat} and where available G , the mineral moduli: M_{min} and G_{min} , K_{fl} and φ .

Case study: Minimum well pressure at the Hejre field

Data

We use well reports and logging data (kindly provided by DONG Energy) from the two wells Hejre-1 and Hejre-2. Both wells lack relevant log data in the upper section. In Hejre-2, the relevant logs (sonic, resistivity, density) were acquired only below 2500 m, while the corresponding Hejre-1 logs were acquired only below 4700 m. An overview of the log data from Hejre-2 is given in **Figure 1**.

Relevant formation pressure data on kicks and inflows from nearby wells as well as measurements of the reservoir pressure in Hejre-1 and Hejre-2 are summarized in **Table 1**. The data from the Norwegian wells were found at the Norwegian Petroleum Directorate website (npd.no/factpages). The data for the Danish wells (Mona-6, Hejre-1, and Hejre-2) were taken from the respective well reports (Chevron Petroleum Company of Denmark 1983, DONG Efterforskning og Produktion 2001, ConocoPhillips AS 2005).

The North Sea is an area of extensional stress regime, and the vertical stress (σ_v) is the maximum regional stress (Bartholomew *et al.* 1993). We assume an isotropic horizontal stress in the Hejre field

($\sigma_h = \sigma_H < \sigma_v$), and that the regional vertical and horizontal stresses are also principal stresses. We assume as well, that the sediments at any given depth have isotropic rock properties.

Data from the leak-off tests (*LOT*) in Hejre-1 indicate leak-off pressures of 33.7 MPa and 78.5 MPa at depth 1791 m and 3752 m respectively (DONG Efterforskning og Produktion 2001). In Hejre-2 at a depth of around 5420 m, dynamic losses were experienced at a well pressure of approximately 113 MPa (ConocoPhillips AS 2005).

Calculation of Vertical/overburden stress

The vertical stress, σ_v (due to the weight of the sediments) can be estimated from the bulk density as:

$$\sigma_v = g \sum \rho_b(z_i) \cdot (z_i - z_{i-1}), \dots\dots\dots (16)$$

where z_i is the depth of the i 'th layer, $\rho_b(z_i)$ is the corresponding bulk density derived from the density log, and g is the Earth's acceleration of gravity (9.81 m/s^2). In the section from sea bed to 2500 meter, where log data are missing, we used a mean bulk density of 2.08 g/cm^3 (Japsen 1998). The density of the sea water was assumed to be 1.03 g/cm^3 .

Estimation of Horizontal stress

In-situ horizontal stress and fracture pressure in an oil field are usually determined by hydraulic fracturing tests (the so called extended Leak-Off Tests, *xLOT*). In these tests, the pressure inside the wellbore is increased by pumping fluid in the well until the borehole wall breaks and part of the

pumped fluid is lost to the formation. The “breaking” point determines the so called Leak-Off Pressure, *LOP*, i.e. the pressure at which a fracture is created. This pressure is often referred to as the fracture pressure and it depends also on the lithology (i.e. the rock strength). The pressure, at which the fracture is closing, is usually referred as the minimum horizontal stress (Brudy *et al.* 1997). In intact rock formations (i.e. no fractures or cracks) the fracture pressure is larger than the minimum horizontal stress (which is in fact a confining stress). Here, it is assumed that the horizontal stress, unlike the fracture pressure, is independent of lithology and rock type.

An upper limit for the horizontal stress ($\sigma_{h,U}$) was determined using the *LOP* values obtained from the two leak-off tests performed in the Hejre-1 well (DONG Efterforskning og Produktion 2001). The two data points define a line, which was extended from sea bed to *TD* (Total Drilled depth), assuming a constant slope. Since no digital data (pressure versus time or pumped volume) from the *LOT* tests were available, it was not possible to verify the accuracy of the reported values.

A lower limit of the horizontal stress ($\sigma_{h,L}$) was defined from losses experienced while drilling Hejre-2, just below the Heno Reservoir. The data were linearly extrapolated from sea bed to *TD*, assuming the same slope as the one used for the upper limit.

Estimation of Pore pressure profile

Compaction trend analysis of the sonic and the resistivity logs is one of the most used methods in the oil industry to evaluate the pore pressure, P_p . This analysis is based on the assumption that deviations of these logs from a normal compaction trend line can be used to estimate the actual pore pressure by empirical relations, e.g. Eaton’s relation (Eaton 1967). The so calculated P_p must always be calibrated to actual P_p data and experience gained in other wells, such as kicks, inflow, reservoir pressure

measurements, wellbore instabilities etc.. In order to define a normal compaction trend line from well log data, we need to have the above mentioned logs from sea bed to *TD*.

The lack of relevant logs (resistivity, sonic, density) from sea bed to 2500 m depth in both Hejre-1 and Hejre-2 did not allow us to define a normal compaction trend line and to apply trend analysis in order to evaluate the pore pressure.

Instead we used data on kicks, inflows and reservoir pressure data from Hejre-1, Hejre-2, and a number of near-by wells (**Table 1**). The depths of the pressure data points in the near-by wells were “stretched” to the local structure at the Hejre-2 location, i.e., the measured overpressure and the relative distance from the closest stratigraphic boundaries were preserved.

An upper ($P_{p,upper}$) and a lower limit ($P_{p,lower}$) for the pore pressure were defined in order to account for the spread in the pressure data. In both cases, it is assumed that the pore pressure is hydrostatic from sea bed to approximately 800 m–900 m. Below that depth, $P_{p,upper}$ is assumed to increase with a constant slope down to *TD*, while the slope of $P_{p,lower}$ is changing approximately at the top of the Chalk (Shetland Group).

Results: Regional stresses and pore pressure

The calculated regional stresses (the vertical, σ_v , and the horizontal, σ_h) and the pore pressure profile, P_p in the Hejre field are shown in **Figure 2**. The lower limit of the pore pressure, $P_{p,L}$, consists of three sections with increasing gradient **Figure 2**: one from sea bed to approximately 800 m depth, where the pore pressure is considered hydrostatic; the second one – from 800 m to the top of the Shetland Group (appr. 3000 m) and the third one – from the top of the Shetland Group to 5500 m. The slope of the middle section is defined from the kicks/inflows **Table 1** in the lower part of the Hordaland Group

(appr. 2400-2500 m) and at the base of the Rogaland / top of the Shetland Group. The kicks/inflows observed at the base of Rogaland, the upper parts of Cromer Knoll (appr. 3800 - 3900 m) and the Tyne (appr. 4500 m) Groups and the reservoir pressures in the Heno Formation determined the trend line of the lower section of $P_{p,L}$. The upper limit of pore pressure, $P_{p,U}$ is defined as consisting of two sections, the upper one (from sea bed to 800 m) is defined as hydrostatic, while the lower one (from 800 m to 5000 m) is defined as a trend line which accounts for the kicks observed in the upper part of the Hordaland Group and at the base of the Tyne Group.

Results: calculating Biot's coefficient

Resistivity logs from the highly porous section of the Tor formation (3250-3370 m) were used in the pore water salinity estimation. The deep resistivity log is free of mud invasion and we set the water saturation $S_w = 1$. We assume that the porosity from the neutron porosity log is valid in the clay free chalk section so by solving equation (12) with $\phi = 0.3$, $R_t = 0.4 \Omega\text{m}$ and $m = 2$ we find an apparent water resistivity of $R_{wa} = 0.0364 \Omega\text{m}$. For temperature $T = 80^\circ\text{C}$, the pore water salinity is then, $S = 90,000$ ppm. When calculating the pore water density from equation (A-6) with $T = 80^\circ\text{C}$, formation pressure $P_p = 45\text{MPa}$ and $S = 90,000$ ppm, we obtain a pore water density of $\rho_{br} = 1.05 \text{ g/cc}$. We back calculate using equation (11) with $\rho_{\min} = 2.71 \text{ g/cm}^3$ for chalk, and a $\rho_b = 2.2 \text{ g/cm}^3$ and obtain a porosity of $\phi = 0.307$. The results are plotted in **Figure 3**.

The trend of increasing resistivity down the well bore in **Figure 1** suggests a possible change in the fluid composition. It cannot be explained by the change in cementation exponent or porosity. With

salinity being above 40,000 ppm, the excess conductivity of shale will be practically negligible (Clavier *et al.* 1984) and we dismiss the possibility of decreasing salinity with depth. Hence the only explanation for the increase in resistivity is the presence of hydrocarbons from depth 4100 m. We assume that the hydrocarbons constitute a light oil of $\rho_{oil} = 0.56\text{g/cm}^3$ as reported by (DONG Efterforskning og Produktion 2001). By continuous iteration we find that the water saturation varies between 0.4 and 0.8 down the wellbore. We use mineral density $\rho_{min} = 2.73\text{ g/cm}^3$ for the Cromer Knoll Group and $\rho_{min} = 2.76\text{g/cm}^3$ for Tyne Group (Mbia *et al.* 2013). The brine density decreases with the increasing pressure and temperature, as given by equation (A-6). We find that an average fluid density of 0.85g/cm^3 is satisfying reasonably well both equation (16) and (A-2).

The effective bulk fluid modulus of mixed fluids is calculated with equation (15) and the equations given in Appendix. As mentioned above, the resistivity log suggests hydrocarbon presence below 4100 m. Thus, we assume the pore fluid to be brine (i.e. water saturation $S_w = 1$) down to 4100 m. Below that depth and down to the reservoir, S_w decreases to 0.8. The brine fluid modulus is calculated with a salinity of 90,000 ppm (A-8), (A-9) and (A-10) and an oil of density 0.56 g/cm^3 or 121 API is used to estimate the oil fluid modulus (A-8) and (A-21). The fluid moduli profiles are shown in **Figure 4**.

Biot's coefficient was then estimated for chalk, shale and sandstone using three different mineral moduli, K_{min} , M_{min} , and M_{min-E} (**Table 3**). We find that Biot's coefficient calculated using the bulk modulus (K_{min}) is above 0.8 for the Shetland Group (chalk), above 0.8 for the Tyne Group (shales) and between 0.6 and 0.8 for the Heno sand Formation. We obtained no results for the Cromer Knoll Group due to lack of S-wave data. When Biot's coefficient α is estimated by using the P-wave mineral modulus (M_{min}); results range between 0.7 and 0.9 in the Shetland and in the Tyne Group, between 0.4 and 0.8 in the Cromer Knoll Group and between 0.6 and 0.8 in the Heno sand Formation. We thus

found that by using M_{min} instead of K_{min} , we obtained lower values for α , but that both results follow the same trend. The mineral modulus M_{min-E} differs from M_{min} only for the shales in the Cromer Knoll Group, where it results in Biot's coefficient being above 0.9. The estimated Biot's coefficients are shown in **Figure 4**.

Results: Effective stress and Shear Failure Pressure

Having found the Biot's coefficient α , we estimated the effective principle stresses and then, the shear failure pressure, i.e. the minimum well pressure needed to avoid shear failure collapse of the borehole. The estimated Shear Failure Pressures (*SFP*) for different pore pressures, horizontal stress and Biot's coefficients are shown in **Figure 5**. *SFP* estimated with the minimum value for α (corresponding to M_{min}) are lower than the *SFP* estimated with $\alpha = 1$ by approximately 5 MPa.

When the effective stresses are estimated with $\alpha = 1$, the *SFP* values become above the lower limit of P_p , $P_{p,lower}$ (**Figure 5**). This means, that if the pore pressure is $P_{p,lower}$, then the safe drilling window will be limited from *SFP* to σ_h . When the effective stresses are estimated with α derived from the logs (right track, **Figure 5**), the *SFP* values are below $P_{p,lower}$ and the drilling window is larger and ranging from $P_{p,lower}$ to σ_h .

Figure 6 shows how the *SFP* is changing when using Biot's coefficient below 1 with respect to well inclination. Only the lower section is represented (from 5000 m to 5400 m). If Biot's coefficient of $\alpha = 1$ is used in the calculation, the *SFP* is well above $P_{p,lower}$ for well inclination of 50° (from a vertical plane), which restricts the drilling window severely. When *SFP* is calculated with a Biot's coefficient < 1 , *SFP* is below $P_{p,lower}$ for the deviated well, thus allowing for much larger drilling window, which in this case is limited by $P_{p,lower}$

Discussion

Biot's coefficient α estimated from petrophysical logs in the Hejre field (below 2500 m) ranges on average, depending on the moduli used, from above 0.7 in the Shetland Group (chalk), above 0.6 (with occasional low peaks to 0.4) in the Cromer Knoll Group (shales), and from above 0.8 in the Tyne Group (shales) to between 0.4 and 0.6 in the Heno Formation (sandstone). An $\alpha < 1$ is expected for stiff saturated formations (e.g. Shah and Shroff 2003), thus our estimates are in agreement with expectations. Gommesen *et al.* (2007) found a similar Biot's coefficient of 0.8 for the Tor formation in North Sea chalk. The theoretical lower limit of α is the porosity (Fjær *et al.* 2008), which (on average) is 0.15. Our estimates show values well above the theoretical lower limit.

The chalk sediments in the Shetland Group (3109 m–3773 m) and the sandstone in the Heno Formation (5360 m–5411 m) are stiff formations compared to the shales in the Cromer Knoll and in the Tyne groups. The stiffer rock-frames makes the fluid substitution relatively straight forward as the mineral modulus for the load bearing mineral in chalk (calcite) and in sandstone (quartz) are relative well determined. The stiff rock frame is dominating the bulk stiffness so changes in fluid modulus of 0.5 GPa has a negligible impact on the resulting Biot's coefficient.

By contrast, in the much softer shale parts of Cromer Knoll and Tyne groups, caution is needed when choosing the fluid and mineral moduli, because fluid and mineral moduli can be chosen so as to obtain unphysical dry rock frame moduli. The elastic properties of minerals in shale are much debated (Cagatay *et al.* 1994, Mavko *et al.* 2009), and the reported mineral moduli range from 16 GPa (Simms 2007) to over 200 GPa (Chen and Evans 2006).

The chosen fluid modulus will dictate the solution space of the mineral modulus where a high fluid modulus will reduce the possible size of the mineral modulus. We chose to compute a fluid modulus from the fluid equations from (Batzle and Wang 1992) and this approach gave us an increasing fluid modulus with depth. We found that the temperature and pressure input in equation (A-6) and (A-8) could be changed with $\pm 10^\circ\text{C}$ or $\pm 10\text{ MPa}$ for any depth point without any noticeable change in the calculated Biot's coefficients, meaning that for this paper, a precision estimation of these parameters is not needed. However, the estimation of the salinity causes great trouble due to the large temperatures and the low apparent water resistivity. By following the Schlumberger salinity chart, small changes in the range of $0.02\ \Omega\text{m}$ to $0.015\ \Omega\text{m}$ will at 100°C or more lead to changes in salinity in the size of 100,000 ppm. Such an increase in salinity would cause the calculated fluid modulus of brine to be outside the range studied by (Batzle and Wang 1992) and as a result the fluid substitution becomes inaccurate. The fluctuations in the apparent water saturation are a result of the difficulties of balancing the input parameters in Archie's equation. With no fluid samples to correlate with, the result from the logs becomes highly dependent on the log interpreter's choices. It should be kept in mind, that Gassmann fluid substitution using the P-wave modulus, equation (12) and (13) instead of the bulk modulus, equation (9) and (11) is an approximation, which gives lower values for α as compared to the one estimated with the bulk moduli. All these assumptions and limitations lead to considerable uncertainty in the estimated values of the Biot's coefficient α .

Bearing these assumptions and shortcomings in mind, in this study we showed, that accounting for $\alpha < 1$ leads to lower shear failure pressures (*SFP*) as compared to the ones estimated assuming $\alpha = 1$. Here, by "shear failure pressure" we denote the minimum well pressure (caused by the drilling fluid inside the well) needed to avoid shear failure collapse of the borehole wall. The effect is even larger for

inclined wells. Thus, using these “in-situ” values for α instead of a default value of 1, probably accounts better for the in-situ conditions. A value of α below one indicates a solid frame (which is the part that can break) that is probably able to support larger stresses and, thus, is more resistant to shear failure, than a loose packing of grains (which would be indicated by $\alpha = 1$).

In several published studies, it is assumed that the most appropriate definition of effective stress to be used in failure criteria is Terzaghi's: $\sigma_{eff} = \sigma - P_p$, i.e. postulating $\alpha = 1$. For example, when measuring stress at failure by performing a set of triaxial experiments on Tavel limestone at three different pore pressures (Bouteca and Gueguen 1999) concluded that the effective stress at failure can be expressed as $\sigma_{i,eff} = \sigma_i - P_p$. From the geotechnical literature (e. g. Shah and Shroff, 2003) it is well known that for soft, saturated soils $\alpha = 1$ (and the Terzaghi's formula is valid), while for stiff saturated soils $\alpha < 1$. Here, the shales in the upper section (from sea bed to the top of the chalk) can be considered as soft saturated soils with $\alpha = 1$, while the shales below the Chalk (i.e. below 3600 m) are much stiffer and $\alpha < 1$ is expected. Thus, we recommend to use $\alpha = 1$ from sea bed to the Chalk and the “in-situ” $\alpha < 1$, estimated from the log data to calculate the effective principal stresses and the corresponding shear failure pressure used in the wellbore stability analysis.

A serious limitation in this study was the availability and the quality of the log data. The lack of sonic, resistivity, density etc. logs in the upper well sections (from sea bed to approximately 2500 m) did not allow a more detailed evaluation of the pore pressure, salinity, water saturation, the different moduli, rock properties etc. The lack of digital data (pressures versus time or pumped volume) from the leak-off tests did not allow proper evaluation of the quality and the type of the measured leak-off pressure. The poor knowledge of the elastic moduli of minerals in shale limits how precise Biot's

coefficient is determined. All these limitations affected the evaluation of the pore pressure and the horizontal stress.

All above discussed assumptions and limitations affects also the estimate of the shear failure pressure. The *SFP* values depend also on the failure criteria used (Mohr-Coloumb, Lade etc.). Thus, it is indeed very hard to quantify the uncertainties.

Conclusion

In this study, we have shown a way to estimate the Biot's coefficient and moduli from log data in an HPHT field. We have shown as well, that using a Biot's coefficient different from 1 might lead to a better estimate of the in-situ effective stresses, which on their turn are used in the analysis of borehole stability in terms of shear failure pressure.

In a case of a narrow drilling margins (pore pressure close to the fracture pressure or minimum horizontal stress), using an $\alpha = 1$ instead of, for example, an $\alpha = 0.8$ might lead to an estimated shear failure pressure larger than the pore pressure and thus restricting the drilling window even more. Using a Biot's coefficient below one for deep formations (below the Chalk Group) in the North Sea, leads to more correct estimate of the effective stresses acting on the borehole wall. This, on its turn, leads to improved estimate of the drilling margins in deep HPHT prospects.

However, the quality and the availability of the input data were a considerable issue and put severe limitations to this study. No laboratory results were available at the time of this study and comparing or calibrating the results of this study with laboratory studies would be an interesting next step.

Acknowledgements

We wish to express our thanks to DONG Energy for the financial support and access to the Hejre field data. We also acknowledge support of this work by Halliburton Software and Services, a Halliburton Company, by allowing us to use the Drillworks/Predict software.

References

- Archie G.E. 1942. The electrical resistivity as an aid in determining some reservoir characteristics. *Petroleum Transactions of AIME* **146**: 54–62
- Bartholomew, I.D., Peters, J.D. and Powell C.M, 1993. Regional structural evolution of the North Sea: oblique slip and the reactivation of basement lineaments. *Geological Society, London, Petroleum Geology Conference series* **4**: 1109–1122.
- Batzle, M. and Wang, Z. 1992. Seismic properties of pore fluids. *Gephysics* **57**(11): 1396–1408.
- Biot, M.A. 1941. General Theory of Three Dimensional Consolidation. *Journal of Applied Physics* **12**: 155-164.
- Bouteca, M. and Gueguen, Y. 1999. Mechanical properties of rocks: pore pressure and scale effects. *Oil & Gas Science and Technology. Rev. IFP* **54**(6) 703–714.
- Brudy, M., Zoback, M.D., Fuchs, K., Rummel, F., and Baumgärtner, J. 1997. Estimation of the complete stress tensor to 8 km depth in the KTB scientific drill holes: Implications for crustal strength. *Journal of Geophysical Research* **102**: 18,453–18,475.
- Cagatay, M.N., Fossail, K.A., and Saner, S.1994. Shaliness Effect on the Log-Derived Archie Cementation Factor: Study of a Saudi Arabian Sandstone Reservoir. *The Log Analyst* **35**(6): 16–27.
- Chevron Petroleum Company of Denmark. 1983. MonA-6, Completion report. (<http://www.geus.dk>).
- ConocoPhillips AS. 2005. Hejre-2, Final well report. Licence 5/98. (<http://www.geus.dk>).
- Clavier, C., Coates, G., and Dumanoir, J. 1984. Theoretical and experimental Bases for the Dual-Water Model for Interpretation of Shaly Sands. *SPE J* **24**(2): 153-168. SPE 06859.
- Chen, B. and Evans, J.R.G. 2006. Elastic moduli of clay platelets. Elsevier, *Scripta Materialia* **54**: 1581–1585.
- DONG Efterforskning og Produktion. 2001. Hejre-1 (5603/28-4). Final well report. Licence 5/98 A/S. (<http://www.geus.dk>).
- Eaton, B.A. 1969. Fracture Gradient predictions and its applications in oil field operations. *J Pet Tech* **21**(10): 1353–1360. SPE 2163-PA.
- Fabricius, I.L. 2014. Burial stress and elastic strain of carbonate rocks. *Geophysical Prospecting* **62**: 1327–1336.
- Fjær, E., Holt, R.M., Horsrud, P., Raaen, A.M., and Risnes, R. 2008. *Petroleum related rock mechanics*, second edition. Amsterdam: Elsevier.
- Gassmann, F. 1951. Über die Elastizität poröser Medien. *Viertel. Naturforsch. Ges. Zürich* **96**: 1–23.
- Gommesen, L., Fabricius, I.L., Mukerji, T., Mavko, G., and Pedersen, J.M. 2007. Elastic behavior of North Sea chalk: A well-log study. *Geophysical Prospecting* **55**: 307–322.
- Japsen, P. 1998. Regional Velocity-Depth Anomalies, North Sea Chalk: A Record of Overpressure and Noegene Uplift and Erosion. *AAPG Bulletin* **83**(11): 2031–2074.

- Lal, M. 1999. Shale stability: Drilling-fluid interaction and shale strength. Paper SPE 54356-MS presented at the SPE Latin American and Caribbean Petroleum Engineering Conference, Caracas, Venezuela, 21–23 April.
- Lang, J., Li S., Zhang J., 2011. Wellbore stability modelling and real-time surveillance for deep-water drilling to weak bedding planes and depleted reservoirs. SPE/IADC 139708.
- Mavko, G., Mukerji, T., and Dvorkin, J. 2009. *The Rock Physics Handbook*, second edition, New York: Cambridge University Press.
- Mbia, E.N., Fabricius, I.L., and Oji, C.O. 2013. Equivalent pore radius and velocity of elastic waves in shale. Skjold Flank-1 Well, Danish North Sea. *Journal of Petroleum Science and Engineering* **109**: 280–290.
- Schlumberger. 1995. *Log Interpretations Charts*. Houston.
- Shah, D.L. and Shroff, A.V. 2003. *Soil Mechanics and Geotechnical Engineering*. Balkema.
- Simms, R. 2007. Practical Gassmann fluid substitution in sand/shale sequences. *First break* **25**(12): 61-68.
- Yew, C.H. and Liu, G. 1992. Pore Fluid and Wellbore Stabilities. SPE International Meeting on Petroleum Engineering, Beijing, China, 24-27 March, 1992. SPE 22381.
- Zimmermann, R.W. 1991. *Compressibility of sandstones*. Amsterdam: Elsevier.
- Zoback, M.D. 2007. *Reservoir Geomechanics*. Cambridge University Press, Cambridge, UK. ISBN-978-0-521-77069-9.

Appendix A – Methodology with log data.

Porosity

The porosity, φ , is calculated from the density log:

$$\varphi = \frac{\rho_b - \rho_{\min}}{\rho_{fl} - \rho_{\min}}, \dots\dots\dots (A-1)$$

where ρ_{\min} is the mineral density and ρ_{fl} is the fluid density. Where a reliable neutron log is available, φ is best determined from the density and neutron log in combination.

Fluid modulus

The density of the fluid depends on the pressure, temperature, water saturation, S_w , and the salinity of the pore water and can be calculated from equation (A-6). By assuming $S_w = 1$, we use Archie's equation to estimate the apparent resistivity of the pore water, R_{wa} Archie (1942):

$$\varphi = \left(\frac{a \cdot R_w}{S_w^n \cdot R_t} \right)^{\frac{1}{m}} \quad \text{and} \quad \varphi = \left(\frac{a \cdot R_{wa}}{R_t} \right)^{\frac{1}{m}} \dots\dots\dots (A-2)$$

where R_t is the formation resistivity, R_w is the pore water resistivity, n is the saturation exponent, a is Archie's constant and m is the cementation exponent. Equation (A-1) and (A-2) are coupled through the porosity and can be solved by iteration.

The salinity of the pore water is estimated from R_{wa} and by using the Schlumberger resistivity-salinity conversion chart (Schlumberger 1995). We use $a = 1$, and $m = 2$ for clay free rocks. For shale we find a cementation exponent based on the volumetric amount of shale **Table 2**. By a linear fit of these data we find the relationship:

$$m = -0.7533 \cdot V_{sh} + 2 \quad , \quad \dots \dots \dots \quad (A-3)$$

where V_{sh} is the volume fraction of shale as estimated from the gamma ray log:

$$V_{sh} = \frac{GR_{log} - GR_{base}}{GR_{sh} - GR_{base}} \quad , \quad \dots \dots \dots \quad (A-4)$$

and where GR_{sh} is the gamma log signal of pure (100%) shale (corresponding to the maximum GR value from the log), GR_{base} is the gamma ray signal of pure (100%) sand (i.e. the lowest GR value) and GR_{log} is the actual gamma ray log reading.

The fluid modulus of brine is dependent on pressure, temperature and salinity equation (A-9), and the modulus of oil is dependent on pressure, temperature and API degree equation (A-11). A temperature gradient of $\Delta T = 40^\circ\text{C}/\text{km}$ for formation below 2500 m was established based on the temperature readings from the final well reports (DONG Efterforskning og Produktion. 2001, ConocoPhillips AS. 2005). The modulus of a fluid composed of two or more components is calculated on the basis of their fractional amounts Batzle and Wang (1992):

$$K_{fl,mix} = \left(\frac{S_w}{K_{br}} + \frac{1-S_w}{K_{oil}} \right)^{-1} \quad , \quad \dots \dots \dots \quad (A-5)$$

where K_{br} is bulk modulus of pore water and K_{oil} is bulk modulus of oil.

Fluid properties

Fluid properties can be predicted as follows (Batzle and Wang 1992). The brine density, ρ_{br} in g/cm^3 , can be estimated as:

$$\rho_{br} = \rho_w + S \cdot \left\{ 0.668 + 0.44S + 10^{-6} \cdot \left(330P - 2400P \cdot S + T \cdot [80 + 3T - 3000S + 13P + 47P \cdot S] \right) \right\} \dots\dots\dots (A-6)$$

where P is water pressure in Megapascal, T is temperature in celcius, and S is salinity in fractions of one (ppm x 10^{-6}).

The density of fresh water ρ_w is given as:

$$\rho_w = 1 + 10^{-6} \left(-80T - 3.3T^2 + 0.00175T^2 + 489P - 2T + 0.013T^2P - 1.3 \cdot 10^{-5} T^3P - 0.333P^2 - 0.002T \cdot P^2 \right), \dots\dots (A-7)$$

The procedure for calculating the modulus of a fluid is similar to the one for a solid. However, the fluid does not have a shear component so the bulk modulus of a fluid equals the P-wave modulus:

$$K_{fl} = \rho_{fl} \cdot V_{fl}^2 \dots\dots\dots (A-8)$$

The P-wave velocity of a brine is found as:

$$V_{fl} = V_w + S \cdot \left(1170 - 9.6T + 0.055T^2 - 8.5 \cdot 10^{-5} \cdot T^3 + 2.6P - 0.0029T \cdot P - 0.0476 \cdot P^2 \right) + S^{1.5} \left(780 - 10P + 0.16P^2 \right) - 820S^2, \dots\dots\dots (A-9)$$

where the velocity of fresh water V_w is found from:

$$V_w = \sum_{i=0}^4 \sum_{j=0}^3 W_{ij} \cdot T^i \cdot P^j, \dots\dots\dots (A-10)$$

and where the computational constants is found in Table A-1:

TABLE A-1 – COMPUTATIONAL CONSTANTS				
i \ j	0	1	2	3
0	1402.85	1.524	$3.431 \cdot 10^{-3}$	$-1.197 \cdot 10^{-5}$
1	4.871	-0.0111	$1.739 \cdot 10^{-4}$	$-1.628 \cdot 10^{-6}$
2	-0.004783	$2.747 \cdot 10^{-4}$	$-2.135 \cdot 10^{-6}$	$1.237 \cdot 10^{-8}$
3	$1.487 \cdot 10^{-4}$	$-6.503 \cdot 10^{-7}$	$-1.455 \cdot 10^{-8}$	$1.327 \cdot 10^{-10}$
4	$-2.197 \cdot 10^{-7}$	$7.987 \cdot 10^{-10}$	$5.23 \cdot 10^{-11}$	$-4.614 \cdot 10^{-13}$

The fluid modulus of oil is calculated from equation (A-8) where the fluid velocity is given as (Mavko *et al.* 2009):

$$V_{oil} = 15450 \cdot (77.1 + API)^{-1/2} - 3.7T + 4.64P + 0.0115T \cdot P \cdot (0.36API^{1/2} - 1) \dots \dots \dots (A-11)$$