Maximum auto-mutual-information factor analysis

Nielsen, Allan Aasbjerg

Published in:

Proceedings Volume 10427, Image and Signal Processing for Remote Sensing XXIII

Link to article, DOI:

[10.1117/12.2278290](https://doi.org/10.1117/12.2278290)

Publication date:

2017

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Nielsen, A. A. (2017). Maximum auto-mutual-information factor analysis. In *Proceedings Volume 10427, Image and Signal Processing for Remote Sensing XXIII* (Vol. 10427). SPIE - International Society for Optical Engineering. Proceedings of SPIE - The International Society for Optical Engineering
<https://doi.org/10.1117/12.2278290>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Maximum auto-mutual-information factor analysis

Allan A. Nielsen

Technical University of Denmark
DTU Compute – Applied Mathematics and Computer Science
DK-2800 Kgs. Lyngby, Denmark
alan@dtu.dk

ABSTRACT

Based on the information theoretical measure mutual information derived from entropy and Kullback-Leibler divergence, an alternative to maximum autocorrelation factor analysis is sketched.

1. INTRODUCTION

In signal and image processing principal component analysis¹ (PCA) is often used for dimensionality reduction and feature extraction in pre-processing steps to for example classification.

In remote sensing image analysis PCA is often replaced by maximum autocorrelation factor² (MAF) or minimum noise fraction³ (MNF) analysis. This is done because MAF and MNF analyses incorporate spatial information in the orthogonalization of the multivariate data which is conceptually more satisfactory and which typically gives better results.

In this contribution, autocorrelation between the multivariate data and a spatially shifted version of the same data in the MAF analysis is replaced by the information theoretical, entropy and Kullback-Leibler divergence based measure mutual information.^{4–8} This potentially gives a more detailed decomposition of the data. Also, the orthogonality between already found components and components of higher order requested in the MAF analysis is replaced by a requirement of minimum mutual information between components. These ideas resulting in maximum auto-mutual-information factor analysis are in turn based on.^{9–11}

The sketched methods are used on the well-known AVIRIS*¹² Indian Pines data.

REFERENCES

- [1] Hotelling, H., “Analysis of a complex of statistical variables into principal components,” *Journal of Educational Psychology* **24**, 417–441 (1933).
- [2] Switzer, P. and Green, A. A., “Min/max autocorrelation factors for multivariate spatial imagery,” Tech. Rep. 6, Department of Statistics, Stanford University (1984).
- [3] Green, A. A., Berman, M., Switzer, P., and Craig, M. D., “A transformation for ordering multispectral data in terms of image quality with implications for noise removal,” *IEEE Transactions on Geoscience and Remote Sensing* **26**, 65–74 (Jan. 1988).
- [4] Shannon, C. E., “A mathematical theory of communication,” *Bell System Technical Journal* **27**(3), 379–423 and 623–656 (1948).
- [5] Hyvärinen, A., Karhunen, J., and Oja, E., *Independent Component Analysis*, J. Wiley (2001).
- [6] Mackay, D. J. C., *Information Theory, Inference and Learning Algorithms*, Cambridge University Press (2003).
- [7] Bishop, C. M., *Pattern Recognition and Machine Learning*, Springer (2007).
- [8] Canty, M. J., *Image Analysis, Classification and Change Detection in Remote Sensing. With Algorithms for ENVI/IDL and Python*, Taylor & Francis, CRC Press, third ed. (2014).
- [9] Yin, X., “Canonical correlation analysis based on information theory,” *Journal of Multivariate Analysis* **91**, 161–176 (2004).

*<https://aviris.jpl.nasa.gov/>

- [10] Karasuyama, M. and Sugiyama, M., “Canonical dependency analysis based on squared-loss mutual information,” *Neural Networks* **34**, 46–55 (2012).
- [11] Vestergaard, J. S. and Nielsen, A. A., “Canonical information analysis,” *ISPRS Journal of Photogrammetry and Remote Sensing* **101**, 1–9 (2015). <http://www.imm.dtu.dk/pubdb/p.php?6270>, Matlab code at <https://github.com/schackv/cia>.
- [12] Vane, G., Green, R. O., Chrien, T. G., Enmark, H. T., Hansen, E. G., and Porter, W. M., “The airborne/infrared imaging spectrometer (AVIRIS),” *Remote Sensing of Environment* **44**, 127–143 (1993).