Algal growth inhibition test results of 425 organic chemical substances

Kusk, Kresten Ole; Christensen, Anne Munch; Nyholm, Niels

Published in:
Chemosphere

Link to article, DOI:
[10.1016/j.chemosphere.2018.04.047](https://doi.org/10.1016/j.chemosphere.2018.04.047)

Publication date:
2018

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Kusk, K. O., Christensen, A. M., & Nyholm, N. (2018). Algal growth inhibition test results of 425 organic chemical substances. *Chemosphere*, 204, 405-412. <https://doi.org/10.1016/j.chemosphere.2018.04.047>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Accepted Manuscript

Algal growth inhibition test results of 425 organic chemical substances

Kresten Ole Kusk, Anne Munch Christensen, Niels Nyholm

PII: S0045-6535(18)30689-1

DOI: [10.1016/j.chemosphere.2018.04.047](https://doi.org/10.1016/j.chemosphere.2018.04.047)

Reference: CHEM 21195

To appear in: *ECSN*

Received Date: 17 January 2018

Revised Date: 6 April 2018

Accepted Date: 9 April 2018

Please cite this article as: Kusk, K.O., Christensen, A.M., Nyholm, N., Algal growth inhibition test results of 425 organic chemical substances, *Chemosphere* (2018), doi: 10.1016/j.chemosphere.2018.04.047.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Running title:

425 Algal Growth Inhibition Test Results

Corresponding author:

Kresten Ole Kusk

Department of Environmental Engineering,

Technical University of Denmark

Bygningstorvet 115

DK-2800 Kgs. Lyngby

Denmark

e-mail: koku@env.dtu.dk

Algal Growth Inhibition Test Results of 425 Organic Chemical Substances

¹Kusk, Kresten Ole, ^{1,2}Christensen, Anne Munch, ¹Nyholm, Niels

¹Department of Environmental Engineering, Technical University of Denmark,
Bygningstorvet 115, DK-2800 Kgs. Lyngby, Denmark

²Danish Environmental Protection Agency (present address), Haraldsgade 53, 2100
København Ø, Denmark

ABSTRACT

The toxicity towards the algal species *Pseudokirchneriella subcapitata* of 425 organic chemical substances was tested in a growth inhibition test. Precautions were taken to prevent loss of the compounds from the water phase and the test system (closed test system, low biomass, shorter test duration, silanized glass) and to keep pH constant by applying a higher alkalinity. Chemical phase distribution was modelled taking ionization, volatilisation, and adsorption to glass and biomass into consideration. If the modelled water concentration was below 90 % of the nominal concentration the calculated EC values were corrected accordingly. The model helped to identify substances, where the calculated water concentration was too uncertain. Substances covering a wide range of physical-chemical properties and different modes of action were tested. Median effect concentrations (EC₅₀) lower than 1000 mg/L were found for 310 substances; 216 of these were in the range from 1 to 1000 mg/L and 94 substances had EC₅₀s below 1 mg/L and should be classified as “Very toxic”. 36 substances fell in the group with EC₅₀ > 1000 mg/L. An EC₅₀ could not be established for 79 substances. These 425 different organic substances were tested under uniform conditions and thus considered a valuable source of information for administrators, industry, risk assessors and QSAR modellers.

Keywords

Algae, toxicity, chemicals, partitioning, QSAR, environmental risk

INTRODUCTION

The number of chemical substances used in daily life in household, agriculture, industry, etc. is very high. With the EU chemical legislation, covered by e.g. the EU REACH Regulation, CLP Regulation, Biocidal Products Regulation, Pesticide Regulation, all chemical substances in use have to be registered, authorised or notified dependent on the regulation. By the end of the REACH registration about 149,000 substances were registered (Trapp et al., 2010). For many of these including possible degradation products, there is still a general lack of data including physical-chemical data as well as ecotoxicological data hereunder toxicity toward unicellular algae.

Environmental hazard and risk assessment and classification of chemical substances as well as the different regulations demand results from ecotoxicological studies, e.g. data from toxicity tests with algae, crustaceans and fish. Ecotoxicological tests are costly and time consuming and this is one reason for the slow and resource-intensive risk assessment process. Alternative methods like QSARs (Quantitative Structure Activity Relationships) are increasingly used in regulatory contexts to supplement experimental data especially for degradation products. QSAR models that can predict/estimate ecotoxicological effects from e.g. structure and physical-chemical properties, therefore provide a valuable tool for performing environmental hazard and risk assessment, PBT (Persistence, Bioaccumulation, Toxicity) assessment and classification much faster and cheaper compared to assessments based on experimental data for each individual compound. QSAR models for predicting ecotoxicological effects on crustacean and fish were some of the first to be developed by the Danish Environmental Protection Agency (2004, 2015.).

86 However, for the third important group of organisms, the algae, it was proved difficult to find
87 homogenous data sets to form basis for global (covering a diversity of chemical classes)
88 QSAR models for algae toxicity. Microscopic algae are the most important group of primary
89 producers of biomass in most aquatic ecosystems and thereby form an important ecological
90 base for higher life forms. Toxic effects on this group of organisms may harm the whole
91 ecosystem because the food base of the ecosystem may be harmed leading to secondary
92 effects at higher trophic levels. Thus, it is essential to investigate the effect of toxic
93 substances on this group of organisms.

94
95 This paper presents the methods and data generated to develop a model for prediction of
96 ecotoxicity of chemical substances on algae. The final model based on the results presented
97 here and some literature values was run with 170,000 substances in the first version and in a
98 newly updated version with more than 600,000 substances and the outcome is available online
99 (Danish Environmental Protection Agency, 2004, 2015). Only the modelled results are
100 presented in the Danish EPA (Q)SAR database, whereas the experimental results were not
101 published before.

102
103 In this project a cost-effective method was used taking special care to achieve precise and
104 reliable results beyond the scope of routine testing. In order to keep the dissolved
105 concentrations of the tested substances as constant as possible, some modifications were done
106 relative to standard test methods (Organization for Economic Cooperation and Development,
107 1984). Special care was taken to keep the pH constant, to reduce losses of chemical substance
108 due to sorption on glass and biomass and due to volatilization and degradation and a modified
109 Mackay level 1 partitioning model (Mackay, 1991) for the system taking ionisation into
110 consideration was set up and run for each substance to evaluate the water concentration.

Due to the lack of algae toxicity data the Danish EPA started to financially support this effort to generate high quality data under uniform experimental conditions within one laboratory at Technical University of Denmark. The resulting test data set was iteratively used as the basis for development of interim QSAR models throughout the testing period to select new test substances to further strengthen the model and expand its applicability domain. Thus, chemicals covering a broad range of physical-chemical properties and groups were chosen for testing. As 425 different organic chemical substances were tested in exactly the same way we consider these results a valuable source of information for administrators, industry, risk assessors and QSAR modellers.

METHODS AND MATERIALS

Algae test

The method used was based on the OECD Guideline 201 (Organization for Economic Cooperation and Development, 1984) and ISO 8692 (International Organization for Standardization, 1997) standards using average growth rate as the endpoint.

The test organism was the green alga *Pseudokirchneriella subcapitata*, formerly known as *Selenastrum capricornutum* or as *Raphidocelis subcapitata* (obtained from the Norwegian Institute of Water Research).

Most chemicals were of analytical grade and at least of 95% purity.

Some modification of the ISO 8692 method was performed to keep the conditions in the test system as stable as possible. A small closed test system was used together with a higher buffer

capacity, a low inoculate of 10^4 cells $\cdot$ mL⁻¹ and a shorter test duration (48 hours). These modifications will be discussed later.

The stock solutions and test concentrations were prepared with modified ISO 8692 freshwater algal growth media enriched with 200 mg/L NaHCO₃ (4 times higher than ISO medium). The dilution series was prepared by mixing growth media with a stock solution of the test substance and then inoculate with a pre-culture of exponentially growing algal cells propagated under the actual test conditions to eliminate a lag phase. All stock solutions were pH-adjusted to the pH of the growth media.

Glass vials were used as test vessels. Mini-scale algal growth inhibition tests were conducted as closed tests with 4 mL test medium and 17 mL CO₂-enriched headspace (1% CO₂) as described by Halling-Sørensen et al. (1996). The vials were closed with a teflon-covered septum and CO₂ was added with a syringe. At equilibrium with the CO₂-enriched headspace the resulting pH of the media was 7.2 ± 0.2 . Test vials were incubated on a microplate shaker (100 rpm) in continuous white fluorescent light ($70\text{--}90 \mu\text{E} \cdot \text{m}^{-2} \cdot \text{s}^{-1}$) at 20 ± 1 °C.

Algal biomass was determined at the start, after 24 hours and at the end (48 hours) from acetone extractions as described by Mayer et al. (1997). pH was measured at the start and at the end. The fluorescence of the extracted chlorophyll was measured on a Hitachi F-2000 Fluorescence Spectrophotometer with excitation light at 420 nm and emission light at 671 nm. Algal growth rates in each vial were calculated directly from the fluorescence measurements. Specific average growth rates were calculated for each vial from the three biomass determinations.

For substances with low solubility, either dimethyl sulfoxide (DMSO, CAS 67-68-5), acetone (CAS 67-64-1) or chloroform (67-66-3) was used as a co-solvent, with a maximum concentration of 1-2% in the final solution. Results from testing of the solvents are included in the supplementary materials. If a co-solvent was used the concentration was equal in all test concentrations. Potassium dichromate was used as a reference compound and tested every second to third month.

Each substance was tested in both a range finding test and in a definitive test. The number of replicates in definitive tests varied in the project period. At the start 3 replicates of each of six test concentrations were used. Later, nine test concentrations with two replicates were used. In the last part of the project only one replicate of each of the thirteen concentrations was used as recommended by Andersen et al. (1998). Despite the number of replicate the concentrations were chosen with a constant factor between concentrations (equal distances between concentrations on a logarithmic scale). During the whole period six control replicates were used and run simultaneously to each test substance.

Statistical calculations

EC₁₀ and EC₅₀ (concentrations reducing the specific average growth rate by 10 and 50%, respectively) and their confidence limits were estimated by fitting the obtained concentration-response data to the logarithmic normal distribution function (Christensen et al., 2009). The obtained growth rates were normalised by dividing with the (negative or if a solvent was used the solvent) control response estimate. The influence of the control covariance was taken into account in the statistical calculations using a weighting function that was inversely proportional to the total variance. Further, experimental designs were made with six control

replicates and narrow spacing of test concentrations at all effect levels to give enough data points for an accurate estimation of the concentration-response relationship.

Phase partitioning

A partitioning model based on Mackey's fugacity model level 1 (Mackay, 1991), assuming equilibrium was developed. The model estimates the phase distribution of chemical substances between water, algal biomass, air headspace, and glass surface in the test system taking into account ionization, volatilization and sorption to algal biomass and glass. For further details see Christensen et al. (2009). If the estimated water concentration was lower than 90% of the nominal concentration the test result was corrected accordingly.

Dimensions used for the algal test model were: water (4.0 mL), air (17.0 mL), glass wall (11.3 cm²), and algae (cell density after 48 h at a growth rate of 1.70) $3.66 \cdot 10^5$ cells /mL ~ biomass volume $1.46 \cdot 10^{-4}$ mL. 1 mg dwt of algae was equivalent to $5 \cdot 10^7$ cells with 10% carbon content (Christensen, 2009). The carbon content of the final algal biomass was used for estimation of sorption to algae.

For estimation of sorption to glass a study was performed to determine the glass-water distribution coefficient. Sorption was measured in abiotic control experiments using silanized as well as borosilicate (normal) glass and with six different ¹⁴C-labeled substances to cover the widest possible range of K_{OW}'s, see Table 1. Analyses were made using a Tri-Carb 2000 Liquid scintillation Counter (*United Technologies Packard*). Some experiments were also made with addition of co-solvent (DMSO) in order to investigate if such addition influenced sorption.

Medium (4.0 mL) was spiked with radiolabelled substance. Six replicates of each of the spiked samples were prepared in normal glass vials and six in silanized glass vials. After four, 24 hours and at the end of the experiment (48 hours) samples were taken from three of each glass type and analysed by liquid scintillation counting. Radiolabelled substances adsorbed to the glass were extracted with 4 mL of acetone under continuous shaking for 24 h followed by scintillation counting. Isotope mass balances were made and the glass-water partitioning coefficient, K_{Glass} , was calculated using the equation

$$K_{\text{Glass}} = C_{\text{GLASS}}/C_{\text{W}} \quad (\text{L}/\text{cm}^2)$$

where C_{GLASS} is the amount of the substance sorbed onto the glass surface (mg/cm^2) and C_{W} is the water concentration (mg/L).

For lipophilic compounds, such as phenanthrene and DDT the mass balance indicated that acetone could not extract all of the sorbed substance. In that case K_{Glass} was calculated indirectly from the water concentration using nominal concentrations. In the experiment and in the partitioning model it is assumed that sorption to the glass surface only will take place at the glass surface area in contact with the 4 mL water sample (vial diameter 1.87 cm; surface area 11.3 cm^2).

The model assumes quasi-stationary conditions for the partitioning processes and takes into account the following two dynamic phenomena: 1) Increasing sorption to the exponentially growing algal biomass, and 2) progression with time of sorption to the glass surface of the test vessel. Both processes result in decreasing water concentration and hence chemical substances sorbed onto the growing algae also become “growth diluted” (decreasing dose per algal dry weight resulting from increased algal dry weight) reducing the toxic impact.

Sorption to glass is a time dependent process, which likewise reduces the effective concentration and hence the toxic impact. The processes are all considered fast due to the small volume and short transport distances (happen within 48 hours). In this way a dynamic problem is turned into a problem of estimating an equilibrium distribution at a specified time (48 hours) and one of solving linear algebraic equations assuming linear partitioning justified by low concentrations.

For the less volatile test substances escape to the air is of little significance, whereas for the more volatile substances equilibrium is assumed to be established within minutes to hours at constant shaking due to the small volumes and short distances. Thus, we assume to have equilibrium between all phases well before the end of the test.

The physical and chemical data that is used in the partitioning model was mainly found in or by use of EPISuite (2001-2014) (solubility, molar weight, octanol water partitioning coefficient and vapor pressure) and SPARC On-line Calculator (2002-2005) (pK_a values). ACD/I-lab (2010-2016) was used to verify data and in some cases to find data when the other data bases failed to come up with values.

Choice of substances

Chemical substances were chosen based on preliminary QSAR modelling and on molecular structure (inactive or active fragments e.g. aromatic amino group, aromatic chlorine group, aromatic alcohol group, etc.), mode of action, special physico-chemical properties – including some basic natural structures e.g. amino acids and other organic acids. The choice of test substances was a feedback process based on previous test results and identification of potentially active groups not yet tested.

All substances were handled and working procedures were performed in accordance to the OECD Guidance Document on Aquatic Toxicity Testing of Difficult Substances and Mixtures (Organization for Economic Cooperation and Development, 2000).

RESULTS AND DISCUSSION

Partitioning model and sorption to glass

In this project with more than 400 substances tested it was not possible to verify the concentrations in the tests with chemical analysis. Instead it was chosen to estimate the partitioning of the substances in the four phases of the closed test system, air, algal biomass, glass and water. Due to the small size of the test vessels (short distances) and the continuous shaking it was assumed that equilibrium between the phases was achieved quickly and long before the end of the 48 hours test period.

To use a Mackey's fugacity level I model we needed to find the glass sorption coefficient. In the glass sorption experiments ionization was accounted for. For the six substances used to study glass sorption (Table 1) a mass balance showed that no significant volatilization took place. Furthermore no algae were added in the experiments so sorption to algae could be excluded. In Table 1 physical and chemical properties of the compounds used in these experiments are shown.

The results revealed that sorption to glass surfaces increases with time, but it was almost completed after 24 hours. In the distribution model it was chosen to use data from 48 hours because the duration of the algae test was 48 hours and because equilibrium was complete at that time even for DDT, which had the highest K_{ow} .

Addition of DMSO had only little influence on the adsorption and in the distribution model it was chosen not to account for DMSO addition because most tests were performed without a co-solvent.

In Figure 1 correlations between K_{Glass} and $\text{Log } K_{\text{OW}}$ in the range of 0.90 to 6.91 were achieved using polynomial equations; the curves and equations for normal and silanized glass are almost identical:

Normal glass: $\text{Log } K_{\text{Glass}} = 0.0289 \cdot \log K_{\text{OW}}^2 + 0.1342 \cdot \text{Log } K_{\text{OW}} - 2.2986$; ($R^2 = 0.923$)

Silanized glass: $\text{Log } K_{\text{Glass}} = 0.0307 \cdot \log K_{\text{OW}}^2 + 0.1065 \cdot \text{Log } K_{\text{OW}} - 2.2209$; ($R^2 = 0.903$)

As could be expected $\text{Log } K_{\text{OW}}$ alone can describe the sorption. For substances having $\log K_{\text{OW}}$ values lower than zero, it was assumed that no adsorption took place and for these K_{Glass} was set to zero. For substances having $\log K_{\text{OW}}$ values higher than zero the equation for silanized glass was used in the partitioning model

Additionally, investigations of sorption of substances to the glass surface was performed to develop a partitioning model to estimate the partitioning of each test substance in the specific test system consisting of water, headspace (air), algae and glass, accounting for volatilisation and sorption to algal biomass and to glass surface. The model also considered ionization; thus, the dissolved water concentration accounted for the ionized plus un-ionized water fractions. The results obtained from this model were used for an evaluation of change in the dissolved water concentration, in order to avoid under-estimations of toxicity. In OECD test guidelines (e.g. Organization for Economic Cooperation and Development, 2008) it is recommended that test results are based on measured concentrations, but if the result of the chemical analysis is within $\pm 20\%$ of the nominal concentration the test result can be based on nominal

concentrations as well. For 235 substances the model showed that the water concentration was at or above 90% of the nominal concentration and it was chosen not to correct these EC values. If the estimated water concentration was between 20% and 90% the EC values were corrected accordingly, which was the case in 104 tests. If the model showed a water concentration below 20%, the concentration was considered too uncertain to give trustworthy EC values.

Test duration

Some justified modifications of the standard method ISO 8692 were made to minimise changes in the water concentrations during the test period. One modification was to use a test period of 48 hour instead of the standard period of 72 hours. If the growth is exponential the growth curve in a semi log plot will be a straight line where the slope will correlate the specific growth rate. Thus, as long as the biomass can be measure with a sufficient precision the growth rate of an exponential growing algal culture is independent of time. In our case we were able to measure the biomass precisely enough to get a growth rate based on the three measurements from 0, 24 and 48 h, which in the control vials had a correlation coefficient of 0.98 or better in a semi-logarithmic plot.

The average control growth rate in our tests was generally in the range of 1.6-1.9 day⁻¹ with a variation coefficient of the control growth rate of less than 3% and a pH change of less than ± 0.2 , thus fulfilling the validity criteria of ISO 8692 (International Organization for Standardization, 1997.).

Adsorption and degradation

Adsorption to the biomass was reduced by using a low inoculate of 10^4 cells/L, by shortening the test duration to 48 hours (from 72 hours normally) and by applying a test temperature in the lower end of the range (21 °C) of that specified by ISO 8692 thereby reducing the final algal biomass. The lower final biomass also helps reducing pH drift, which mainly takes place at the end of a test where the biomass is highest. Besides, the shorter test duration leaves less time for degradation to take place. Degradation might have taken place, but since there was no microbial inoculation (except for the algal culture) and because of the short test duration biodegradation is considered insignificant. Due to the use of glass vials also photo degradation is considered of less importance. Finally silanized glass vials were used throughout the whole project period to minimize adsorption, though the difference to borosilicate (normal) glass seemed small. The modifications are in accordance with recommendations in the OECD Guidance Document on Aquatic Toxicity Testing of Difficult Substances and Mixtures (Organization for Economic Cooperation and Development, 2000).

Closed system

A small, closed system was used with all test substances to avoid volatilisation from the system. pH drift was minimized by increasing the alkalinity in the growth media 4 fold (200 mg NaHCO_3/L) relative to the ISO standard and by injecting CO_2 to the headspace (1% CO_2) resulting in a pH of the medium of 7.2 ± 0.2 . This also optimizes the CO_2 supply of the alga. pH may increase in standard algal tests due to uptake of CO_2 by the alga, which for ionizing compounds means that the fraction of the (toxic) non-ionized species will change during the test. By adding more bicarbonate and carbon dioxide to the system such a pH change was minimized, and thereby the fraction of the non-ionized substance becomes more constant and with that also the toxicity.

Closed test systems have also been used by Mayer et al. (2000), Lin et al. (2005), Hsieh et al. (2006) and by Fu et al. (2015). Fu et al. evaluated algal toxicity data from many different sources and found indications that 48 hours tests were slightly more sensitive than 72 hours tests; besides they found that tests performed in open and closed systems had the same sensitivity for most test compounds. Aruoja et al. (2011, 2014) tested 50 nonpolar and 58 polar narcotics and obtained results in a closed and open test that were sufficiently similar for a direct comparison. In contrast to Tsai and Chen (2007) tested 90 organic compounds and found 2 to 380-fold higher sensitivity (~lower EC values) in closed tests. *Pseudokirchneriella subcapitata* (formerly *Selenastrum capricornutum* or *Raphidocelis subcapitata*) were used in all these cited papers.

Tests with reference compound

In Table 2 is shown the result of tests performed with potassium dichromate ($K_2Cr_2O_7$) during the project period. An average EC_{50} of 0.60 mg/L $K_2Cr_2O_7$ was found in 14 tests with a standard deviation of 0.16 mg/L and a coefficient of variation of 25 %. Thus, the sensitivity of the test was constant during the project period. The average EC_{50} is lower than results presented by ISO from an inter-laboratory investigation, where an average EC_{50} of 1.19 mg/L was found (International Organization for Standardization, 1997), but this is probably caused by the lower pH used here (pH 7.2 ± 0.2 versus 8.1 ± 0.2 in standard ISO tests).

Chemical substances

In total 425 organic chemical substances including three co-solvents (DMSO, acetone and chloroform) were tested. None of the co-solvents had any effect on the growth at the concentrations at which they were added as co-solvents. Besides solvents at low concentrations do not significantly influence the water solubility in accordance with basic physical/chemical principles (ECETOC, 1996) and, thus, will not change the partitioning of the

test substances. The test substances belong to different groups: narcotic, non-narcotic, polar, non-polar, specific reacting and non-specific reacting substances, but were not characterized as such before testing because the preliminary test result gave the concentration range to be tested in the definitive test. In Figure 2A is shown a distribution of log K_{ow} values for the substances tested. Most of the compounds had low or relatively low K_{ow} values. 78 of the compounds had Log K_{ow} values higher than 4. Only five substances had Log K_{ow} higher than 7. At this level of K_{ow} , the water solubility becomes very low and the compounds generally have a high sorption to solid materials like glass and biomass and also have a tendency to form molecular aggregates. The compounds are difficult to get into solution in water, and it was necessary to use a co-solvent. The concentrations estimated in the different phases thus become more uncertain than at lower K_{ow} values.

For a series of substances it was not possible to find pK_a values. Among these are the quaternary ammonium compounds, which are permanently charged. To evaluate their partitioning we assumed a worst case scenario where they were considered them uncharged when we estimated their partitioning. In most cases the model predicted more than 90% of the (uncharged) substance to be found in the water phase, which means that the charged water fraction was probably higher. These substances had relatively low K_{ow} 's and high water solubility, so one would expect most of the compounds in the water phase. Though, for two compounds, 1-Heptanaminium, N,N,N-triheptyl-, bromide (CAS 4368-51-8) and 1-Octanaminium, N-methyl-N,N-dioctyl-, chloride (CAS 5137-55-3) the percentages of the uncharged fraction in water were estimated to 1.5% and 24%, respectively. Since they are charged, these two compounds will probably not behave like neutral compounds. Thus, it is not possible to estimate their water phase concentration with any certainty and therefore the EC values for these two substances are neither shown in the distribution of EC_{50} values

(Figure 2D) nor under the corrected EC values (but can still be seen under the uncorrected values in the Supplemental materials Table 1).

Another problematic group is the polyfluorinated substances of which we tested about 20. When assuming these substances were uncharged, the distribution model showed that for most of these more than 70 % was in the water phase. Though, for four of them the model showed that 1% or less was in the water phase. These were Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-iodo- (CAS 423-39-2); 1-Octanol, 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluoro- (CAS 647-42-7); Furan, 2,2,3,3,4,4,5-heptafluorotetrahydro-5-(nonafluorobutyl)- (CAS 335-36-5); and Pentane, dodecafluoro- (CAS 678-26-2). Again it means that the estimated water concentrations for these compounds are very uncertain, and they are not included in the distribution of EC₅₀ values (Figure 2D), but the results are still shown under the uncorrected values (Supplemental materials) if found. Likewise, if for other substances the distribution model showed less than 20% of the nominal concentration was to be found in the water phase, the EC₅₀ of that substance is not included in Figure 2D (e.g. cyclohexene, 1-methyl- (CAS 591-49-1), for which 92% is estimated to escape to the air compartment).

Figure 2B shows the distribution of molar weights of the 425 test chemical substances. More than 80 % of the substances had molar weight in the range from 100 to 300. 35 had molar weights above 350.

Henry's law constants (Log values) are shown in Figure 2C. Substances with log K_H values lower than -6.5 atm · m³ · mol⁻¹ are less volatile than water and are not expected to escape to the air phase (Lyman, 1990). Compounds with a log K_H above -3 atm · m³ · mol⁻¹ can be considered as volatile. 43 of the tested compounds belong to this group, which justifies the use of a closed test system.

EC₅₀ values were determined for 346 substances (Figure 2D). EC₅₀s lower than 1000 mg/L were found for 310; 216 of these can be classified as “Toxic” (EC₅₀ from 1 to 1000 mg/L) (depending of their toxicity to other groups of organisms their classification might be stricter) (Van Leeuwen and Hermens, 1995). 94 substances had EC₅₀s below 1 mg/L and shall be classified as “Very toxic” according to the EU classification. 36 compounds fell in the group with EC₅₀ > 1000 mg/L. No (or an un-trustworthy) EC₅₀ was found for 79 substances either because the effects were so low that an effect curve could not be established or because an extrapolation from low effect results to the EC₅₀ was not considered valid or because the estimation of the water phase concentration was too uncertain.

Partitioning examples

Some results from the partitioning model are show in Figure 3. N-(butoxymethyl)-2-chloro-N-(2,6-diethylphenyl)acetamide (CAS 23184-66-9) (Fig. 3A) is a neutral compound with a log K_{ow} of 4.84 and 72 % is found in the water phase, 21 % on the glass and 7 % on the algae. In cases like this the obtained EC values were corrected since the predicted water concentration was significantly below (<90%) the nominal concentration.

In Figure 3B is estimated the partitioning of 2,4,6-Tri-tert-butylaniline (CAS 961-38-6). It has a log K_{OW} of 6.8 and a low water solubility of 0.3 mg/L. As expected most of the material is sorbed, 73% to the biomass and 18% to the glass leaving only 8% in the water phase. In cases like this we have generally considered the partioning model results too uncertain. In the case here there was no effect at the highest tested concentration (0.028 mg/L nominal concentration), so no EC values could be found (EC₁₀ > 0.028 mg/L).

Figure 3C shows the estimated partitioning between air, algal biomass, glass and water of p-amino benzoic acid methyl ester (CAS 619-45-4). This compound has a low Log K_{OW} of 1.37. Almost all the substance is dissolved in the water phase and only 3 % is expected to sorb to the glass of the test vial. The compound is a base with a pK_a of 2.37 and is not expected to ionize at the test pH. The majority of chemicals tested behaved like this one either because they had a low K_{OW} and relatively high water solubility or because they ionized at the test pH leaving most of the compound in the water phase.

Figure 3D shows the partitioning of the neutral and highly volatile compound 1-methylcyclohexene (CAS 591-49-1) with a log K_H of $-1.16 \text{ atm} \cdot \text{m}^3 \cdot \text{mol}^{-1}$. 91 % of the compound was expected to be found in the air volume of the closed system and only 7 % in the water. Adsorption to the glass is low - only 1 % due to a relative low fraction of the compound in the water and a moderate Log K_{OW} of 3.51. With only 7% in the water phase some uncertainty accompanies this result. Thus, correction of EC values have not been done, but the uncorrected values are shown in the Table 1 of Supplemental materials.

CONCLUSION

In this work the toxicity towards the single cellular algal species *Pseudokirchneriella subcapitata* of 425 organic compounds was investigated in a growth inhibition test performed in a closed system. Chemical substances covered a wide molecular weight range, wide K_{OW} (and solubility) range, and a wide volatility range, and in the end it showed a wide toxicity range. Precautions were taken to prevent loss of the substances from the water phase and the test system (closed test system, low biomass, shorter test duration, silanized glass) and to keep pH constant. Phase distribution was modelled taking ionization, adsorption to glass and biomass, and volatilisation into consideration. If the modelled water concentration was below 90 % of the nominal concentration the calculated EC values were corrected accordingly. If the modelled water concentration was below 20% of the nominal concentration the calculated EC values were considered too uncertain and no corrected EC values were given. Then only

the uncorrected EC values were given in the supplemental material. EC₅₀ lower than 1000 mg/L was found for 310 substances; 216 of these were in the range from 1 to 1000 mg/L. 94 substances had an EC₅₀ below 1 mg/L and should be classified as “Very toxic” according to the EU classification. 36 substances fell in the group with EC₅₀ > 1000 mg/L. An EC₅₀ was not found for 79 chemicals. Chemicals from many different groups and with different physical-chemical properties and active molecular fractions, thus with different modes of action, were tested. As 425 different organic chemicals were tested in exactly the same way we consider these results a valuable source of information for environmental administrators, industry using existing or developing new substances or products, environmental risk assessors, QSAR modellers and others working with environmental risk assessing.

Supplemental material

All data and results from testing of 425 organic chemical substances (plus the reference compound potassium dichromate [CAS 7778-50-10]) are listed in the Supplemental material Table 1.

The Table 1 includes:

- CAS number
- Name
- EC₁₀ and EC₅₀ and their 95% confidence limits (corrected accordingly if less than 90% in water phase)
- Physical and chemical properties (Log K_{OW}, water solubility, molar weight, vapour pressure, acid dissociation constant)
- Base or acid characteristic of substance
- Dissolved fraction of the substance present in the water phase (ionized plus dissolved estimated using the partitioning model)
- Unionized fraction of the substance

- If a solvent was used, the amount (in %) and the kind of solvent is given
- Other remarks (if any)
- Uncorrected EC₁₀ and EC₅₀ and their 95% confidence limits (nominal concentrations)

For some substances a 50% inhibition of the growth rate was not reached at the water solubility limit. If the extrapolated EC₅₀ was less than two times the highest test concentration, the EC₅₀ was included. Values higher than this were considered too uncertain and the result was given as “higher than” the highest test concentration.

ACKNOWLEDGEMENT

The project was supported by the Danish Environmental Protection Agency under the following contract No.: J.nr. M 7041-0206; J.nr. M 7041-0334; J.nr. M 7041-0349; J.nr. M 7041-0350; J.nr. M 7041-0507; J.nr. M 7041-0497; J.nr. M 7041-0079; J.nr. M7041-0312.

A group of highly skilled laboratory technicians at DTU Environment are thanked for their excellent and precise work: Jane Bergstrøm, Signe Qualmann, Susanne Kruse, and Birthe Ebert. Also thanks to Anders Baun, Ph.D., Professor, DTU Environment, who acted as Quality Assurance Officer on this project.

REFERENCES

ACD/I-Lab 2.0. 2010-2015. ACD Labs. Available on: <https://ilab.acdlabs.com/iLab2/>

Andersen, J.S., Holst, H., Spliid, H., Baun, A., Nyholm, N. 1998. Continuous ecotoxicological data evaluated relative to a control response. *J Agric Biol Environ Stat* 3: 405-420.

Aruoja, V., Sihtmäe, M., Dubourguier, H.-C., Kahru, A. 2011. Toxicity of 58 substituted anilines and phenols to algae *Pseudokirchneriella subcapitata* and bacteria *Vibrio fischeri*: Comparison with published data and QSARs. *Chemosphere* 84: 1310-1320.

Aruoja, V., Moosus, M., Kahru, A., Sihtmäe, M., Maran, U. 2014. Measurement of baseline toxicity and QSAR analysis of 50 non-polar and 58 polar narcotic chemicals for the alga *Pseudokirchneriella subcapitata*. *Chemosphere* 96: 23-32.

Christensen, E.R., Kusk, K.O., Nyholm, N. 2009. Dose-response regressions for algal growth and similar continuous endpoints: Calculation of EC₁₀ based on EC₅₀ and slope at 50% inhibition. *Environ Toxicol Chem* 28 (4): 826-835.

Danish Environmental Protection Agency. 2004, 2015. Danish (Q)SAR Database available online at: <http://qsar.food.dtu.dk>

ECETOC 1996. Aquatic toxicity testing of sparingly soluble, volatile and unstable substances. Monograph No. 26, European Centre for Ecotoxicology and Toxicology of Chemicals, Avenue E Van Nieuwenhuyse 4 (Bte 6), B-1160 Brussels, Belgium.

- Fu, L., Li, J.J., Wang, Y.W., Wang, X.H., Qin, W.C., Su, L.M., Zhao, Y.H. 2015. Evaluation of toxicity data to green algae and relationship with hydrophobicity. *Chemosphere* 120: 16-22.
- Halling-Sørensen, B., Nyholm, N., Baun, A. 1996. Algal toxicity tests with volatile and hazardous compounds in air-tight tests flasks with CO₂ enriched headspace. *Chemosphere* 32:1513-1526.
- Hsieh, S.H., Hsu, C.-H., Tsai, D.Y., Chen, C.-Y. 2006, Quantitative structure-activity relationships for toxicity of nonpolar narcotic chemicals to *Pseudokirchneriella subcapitata*. *Environ Toxicol Chem* 25: 2920-2926.
- International Organization for Standardization. 1997. Water quality - Fresh water algal growth test with *Scenedesmus subspicatus* and *Raphidocelis subcapitata*. ISO Standard 8692, Geneva, Switzerland.
- Lin, J.-H., Kao, W.-C., Tsai, K.-P., Chen, C.-Y. 2005. A novel algal toxicity testing technique for assessing the toxicity of both metallic and organic toxicants. *Water Res* 39: 1869-1877.
- Lyman, W.J., Reel, W.F., Rosenblatt, D.H. 1990. Handbook of chemical property estimation methods. Environmental behavior of organic compounds. American Chemical Society, Washington DC USA. Pp. 15.1-15.34.

Mackay, D. 1991. Multimedia environmental models: The fugacity approach. Lewis
Publisher, Boca Raton, FL, USA.

Mayer, P., Cuhel, R., Nyholm, N. 1997. A simple *in vitro* fluorescence method for biomass
measurements in algal growth inhibition tests. *Water Res* 31: 2525-2531.

Mayer, P., Nyholm, N., Verbruggen, E.M.J., Hermens, J.L.M., Tolls, J. 2000. Algal growth
inhibition test in filled, closed bottles for volatile and sorptive materials. *Environ Toxicol
Chem* 19: 2551-2556

Organization for Economic Cooperation and Development. 1984. OECD 201. Guideline for
Testing of Chemicals “Algal Growth Inhibition Test”. OECD, Paris, France.

Organization for Economic Cooperation and Development. 2000. Guidance Document on
Aquatic Toxicity testing of Difficult Substances and Mixtures. OECD Series on testing and
Assessment No 23. OECD, Paris, France.

Organization for Economic Cooperation and Development. 2008. OECD 211. “*Daphnia magna*
Reproduction Test”. OECD, Paris, France.

Trapp, S., Franco, A. Mackay, D. 2010. Activity-Based Concept for Transport and
Partitioning of Ionizing Organics. *Environ Sci Technol* 2010, 44, 6123–6129.

Tsai, K.-P., Chen, C.-Y. 2007. An algal toxicity database of organic toxicants derived by a
closed-system technique. *Environ Toxicol Chem* 26: 1931-1939.

University of Georgia. 2002. (Carreira, LA). SPARC On-line Calculator 2002-2005.

<https://archemcalc.com/sparc/>.

US Environmental Protection Agency 2001-20014. EPISuite ver. 3.10 and 3.11. Available on:

<http://www.epa.gov/oppt/exposure/docs/episuitedl.htm>

Van Leeuwen, C.J., Hermens, J.L.M. 1995. Risk Assessment of Chemicals: An Introduction.

Kluwer Academic Publishers, Dordrecht.

Figure legends:

Figure 1: Sorption of six chemical substances to normal and silanized glass after 48 hours

Figure 2: Distribution of the test substances with respect to

- A: Log K_{ow} (octanol-water partitioning constant)
- B: Molecular weight
- C: Log K_H (Henry's constant)
- D: EC_{50} values (corrected)

Figure 3: Estimated partitioning of four test substances:

- A: N-(butoxymethyl)-2-chloro-N-(2,6-diethylphenyl)acetamide (CAS 23184-66-9)
- B: 2,4,6-Tri-tert-butylaniline (CAS 961-38-6)
- C: p-amino benzoic acid methyl ester (CAS 619-45-4)
- D: 1-methyl-cyclohexene (CAS 591-49-1)

Figure 4: Correlation between EC_{50} s obtained by Aruoja et al. [23, 24] and by DTU. The solid line represents the 1:1 ratio.

Table 1: Physical and chemical properties of the compounds used in the sorption experiment. Data from US EPA EPISuite (2001-2014) and ACD (2010-2015).

CAS	NAME	Log K _{OW}	*Sol (mg/L)	**MOLW.	***VAP(mm Hg)	pK _a
50-29-3	DDT α	6.91	5.50·10 ⁻³	354.49	7.5·10 ⁻⁶	-
57-63-6	Ethenyl estradiol #	3.67	1.13·10 ²	296.41	1.95·10 ⁻⁹	10.2
62-53-3	Aniline %	0.90	2.08·10 ⁴	93.13	7.91·10 ⁻¹	4.6
85-01-8	Phenanthrene α	4.46	6.77·10 ⁻¹	178.24	4.32·10 ⁻⁵	-
100-02-7	4-Nitrophenol #	1.91	7.51·10 ³	139.11	2.90·10 ⁻³	7.1
106-47-8	4-Chloroaniline %	1.83	3.90·10 ³	127.57	2.70·10 ⁻²	4.0

* : Solubility in water

α: Neutral compound

** : Molecular weight

#: Acid

*** : Vapor pressure

#: Base

Table 2: Results of closed tests with reference compound potassium dichromate at pH 7.2.

N (Number of tests with reference compound):	14
EC ₅₀ mean value:	0.60 mg/L
Standard deviation:	0.16 mg/L
Coefficient of variation:	25 %

Highlights

- More than 400 algal tests were performed under identical conditions
- Chemical phase distribution was modelled using Mackay level I
- The model helped to identify substances with low and uncertain concentrations
- EC₅₀ for 94 substances were below 1 mg/L and should be classified as “Very toxic”
- Results are considered important for environmental risk assessment