



High permittivity dielectric elastomers with ionic liquid (IL) loading

Liu, Xue; Nie, Yi; Yu, Liyun; Zhang, Suojing; Skov, Anne Ladegaard

Publication date:
2019

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):

Liu, X., Nie, Y., Yu, L., Zhang, S., & Skov, A. L. (2019). *High permittivity dielectric elastomers with ionic liquid (IL) loading*. Abstract from 9th International Conference on Electromechanically Active Polymer (EAP) Transducers & Artificial Muscles (EuroEAP 2019), Dresden, Germany.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

High permittivity dielectric elastomers with ionic liquid (IL) loading

Xue Liu (1)(2), Yi Nie(2), Liyun Yu(1), Suojiang Zhang (2), Anne Ladegaard Skov(1)*

(1) Danish Polymer Centre, Department of Chemical and Biochemical Engineering, Technical University of Denmark, Kgs. Lyngby, Denmark;

(2) CAS Key Laboratory of Green Process and Engineering, Institute of Process Engineering, Chinese Academy of Sciences, Beijing, China;

Dielectric elastomers (DEs) represent a promising transducer technology, due to their excellent ability to undergo large and reversible deformations under an applied electric field. The most obvious challenge that current elastomers face is the high driving voltages necessary to activate the elastomers. An effective way to overcome this shortcoming is to increase the permittivity of DEs. Ionic liquids (ILs) have high permittivity and conductivity. It is therefore meaningful to blend ILs in elastomers to increase their dielectric permittivity while focusing on maintaining the non-conductive nature of silicone elastomers. In this work, high permittivity dielectric elastomers were prepared through the synthesis of silicone elastomers loaded with ILs. The influence of the structure and amount of ILs on the material properties was discussed, and other important properties for the material's application as DEs, such as resulting gel fractions and mechanical properties, were investigated. It was found that 1-butyl-3-methylimidazolium hexafluoroantimonate (BmimSbF_6) is the most suitable IL for the given system, and the dielectric permittivity of the elastomers increased with the increasing amount content of BmimSbF_6 . A simple figure of merit (F_{om}) for actuators was used and the resulting F_{om} of elastomer with 90 phr IL loading is 10.40, compared to that of the pristine elastomer indicating a great potential.