



Forming of low cost and high performance SiC membranes by liquid-phase sintering

Candelario, Victor M. ; Jørgensen, Jan Hoffmann; Agersted, Karsten; Reddy, Bhaskar ; Hansen, Karsten Klemens

Publication date:
2019

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Candelario, V. M., Jørgensen, J. H., Agersted, K., Reddy, B., & Hansen, K. K. (2019). *Forming of low cost and high performance SiC membranes by liquid-phase sintering*. Abstract from 2nd Nordic Conference on Ceramic and Glass Technology, Roskilde, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Forming of low cost and high performance SiC membranes by liquid-phase sintering.

Victor M. Candelario^a, Jan Hoffman Jørgensen^a, Karsten Agersted^b, Bhaskar Reddy^b, Karsten Klemens Hansen^a

^a Liqtech International A/S, DK-2750, Ballerup, Denmark.

^b Department of Energy Conversion and Storage, Technical University of Denmark, Risø Campus, Frederiksborgvej 399, DK-4000 Roskilde, Denmark.

The advantages of ceramic membranes are numerous and especially long life time, higher flux, smaller foot print are some of the main characteristics. Furthermore, SiC membranes offer extreme durability with respect to chemical and temperature resistances compared to polymeric membranes and alumina based ceramic membranes. This means that SiC membranes can be used in applications that have been too difficult for existing membranes, as well as improve the performance of existing systems. The main obstacle to growth for ceramic membranes, is the perception in the industry that they are expensive.

With these premises in mind, here we have studied the aqueous colloidal processing of powder mixtures of SiC and liquid-phase sintering additives. The study involves zeta potential of the starting powder, and the election of the best condition to prepare the suspension for the membranes. The resulting membrane were sintered with different temperatures, and different holding time. These membranes are in the range of ultrafiltration with lower porosity and good joining between membrane and substrate.