Approaches to fill data gaps and evaluate process completeness in LCA—perspectives from solid waste management systems

Henriksen, Trine; Levis, James W.; Barlaz, Morton A.; Damgaard, Anders

Published in:
International Journal of Life Cycle Assessment

Link to article, DOI:
[10.1007/s11367-019-01592-z](https://doi.org/10.1007/s11367-019-01592-z)

Publication date:
2019

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Henriksen, T., Levis, J. W., Barlaz, M. A., & Damgaard, A. (2019). Approaches to fill data gaps and evaluate process completeness in LCA—perspectives from solid waste management systems. *International Journal of Life Cycle Assessment*, 24(9), 1587-1601. <https://doi.org/10.1007/s11367-019-01592-z>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Approaches to fill data gaps and evaluate process completeness in LCA - Perspectives from solid waste management systems

Trine Henriksen^{a}, James W. Levis^b, Morton A. Barlaz^b, Anders Damgaard^a*

^a Technical University of Denmark, Department of Environmental Engineering, Bygningstorvet 115, 2800 Kongens Lyngby, Denmark

^b North Carolina State University, Department of Civil, Construction, and Environmental Engineering, Campus Box 7908, Raleigh, NC 27695-7908, USA

* Corresponding author. Phone: +45 4525 2169; E-mail: trinh@env.dtu.dk

Acknowledgements

The research was financially supported by the Technical University of Denmark through a scholarship from the R98 foundation.

Abstract

Purpose Large data amounts are required in an LCA, but often, site-specific data are missing and less representative surrogate data must be used to fill data gaps. No standardized rules exist on how to address data gaps and process completeness. We suggest a systematic evaluation of process completeness, identification of data gaps, and application of surrogate values to fill the gaps. The study focuses on foreground process data.

Methods A solid waste management (SWM) scenario was used to illustrate the suggested method. The expected input and output flows in a waste incineration model were identified based on legislation and expert judgement, after which process completeness scores were calculated and missing flows identified. To illustrate the use of different types of surrogate data to fill data gaps, data gaps were selected for 16 different parameters in five SWM processes. We compared the global warming potential (GWP) from using surrogate data, and from leaving the gap, to identify the data gaps where representative surrogate data should be used.

Results and discussion The completeness score for the material inputs to waste incineration was 78%, and the missing flows were auxiliary fuels and precipitation chemicals. The completeness score for air emissions were between 38% and 50% with and without expert judgement. If only greenhouse gases were considered (CO_2 , CH_4 , and N_2O), the completeness score would be 67%. Applying weighting factors according to the greenhouse gas contribution in the US gave a completeness score of 94%. The system-wide data gaps, where representative surrogate data should be applied, were the CH_4 release from composting; electricity generation efficiency of incineration; recovery efficiencies at a material recovery facility; and composition of the plastic, metal, and paper fractions in the household waste; in these cases, leaving the gap changed the GWP results by >5%.

Conclusions Completeness evaluation should take into account the relevance and importance of flows; relevance depends on the considered life cycle impact methods and importance depends on the weighting of the different flows. The set of expected flows and evaluation of relevance and importance must be documented in a transparent manner. The choice of surrogate values to fill data gaps depends on the availability of secondary data and on whether the data gap matters, i.e. significantly affects the LCA results. The suggested method can be used to properly document the identification of missing flows, and to select and apply surrogate values to fill the data gaps.

Keywords: Completeness, data gaps, surrogate values, representativeness, waste management, LCA

1 Introduction

There is an increasing need for predictive models to support environmental policy and decision making. The validity of these models is dependent on the availability of reliable data generated in a valid manner and relevant to the study context. Life cycle assessment (LCA) is an example of a data intensive modeling framework that is often used for environmental policy analysis. It is an analytical framework used to estimate and compare the potential environmental impacts of products, processes, and systems. LCAs cover multiple impact categories (e.g., global warming, resource use, eutrophication) as well as upstream and downstream processes to assess and explore trade-offs between different impacts and life cycle stages (e.g., use and end-of-life). The comprehensive nature of LCA implies the need for large amounts of data representing both foreground and background processes. As a result, missing data (i.e. data gaps) are common. Data gaps can be defined as values that are unavailable but would improve the accuracy and reliability of LCA results if they were included (Little et al., 2012). Data gaps that are ignored, i.e. not filled by some alternative data, may bias the results of an LCA. As described by Zhou et al. (2014), even when data are missing, the goal remains to make conclusions about the facilities and processes covered by the goal and scope of the analysis. Thus, to ensure that reliable conclusions are drawn from an LCA study, it is important that the practitioner identifies data gaps and applies methods to fill them.

Data gaps may occur in the life cycle inventories (LCIs) or life cycle impact assessment (LCIA) methods. The focus of this study is on data gaps in LCIs, which include entire processes or single data points within a process (Hischier et al., 2001). For example, an LCA practitioner may neglect the emissions and material use related to the process of constructing a garage when modeling waste collection. A *single* data point, that is typically unknown and likely neglected, is the benzene emission associated with waste collection vehicles. There are principally two types of missing data: complete lack of data and lack of site-specific (i.e. technologically, temporally, and/or geographically representative) data (Huijbregts et al., 2001). In the case of a complete lack of data, no secondary data are available to fill the data gap, while in the case of a lack of site-specific data, it is possible to apply secondary data as surrogates. A common situation in which a lack of data occurs is when novel or future technologies are assessed or when there is a need to include emissions that are not monitored; complete lack of data can therefore include ‘unknown unknowns’, i.e. data that are missing without the awareness of the practitioner, due to ignorance about the processes under study (e.g., a practitioner may be unaware of the potential presence of chlorofluorocarbons (CFCs) in landfill gas [Hodson et al., 2010]). Lack of site-specific data, e.g. measured at the operated process, is frequent in LCA and can include ‘known unknowns’, as the data need is known but only secondary, potentially non-representative, data are available (e.g., a

57 practitioner may be aware of potential CFC emissions in landfill gas, but have no data on the CFC emissions from the
 58 landfill under study). Scarce or missing data in LCAs of waste management systems include complete lack of data, such
 59 as emissions from wastewater treatment plants due to limited substance coverage of monitoring programs (Yoshida et
 60 al., 2014), and lack of site-specific data, such as the physico-chemical composition of local household waste material
 61 fractions (Götze et al., 2016). Thus, missing data is a challenge when modeling waste management systems, particularly
 62 because of the local specificities and the linked nature of the waste composition, collection, and treatment processes.
 63 The ISO 14044 standard requires that missing data is treated by a justified application of a non-zero value, a zero value,
 64 or a calculated value (ISO, 2006). A number of publications have demonstrated methods to fill data gaps, including the
 65 use of proxies, extrapolation methods, regression models, expert elicitation, and input-output data (Canals et al., 2011;
 66 Majeau-Bettez et al., 2011; Moreau et al., 2012; Steinmann et al., 2014; Subramanian and Golden, 2016). These
 67 methods differ in level of sophistication, and previous studies have not yet compared different approaches to fill the
 68 same data gap.

69 The occurrence of data gaps is closely linked with data completeness. Completeness is a data quality requirement in
 70 ISO 14044, defined as the ‘percentage of flow that is measured or estimated’ (ISO, 2006), which allows for multiple
 71 interpretations. The data quality assessment scheme used for the ecoinvent database evaluates completeness as the
 72 quality of a single flow in terms of whether the data sampling represents variations over time and space (Weidema et
 73 al., 2013). For example, NO_x emissions from waste collection fluctuate depending on the type of truck, duty cycle, and
 74 collection system for a specific city, which should ideally be estimated using a sufficient sampling size and period. The
 75 ILCD Handbook (JRC, 2010) and the US Environmental Protection Agency (US EPA) (Edelen and Ingwersen, 2016)
 76 define completeness at the process level as the number of included substances to model a process relative to the number
 77 of expected substances for a process. In this study, we will focus on completeness at the process level. Few publications
 78 describe how to calculate completeness scores for process inventories in practice. The approach by Edelen and
 79 Ingwersen (2016) includes different types of data used to model a unit process (e.g. emissions, raw inputs, and reference
 80 product). It provides a generic method for weighting completeness scores that can be adjusted to consider the relevant
 81 priorities of a project stakeholder (e.g. a study may weigh the completeness of air emissions stronger than the
 82 completeness of intermediate inputs). However, Edelen and Ingwersen (2016) do not offer an approach to identify the
 83 expected flows in the calculation of the completeness score. Other authors provide examples of using the method by
 84 JRC (2010) to calculate the completeness of fuel and electricity datasets regarding substance flows to and from the
 85 environment (Fazio et al., 2015; Garraín et al., 2015a, 2015b). The authors first conducted a sectorial analysis to

86 identify the substances that should be included in the process inventory, they then listed the substances actually
87 included according to how many impact categories they cover, and finally they compared the number of included
88 substances relative to the number of expected substances per impact category (they did not include weighting). While
89 publications on process completeness base the estimation of expected substances on expert judgement, substances
90 identified by environmental regulation and monitoring programs are also relevant. In this study, we suggest a systematic
91 approach to evaluate completeness that considers current and potential regulations, existing literature, and expert
92 judgement.

93 This study addresses foreground process data, and site-specific data gaps that can be identified and filled using
94 secondary surrogate data to build more complete lifecycle inventories. The aim of this study is to suggest a combined
95 systematic approach to calculate process completeness, identify missing flows (data gaps), and apply surrogate values to
96 fill the data gaps. A solid waste management (SWM) scenario is used as case study to illustrate the method. The
97 specific objectives are to 1) describe methods to fill data gaps and calculate completeness scores, 2) calculate process
98 completeness scores and identify missing flows for the waste incineration process as an example, and 3) suggest
99 methods and surrogate values to fill the data gaps for 16 parameters in five SWM processes. The next section describes
100 methods to fill data gaps and calculate completeness scores, followed by a description of the case study, and a
101 presentation and discussion of the study results.

102 **2 Methods**

103 **2.1 Published methods to fill data gaps**

104 Methods used to approximate the missing data in the SWM case study include deterministic approaches based on
105 single-point values and intervals as well as stochastic approaches using statistical distributions. Table 1 shows a
106 glossary of terms for the approaches used to fill data gaps in this study and each is described in this section.

107 Direct and average proxies require relatively little data (Canals et al., 2011). A direct proxy consists of using another
108 value from a different process or system in place of the missing value, while an average proxy uses some value of
109 central tendency (e.g., mean, median, mode) of a set of direct proxies. If more than one proxy representing the same
110 process is available, an interval can be obtained (e.g. using the standard deviation). Scaled proxies are typically used for
111 product portfolios, production volumes, and other compositional data. Compositional data contains relative information
112 about the parts of a whole, given as proportions and percentages. In the SWM field, scaled proxies have been used to
113 construct food waste composition by defining a set of food item proxies per food category. For example, Tonini et al.

114 (2017) used beef, pork, and chicken as proxies for the entire fraction of meat and meat products, where other meats
 115 were considered negligible. Regression techniques can also be used to derive proxies, e.g. Moreau et al. (2012)
 116 predicted material flows for power plants from relationships between properties of different plants.

117 Min-max intervals cover the extreme observations of a sample. For example, min-max intervals were used to establish
 118 landfill LCIs representing the expected technological and geographical variability within a given scope of study
 119 (Henriksen et al., 2017). Alternatively, statistical distributions may be developed for the input values. When data are
 120 limited, uniform or triangular distributions are often used to create approximate distributions (Bisinella et al., 2017;
 121 Clavreul et al., 2013; Laner et al., 2015). If the sample is sufficiently large, fitting a statistical distribution to the
 122 available data provides an estimate of the uncertainty of the value.

123 **Table 1** Glossary of terms for the methods used to fill data gaps in the case study

Proxy	Available surrogate data intended to reasonably represent missing data based on an underlying understanding of the process, material, or system
Direct proxy	Use of surrogate data without any modification of its original value(s)
Average proxy	Use of a measure of central tendency of multiple surrogate data values (i.e. arithmetic mean, median, mode)
Scaled proxy	Linear scaling of known part of some compositional data to cover an unknown part of the data
Min-max interval	Extremes of a data interval based on measured data, literature, or estimates
Statistical distribution	Fitting a statistical distribution to a data sample (normal, lognormal, triangular, etc.)
Leaving a gap	A gap in data is neglected because the practitioner is unable or unwilling to use any surrogate data to fill a data gap

124

125 In addition, models can be used to approximate missing data by describing the relationship between independent and
 126 dependent variables. For example, the energy use at material recycling facilities (MRFs) was estimated from mass flows
 127 to each piece of equipment and energy use per unit mass of material processed (Pressley et al., 2015). A limitation of
 128 using models is that detailed information about sub-processes in a facility is required, which – if not available – creates
 129 even more data gaps. Input-output data have been used to address background data gaps (Moberg et al. 2014), but may
 130 overestimate the actual impact when including emissions from other sectorial processes. Finally, leaving a data gap is
 131 an alternative to filling the gap, which, however, may favor the least documented process in an LCA (Moreau et al.,
 132 2012).

2.2 Method to calculate process completeness scores

The applied method to calculate completeness scores follows the principles reported by the US EPA (Edelen and Ingwersen, 2016) and ILCD Handbook (JRC, 2010). The basic principle is to calculate process completeness as the number of included flows relative to the number of expected flows. Flows here are distinguished as elementary (exchanges with the environment) and intermediate (between industrial processes). In this study, elementary and intermediate flows are assessed separately, because the former targets the impact coverage of the included data. Equation 1 is used to calculate the completeness score for process p , and Eq. 2 calculates the system completeness by dividing the total number of included flows for all P processes by the total number of expected flows for all P processes. Process and system completeness can be calculated using either elementary or intermediate flows either as a whole or for specific impact categories.

$$\text{Process Completeness}_p = \frac{\text{Number of Included Flows}_p}{\text{Number of Expected Flows}_p} \quad (1)$$

$$\text{System Completeness} = \frac{\sum_1^P \text{Number of Included Flows}_p}{\sum_1^P \text{Number of Expected Flows}_p} \quad (2)$$

Depending on the type of LCI model, Eq. 1 and 2 may also be used to assess the completeness of flows modeled indirectly, i.e. flows that are a function of parameters such as transfer coefficients and other efficiencies. The set of expected flows should be identified in a transparent manner and be based on published sources and expert judgement. The next section describes a decision-support framework for evaluating process or system completeness that includes the identification of expected flows.

2.3 Decision-support framework

The decision-support framework shown in Figure 1 illustrates the suggested method to evaluate process completeness, identify missing flows (data gaps), and apply surrogate values to fill the data gaps. The method consists of four steps, and we recommend that a user sets up a similar diagram when conducting an LCA. Step 1 is the initial modeling of the processes under study, where the available input and output data are collected. The required data depend on the goal and scope of the study, e.g., in a carbon footprint study only elementary exchanges of greenhouse gases are required. Step 2, the identification of the expected flows for a process p , help to establish the required data. Legislative documents contain lists of monitored substances, which are relevant to the process and should be included in the model, and other relevant substances can be found in literature and based on expert judgement. In step 3, the included flows and set of expected flows are used to calculate a process completeness score and identify the missing flows (i.e. data gaps). In step 4, the data gap is characterized as either a complete gap or a site-specific data gap, as this influences the ability to apply

159 secondary data as surrogates. If it is a complete data gap, a rough estimate can be used. If it is a site-specific data gap,
160 secondary surrogate data can be collected; starting with, potentially lower-quality, easily available data. The user should
161 then further evaluate the data gaps that significantly change the results (e.g., >0.1, 1 or 5% change) if not filled by
162 surrogate data. Final surrogate data values should be selected for the important data gaps based on a comparison of the
163 representativeness of the possible surrogate values (site-specific gap) or by refining the rough estimate, e.g. by
164 consulting an expert (complete gap). For the data gaps not considered important (<0.1, 1 or 5% change), it is sufficient
165 to use lower quality surrogate data (or to leave the gap un-filled), as this will not significantly alter the LCA results.

166

167

168

169 **Fig. 1** Decision-support framework diagram with the method applied in this study

3 Case study

3.1 Solid waste management scenario

A SWM scenario (Figure 2) was modeled to illustrate the application of the suggested method in Figure 1. The scenario represents the management of household waste in the US, with the functional unit being the collection, transport, and treatment of 1 metric ton of household waste including disposal of final residues. The included processes are waste generation and source separation, collection of waste fractions, sorting at a MRF, composting of yard and food waste, remanufacturing of recyclable materials, and incineration of the residuals with energy recovery. The LCI is documented in the Supplementary Information (SI). The SI also contains an analysis of an additional SWM scenario where the residual waste is landfilled. The second scenario was added to ensure generalizability for the proposed approach, and the SI (section 3) includes a comparison of both scenarios. A consequential modeling approach was applied, hence, multifunctionality was addressed by system expansion to account for avoided products. Mainly North American data were used as a baseline, but the outcomes related to filling data gaps and calculating process completeness are generally applicable to the LCA field. The LCA model EASETECH was applied (Clavreul et al., 2014).

Fig. 2 Flow diagram for the SWM scenario used as case study. Squares with solid lines indicate waste treatment processes and ovals indicate material flows. Dotted lines indicate the substitution of marginal energy, virgin materials, or fertilizer by recovered energy or secondary materials from the waste treatment. Arrows indicate collection from households and inter-facility transportation. Data gaps are selected for the five processes with bold edges

The four steps of the decision-support framework shown in Figure 1 was demonstrated as follows: The scenario was modeled with the included data stemming from available secondary sources (step 1). Next, the waste incineration process was used as an example to estimate the set of expected flows, calculate the completeness score, and identify the missing flows (step 2 and 3). Then, 16 different parameters were selected as site-specific data gaps in five processes in

193 the scenario to provide multiple examples of applying different approaches and surrogate data to fill data gaps (step 4).
194 Lastly, final surrogate values were selected based on their representativeness and other data quality aspects (step 4).
195 To present the results from using surrogate data to fill the data gaps, we applied the global warming potential (GWP)
196 metric. The purpose of this study was to compare approaches to fill the data gaps, rather than to present a full LCIA.
197 Thus, a carbon footprint study was adequate to illustrate the methodology. We quantified the GWP using the method
198 developed by the Intergovernmental Panel on Climate Change as recommended in Hauschild et al. (2012).

199 **3.2 Included and expected flows for the waste incineration process**

200 To identify the missing flows and evaluate the completeness for the waste incineration process, the included and
201 expected intermediate and elementary flows were identified (Table 2); this corresponds to step 1 and 2 in Figure 1. The
202 intermediate flows were material inputs to the waste incineration plant, and the elementary flows were air emissions via
203 the flue gas. Relevant expected flows were identified based on legislative documents.

204 The reference for the intermediate flows was the former Danish register in which Danish waste incineration facilities
205 were legally obliged to report annual consumption data (Danish EPA, 2010). The set of expected intermediate flows
206 was identified based on an internal review of data reported by 10 Danish incineration plants from 1995 to 2016.

207 Multiple references were used to obtain an aggregated set of expected elementary flows, with and without additions
208 based on expert judgement. Under the Clean Air Act, the US EPA has developed New Source Performance Standards
209 for large municipal waste combustors (US EPA, 2006), named 'US standards' in Table 2. Within Europe, the Integrated
210 Pollution Prevention and Control (IPPC) directive regulates emissions from industrial facilities, including dedicated
211 waste incineration plants (European Parliament and Council, 2010), which contain emission limit values. Also in
212 Europe, waste incineration plants must comply with the European Pollutant Release and Transfer Register (PRTR)
213 (European Commission, 2006), which requires reporting of emissions that may or may not be regulated by the IPPC.

214 The additional flows from expert judgement were provided by Michael Van Brunt (Sr. Director of Sustainability,
215 Covanta Energy Corporation). The additional flows included emissions that may be regulated in local/regional
216 jurisdictions in the US (e.g. states and air quality districts), due to specific conditions. For example, individual states
217 may regulate emissions that are not regulated at the national level. Flows were therefore aggregated into two sets; one
218 with and one without flows based on expert judgement.

219 **Table 2** Included input-output flows in the waste incineration model as well sets of expected intermediate and elementary
 220 flows. The full names/chemical formulas are explained in the SI

Included flows	
Intermediate (material use at plant)	Elementary (emissions to air)
Activated carbon, calcium agent (CaCO ₃ , Ca(OH) ₂), electricity, heat, NH ₃ , scrubber (NaOH, HCl), water	As, Cd, CH ₄ , CO, CO ₂ , Cr, Cu, dioxins, particles, HCl, HF, Hg, NH ₃ , Ni, NO ₂ , Pb, PM, Sb, SO ₂ , TOC
Expected flows	
Intermediate (material use at plant)	
Danish register	Activated carbon, calcium agent (CaCO ₃ , CaO, Ca(OH) ₂), electricity, heat, fuel (gas, oil, biomass), NH ₃ , precipitation chemicals (TMT15, FeCl ₃ , FeSO ₄), scrubber (NaOH, NaHCO ₃ , HCl), water
Elementary (emissions to air)	
US standards	Dioxins/furans, Cd, Pb, Hg, particles, HCl, SO ₂ , NO _x , CO, CO ₂ , N ₂ O, CH ₄
IPPC directive	As, Cd, Co, Cr, Cu, dioxins, furans, particles, HCl, HF, Hg, Mn, Ni, NO ₂ , Pb, Sb, SO ₂ , Tl, TOC, V
PRTR register	As, C ₆ H ₆ , Cd, CH ₄ , CO, CO ₂ , Cr, Cu, dioxins/furans, HCB, HCl, HF, Hg, NH ₃ , Ni, NMVOC, N ₂ O, NO ₂ /NO _x , PAH, , PM10, Pb, PCB, PeCB, PER, SO ₂ /SO _x , C ₂ H ₃ Cl, Zn
Expert judgement	‘US standards’ + Be, Cr, Cr VI, As, Ni, NH ₃ , HF, Zn, Sb, Se, V, Cu, Mn, C ₂₀ H ₁₂ , PAH, VOC, F ⁻ , HBr, Al, P, PCBs, Sn, Si, Ba, Tl, C ₂ Cl ₄ , CCl ₄ , C ₂ H ₃ Cl, C ₂ HCl ₃
Sum without experts addition	Dioxins/furans, Cd, Pb, Hg, particles, HCl, SO ₂ , NO ₂ , PAH, PCB, PeCB, PER, NO _x , CO, CO ₂ , N ₂ O, CH ₄ , As, Cd, Co, Cr, Cu, HF, Hg, Mn, Ni, NO ₂ , Sb, Tl, TOC, V, C ₆ H ₆ , NH ₃ , HCB, Ni, NMVOC, C ₂ H ₃ Cl, Zn
Sum with experts addition	‘Sum without’ + Be, Se, C ₂₀ H ₁₂ , F ⁻ , HBr, Al, P, Sn, Si, Ba, C ₂ Cl ₄ , CCl ₄ , C ₂ HCl ₃

221 IPPC=Integrated Pollution Prevention and Control, PRTR=European Pollutant Release and Transfer Register,

222 3.3 Data gaps in the case study

223 We selected hypothetical data gaps for 16 parameters in five processes in the SWM scenario (highlighted in Figure 2).

224 The data gaps are examples of missing site-specific data in the modeling of SWM processes. Some parameters are
 225 included as gaps (e.g. CH₄ emissions from composting and MRF recovery rates) to highlight the importance of using
 226 representative surrogates, as SWM models are often sensitive to these parameters. The data gaps are described in this
 227 section.

228 The waste generation process describes the household waste composition, which influences the environmental impacts
 229 of waste treatment and disposal (Bisinella et al., 2017). The waste composition was developed from a residual waste
 230 sorting study for Wake County, North Carolina, and data on recyclable waste composition for municipalities within the
 231 county (SCS Engineers, 2014). Municipal solid waste composition data are available in the literature, e.g. the World
 232 Bank includes six fractions (Hoornweg and Bhada-Tata, 2012) and other studies include more fractions (Burnley, 2007;
 233 Edjabou et al., 2014, US EPA, 2016). However, detailed waste composition data, e.g. the proportion of different plastic
 234 polymers, is limited, which leads to a frequent use of surrogate data to fill gaps. Consequently, we selected data gaps for
 235 the composition of the food, paper, plastic, ferrous metal, aluminum, and glass fractions. Specific considerations on
 236 how to approach the data gaps were developed for the waste composition. As the data gap is the composition of the

237 waste fractions, the proportions of the overall fractions were known, i.e. food (9%), paper (17%), plastic (12%), metal
 238 (4%), and glass (7%). The unknowns were the proportions of the *constituents* of the fractions; e.g. for food waste, the
 239 proportion of non-meat versus meat.

240 The MRF process controls the difference between the amount of materials *collected* for remanufacturing and the
 241 amount *sent* to remanufacturing. MRF types are single (receiving a commingled recyclables stream), mixed (receiving
 242 mixed waste containing recyclables and non-recyclable wastes), dual (receiving two streams of recyclables [e.g., mixed
 243 containers and presorted paper] for separate treatment), and presorted MRFs (receiving source-separated streams that go
 244 through final sorting and bailing) (Pressley et al., 2015). The performance of MRFs depends on individual design and
 245 operational configurations governed by the waste to be treated, which is why there is no single industry-average dataset
 246 (Pressley et al., 2015). This suggests the need for site-specific data that are often not available. To assess the influence
 247 of MRF data gaps, we selected data gaps for material recovery efficiencies as well as diesel and electricity use.

248 The paper, plastic, glass, and metal remanufacturing processes in the system are based on relatively old data
 249 representing the US (RTI International, 2003). Data for the conversion of waste materials to secondary products are
 250 generally limited and variable (Brogaard et al., 2014). Hence, we selected data gaps for direct CO₂ emissions as well as
 251 electricity and natural gas use in remanufacturing. Instead of analyzing all remanufacturing processes, we used
 252 cardboard remanufacturing as an illustrative example. The influence of using remanufacturing surrogate data for other
 253 types of fiber (newsprint, office paper, etc.) was assessed.

254 The composting process included food and yard waste from households. Over 60% of yard waste is composted in the
 255 US (US EPA, 2016). Still, LCI data for composting is limited, e.g. material use, energy use, and input-specific
 256 emissions. Furthermore, composting technologies, e.g. open and enclosed, differ in the level of environmental
 257 exchanges (Boldrin et al., 2009). Thus, site-specific composting data is relevant but its availability is often limited. We
 258 selected data gaps for diesel and electricity use as well as input-specific greenhouse gas emissions. The land application
 259 of the finished compost was included in the model and was assumed to substitute commercial fertilizers, similar to other
 260 studies (e.g. Yoshida et al., 2016).

261 The waste incineration process recovers electricity and metals from the bottom ash. Relevant incineration data are
 262 material consumption, energy recovery, and flue gas emissions. Flue gas emissions are regulated and therefore not
 263 expected to exceed threshold values, e.g. European or US limits (European Parliament and Council, 2010; US EPA,

2006); thus, in the case of data gaps, emission limits can be used as proxies. The technology and efficiency of energy recovery is less regulated so a regulation-based proxy is not possible. Energy recovery depends on site-specific configurations, e.g. combined heat and power production or only heat or power production (Astrup et al., 2014). Empirical data for the electricity efficiency of 58 incineration facilities in the US – of which two produce combined heat and power - ranged from 7 to 22% (US EPA, 2017). While data are available for waste incineration, it is challenging to get site-specific data, which is why we selected electricity recovery as an illustrative data gap.

270 **3.4 Methods to fill the data gaps in the case study**

271 We applied approaches to fill the data gaps based on the type of data gap and availability of surrogate values. The data gaps described in the previous section were missing site-specific data, thus, secondary data were identified for use as surrogate values. As shown in Table 3, not all approaches matched with all data gaps. Direct and average proxies require single surrogate values, and could be paired with the data gaps in all five SWM processes. Scaled proxies are suitable for compositional data and were therefore only paired with the waste composition data gaps. Min-max intervals were used when multiple surrogate values were available for the same data gap, enabling an interval consisting of the extremes of the multiple surrogate values. A sufficiently large number of sampled data were available for the incineration electricity recovery, which enabled the development of a statistical distribution. Furthermore, arithmetic mean values and standard deviations for the CO₂ emissions from cardboard remanufacturing are available in literature, and were used for uncertainty propagation of the LCA results (see documentation in the SI).

281 **Table 3** Approaches used to fill the data gaps in the SWM scenario

Solid waste management process	Approach to fill data gaps
Waste generation	Direct, average, and scaled proxy
Cardboard remanufacturing; Incineration	Direct and average proxy, min-max interval, statistical distribution
Material recovery facility; Composting	Direct and average proxy, min-max interval

282 Table 4 shows the applied surrogate data. For ‘leaving gap’, we inserted a zero value in all processes except for the MRF process, to illustrate the importance of filling a data gap even though it might not be realistic to use a value of zero in an actual study. In the MRF process, we interpreted leaving the gap as setting the material recovery efficiency to 100%. This interpretation is based on the fact that any input varying from 1 to 0 can be reversed to make 0 or 1 the appropriate leave-gap value (e.g., if MRF recovery rates are 100%, then residual rates are 0%).

288 The waste composition data gaps regarded the constituents, i.e. the sub-fractions of the waste fractions (e.g., meat and
289 non-meat were constituents of food waste). For waste fractions with two constituents (i.e. food: non-meat and meat;
290 aluminum: cans and others; ferrous metal: cans and others) or three constituents (i.e. paper: mixed paper, office paper,
291 and newsprint; glass: brown, green, and clear glass),

- 292 a. Leave gap = one constituent set to 100%, the other(s) set to 0%
- 293 b. Direct proxy ('default') = Proportional split based on US county data (SCS Engineers, 2014)
- 294 c. Direct proxy ('equal') = equally split between all constituents.

295 For waste fractions with five constituents (plastic: LDPE, HDPE, PET, mixed, and non-recyclable plastic),

- 296 a. Leave gap = one constituent set to 100%, the others set to 0%
- 297 b. Direct proxy ('default') = Proportional split based on US county data (SCS Engineers, 2014)
- 298 c. Direct proxy ('equal') = equally split between all constituents
- 299 d. Scaled proxy = unknown proportion of two constituents; known proportion of the other three constituents
300 scaled to 100%.

301 The applied method for 'leave gap' reflected that the functional unit of 1000 kg was maintained to obtain equivalent
302 functionalities. Furthermore, it reflected that we chose the data gaps at the constituent level, e.g. the unknown
303 proportion of meat and non-meat. Hence, 'leave gap' was interpreted as setting a single constituent to 100% and the
304 others set to 0%, and the 'scaling method' was interpreted as extending the proportions of the known constituents to all
305 the constituents of a fraction, e.g. the known proportions of PET, Mixed, and Non-recyclable plastic were extended to
306 the entire plastic fraction. Accuracy of the fractional waste composition is important as it influences the physio-
307 chemical composition of the waste (e.g., more plastic enhances the fossil carbon content).

Table 4 Applied surrogate values to fill the selected data gaps. Bold values are inserted as default values when the data gap is not analyzed. The square brackets in the table note contain the type of technologies and data in the literature references. N.A.=not available in literature

SWM process	Data gap	Applied surrogate data values			
		<i>Direct proxies</i>	<i>Average proxies</i>	<i>Min-max intervals</i>	<i>Statistical distr.</i>
Material recovery facility (MRF)	Diesel use [kg/kg waste]	0.0007 ^{a,b} , 0.0008 ^b	0.0008 ^b	0.0007-0.001 ^c	-
	Electricity use [kWh/kg input]	0.0047/0.0060/ 0.0062 /0.0078 ^a , 0.0115/0.0138 ^b	0.0088 ^{a,b} , 0.020 ^c , 0.016 ^d , 0.01735 ^{a,b,c,d}	0.009-0.03 ^c , 0.012-0.02 ^d , 0.0047-0.03 ^{a,b,c,d}	-
	Material recovery rates:				-
	• Cardboard [% input]	• Cardboard: 54 /76/99 ^a	• Cardboard: 77/88 ^a	• Cardboard: 54-99 ^a	
	• Paper [% input]	• Paper: 39/ 77 /98 ^a	• Paper: 69 ^a	• Paper: 39-98 ^a	
	• Al [% input]	• Al: 87/96/ 97 ^a	• Al: 92 ^a	• Al: 87-100 ^a	
	• Fe [% input]	• Fe: 88/97/ 98 ^a	• Fe: 93 ^a	• Fe: 87-100 ^a	
	• Glass [% input]	• Glass: 69/93/ 95 ^a	• Glass: 81 ^a	• Glass: 69-95 ^a	
	• HDPE-PET [% input]	• HDPE-PET: 83/97/ 98 ^a	• HDPE-PET: 90 ^a	• HDPE-PET: 83-100 ^a	
	• LDPE [% input]	• LDPE: 77/ 98 ^a	• LDPE: N.A.	• LDPE: 77-98 ^a	
Cardboard remanufacturing	Electricity use [kWh/kg input]	0.462/ 0.589 /0.620/1.258 ^e	0.73 ^e	0.589-1.258 ^e	-
	Natural gas use [kg/kg input]	0.0243 /0.080/0.107/0.175 ^e	0.097 ^e	0.0243-0.175 ^e	-
	Direct CO ₂ emissions [kg/kg input]	1.04 /1.06/1.4 ^e	1.2 ^e , 0.73/0.82/0.89 ^f	0.61-1.4 ^{e,f} , 0.38-1.56 ^f , 0.22-1.86 ^f , 0.31-1.26 ^f	Norm(0.82, 0.31²) ^f Norm(0.73, 0.41²) ^f Norm(0.89, 0.60²) ^f
Composting	Diesel use [kg/kg input]	0.00265 ^g	0.003 ^h	0.0004-0.006 ^h	-
	CH ₄ emission [% kg C transformed]	1.7 ^g	1.7/2.7/7.2/9.3 ^h	2.4-3, 5.1-13.5, 0.8-2.5 ^h	-
	N ₂ O emission [% kg N transformed]	0.4 ^g , 1.8 ^h	0.4 ^h	0.1-0.7 ^h	-
Incineration	Electricity recovery [% input energy]	18.2/ 20.9 /24.4 ⁱ	17.2 ^j	7.7-22.2 ^j , 18.2-24.4 ⁱ	Norm(17.2, 2.70²) ^j

a: Pressley et al. (2015) [single, dual, presorted, and mixed MRF], **b:** Fitzgerald et al. (2012) [presorted MRF], **c:** Merrill et al. (2009) [paper MRF], **d:** Larsen et al. (2009) [glass MRF], **e:** RTI International (2003) [newsprint, magazines, office paper, and corrugated cardboard], **f:** Brogaard et al. (2014) [copy paper, newsprint, corrugated cardboard, and cardboard], **g:** Levis and Barlaz (2013) [SWOLF model default values], **h:** Boldrin et al. (2009) [values from literature review], **i:** Hodge et al. (2016) [US estimates], **j:** US EPA (2017) [US incineration facility data], **k:** De la Cruz and Barlaz (2010) [default, low, medium, and high decay rates], **l:** IPCC (2006) [decay rates for temperate, dry, and wet climate]

4 Results and Discussion

4.1 Completeness scores and missing flows for the incineration process

Table 5 shows the completeness scores calculated for the waste incineration process, which corresponds to step 3 in Figure 1. A single completeness score was obtained for the intermediate flows, while a score range was obtained for the elementary flows (with and without expert judgement) as well as an example of a weighted score for the GWP metric.

Table 5 Completeness scores for the waste incineration process in the SWM scenario

Reference of expected flows	Completeness score [%] (included no. flows / expected no. flows)
Intermediate flows completeness	
Danish register	78 (7/9)
Elementary flows completeness	
Sum without experts addition	51 (19/37)
Sum with experts addition	38 (19/50)
Example of weighted score	
GWP metric	94%

The completeness score for the intermediate flows was 78%, as 7 out of 9 flows were included. From Table 2, the missing intermediate flows were auxiliary fuel and precipitation chemicals which are common material inputs at incineration plants. Secondary fuel is typically oil with natural gas becoming more common and precipitation chemicals are e.g. TMT15, FeCl₃, and FeSO₄. Generic secondary data are available for the production of both fossil oil and FeCl₃. Thus, they are site-specific data gaps for which process data exist; flow amounts can be estimated by expert judgement.

The completeness score for the total elementary flows were between 38% and 51% depending on whether expert judgement was applied and how many flows were added by the expert. In the case of the score of 38%, all the possible additional flows by the expert were added (see flows in Table 2). The relatively low score range suggests that the included air emissions do not sufficiently represent the true number of air emissions from waste incineration plants. However, the unweighted completeness score does not say anything about the amounts emitted nor the importance or relevance of the flows. Relevance of the flows can relate to the LCIA methods being investigated in an LCA study. For example, in a carbon footprint study only greenhouse gases are relevant. The main greenhouse gas emissions from waste incineration are CO₂, CH₄, and N₂O (Astrup et al., 2009). As CO₂ and CH₄ are included in the LCI of the waste incineration process, but N₂O is not; this gives a completeness score of 67%. Furthermore, the importance can be considered by adding weighting factors to the equation. Weighting factors for individual flows may be based on the contribution of emissions to global warming within the geographical area of interest. For example, in the US, 97.4% of

the contribution to global warming stems from the emission of CO₂ (81.6%), CH₄ (10.1%), and N₂O (5.7%) given as percentages based on CO₂ eq (US EPA, 2018). Using these numbers as weighting factors gives a completeness score of 94% (i.e. $\frac{0.816 \times 1 \text{ CO}_2 + 0.101 \times 1 \text{ CH}_4}{0.816 \times 1 \text{ CO}_2 + 0.101 \times 1 \text{ CH}_4 + 0.057 \times 1 \text{ N}_2\text{O}}$), shown in Table 5. This notably higher weighted completeness score seems appropriate for the waste incineration process, because - despite N₂O being a very potent greenhouse gas - the emitted amounts are significantly smaller compared to CO₂ (Astrup et al., 2009; US EPA, 2017), and thus the impact contribution from CO₂ is expected to be larger. We therefore suggest the addition of weighting factors to obtain a more valid completeness score, which is in alignment with the guidelines suggested by the US EPA (Edelen and Ingwersen, 2016).

4.1.1 Is the subjectivity of the completeness metric a problem?

In the context of data quality assessment, the process completeness scores are usually converted to a quality rating 1-5 based on defined criteria, e.g. 1 ($\geq 95\%$), 2 (85-95%), 3 (75-85%), 4 (50-75%), and 5 ($< 50\%$) (JRC, 2010). Applying these criteria to the completeness scores in Table 5 give ratings of 3 (intermediate flows) and 2, 4 or 5 (elementary flows). The completeness metric is influenced by the subjective judgement of the user, which is why we suggest a more systematic method to estimate the set of expected flows (Figure 1). Furthermore, transparency in the choice of weighting factors is crucial, e.g. by documentation of references as in the above example with greenhouse gas contributions in the US. Due to the subjectivity of the completeness metric, it can be argued that a qualitative assessment of process completeness is just as useful, e.g. scoring completeness as Good, Average, or Poor based on whether the missing flows were from a priority list or not (van den Berg et al., 1999). However, authors have argued that data quality criteria do not need to be objective but must be inter-subjective, meaning that multiple individuals should be able to come up with similar data quality scores based on the same criteria (Funtowicz and Ravetz, 1990). As the data quality criteria for process completeness equals the set of expected flows, this highlights the importance of validation and transparency of the identification of the expected flows.

4.2 Carbon footprint results

This section corresponds to the part of step 4 in Figure 1 that evaluates whether the data gaps matter, i.e. if they will affect the final GWP results if not filled by surrogate data. We have evaluated this by comparing the GWP when applying a surrogate value with the GWP when leaving the gap for each of the 16 parameters in Table 4; if the difference between the GWP is larger than 5% then the data gap matters (i.e. is considered important). Section 4.3 then targets the part of step 4 in Figure 1, where the final surrogate values are selected for the data gaps identified as being important.

Figures 3 and 4 illustrate the GWP as a function of the data gap and surrogate value/method. In addition, Figure 5 illustrates the summary data of the results and illustrates the variability of the applied surrogate data from literature. The applied surrogate data are shown in Table 4, however, it is not possible to identify each specific value in the plots, which are meant to show the overall trends in the results. It should be mentioned that the GWP results from use of the statistical data are not shown in the plots, instead they are described in the text below for comparison.

Fig. 3 Global warming potential (per functional unit) from filling or leaving the data gaps for the 16 parameters in Table 4. The results are shown at scenario level. The symbol shape denotes the method (i.e. type of surrogate data) and the color denotes the parameter. Horizontal placement of the values is irrelevant

Fig. 4 Global warming potential results (per functional unit) from filling or leaving the data gaps for the 16 parameters in Table 4. The results are shown at process level. The symbol shape denotes the method (i.e. type of surrogate data) and the color denotes the parameter. Horizontal placement of the values is irrelevant. Note that the y scale of the plots differs

Figure 3 illustrates the results at the scenario level, i.e. the net scenario results. Regarding the composting process, only the data gap representing the CH₄ emission factor deviated >5% to leaving the gap, when applying maximum and average proxy values from Boldrin et al. (2009). Thus, the potential anaerobic CH₄ generation, occurring locally in the piled waste, should be modeled accurately. Regarding the incineration process, there is clearly >5% difference between leaving the gap and applying proxy values, thus, electricity efficiency is an important parameter that should also be modeled accurately. The outlier in Figure 5 (scenario level) were associated with the minimum value for electricity recovery from the US EPA (2017). To compare, fitting a normal distribution to the empirical energy recovery data for the US plants, resulted in -151±45 kg CO₂ eq, which corresponds to the average proxy result in Figure 3 with a standard deviation of 45 kg CO₂ eq around it. Regarding the MRF process, the GWP from using the material recovery proxies for cardboard, paper, and ferrous metal from Pressley et al. (2015) differed >5% to leaving the gaps. This is due to the linked nature of the processes and data, as differences are only seen for the net scenario (Figure 3) where the values control how much material can be finally recycled, but the material recovery efficiencies are insignificant when looking at the MRF process independently (Figure 4.) Another outcome is that, for cardboard, there were less environmental savings with 100% recovery (leaving the gap), because the savings from the subsequent cardboard recycling (-0.09 kg CO₂ eq per kg) were lower than the savings from incineration of the non-recovered cardboard (-1.1 kg CO₂ eq per kg). However, this is not a general conclusion but is based on the data for secondary and primary material production used in this study (RTI International, 2003) as well as the electricity efficiency and marginal electricity fuel (natural gas) assumed for incineration in the US. In the cardboard remanufacturing process, the difference between using surrogate values and leaving the gap was >5% for the electricity use and CO₂ emissions, with proxies from RTI International (2003) and Brogaard et al. (2014); using these proxies caused minor outliers (Figure 5). The natural gas data gap gave differences <5%, thus, an easily available surrogate value is sufficient for this parameter. To compare, the use of statistical data for the CO₂ emissions from three different fiber proxies (Brogaard et al., 2014) resulted in -216±7, -219±9, and -215±13 kg CO₂ eq, which are close to the GWP results in Figure 3.

The identified important data gaps in the waste composition (>5% difference) were related to the plastic, metal (aluminum), and paper fraction in the waste, which were also those proxies causing outliers (Figure 5). For plastic, first, leaving the gap (i.e. assuming 100% LDPE) reduced the environmental benefits from the scenarios because the GWP savings per kg recycled material for PET (-2.4 kg CO₂ eq/kg) and HDPE (-1.8 kg CO₂ eq/kg) were larger than for LDPE (-0.2 kg CO₂ eq/kg). Second, the equal split between the plastic constituents decreased the environmental savings for the same reason, but to a smaller extent. Third, using the scaled proxy (i.e. assuming unknown proportion of HDPE

and LDPE) led to larger environmental savings than the default settings, as more PET was recovered giving larger savings from recycling. For aluminum, the equal split between the constituents differed >5% to leaving the gap (i.e. assuming only aluminum cans). Leaving the gap gave a biased results in the form of enhanced environmental savings because aluminum cans had larger recycling benefits than aluminum foil in the model. Leaving the gap for the paper fraction (i.e. assuming only office paper) gave a bias in the form of reduced environmental savings, because the assumed energy content in office paper was lower compared to the other paper fractions (larger amount of mineral fillers), thus, less electricity was generated at the incineration plant.

To summarize, the data gaps identified as important in this case study were the CH₄ emission factor in composting; electricity efficiency in incineration; recovery efficiencies at the MRF; electricity use and CO₂ emissions in remanufacturing; and composition of the plastic, metal, and paper fraction in the household waste. Final surrogate values must be selected for these parameters, which is done in section 4.3.

Fig. 5 Boxplots summarizing the GWP results per functional unit for the SWM processes, at process and scenario level. The 50th (median), 25th and 75th percentile are shown. Outliers (dots) are the values beyond 75th percentile+1.5×IQR and below 25th percentile-1.5×IQR. Interquartile range (IQR) = 75th percentile-25th percentile

Figure 4 illustrates the GWP at the process level, i.e. how the data gaps influenced the net results for the processes. These outcomes are relevant if the user is modeling a single process thoroughly instead of an entire SWM system. The data gaps with >5% difference between using surrogate data and leaving the gap were the CH₄ and N₂O emissions as well as diesel use in the composting process (differs to scenario level results), and the electricity efficiency in the

432 incineration process. The latter was important at process level because our incineration module included the avoided
433 production of marginal electricity. For the MRF process, there was a shift of the important data gaps from the recovery
434 efficiencies to the electricity use, because the recovery efficiencies only affect the subsequent remanufacturing and
435 avoided primary production. Finally, for the cardboard remanufacturing process, all the parameters differed >5%, i.e.
436 also natural gas in contrary to the scenario level results. This highlights the need for assessing the importance of data
437 gaps with regard to the entire system, and not just aggregated important data gaps at the process level, when modeling a
438 SWM scenario.

439 The threshold of 5% was a type of cut-off rule for contribution to impacts, which affected how many data gaps were
440 considered important to the LCA results. In a comparative LCA study, the threshold level should be decided taking into
441 account the difference between the scenarios, because the threshold should be smaller than the difference between the
442 scenarios' potential impacts. Furthermore, we evaluated the threshold relative to the net impacts, but it could also be
443 relative to the absolute impacts from a unit process.

444 **4.3 Selection of final surrogate values by evaluation of representativeness**

445 The final surrogate values were selected among the possible values in Table 4, and were those with the best match of
446 the temporal, geographical, and technological scope of the case study, being 2018-2020 (temporal scope), the US
447 (geographical scope), and US average (technological scope). Table 6 shows the final surrogate values. In some cases,
448 the reason for not selecting the other surrogate data in Table 4 was discrepancies with the technological scope of the
449 case study. For example, the material recovery efficiencies of the other MRF surrogate data represented mixed waste
450 stream, dual stream, and presorted stream MRFs (Pressley et al., 2015), whereas the case study targeted single stream
451 MRFs. Also, it was assumed that the composting facility was an aerated pile (open technology) receiving food and yard
452 waste, while the other surrogate data in Table 4 represented enclosed, home, or pure garden composting (Boldrin et al.,
453 2009). For the incineration process and waste composition data, the selection of final surrogate values was a matter of
454 representativeness as well as data reliability. The electricity efficiencies for 'state-of-the-art', 'average' or 'worse'
455 incineration plants are based on expert judgement (Hodge et al., 2016), while the selected final surrogate data are based
456 on actual measurements (US EPA, 2017). Similarly, the waste composition from SCS Engineers (2014) are based partly
457 on site-specific data for the Wake County as well as literature data from Riber et al. (2009), which is considered more
458 valid than the direct and scaled proxies that we assumed for the waste composition. Finally, in the selection of the final
459 surrogate values for the cardboard remanufacturing process, we prioritized data that were generated to represent
460 cardboard remanufacturing in the USA, despite the relatively outdated data (from 1990-1992).

461 **Table 2** Final surrogate values selected to fill the important data gaps in the case study

Process	Parameter	Final surrogate values	Temporal coverage	Geographical coverage	Technological coverage
Composting	CH ₄ emission	g/h:0.8-2.5 (average 1.7)	2000-2020	No specific area / generic	Open technologies
Incineration	Electricity efficiency	j: 17.2±2.7	2016	USA	Average of 58 plants
Material recycling facility	Recovery efficiency	a: 100 (cardboard), 99 (paper), 97 (Al), 98 (Fe), 90 (LDPE), 98 (HDPE, PET), 95 (glass)	2014	USA	Single stream
Waste generation	Paper, plastic, and metal	k: fractional composition	2008	Wake County, USA	Household waste
Cardboard remanufacturing	Electricity use	e: 0.589	1990-1992	USA	Secondary cardboard, average of unknown technology differences
	CO ₂ emission	e: 1.04	1990-1992	USA	

462 a: (Pressley et al., 2015), e: (RTI International, 2003), g: (Levis and Barlaz, 2013), h: (Boldrin et al., 2009), j: (US EPA,
463 2017), k: (Riber et al., 2009)

464 **5 Conclusions**

465 In this study, we suggested a method for systematically estimating system and process completeness, identification of
466 missing flows (data gaps), and application of surrogate values to fill the data gaps. The study targeted foreground
467 process data and used a solid waste management (SWM) scenario as case study. The expected input and output flows in
468 a waste incineration model were identified based on legislative documents and expert judgement, after which process
469 completeness scores were calculated and missing flows identified. The completeness score for the material inputs to
470 waste incineration was 78%, and the missing flows were auxiliary fuels and precipitation chemicals. The completeness
471 score for air emissions ranged from 38% and 50%, with and without expert judgement. If only greenhouse gases were
472 relevant (CO₂, CH₄, and N₂O), the completeness score increased from 38% or 50% to 67%. Further, when impact-based
473 weighting factors were applied the score increased to 94%, which provided a better reflection of the actual
474 completeness of the model concerning the coverage of the global warming potential. Thus, the evaluation of
475 completeness should consider the relevance and importance of flows, depending on the included life cycle impact
476 methods and the weighting of different flows, respectively. To illustrate the use of approaches and surrogate data to fill
477 data gaps, data gaps were selected for 16 different parameters in five SWM processes. The global warming potential
478 was used as the metric to compare the results from the use of surrogate data, and from leaving the gap, to identify the
479 important data gaps that should be filled by representative surrogates. The important data gaps were the CH₄ emission
480 factor in the composting process; electricity efficiency of incineration; recovery efficiencies at the MRF; electricity use
481 and CO₂ emissions in remanufacturing; and composition of the plastic, metal, and paper fraction in the household

482 waste. For these parameters, leaving the gap would change the LCA results >5%. For the other parameters, even the use
 483 of min-max surrogates led to relatively small changes in the results, therefore lower quality surrogate values are
 484 sufficient. It is recommended that practitioners follow the suggested method for a more systematic identification of
 485 missing flows and application of surrogate values in the life cycle inventories process modeling.

486 **References**

- 487 Astrup, T., Møller, J., Fruergaard, T., 2009. Incineration and co-combustion of waste: accounting of greenhouse gases
 488 and global warming contributions. *Waste Manag. Res.* 27, 789–799. doi:10.1177/0734242x09348529
- 489 Astrup, T.F., Tonini, D., Turconi, R., Boldrin, A., 2014. Life cycle assessment of thermal Waste-to-Energy technologies:
 490 Review and recommendations. *Waste Manag.* 37, 104–115. doi:10.1016/j.wasman.2014.06.011
- 491 Bisinella, V., Götze, R., Conradsen, K., Damgaard, A., Christensen, T.H., Astrup, T.F., 2017. Importance of waste
 492 composition for Life Cycle Assessment of waste management solutions. *J. Clean. Prod.* 164, 1180–1191.
 493 doi:10.1016/j.jclepro.2017.07.013
- 494 Boldrin, A., Andersen, J.K.J.K., Møller, J., Christensen, T.H.T.H., Favoino, E., 2009. Composting and compost
 495 utilization: accounting of greenhouse gases and global warming contributions. *Waste Manag. Res.* 27, 800–812.
 496 doi:10.1177/0734242X09345275
- 497 Brogaard, L.K., Damgaard, A., Jensen, M.B., Barlaz, M., Christensen, T.H., 2014. Evaluation of life cycle inventory data
 498 for recycling systems. *Resour. Conserv. Recycl.* 87, 30–45. doi:10.1016/j.resconrec.2014.03.011
- 499 Burnley, S.J., 2007. A review of municipal solid waste composition in the United Kingdom. *Waste Manag.* 1274–1285.
- 500 Canals, L.M.I., Azapagic, A., Doka, G., Jefferies, D., King, H., Mutel, C., Nemecek, T., Roches, A., Sim, S., Stichnothe,
 501 H., Thoma, G., Williams, A., 2011. Approaches for addressing life cycle assessment data gaps for bio-based
 502 products. *J. Ind. Ecol.* 15, 707–725. doi:10.1111/j.1530-9290.2011.00369.x
- 503 Clavreul, J., Baumeister, H., Christensen, T.H., Damgaard, A., 2014. An environmental assessment system for
 504 environmental technologies. *Environ. Model. Softw.* 60, 18–30. doi:10.1016/j.envsoft.2014.06.007
- 505 Clavreul, J., Guyonnet, D., Tonini, D., Christensen, T.H., 2013. Stochastic and epistemic uncertainty propagation in LCA.
 506 *Int. J. Life Cycle Assess.* 18, 1393–1403. doi:10.1007/s11367-013-0572-6
- 507 Danish EPA, 2015. Bekendtgørelse om et register over udledning og overførsel af forurenende stoffer (PRTR). BEK nr.
 508 1172 af 13/10/2015 (Gældende).
- 509 Danish EPA, 2010. Bekendtgørelse om visse virksomheders afgivelse af miljøoplysninger (historisk).
- 510 Edelen, A., Ingwersen, W., 2016. Guidance on Data Quality Assessment for Life Cycle Inventory Data. US EPA,
 511 Cincinnati, Ohio, USA.
- 512 Edjabou, M.E., Bang Jensen, M., Götze, R., Pivnenko, K., Petersen, C., Scheutz, C., Astrup, T.F., 2014. Municipal solid
 513 waste composition: Sampling methodology, statistical analyses, and case study evaluation. *Waste Manag.* 36, 12–
 514 23.
- 515 European Commission, 2006. Vejledning for gennemførelse af det europæiske Pollutant Release and Transfer Register
 516 (PRTR).
- 517 European Parliament and Council, 2010. DIRECTIVE 2010/75/EU OF THE EUROPEAN PARLIAMENT AND OF
 518 THE COUNCIL of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
 519 (Recast). doi:10.3000/17252555.L_2010.334.eng
- 520 Fazio, S., Garraín, D., Mathieux, F., De la Rúa, C., Recchioni, M., Lechón, Y., 2015. Method applied to the background

521 analysis of energy data to be considered for the European Reference Life Cycle Database (ELCD). Springerplus 4.
522 doi:10.1186/s40064-015-0914-x

523 Funtowicz, S.O., Ravetz, J.R., 1990. Uncertainty and quality in science for policy, in: *Uncertainty and Quality in Science*
524 *for Policy*. Kluwer Academic Publishers, p. 229.

525 Garraín, D., Fazio, S., de la Rúa, C., Recchioni, M., Lechón, Y., Mathieux, F., 2015. Background qualitative analysis of
526 the European reference life cycle database (ELCD) energy datasets – part II: electricity datasets. Springerplus 4,
527 30. doi:10.1186/s40064-015-0812-2

528 Götze, R., Boldrin, A., Scheutz, C., Astrup, T.F., 2016. Physico-chemical characterisation of material fractions in
529 household waste: Overview of data in literature. *Waste Manag.* 49, 3–14. doi:10.1016/j.wasman.2016.01.008

530 Hauschild, M.Z., Goedkoop, M., Guinée, J., Heijungs, R., Huijbregts, M., Joliet, O., Margni, M., Schryver, A., Humbert,
531 S., Laurent, A., Sala, S., Pant, R., Guinée, J., Heijungs, R., Huijbregts, M., Joliet, O., Margni, M., De Schryver, A.,
532 Humbert, S., Laurent, A., Sala, S., Pant, R., Guinée, J., Heijungs, R., Huijbregts, M., Joliet, O., Margni, M.,
533 Schryver, A., Humbert, S., Laurent, A., Sala, S., Pant, R., 2012. Identifying best existing practice for
534 characterization modeling in life cycle impact assessment. *Int. J. Life Cycle Assess.* 18, 683–697.

535 Henriksen, T., Astrup, T.F., Damgaard, A., 2017. Linking Data Choices and Context Specificity in Life Cycle Assessment
536 of Waste Treatment Technologies: A Landfill Case Study. *J. Ind. Ecol.* 00, 1–11. doi:10.1111/jiec.12709

537 Hischier, R., Baitz, M., Bretz, R., Frischknecht, R., Jungbluth, N., Marheineke, T., Mckeown, P., Oele, M., Osset, P.,
538 Renner, I., Skone, T., Wessman, H., Beaufort, A.S.H. De, 2001. Guidelines for Consistent Reporting of Exchanges
539 from / to Nature within Life Cycle Inventories (LCI). *Int. J. Li* 6, 192–198. doi:10.1007/BF02979374

540 Hodge, K.L., Levis, J.W., DeCarolus, J.F., Barlaz, M.A., 2016. Systematic Evaluation of Industrial, Commercial, and
541 Institutional Food Waste Management Strategies in the United States. *Environ. Sci. Technol.* 50, 8444–8452.
542 doi:10.1021/acs.est.6b00893

543 Hodson, E.L., Martin, D., Prinn, R.G., 2010. The municipal solid waste landfill as a source of ozone-depleting substances
544 in the United States and United Kingdom. *Atmos. Chem. Phys.* 10.

545 Hoornweg, D., Bhada-Tata, P., 2012. Urban development series - Knowledge papers - Waste composition. World Bank,
546 Washington DC, USA.

547 Huijbregts, M.A.J., Norris, G., Bretz, R., Ciroth, A., Maurice, B., von Bahr, B., Weidema, B., Beaufort, A.S.H. De, 2001.
548 Framework for Modelling Data Uncertainty in Life Cycle Inventories. *Int. J.* 6, 127–132. doi:10.1007/BF02978728

549 ISO, 2006. ISO 14044 - Environmental management – Life cycle assessment – Requirements and guidelines. Geneva,
550 Switzerland.

551 JRC, 2010. ILCD Handbook - International Reference Life Cycle Data System - General guide for Life Cycle Assessment
552 - Detailed guidance, International Reference Life Cycle Data System (ILCD) Handbook. Ispra, Italy.
553 doi:10.2788/38479

554 Laner, D., Rechberger, H., Astrup, T., 2015. Applying Fuzzy and Probabilistic Uncertainty Concepts to the Material Flow
555 Analysis of Palladium in Austria. *J. Ind. Ecol.* 19, n/a-n/a. doi:10.1111/jiec.12235

556 Little, R.J., D'Aostino, R., Cohen, M.L., Dickersin, K., Emerson, S.S., Farrar, J.T., Frangakis, C., Hogan, J.W.,
557 Molenberghs, G., Murphy, S.A., Neaton, J.D., Rotnitzky, A., Scharfstein, D., Shih, W.J., Siegel, J.P., Stern, H.,
558 2012. The prevention and treatment of missing data in clinical trials. *N. Engl. J. Med.* 1355–1360.

559 Majeau-Bettez, G., Strømman, A.H., Hertwich, E.G., 2011. Evaluation of process- and Input-Output-based Life Cycle
560 Inventory Databases with Regards to Truncation and Aggregation Issues. *Environ. Sci. Technol.* 45, 10170–10177.
561 doi:10.1021/es201308x

562 Moberg, A., Borggren, C., Ambell, C., Finnveden, G., Guldbrandsson, F., Bondesson, A., Malmödin, J., Bergmark, P.,
563 2014. Simplifying a life cycle assessment of a mobile phone. *Int. J. Life Cycle Assess.* 19, 979–993. doi:DOI
564 10.1007/s11367-014-0721-6

565 Moreau, V., Bage, G., Marcotte, D., Samson, R., 2012. Statistical estimation of missing data in life cycle inventory: An
566 application to hydroelectric power plants. *J. Clean. Prod.* 37, 335–341. doi:10.1016/j.jclepro.2012.07.036

567 Pressley, P.N., Levis, J.W., Damgaard, A., Barlaz, M.A., DeCarolis, J.F., 2015. Analysis of material recovery facilities
568 for use in life-cycle assessment. *Waste Manag.* 35, 307–317. doi:10.1016/j.wasman.2014.09.012

569 Riber, C., Petersen, C., Christensen, T.H., 2009. Chemical composition of material fractions in Danish household waste.
570 *Waste Manag.* 29, 1251–1257. doi:10.1016/j.wasman.2008.09.013

571 RTI International, 2003. Life-Cycle Inventory Data Sets for Material Production of Aluminium, Glass, Paper, Plastic, and
572 Steel in North America. Research Triangle Park, North Carolina, USA.

573 SCS Engineers, 2014. Wake County, North Carolina. Waste Characterization Study: Summary of Results. Wake County,
574 North Carolina, USA.

575 Steinmann, Z.J.N., Venkatesh, A., Hauck, M., Schipper, A.M., Karuppiah, R., Laurenzi, I.J., Huijbregts, M.A.J., 2014.
576 How to address data gaps in life cycle inventories: A case study on estimating CO₂ emissions from coal-fired
577 electricity plants on a global scale. *Environ. Sci. Technol.* 48, 5282–5289. doi:10.1021/es500757p

578 Subramanian, V., Golden, J.S., 2016. Patching Life Cycle Inventory (LCI) data gaps through expert elicitation: Case
579 study of laundry detergents. *J. Clean. Prod.* 115, 354–361. doi:10.1016/j.jclepro.2015.11.098

580 US EPA, 2018. Inventory of U.S. Greenhouse Gas Emissions and Sinks: 1990-2016. US EPA, USA.

581 US EPA, 2017. eGRID2014 Data File v2 (Version 2.0) [WWW Document]. URL [https://www.epa.gov/energy/emissions-](https://www.epa.gov/energy/emissions-generation-resource-integrated-database-egrid)
582 [generation-resource-integrated-database-egrid](https://www.epa.gov/energy/emissions-generation-resource-integrated-database-egrid) (accessed 5.21.18).

583 US EPA, 2016. Advancing Sustainable Materials Management: 2014 Fact Sheet - Assessing Trends in Material
584 Generation, Recycling, Composting, Combustion with Energy Recovery and Landfilling in the United States. US
585 EPA, USA.

586 US EPA, 2006. Part II - 40 CFR Part 60 - Standards of Performance for New Stationary Sources and Emission Guidelines
587 for Existing Sources: Large Municipal Waste Combustors; Final Rule.

588 van den Berg, N.W., Huppes, G., Lindeijer, E., Ven, B.L. Van Der, Wrisberg, N.M., 1999. Quality Assessment for LCA.

589 Weidema, B.P., Bauer, C., Hirschier, R., Mutel, C., Nemecek, T., Reinhard, J., Vadenbo, C.O., Wenet, G., 2013. Overview
590 and methodology. Data quality guideline for the ecoinvent database version 3. St. Gallen, Switzerland.

591 Yoshida, H., Clavreul, J., Scheutz, C., Christensen, T.H., 2014. Influence of data collection schemes on the Life Cycle
592 Assessment of a municipal wastewater treatment plant. *Water Res.* 56, 292–303. doi:10.1016/j.watres.2014.03.014

593 Yoshida, H., Nielsen, M.P., Scheutz, C., Jensen, L.S., Bruun, S., Christensen, T.H., 2016. Long-Term Emission Factors
594 for Land Application of Treated Organic Municipal Waste. *Environ. Model. Assess.* 21, 111–124.
595 doi:10.1007/s10666-015-9471-5

596 Zhou, X., Zhou, C., Liu, D., Ding, X., 2014. Applied Missing Data Analysis in the Health Sciences: Chapter 1. John
597 Wiley and Sons Inc., Hoboken, New Jersey.