

Non-invasive estimation of intravascular pressure changes using vector velocity ultrasound (us)

Olesen, Jacob Bjerring; Jensen, Jørgen Arendt; Villagomez-Hoyos, Carlos Armando

Publication date: 2018

Document Version Publisher's PDF, also known as Version of record

Link back to DTU Orbit

Citation (APA): Olesen, J. B., Jensen, J. A., & Villagomez-Hoyos, C. A. (2018). Non-invasive estimation of intravascular pressure changes using vector velocity ultrasound (us). (Patent No. *EP3273863*). European Patent Office.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

(19)





(11) **EP 3 273 863 B1**

(12)

EUROPEAN PATENT SPECIFICATION

- (45) Date of publication and mention of the grant of the patent:26.12.2018 Bulletin 2018/52
- (21) Application number: 15742388.0
- (22) Date of filing: 04.06.2015

(51) Int Cl.: A61B 8/04 ^(2006.01) A61B 8/08 ^(2006.01) G01S 15/89 ^(2006.01) G01F 1/66 ^(2006.01)

A61B 8/06 ^(2006.01) A61B 5/021 ^(2006.01) G01N 29/02 ^(2006.01)

- (86) International application number: PCT/IB2015/054246
- (87) International publication number: WO 2016/139515 (09.09.2016 Gazette 2016/36)

(54) NON-INVASIVE ESTIMATION OF INTRAVASCULAR PRESSURE CHANGES USING VECTOR VELOCITY ULTRASOUND (US)

NICHTINVASIVE SCHÄTZUNG VON INTRAVASKULÄREN DRUCKÄNDERUNGEN MIT VEKTORGESCHWINDIGKEITSULTRASCHALL

ESTIMATION NON-INVASIVE DE VARIATIONS DE PRESSION INTRAVASCULAIRE PAR ULTRASONS (US) DÉTERMINANT DES VECTEURS DE VITESSE

- (84) Designated Contracting States: AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
- (30) Priority: 02.03.2015 US 201562126972 P
- (43) Date of publication of application: 31.01.2018 Bulletin 2018/05
- (73) Proprietor: B-K Medical ApS 2730 Herlev (DK)
- (72) Inventors:
 - OLESEN, Jacob
 2300 Copenhagen S. (DK)
 - JENSEN, Jorgen Arendt 2970 Horsholm (DK)
 - VILLAGOMEZ-HOYOS, Carlos Armando 2730 Herlev (DK)
- (74) Representative: Gevers Patents Intellectual Property House Holidaystraat 5 1831 Diegem (BE)

- (56) References cited: EP-A1- 2 769 677
 - OLESEN JACOB BJERRING ET AL: "Non-invasive estimation of pressure gradients in pulsatile flow using ultrasound", 2014 IEEE INTERNATIONAL ULTRASONICS SYMPOSIUM, IEEE, 3 September 2014 (2014-09-03), pages 2257-2260, XP032667140, DOI: 10.1109/ULTSYM.2014.0562 [retrieved on 2014-10-20]
 - PEDRIZZETTI GIANNI ET AL: "Left Ventricular Fluid Mechanics: The Long Way from Theoretical Models to Clinical Applications", ANNALS OF BIOMEDICAL ENGINEERING, PERGAMON PRESS, OXFORD, GB, vol. 43, no. 1, 4 September 2014 (2014-09-04), pages 26-40, XP035422499, ISSN: 0090-6964, DOI:

10.1007/S10439-014-1101-X [retrieved on 2014-09-04]

• JACOB BJERRING OLESEN ET AL: "Noninvasive estimation of 2-D pressure gradients in steady flow using ultrasound", IEEE TRANSACTIONS ON ULTRASONICS, FERROELECTRICS AND FREQUENCY CONTROL, vol. 61, no. 8, 2 August 2014 (2014-08-02), pages 1409-1418, XP055224085, US ISSN: 0885-3010, DOI: 10.1109/TUFFC.2014.3050

3 273 863 B1 Ч

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

TECHNICAL FIELD

⁵ **[0001]** The following generally relates to ultrasound imaging and more particularly to non-invasively estimating intravascular pressure changes with velocity vector ultrasound (US).

BACKGROUND

- ¹⁰ **[0002]** Abnormal changes in intravascular blood pressure have been an indication of a diseased vessel. The literature indicates that measured pressure variations have been used clinically as a diagnostic marker in assessing the physio-logical state of a cardiovascular region. Intravascular pressure can be determined by inserting pressure sensing wires or catheters to the femoral artery and threading them to the region of interest. Such a procedure is invasive and has required the use of ionizing radiation for guidance of the pressure sensory device. Unfortunately, invasive procedures
- ¹⁵ leave the patient susceptible to infection, bleeding, etc., and ionizing radiation can damage or kill cells. Furthermore, the literature has indicated that the accuracy of using catheters is greatly dependent on the physical size and shape of the catheter.

[0003] A less invasive approach estimates local pressure changes using microbubbles. This approach relies on injecting gas-filled bubbles into the circulatory system to measure the frequency shift that occurred in the scattered spectrum as

- ²⁰ ultrasonic waves were applied. Unfortunately, this approach requires the injection of microbubbles. A non-invasive approach is based on Doppler ultrasound. This approach includes analyzing audio signals of the frequency shifts received from the mitral jet, which reveals the peak systolic velocity. From this, local pressure gradients are calculated using an orifice equation. This approach is reliant on a single velocity estimate. Unfortunately, this renders the approach sensitive to hemodynamic factors unrelated to the constricted vessel's effect on the peak velocity, e.g. abnormal cardiac output.
 ²⁵ This approach has been considered in the literature as unreliable.
 - This approach has been considered in the literature as unreliable.
 [0004] In view of at least the above, there is an unresolved need for another approach for measuring intravascular blood pressure.

[0005] Jacob Bjerring Olesen et al., in their paper "Non-invasive estimation of pressure gradients in pulsatile flow using ultrasound" (2014 IEEE INTERNATIONAL ULTRASONICS SYMPOSIUM, IEEE, 3 September 2014, pages 2257 to

30 2260), describes how pressure gradients in a pulsatile flow environment can be measured non-invasively using ultrasound to an accuracy of more than 85% when considering three cardiac cycles. Navier-Stokes equations for incompressible fluids are used to calculate the pressure gradients.

[0006] In the article entitled "Left Ventricular Fluid Mechanics: The Long Way from Theoretical Models to Clinical Applications" by Gianni Pedrizzetti et al. (ANNALS OF BIOMEDICAL ENGINEERING, PERGAMON PRESS, OXFORD,

- ³⁵ GB, Vol. 43, No. 1, 4 September 2014, pages 26 to 40), the flow inside the left ventricle is characterized by the formation of vortices which accompany blood from the mitral inlet to the aortic outlet. Numerical simulations are proposed which provide information on the physical phenomena involved in left ventricular fluid dynamics, such as, intraventricular flow in different cardiovascular states.
- [0007] Jacob Bjerring Olesen et al. also describes a noninvasive method for estimating pressure gradients from ultrasound velocity data in "Noninvasive estimation of2-D pressure gradients in steady flow using ultrasound" (IEEE TRANSACTIONS ON ULTRASONICS, FERROELECTRICS AND FREQUENCY CONTROL, Vol. 61, No. 8, 1 August 2014, pages 1409 to 1418). Scans of a carotid bifurcation phantom were obtained using a linear transducer connected to a scanner, and, the results from the estimator were compared to a model of the same carotid bifurcation phantom derived using magnetic resonance imaging.
- 45 [0008] EP-A-2769677 discloses an ultrasound imaging method for obtaining diagnostic information of a fluid contained in a test subject using echo signals. Velocity information is obtained from the velocity distribution of the fluid. A flow velocity distribution acquisition component detects fluid flow in the vicinity of tissue from the echo signals and a velocity determination component extracts velocity information. The velocity determination component sets a model of the objective fluid flow, and determines a measured velocity distribution consistent with velocity distribution estimated from the model.
- model

SUMMARY

[0009] Aspects of the application address the above matters, and others.

⁵⁵ **[0010]** In one aspect, a method for determining pressure gradients with ultrasound data includes acquiring ultrasound data of a vessel and generating a velocity vector profile for flow in the vessel with the ultrasound data. The method further includes computing an acceleration with the velocity vector profile. The acceleration includes at least a temporal acceleration, and computing the temporal acceleration includes transforming the velocity vector profile from a time

domain to a frequency domain, selecting a sub-set of the frequency components that satisfy predetermined energy criteria, processing the selected sub-set by differentiating the selected sub-set, and processing the selected sub-set by differentiating the selected sub-set thereby reducing noise from the velocity vector profile and determining the temporal acceleration from the noise-reduced velocity data. The method further includes determining the pressure gradients with

- the computed acceleration. The method further includes displaying an ultrasound image of the vessel with indicia indicative of the pressure gradients superimposed thereover.
 [0011] In another aspect, an apparatus for determining pressure gradients with ultrasound data which includes a velocity estimator that processes ultrasound image data acquired by an ultrasound imaging system and generates
- velocity vector fields based thereon. The apparatus further includes a temporal acceleration processor that processes the velocity vector fields and generates a temporal acceleration, wherein the temporal acceleration processor filters the velocity vector fields while determining the temporal acceleration by transforming the velocity vector profile from a time domain to a frequency domain, selecting a sub-set of the frequency components that satisfy predetermined energy criteria, processing the selected sub-set by differentiating the selected sub-set and transforming the differentiated selected sub-set back to the time domain. The apparatus further includes a spatial acceleration processor that processes the
- velocity vector fields and generates a spatial acceleration. The apparatus further includes a pressure change estimator that estimates pressure gradients for the ultrasound data based on a model and the temporal and spatial accelerations. The apparatus further includes a display configured to display ultrasound image data and the pressure gradients estimates.
- [0012] In another, not claimed In aspect a non-transitory computer readable storage medium is encoded with computer executable instructions which when executed by a processor of the computer causes the processor to: determine a spatial acceleration based on velocity vector fields, transform the velocity vector fields to the frequency domain, producing a sum of sinusoids, differentiate a sub-set of the sinusoids satisfying at least one of a predetermined energy of interest or a predetermine frequency range of interest, producing a sum of cosines, reconstruct the sum of cosines to determine a temporal acceleration, and determine a pressure change with the Navier-Stokes equation based on the spatial acceleration.
 - **[0013]** Those skilled in the art will recognize still other aspects of the present application upon reading and understanding the attached description.

BRIEF DESCRIPTION OF THE DRAWINGS

30

35

45

50

55

[0014] The application is illustrated by way of example and not limited by the figures of the accompanying drawings, in which like references indicate similar elements and in which:

Figure 1 schematically illustrates an example ultrasound imaging system with an intravascular pressure determiner;

Figure 2 schematically illustrates an example of the intravascular pressure determiner;

Figure 3 shows an example inlet profile;

Figure 4 shows an ideal number of sinusoids needed to reconstruct the profile in Figure 3;

- Figure 5 shows the approximated flow from the center of the constriction;
- Figure 6 show results of mapping pressure gradients derived from the velocity data;
- Figure 7 shows a plot of the temporal evolution of the pressure drop for the three measured cardiac cycles;
 Figure 8 shows the mean of three measured pressure profiles plotted together with a simulated pressure drop from an FE model;

Figure 9 illustrates a method, and

Figure 10 shows an example display of 2-D pressure changes through a vessel.

DETAILED DESCRIPTION

[0015] The following generally describes a non-invasive approach for estimating intravascular pressure changes from ultrasound imaging data. In one instance, the approach estimates pressure gradients from 2-D or 3-D vector velocity fields. Changes in pressure are then derived using a model based on, e.g., the Navier-Stokes and/or other equations.

[0016] Initially referring to Figure 1, an example ultrasound imaging system 100 is illustrated.

[0017] A transducer array 102 includes a plurality of transducer elements, which are configured to transmit ultrasound signals and receive echo signals. Examples of suitable one-dimensional (1-D) arrays include arrays with 8, 16, 32, 64, 96, 128, 512, etc. transducer elements. Other numbers of elements and/or dimensions (e.g., two-dimensional, or 2-D) are also contemplated herein. The array 102 can be linear, curved, and/or otherwise shaped. The transducer array 102 can be fully populated or sparse and/or a combination thereof.

[0018] Transmit circuitry 104 generates a set of pulses that are conveyed to the transducer array 102. The set of pulses actuates a corresponding set of the transducer elements of the transducer array 102, causing the elements to

transmit ultrasound signals into an examination or scan field of view. Receive circuitry 106 receives echoes generated in response to the transmitted ultrasound signals from the transducer 102. The echoes, generally, are a result of the interaction between the emitted ultrasound signals and the structure (e.g., flowing blood cells, organ cells, etc.) in the scan field of view.

- ⁵ **[0019]** A controller 108 controls the transmit circuitry 104 and/or receive circuitry 106. In one instance, the controller 108 controls the transmit circuitry 104 to emit waves (e.g., unfocused spherical, weakly focused, plane, etc.) from the aperture by placing virtual sources behind the transducer. A beamformer 112 processes the echoes and generates data at least for generating images and estimating velocity. In one non-limiting instance, this includes generating a sequence of focused, coherent echo samples along focused scanlines of a scanplane.
- ¹⁰ **[0020]** A velocity estimator 113 is configured to estimate 2-D and/or three-dimensional (3-D) vector velocity fields. For example, the velocity estimator 113 can be configured to estimate a 2-D in-plane vector velocity field $\overline{v(r,t)} = (v_x(t), v_z(t))$. The out-of-plane velocity $v_y(t)$ can be set to zero. Alternatively, the out-of-plane velocity $v_y(t)$ is also determined to estimate a 3-D vector velocity field.
- [0021] Examples of velocity estimators are described in Jensen et al., "Directional synthetic aperture flow imaging,"
 ¹⁵ IEEE Trans. Ultrason., Ferroelec., Freq. Contr., 51:1107-1118, 2004, Jensen et al., "Estimation of velocity vectors in synthetic aperture ultrasound imaging," IEEE Trans. Ultrason., Ferroelec., Freq. Contr., 25:1637-1644, 2006, and Jensen, "Vector velocity estimation using directional beam forming and cross-correlation," US 6,725,076 B1.

[0022] Other suitable velocity estimators can be based on Jensen, "A New Estimator for Vector Velocity Estimation," IEEE Trans. Ultrason., Ferroelec., Freq. Contr., 48(4):886-894, 2001, and Jensen, "Estimator for Vector Velocity," US

²⁰ 6,859,659 B1, the entirety of which is incorporated herein by reference, and Jensen, "Apparatus and method for determining movements and velocities of moving objects," US 6,148,224.
 [0023] An intravascular pressure estimator 114 is configured to process the velocity vector to estimate a change in

intravascular pressure. As described in greater detail below, in one instance this includes smoothing the velocity vector profile, computing a temporal acceleration term from the smoothed velocity vector data, and determining a pressure gradient based on the temporal acceleration term, a spatial acceleration term, and the Navier-Stokes equation. The

smoothing, in one instance, de-noises the velocity vector profile. Optionally, the intravascular pressure estimator 114 is further configured to determine pressure drops.

[0024] A scan converter 116 scan converts the scanlines for frames of data to generate data for display, for example, by converting the data to the coordinate system of the display. The scan converter 116 can employ analog and/or digital

- ³⁰ scan converting the data to the coordinate system of the display. The scan converter Pro can employ analog and/or digital scan converting techniques. A display 118 is configured to display an ultrasound image, an intravascular pressure, a change in intravascular pressure, a pressure drop, etc. The pressure can be visually displayed with indicia (e.g., alphanumeric, graphical, etc.).
- [0025] A user interface (UI) 110, which includes an input device (e.g., a button, a slider, a touch surface, etc.) and/or an output device (e.g., a visual and/or audible, etc.), provides an interface between the system 100 and a user of the system 100.

[0026] It is to be appreciated that the beamformer 112, the velocity estimator 113, the intravascular pressure estimator 114, and/or other components of the system 100 can be implemented via a processor (e.g., a microprocessor, central processing unit, a controller, etc.) executing one or more computer readable instructions encoded or embedded on a non-transitory computer readable storage medium such as physical memory. The processor can additionally or alter-

⁴⁰ natively execute a computer readable instruction carried by a carrier wave, a signal, or other transitory medium.
 [0027] Figure 2 illustrates an example of the intravascular pressure estimator 114.

[0028] The illustrated intravascular pressure estimator 114 includes a temporal acceleration processor 208. In this example, the temporal acceleration processor 208 approximates a temporal acceleration analytically by decomposing a measured flow profile into a series of sinusoids through a Fourier transform. These sinusoids oscillate at frequencies,

- ⁴⁵ such as those descriptive for the original profile. The temporal acceleration processor 208 identifies a sub-set of the sinusoids as sinusoids of interest. In one instance, the sub-set includes sinusoids that satisfy energy criterion of interest, e.g., a predetermined number of sinusoids with a highest energy, sinusoids with energy in a predetermined range, etc. In another instance, the sub-set includes sinusoids corresponding to a frequency below a cut-off frequency (e.g., 500 Hz, 1 kHz, etc.). In yet another instance, the sub-set is determined based on a combination of energy and frequency.
- Other criterion is also contemplated herein. **[0029]** The temporal acceleration processor 208 differentiates the selected sinusoids. In this example, the temporal acceleration processor 208 computes a first order derivative as shown in Equation 1:

55

25

Equation 1:

$$\frac{d\vec{v}_m(i,j,t)}{dt} = \sum_{p=1}^{N} |\vec{v}_p(i,j)| 2\pi \vec{f}_p(i,j) \sin\left(2\pi \vec{f}_p(i,j)t - \vec{\varphi}_p(i,j)\right)$$

where *N* represents a number of sinusoids used in reconstructing the flow profile, V_p and φ_p represents an amplitude and a phase of the frequency component f_p , (*i*,*j*) represents a position within the each velocity field, and m a direction (e.g., either axial z or lateral x). Taking the derivative computes the temporal acceleration as a sum of cosines. The temporal acceleration processor 208 reconstructs the sum of cosines, e.g., using a trigonometric function, to transform the data back into the time domain. Reconstructing the flow profile as such in connection with cardiac data is possible as the flow is periodic over the cardiac cycle.

- [0030] With this approach, the velocity profile at each position within the vector field is first transformed from the time domain to the frequency domain, e.g., through a Fourier transform to decompose the vector fields into the frequencies that make it up over a plurality of energy bins. A sub-set of the frequency components is then retained while others are discarded, ignored, etc. In one instance 4 to 12 frequency components, such as 6, 7, 8, 9, 10, etc. frequency components are retained. As discussed above, the selection can be based on energy, frequency, etc. such that a sub-set of the frequency bins are selected. An example where 8 frequency components or bins are selected is discussed below in
- 20 connection with Figure 4 herein. The derivative shifts the phase of the selected frequencies by 90 degrees to produce the temporal acceleration profile. This process has the effect of smoothing the original vector velocity estimates, e.g., by removing higher frequency components, which results in higher precision of pressure gradient estimates. The differentiated data is then transformed back to the time domain and further processed as described herein.
- [0031] The illustrated intravascular pressure estimator 114 further includes a spatial acceleration processor 210. In this example, the spatial acceleration processor 210 calculates a spatial acceleration using polynomial filtering of the measured velocity field. In one instance, the spatial acceleration processor 210 fits a second-order polynomial to a subset of adjacent data points by a linear least-squared approach and then calculates convolution coefficients from a least-squared model, which are used for finding the first- order derivatives. The spatial acceleration processor 210 calculates the axial and lateral derivatives discretely for each position in a scan plane at a given time *t*.
- ³⁰ **[0032]** In one instance, the spatial acceleration processor 210 calculates the axial and lateral derivatives through Equations 2 and 3:

Equation 2:

$$\frac{d\vec{v}_{m}(i,j,t)}{di} \approx \frac{1}{\Delta m} \sum_{p=i-h_{w}}^{i+h_{w}} \vec{v}_{m}(p,j,t) \vec{B}(p-(i-h_{w})+1),$$

and

Equation 3:

$$\frac{d\vec{v}_m(i,j,t)}{dj} \approx \frac{1}{\Delta m} \sum_{p=j-h_w}^{j+h_w} \vec{v}_m^T(p,i,t) \vec{B}(p-(j-h_w)+1),$$

35

40

45

5

where Δm represents a sampling interval of the velocity field in either the axial or lateral direction, p represents an index, \vec{B} represents convolution coefficients, and \vec{v}_m^T represents the transpose of \vec{v}_m . The index number p can be found from

half a window size of the selected subset, which can be calculated by: $h_w = \frac{N_{set}+1}{2} - 1$, where N_{set} represents a number of samples in the subset. The convolution coefficients in \vec{B} depend solely on the order of the fitted polynomial and the size of the selected window, which can be found in look-up tables. The multiplication of \vec{v}_m and \vec{B} , in this example, is performed element by element.

[0033] The illustrated intravascular pressure estimator 114 further includes a pressure change estimator 202. The

pressure change estimator 202 is configured to estimate at least an intravascular pressure with the 2-D or 3-D vector velocity fields based on a model. Model storage 204 stores such a model. In the following example, the model is used to determine, from the 2-D vector velocity, in-plane pressure gradients, using the temporal and spatial acceleration (i.e., the temporal and spatial derivatives), as shown in Equations 4A or 4B:

5

10

20

35

45

55

Equation 4A:

$$\begin{bmatrix} \frac{\partial p}{\partial x} \\ \frac{\partial p}{\partial z} \end{bmatrix} = -\rho \begin{bmatrix} \frac{\partial v_x}{\partial t} + v_x \frac{\partial v_x}{\partial x} + v_z \frac{\partial v_z}{\partial z} \\ \frac{\partial v_z}{\partial t} + v_x \frac{\partial v_z}{\partial x} + v_z \frac{\partial v_z}{\partial z} \end{bmatrix}$$

15 and

Equation 4B:

$$\begin{bmatrix} \frac{\partial p}{\partial x} \\ \frac{\partial p}{\partial z} \end{bmatrix} = -\rho \begin{bmatrix} \frac{\partial v_x}{\partial t} + v_x \frac{\partial v_x}{\partial x} + v_z \frac{\partial v_x}{\partial z} \\ \frac{\partial v_z}{\partial t} + v_x \frac{\partial v_z}{\partial x} + v_z \frac{\partial v_z}{\partial z} \end{bmatrix} + \mu \begin{bmatrix} \frac{\partial^2 v_x}{\partial x^2} + \frac{\partial^2 v_x}{\partial z^2} \\ \frac{\partial^2 v_z}{\partial x^2} + \frac{\partial^2 v_z}{\partial z^2} \end{bmatrix} + \begin{bmatrix} \rho g_x \\ \rho g_z \end{bmatrix}$$

- 25 where p represents the pressure, x represents the axial direction, z represents the lateral direction, t represents time, v_x represents the axial velocity component, v_z represents the lateral velocity component, ρ and μ represents density and viscosity, respectively, and g represents the gravitational force. In general, Equation 4B additionally includes viscous forces and the gravity terms. For Equations 4A and 4B, the out-of-plane velocity v_{ν} and changes in this direction are zero. In a variation, the out-of-plane velocity v_v can be included in Equations 4A or 4B and/or otherwise considered in 30 the determination of the pressure gradients.
 - [0034] Such a model can be based on the Navier-Stokes equation, which is shown in Equation 5:

Equation 5:

$$\rho\left[\frac{\partial \vec{v}}{\partial t} + \vec{v} \cdot \nabla \vec{v}\right] = -\nabla p + \rho \vec{g} + \mu \nabla^2 \vec{v},$$

where *p* represents a density of the fluid, \vec{v} represents a velocity vector, $\frac{\partial \vec{v}}{\partial t}$ represents a partial derivative of the velocity 40

vector as a function of time, ∇ represents a spatial differential operator $\left(\frac{\partial}{\partial x}, \frac{\partial}{\partial y}, \frac{\partial}{\partial z}\right)$, $\vec{v} \cdot \nabla \vec{v}$ represents convective fluid acceleration, ∇p represents a pressure gradient, \vec{g} represents a gravitational force, $\nabla^2 \vec{v}$ a Laplacian of the velocity field, and $\mu \nabla^2 \vec{v}$ represents a viscous drag caused by the viscosity of the fluid.

[0035] Equation 5 describes the development of a fluid's velocity field $(\vec{v}(\vec{r},t) = v_x(t), v_v(t), v_z(t))$ by relating forces acting on an incompressible volume to acceleration and density at a position \vec{r} and a time t. From Equation 5, the pressure gradient ∇p can be determined if the three spatial vector components of \vec{v} are known. The gravitational term, in one instance, can be ignored, for example, as a patient undergoing a scan (e.g., ultrasound) is placed in a supine position. 50 The viscous forces, in one instance, can be ignored, for example, when studying blood flow in larger arteries, for example, due to the forces small effect on the overall movement of flow.

[0036] A pressure drop determiner 206 determines one or more pressure drops based on the pressure gradients. In another embodiment, the pressure drop determiner 206 is omitted. Figure 6 below shows an image with pressure gradients (represented via the arrows) superimposed over a vessel in an image. In one instance, a user can identify (via a mouse, etc.) points of interest in the vessel, e.g., behind, within, and before the constriction. The pressure drop

determiner 206 determines a pressure drop based on these three points. In another example using Figure 6, a user can draw a line along the long axis of the vessel running through the constriction. A pressure drop can be determined for a

particular moment in time by integrating the pressure gradients along the line in the image. This can be repeated for multiple time points based on each corresponding image. In yet another example, pressure drops can be calculated for a plurality of such lines each time point.

[0037] The one or more pressure drops can be graphically and/or alpha-numerically presented or displayed via the

- ⁵ display 118. For example, the three points and the pressure drop can be superimposed over the image. In another example, the pressure drops for the line can be shown as a plot as a function of time as shown below in Figure 7. In another example, the pressure drops for the plurality of lines can be shown as a pressure map, e.g., similar to weather map. Figure 10 shows an example display of 2-D pressure changes through a vessel. The pressure values are given in reference to the entrance of the vessel (left side), which is set to zero. In this case, pressure is derived using EQUATION 6A on multiple streamlines following the vector velocity field.
- 6A on multiple streamlines following the vector velocity field.
 [0038] The following describes a non-limiting example that compares an accuracy of the pressure changes using the approach described herein with a simulation. The simulation includes a finite element (FE) model. The geometry of the model is built from segmented MRI data of the flow phantom obtained using a 3-T scanner. The flow parameters of the simulation model are set to mimic actual flow conditions in the experimental set-up. Figure 3 shows an example inlet
- ¹⁵ profile equivalent to a one measured during experimental settings, which is applied to the entrance of the model. The viscosity (e.g., 4.1e⁻³ pascal-second, or Pa·s) and density (1,030 kilogram per cubic meter, or kg/m³ are assigned values that match the properties of the blood-mimicking fluid. An example of such a model is discussed in Olesen et el., "Noninvasive estimation of 2-D pressure gradients in steady flow using ultrasound," IEEE Transactions on Ultrasonics, Ferroelectrics and Frequency Control, vol. 61, no. 8, pp. 1409-1418.
- 20 [0039] The experimental set-up and equipment are described next. Vector velocity data are acquired on a flow phantom mimicking the carotid bifurcation having a 70% constriction of the internal branch. Measurements are acquired using a linear array transducer such as the BK8670, a product of BK Medical, DK. The linear array transducer is connected to an experimental research scanner. A three-cycle pulse with a center frequency of 7 MHz is emitted at 12 kHz to a depth of 3 cm. Eight low-resolution images are summed for each high resolution image producing an effective frame-rate of
- ²⁵ 1,500 Hz. The ultrasound data can be processed on or off-line. The carotid phantom is connected to a flow system capable of generating customized flow waveforms.

[0040] The local acceleration is approximated by decomposing the measured waveform into a number of sinusoids each oscillating at different frequencies. This is done to express the derivatives for calculating the pressure gradients analytically. The number of sinusoids needed to make a realistic reconstruction of the original flow waveform depends

- 30 on the complexity of the profile and the amount of noise present in the signal. Figure 4 shows an ideal number of sinusoids needed to reconstruct the profile in Figure 3 as a function of an increasing noise level in the measured signal. The system's inlet waveform can be more than 98% recovered from the sum of eight sinusoids, despite having a 20 dB level of white Gaussian noise. The approximated flow from the center of the constriction is plotted in Figure 5.
- [0041] Maps of pressure gradients are derived from the velocity data, and a result is shown in Figure 6. The estimated gradients are plotted during the peak systolic phase of the cardiac cycle. Figure 6 is calculated using the estimator described in Equation 4A. The arrows and their background gray levels indicate a direction and a magnitude of the gradients, respectively. Figure 6 shows arrows that tend to point away from the center of the constriction, indicating that a low pressure is present here. The spatial derivatives used in Figure 6 are calculated using window sizes of 31 (3 mm) and 11 (2 mm) data points for the axial and lateral direction, respectively.
- ⁴⁰ **[0042]** One way of displaying a pressure drop across a region is by using a streamline representation. For instance, adding vector components, v_x and v_z , which underlie the streamline, yields the velocity component tangent to the streamline, v_s . Re-writing the 2-D in-plane velocity components to a single component parallel to the streamline, means that pressure gradients along the line, can be derived using a 1-D representation of Equation 5, as shown in Equations 6A or 6B:

45

Equation 6A:

$$\frac{\partial p}{\partial s} = -\rho \left[\frac{\partial v_s}{\partial t} + v_s \frac{\partial v_s}{\partial s} \right].$$

50

and

Equation 6B:

$$\frac{\partial p}{\partial s} = -\rho \left[\frac{\partial v_s}{\partial t} + v_s \frac{\partial v_s}{\partial s} \right] + \mu \left[\frac{\partial^2 v_{xs}}{\partial s^2} \right]$$

55

In general, Equation 6B additionally includes viscous forces and the gravity terms.

[0043] The total pressure drop that exists across the streamline is estimated as a function of time. The spatial derivatives, which go into the estimator, are calculated using polynomial filtering. A second-order polynomial is fitted to a subset of 71 adjacent velocity estimates covering a 1.4 mm line of the 10.7 mm long streamline. The window size and the order

- of the filter is selected to minimize the effect of estimator noise and under the assumption that flow within a 1.4 mm region can be approximated by a second-order polynomial. Each individual gradient gives an indication of how pressure at that particular position changes relative to neighboring pressure values. Summing the discrete contributions from each estimate along the line, the relative drop in pressure that exists between the two ends of the streamline is obtained. [0044] The temporal evolution of the pressure drop for the three measured cardiac cycles is plotted in Figure 7. The
- figure shows the greatest pressure drop in the systolic phase of the cardiac cycle, and that the drop peaks just before the flow reaches its maximum velocity. The average standard deviation across the pulse is found to 4% in reference to the maximum pressure of 7 Pa. The mean of the three measured pressure profiles is plotted together with the simulated pressure drop from the FE model in Figure 8. A normalized root-mean-square error of 10% is found between the estimated data and the reference model.
- 15 [0045] In this example, non-invasive measurement of pressure changes has been calculated from vector velocity data. The intravascular pressure drop across the constricted phantom varied depending on when in the cardiac cycle it was measured. The largest drop was estimated just prior to the peak systolic phase, reaching 7 Pa with a standard deviation of 4%. A normalized error of 10% was seen between the estimated pressure and the results from the FE model. For this example, the approached described herein employs vector velocity data acquired to a depth of 3 cm using directional and the transformation of 4 cm using directional
- 20 synthetic aperture flow imaging, producing 1,500 velocity frames a second. [0046] Such techniques otherwise allow for averaging across estimates without compromising the peak of the profile. Averaging is beneficial as it essentially performs a low-pass filtering of the estimates, thus, avoiding the higher frequency content, which usually is associated with noise. Noise cancellation can be used for deriving proper derivatives, and can become important when moving into higher order derivatives. The effect of viscosity, which is related to second-order
- ²⁵ differentiation, gets introduced when studying flow in smaller vessel where the influence from the wall is more prominent. Therefore, pressure estimation by the Navier-Stokes equations should for those regions take the viscous forces into account.

[0047] The literature indicated a 24% overestimation of the peak systolic pressure from commonly employed catheters. The example herein showed results within 10% of the reference model and with a standard deviation of 4%, indicating

30 that the approach described herein obtains pressure measurements that are more reliable than an invasive catheter. Superseding catheters in the clinic may eliminate the need for such invasive procedures and their appertaining X-ray radiation for guidance of the catheter.

[0048] Figure 9 illustrates a method.

50

[0049] It is to be understood that the following acts are provided for explanatory purposes and are not limiting. As

³⁵ such, one or more of the acts may be omitted, one or more acts may be added, one or more acts may occur in a different order (including simultaneously with another act), etc.

[0050] At 1402, ultrasound imaging data is acquired. It is to be appreciated that ultrasound imaging data can be acquired in near real-time and thus provides higher timer resolution data for superior filter, e.g., relative to MR and/or other imaging modalities, where data is averaged data over time due to slower acquisition capabilities.

40 **[0051]** At 1404, vector velocity fields are determined from the acquired ultrasound imaging data. As described herein, this includes 2-D and/or 3-D velocity vector fields determined using various approaches such a transverse oscillation, plane wave, synthetic aperture, etc.

[0052] At 1406, temporal and spatial acceleration components are determined based on the velocity vector fields, as described herein and/or otherwise.

⁴⁵ **[0053]** At 1408, pressure gradients are estimated from the temporal and spatial acceleration components, as described herein and/or otherwise.

[0054] At 1410, the pressure gradients are presented, as described herein and/or otherwise.

[0055] At 1412, one or more pressure drops are determined based on the pressure gradients, as described herein and/or otherwise.

[0056] At 1414, the pressure drops are presented, as described herein and/or otherwise.

[0057] In another embodiment, acts 1410 and 1412 are omitted.

[0058] The pressure gradients and/or drops can be conveyed to another device. The other device can be a display, hardware memory, another device, etc. In one instance, a pressure gradient and/or drop that crosses a predetermined threshold level cause the other device to perform an act. For example, the drop may cause the other device to invoke an alarm, transmit a notification to a smartphone, page, or the like, sense another physiologic parameter, etc.

⁵⁵ an alarm, transmit a notification to a smartphone, page, or the like, sense another physiologic parameter, etc. [0059] The methods described herein may be implemented via one or more processors executing one or more computer readable instructions encoded or embodied on computer readable storage medium such as physical memory which causes the one or more processors to carry out the various acts and/or other functions and/or acts. Additionally or

alternatively, the one or more processors can execute instructions carried by transitory medium such as a signal or carrier wave.

[0060] The application has been described with reference to various embodiments. Modifications and alterations will occur to others upon reading the application. It is intended that the invention be construed as including all such modifications and alterations, including insofar as they come within the scope of the appended claims.

Claims

5

15

20

35

40

10 **1.** A method for determining pressure gradients with ultrasound data, the method comprising:

acquiring (1402) ultrasound data of a vessel; generating (1404) a velocity vector profile for flow in the vessel with the ultrasound data; computing (1406) an acceleration with the velocity vector profile, wherein the acceleration includes at least a temporal acceleration, and computing the temporal acceleration includes:

transforming the velocity vector profile from a time domain to a frequency domain; selecting a sub-set of the frequency components that satisfy predetermined energy criteria; processing the selected sub-set by differentiating the selected sub-set; transforming the differentiated selected sub-set back to the time domain thereby reducing noise from the velocity vector profile; and

determining the temporal acceleration from the noise-reduced velocity data;

- determining (1408) the pressure gradients with the computed acceleration; and
 displaying (1414) an ultrasound image of the vessel with indicia indicative of the pressure gradients superimposed thereover.
 - 2. The method of claim 1, wherein the pressure gradients are generated using the Navier-Stokes equation.
- **30 3.** The method of claim 1 or 2, wherein the step of differentiating the selected sub-set includes differentiating selected sinusoids, using:

$$\frac{d\vec{v}_m(i,j,t)}{dt} = \sum_{p=1}^{N} |\vec{v}_p(i,j)| 2\pi \vec{f}_p(i,j) \sin\left(2\pi \vec{f}_p(i,j)t - \vec{\varphi}_p(i,j)\right)$$

where N represents a number of frequency components used in reconstructing a flow profile, V_p and φ_p represent an amplitude and a phase of the frequency component f_p , (i,j) represents a position within the each velocity field, and m represents an axial z or lateral x direction.

- 4. The method of claim 1, wherein the step of transforming of the differentiated selected sub-set back to the time domain includes employing a trigonometric function that reconstructs the data back into the time domain.
- **5.** The method of any one of claims 1 to 4, wherein the step of transforming the velocity vector profile to the frequency domain includes applying a Fourier transform to the velocity vector profile.
 - **6.** The method of any of one of claims 1 to 5, wherein the step of selecting the sub-set of the frequency components includes selecting only 4 to 16 of the frequency components.
- 50

55

- 7. The method of any one of claims 1 to 6, wherein the step of selecting the sub-set of the frequency components include selecting a predetermined number of sinusoids with a highest energy.
- 8. The method of any one of claims 1 to 6, wherein the step of selecting the sub-set of frequency components include selecting sinusoids with an energy in a predetermined range.
- 9. The method of any one of claims 1 to 8, wherein the acceleration further includes a spatial acceleration.

10. The method of any one of claims 1 to 8, wherein the step of determining the pressure drop includes:

receiving an identification of a plurality of points of interest on the ultrasound image, wherein the plurality of points of interest are respectively located behind a constriction of the vessel, within the constriction, and before the constriction;

determining a pressure drop based on the pressure gradients for the plurality of points of interest; visually identifying the plurality of points of interest on the displayed ultrasound image; and displaying the determined pressure drop.

¹⁰ **11.** The method of any one of claims 1 to 8, wherein determining the pressure drop includes:

receiving a signal identifying a set of pixels in the image for a line along a long axis of the vessel; determining a pressure drop by integrating over the pressure gradients corresponding to the identified set of pixels;

- repeating the acts of receiving and determining for each image frame; and visually presenting the pressure drops as a function of time.
 - **12.** The method of claim 11, further comprising:
- 20 repeating the acts of receiving, determining, repeating and presenting for a plurality of different lines along the long axis of the vessel each image frame; and visually presenting the pressure drops as a pressure map.
 - 13. The method of any one of claims 1 to 12, wherein the velocity vector profile is one of a 2-D or 3-D velocity vector profile.
- 25

5

15

- **14.** The method of any one of claims 1 to 13, further comprising: generating the velocity vector profile based on at least one of a transverse oscillation, a plan wave, or a synthetic aperture algorithm.
- **15.** An apparatus for determining pressure gradients with ultrasound data, the apparatus comprising:

a velocity estimator (113) that processes ultrasound image data acquired by an ultrasound imaging system and generates velocity vector fields based thereon;

- a temporal acceleration processor (208) that processes the velocity vector fields and generates a temporal acceleration, wherein the temporal acceleration processor filters the velocity vector fields while determining the temporal acceleration by transforming the velocity vector profile from a time domain to a frequency domain, selecting a sub-set of the frequency components that satisfy predetermined energy criteria, processing the selected sub-set by differentiating the selected sub-set and transforming the differentiated selected sub-set back to the time domain;
- ⁴⁰ a spatial acceleration processor (210) that processes the velocity vector fields and generates a spatial acceleration;

a pressure change estimator (202) that estimates pressure gradients for the ultrasound data based on a model and the temporal and spatial accelerations; and

a display configured to display ultrasound image data and the pressure gradients estimates.

45

Patentansprüche

- **1.** Verfahren zum Bestimmen von Druckgradienten mit Ultraschalldaten, wobei das Verfahren umfasst:
- 50

55

Erfassen (1402) von Ultraschalldaten eines Gefäßes;

Erzeugen (1404) eines Geschwindigkeitsvektorprofils für Strömung im Gefäß mit den Ultraschalldaten; Berechnen (1406) einer Beschleunigung mit dem Geschwindigkeitsvektorprofil, wobei die Beschleunigung mindestens eine zeitliche Beschleunigung einschließt, und das Berechnen der zeitlichen Beschleunigung einschließt:

Transformieren des Geschwindigkeitsvektorprofils von einer Zeitdomäne in eine Frequenzdomäne; Auswählen einer Untermenge der Frequenzkomponenten, die vorbestimmte Energiekriterien erfüllen;

Verarbeiten der ausgewählten Untermenge durch Differenzieren der ausgewählten Untermenge; Rücktransformieren der differenzierten ausgewählten Untermenge in die Zeitdomäne, wodurch Rauschen vom Geschwindigkeitsvektorprofil reduziert wird; und Bestimmen der zeitlichen Beschleunigung von den rauschreduzierten Geschwindigkeitsdaten;

- Bestimmen (1408) der Druckgradienten mit der berechneten Beschleunigung; und Anzeigen (1414) eines Ultraschallbildes des Gefäßes mit auf den Druckgradienten hinweisenden Markierungen darüber überlagert.
- Verfahren nach Anspruch 1, wobei die Druckgradienten unter Verwendung der Navier-Stokes-Gleichung erzeugt
 werden.
 - 3. Verfahren nach Anspruch 1 oder 2, wobei der Schritt des Differenzierens der ausgewählten Untermenge ein Differenzieren ausgewählter Sinuskurven einschließt, unter Verwendung von:
- 15

$$\frac{d\vec{v}_m(i,j,t)}{dt} = \sum_{p=1}^{N} |\vec{v}_p(i,j)| 2\pi \vec{f}_p(i,j) \sin\left(2\pi \vec{f}_p(i,j)t - \vec{\varphi}_p(i,j)\right)$$

- ²⁰ wo N eine Anzahl von Frequenzkomponenten darstellt, die bei einer Rekonstruktion eines Strömungsprofils verwendet werden, V_p und φ_p eine Amplitude und eine Phase der Frequenzkomponente f_p darstellen, (i,j) eine Position innerhalb jedes Geschwindigkeitsfeldes darstellt und m eine axiale z-oder laterale x-Richtung darstellt.
- Verfahren nach Anspruch 1, wobei der Schritt des Rücktransformierens der differenzierten ausgewählten Untermenge in die Zeitdomäne ein Einsetzen einer trigonometrischen Funktion einschließt, die die Daten zurück in die Zeitdomäne rekonstruiert.
 - Verfahren nach einem der Ansprüche 1 bis 4, wobei der Schritt des Transformierens des Geschwindigkeitsvektorprofils in die Frequenzdomäne ein Anwenden einer Fourier-Transformation auf das Geschwindigkeitsvektorprofil einschließt.
 - **6.** Verfahren nach einem der Ansprüche 1 bis 5, wobei der Schritt des Auswählens der Untermenge der Frequenzkomponenten ein Auswählen von nur 4 bis 16 der Frequenzkomponenten einschließt.
- **7.** Verfahren nach einem der Ansprüche 1 bis 6, wobei der Schritt des Auswählens der Untermenge der Frequenzkomponenten ein Auswählen einer vorbestimmten Anzahl von Sinuskurven mit einer höchsten Energie einschließt.
 - 8. Verfahren nach einem der Ansprüche 1 bis 6, wobei der Schritt des Auswählens der Untermenge von Frequenzkomponenten ein Auswählen von Sinuskurven mit einer Energie in einem vorbestimmten Bereich einschließt.
- 40

30

- 9. Verfahren nach einem der Ansprüche 1 bis 8, wobei die Beschleunigung weiter eine räumliche Beschleunigung einschließt.
- 10. Verfahren nach einem der Ansprüche 1 bis 8, wobei der Schritt des Bestimmens des Druckabfalls einschließt:
- 45

50

Empfangen einer Identifikation von einer Vielzahl von interessierenden Punkten auf dem Ultraschallbild, wobei die Vielzahl von interessierenden Punkten sich jeweils hinter einer Verengung des Gefäßes, innerhalb der Verengung und vor der Verengung befinden;

Bestimmen eines Druckabfalls basierend auf den Druckgradienten für die Vielzahl von interessierenden Punkten;

visuelles Identifizieren der Vielzahl von interessierenden Punkten auf dem angezeigten Ultraschallbild; und Anzeigen des bestimmten Druckabfalls.

55

11. Verfahren nach einem der Ansprüche 1 bis 8, wobei das Bestimmen des Druckabfalls einschließt:

Empfangen eines Signals, das einen Satz von Pixeln im Bild für eine Linie entlang einer Längsachse des Gefäßes identifiziert;

Bestimmen eines Druckabfalls durch Integrieren über die Druckgradienten, die dem identifizierten Satz von

Pixeln entsprechen;

Wiederholen der Vorgänge des Empfangens und Bestimmens für jedes Einzelbild; und visuelles Präsentieren der Druckabfälle als eine Zeitfunktion.

⁵ **12.** Verfahren nach Anspruch 11, weiter umfassend:

Wiederholen der Vorgänge des Empfangens, Bestimmens, Wiederholens und Präsentierens für eine Vielzahl von unterschiedlichen Linien entlang der Längsachse des Gefäßes jedes Einzelbildes; und visuelles Präsentieren der Druckabfälle als eine Druckkarte.

10

15

- **13.** Verfahren nach einem der Ansprüche 1 bis 12, wobei das Geschwindigkeitsvektorprofil eines von einem 2D- oder 3D-Geschwindigkeitsvektorprofil ist.
- 14. Verfahren nach einem der Ansprüche 1 bis 13, weiter umfassend:

Erzeugen des Geschwindigkeitsvektorprofils basierend auf mindestens einem von einer transversalen Schwingung, einer ebenen Welle oder einem synthetischen Apertur-Algorithmus.

- 15. Einrichtung zum Bestimmen von Druckgradienten mit Ultraschalldaten, wobei die Einrichtung umfasst:
- einen Geschwindigkeitsschätzer (113), der Ultraschallbilddaten verarbeitet, die durch ein Ultraschallbildgebungssystem erfasst werden, und Geschwindigkeitsvektorfelder darauf basierend erzeugt;
 einen zeitlichen Beschleunigungsprozessor (208), der die Geschwindigkeitsvektorfelder verarbeitet und eine zeitliche Beschleunigung erzeugt, wobei der zeitliche Beschleunigungsprozessor die Geschwindigkeitsvektorfelder filtert, während er die zeitliche Beschleunigung durch Transformieren des Geschwindigkeitsvektorprofils
 von einer Zeitdomäne in eine Frequenzdomäne bestimmt, eine Untermenge der Frequenzkomponenten auswählt, die vorbestimmte Energiekriterien erfüllen, die ausgewählte Untermenge durch Differenzieren der aus
 - gewählten Untermenge und Rücktransformieren der differenzierten ausgewählten Untermenge in die Zeitdomäne verarbeitet;
- einen räumlichen Beschleunigungsprozessor (210), der die Geschwindigkeitsvektorfelder verarbeitet und eine ³⁰ räumliche Beschleunigung erzeugt;
 - einen Druckänderungsschätzer (202), der Druckgradienten für die Ultraschalldaten basierend auf einem Modell und der zeitlichen und räumlichen Beschleunigung schätzt; und

eine Anzeige, die konfiguriert ist, um Ultraschallbilddaten und die Druckgradienten-Schätzungen anzuzeigen.

35

Revendications

- 1. Procédé pour déterminer des gradients de pression à l'aide de données ultrasonores, le procédé comprenant :
- 40 l'acquisition (1402) de données ultrasonores d'un vaisseau ; la génération (1404) d'un profil de vecteur de vitesse pour écoulement dans le vaisseau avec les données ultrasonores; le calcul (1406) d'une accélération avec le profil de vecteur de vitesse, dans lequel l'accélération inclut au moins une accélération temporelle, et le calcul de l'accélération temporelle inclut : 45 la transformation du profil de vecteur de vitesse d'un domaine temporel à un domaine fréquentiel ; la sélection d'un sous-ensemble des composantes de fréquence qui satisfont des critères d'énergie prédéterminés ; le traitement du sous-ensemble sélectionné en différenciant le sous-ensemble sélectionné ; 50 la transformation du sous-ensemble sélectionné différencié de retour au domaine temporel réduisant ainsi le bruit du profil de vecteur de vitesse ; et la détermination de l'accélération temporelle à partir des données de vitesse à bruit réduit ; la détermination (1408) des gradients de pression avec l'accélération calculée ; et l'affichage (1414) d'une image ultrasonore du vaisseau avec des indices indiguant les gradients de pression 55 superposés sur celle-ci.
 - 2. Procédé selon la revendication 1, dans lequel les gradients de pression sont générés à l'aide de l'équation de Navier-Stokes.

3. Procédé selon la revendication 1 ou 2, dans lequel l'étape de différenciation du sous-ensemble sélectionné inclut la différenciation de sinusoïdes sélectionnées, à l'aide de :

5

20

$$\frac{d\vec{v}_m(i,j,t)}{dt} = \sum_{p=1}^N \left|\vec{v}_p(i,j)\right| 2\pi \hat{f}_p(i,j) \sin\left(2\pi \hat{f}_p(i,j)t - \vec{\varphi}_p(i,j)\right)$$

- ¹⁰ où N représente un nombre de composantes de fréquence utilisées pour la reconstruction d'un profil d'écoulement, V_p et φ_p représentent une amplitude et une phase de la composante de fréquence f_p , (i,j) représente une position dans chaque champ de vitesse, et m représente une direction axiale z ou latérale x.
- Procédé selon la revendication 1, dans lequel l'étape de transformation du sous-ensemble sélectionné différencié de retour au domaine temporel inclut l'emploi d'une fonction trigonométrique qui reconstruit les données de retour dans le domaine temporel.
 - Procédé selon l'une quelconque des revendications 1 à 4, dans lequel l'étape de transformation du profil de vecteur de vitesse dans le domaine fréquentiel inclut l'application d'une transformation de Fourier au profil de vecteur de vitesse.
 - **6.** Procédé selon l'une quelconque des revendications 1 à 5, dans lequel l'étape de sélection du sous-ensemble des composantes de fréquence inclut la sélection de seulement 4 à 16 des composantes de fréquence.
- Procédé selon l'une quelconque des revendications 1 à 6, dans lequel l'étape de sélection du sous-ensemble des composantes de fréquence inclut la sélection d'un nombre prédéterminé de sinusoïdes ayant une énergie la plus élevée.
- **8.** Procédé selon l'une quelconque des revendications 1 à 6, dans lequel l'étape de sélection du sous-ensemble de composantes de fréquence inclut la sélection de sinusoïdes ayant une énergie dans une plage prédéterminée.
 - 9. Procédé selon l'une quelconque des revendications 1 à 8, dans lequel l'accélération inclut en outre une accélération spatiale.
- **10.** Procédé selon l'une quelconque des revendications 1 à 8, dans lequel l'étape de détermination de la baisse de pression inclut :
 - la réception d'une identification d'une pluralité de points d'intérêt sur l'image ultrasonore, dans lequel la pluralité de points d'intérêt sont respectivement situés derrière un étranglement du vaisseau, dans l'étranglement et avant l'étranglement ;
 - la détermination d'une baisse de pression sur la base des gradients de pression pour la pluralité de points d'intérêt ;
 - l'identification visuelle de la pluralité de points d'intérêt sur l'image ultrasonore affichée ; et
 - l'affichage de la baisse de pression déterminée.

45

50

40

11. Procédé selon l'une quelconque des revendications 1 à 8, dans lequel la détermination de la baisse de pression inclut :

la réception d'un signal identifiant un ensemble de pixels dans l'image pour une ligne le long d'un axe long du vaisseau ;

la détermination d'une baisse de pression par intégration sur les gradients de pression correspondant à l'ensemble de pixels identifié ;

la répétition des actions de réception et de détermination pour chaque trame d'image ; et

la présentation visuelle des baisses de pression en fonction du temps.

55 **12.** Procédé selon la revendication 11, comprenant en outre :

la répétition des actions de réception, de détermination, de répétition et de présentation pour une pluralité de lignes différentes le long de l'axe long du vaisseau pour chaque trame d'image ; et

la présentation visuelle des baisses de pression comme carte de pression.

- **13.** Procédé selon l'une quelconque des revendications 1 à 12, dans lequel le profil de vecteur de vitesse est l'un parmi un profil de vecteur de vitesse 2-D ou 3-D.
- 5

14. Procédé selon l'une quelconque des revendications 1 à 13, comprenant en outre : la génération du profil de vecteur de vitesse sur la base d'au moins un parmi une oscillation transversale, une onde de plan, ou un algorithme d'ouverture synthétique.

10 **15.** Appareil pour déterminer des gradients de pression avec des données ultrasonores, l'appareil comprenant :

un estimateur de vitesse (113) qui traite des données d'images ultrasonores acquises par un système d'imagerie ultrasonore et génère des champs de vecteur de vitesse sur la base de celles-ci ;

- un processeur d'accélération temporelle (208) qui traite les champs de vecteur de vitesse et génère une accé lération temporelle, dans lequel le processeur d'accélération temporelle filtre les champs de vecteur de vitesse tout en déterminant l'accélération temporelle en transformant le profil de vecteur de vitesse d'un domaine temporel à un domaine fréquentiel, sélectionnant un sous-ensemble des composantes de fréquence qui satisfont des critères d'énergie prédéterminés, traitant le sous-ensemble sélectionné en différenciant le sous-ensemble sélectionné et transformant le sous-ensemble sélectionné différencié de retour dans le domaine temporel ;
- ²⁰ un processeur d'accélération spatiale (210) qui traite les champs de vecteur de vitesse et génère une accélération spatiale ;

un estimateur de changement de pression (202) qui estime des gradients de pression pour les données ultrasonores sur la base d'un modèle et des accélérations temporelles et spatiales ; et

- un dispositif d'affichage configuré pour afficher des données d'images ultrasonores et les estimations de gradients de pression.
- 30
- 35
- 40

- 45
- 50
- 55





FIGURE 2









Measured pressure gradient map







REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- EP 2769677 A [0008]
- US 6725076 B1 [0021]

- US 6859659 B1 [0022]
- US 6148224 A [0022]

Non-patent literature cited in the description

- Non-invasive estimation of pressure gradients in pulsatile flow using ultrasound. JACOB BJERRING OLESEN et al. 2014 IEEE INTERNATIONAL UL-TRASONICS SYMPOSIUM. IEEE, 03 September 2014, 2257-2260 [0005]
- Left Ventricular Fluid Mechanics: The Long Way from Theoretical Models to Clinical Applications. GIANNI PEDRIZZETTI et al. ANNALS OF BIOMEDICAL EN-GINEERING. PERGAMON PRESS, 04 September 2014, vol. 43, 26-40 [0006]
- Noninvasive estimation of2-D pressure gradients in steady flow using ultrasound. IEEE TRANSAC-TIONS ON ULTRASONICS, FERROELECTRICS AND FREQUENCY CONTROL, 01 August 2014, vol. 61 (8), 1409-1418 [0007]

- JENSEN et al. Directional synthetic aperture flow imaging. *IEEE Trans. Ultrason., Ferroelec., Freq. Contr.,* 2004, vol. 51, 1107-1118 [0021]
- JENSEN et al. Estimation of velocity vectors in synthetic aperture ultrasound imaging. *IEEE Trans. Ultrason., Ferroelec., Freq. Contr.,* 2006, vol. 25, 1637-1644 [0021]
- JENSEN. A New Estimator for Vector Velocity Estimation. *IEEE Trans. Ultrason., Ferroelec., Freq. Contr.*, 2001, vol. 48 (4), 886-894 [0022]
- OLESEN. Noninvasive estimation of 2-D pressure gradients in steady flow using ultrasound. *IEEE Transactions on Ultrasonics, Ferroelectrics and Frequency Control,* vol. 61 (8), 1409-1418 [0038]