A Small-Scale Setup for Algal Toxicity Testing of Nanomaterials and Other Difficult Substances

Skjolding, Lars Michael; Kruse, Susanne; Sørensen, Sara Nørgaard; Hjorth, Rune; Baun, Anders

Published in:
Journal of Visualized Experiments

Link to article, DOI:
[10.3791/61209](https://doi.org/10.3791/61209)

Publication date:
2020

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Skjolding, L. M., Kruse, S., Sørensen, S. N., Hjorth, R., & Baun, A. (2020). A Small-Scale Setup for Algal Toxicity Testing of Nanomaterials and Other Difficult Substances. *Journal of Visualized Experiments*, [e61209]. <https://doi.org/10.3791/61209>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

TITLE:

A Small-Scale Setup for Algal Toxicity Testing of Nanomaterials and Other Difficult Substances

AUTHORS AND AFFILIATIONS:

Lars Michael Skjolding, Susanne Kruse, Sara Nørgaard Sørensen, Rune Hjorth, Anders Baun

Department of Environmental Engineering, Technical University of Denmark, Kongens Lyngby, Denmark

Email Addresses of co-authors:

Susanne Kruse (sukr@env.dtu.dk)

Sara Nørgaard Sørensen (sans@env.dtu.dk)

Rune Hjorth (ruhjo@mst.dk)

Anders Baun (abau@env.dtu.dk)

Corresponding Author:

Lars Michael Skjolding (lams@env.dtu.dk)

KEYWORDS:

ecotoxicity, growth inhibition, colored substances, nanomaterials, *Raphidocelis subcapitata*, OECD 201, ISO 8692, LEVITATT

SUMMARY:

We demonstrate algal toxicity testing for difficult substances (e.g., colored substances or nanomaterials) using a setup illuminated vertically with an LED.

LONG ABSTRACT:

Ecotoxicity data is a requirement for pre- and post-market registration of chemicals by European and international regulations (e.g., REACH). The algal toxicity test is frequently used in regulatory risk assessment of chemicals. In order to achieve high reliability and reproducibility the development of standardized guidelines is vital. For algal toxicity testing, the guidelines require stable and uniform conditions of parameters such as pH, temperature, carbon dioxide levels and light intensity. Nanomaterials and other so-called difficult substances can interfere with light causing a large variation in results obtained hampering their regulatory acceptance. To address these challenges, we have developed LEVITATT (LED Vertical Illumination Table for Algal Toxicity Tests). The setup utilizes LED illumination from below allowing for a homogenous light distribution and temperature control while also minimizing intra-sample shading. The setup optimizes the sample volume for biomass quantification and does at the same time ensure a sufficient influx of CO₂ to support exponential growth of the algae. Additionally, the material of the test containers can be tailored to minimize adsorption and volatilization. When testing colored substances or particle suspensions, the use of LED lights also allows for increasing the light intensity without additional heat generation. The compact design and minimal equipment requirements increase the possibilities for implementation of the LEVITATT in a wide range of laboratories. While compliant with standardized ISO and OECD guidelines for algal toxicity

testing, LEVITATT also showed a lower inter-sample variability for two reference substances (3,5-Dichlorophenol and $K_2Cr_2O_7$) and three nanomaterials (ZnO, CeO_2 , and $BaSO_4$) compared to Erlenmeyer flasks and microtiter plates.

INTRODUCTION:

The algal toxicity test is one of only three mandatory tests used to generate the ecotoxicity data required for pre- and post-market registration of chemicals by European and international regulations (e.g., REACH¹ and TSCA (USA)). For this purpose, standardized algal test guidelines have been developed by international organizations (e.g., ISO and OECD). These testing standards and guidelines prescribe ideal test conditions in terms of pH, temperature, carbon dioxide levels and light intensity. However, maintaining stable test conditions during algal testing is in practice difficult and the results suffer from problems with reproducibility and reliability for a range of chemical substances and nanomaterials (often referred to as “difficult substances”)². Most of the existing algal toxicity testing setups operate with relatively large volumes (100–250 mL) situated on an orbital shaker inside an incubator. Such a setup limits the number of test concentrations and replicates achievable and high volumes of algal culture and test material. Additionally, these setups rarely have a uniform light field and reliable lighting conditions are furthermore difficult to obtain in large flasks, partly as light intensity decreases exponentially the further the light travels and partly due to the flask geometry. Alternative setups comprise plastic microtiter³ plates containing small sample volumes that do not allow for adequate sampling volumes to measure pH, additional biomass measurements, pigment extraction or other analyses requiring destructive sampling. One particular challenge using existing setups for algal toxicity testing of nanomaterials and substances forming colored suspensions is the interference or blocking of the light available to the algal cells, often referred to as “shading”^{4,5}. Shading may occur within vials by the test material and/or interactions between the test material and the algal cells, or shading can occur between vials, due to their positioning relative to each other and the light source.

The method is based on the small-scale algal toxicity test setup introduced by Arensberg et al.⁶ that allows for testing in compliance with standards such as OECD 201⁷, and ISO 8692⁸. The method is further optimized to address the limitations stated above by: 1) utilizing the LED light technology to ensure uniform light conditions with minimal heat generation, 2) providing adequate sample volume for chemical/biological analysis while maintaining constant pH, CO_2 levels, and 3) enabling the use of versatile test container material for testing of volatile substances or substances with a high sorption potential.

PROTOCOL:

1. Description of the LEVITATT setup

1.1. Use 20 mL scintillation glass vials (**Figure 1**, insert 1) allowing light penetration. Alternatively, light penetrable plastic vials can be used. Quantify the light intensity using a photometer.

1.2. Use at least a 4 mL test suspension at the beginning of the test to allow for quantification

of biomass and for characterization/quantification of nanomaterials during and after incubation (**Figure 1**, insert 2).

1.3. Fit the 20 mL scintillation vials with a cap (**Figure 1**, insert 3) where a small hole is drilled (approximately 1 mm in diameter) to allow for CO₂ exchange with the atmosphere. This exchange is crucial to ensure stable pH and CO₂ levels during testing.

1.4. For volatile substances, use an air-tight Teflon coated cap to allow for CO₂ enriching of the headspace using a syringe⁹ or completely closed flasks with no gas phase in which CO₂ is maintained in solution by an enriched sodium bicarbonate (NaHCO₃) buffer system¹⁰.

1.5. Fasten the vials with clamps mounted on the exterior casing (**Figure 1**, insert 4).

1.6. Use an LED light source located below the test vials (**Figure 1**, insert 5) providing a uniform fluorescent illumination of “cool-white” or “daylight” type and a light intensity in the range 60–120 $\mu\text{E}\cdot\text{m}^{-2}\cdot\text{s}^{-1}$ measured in the photosynthetically effective wavelength range of 400 nm to 700 nm. The setup employs adjustable light intensity in the range 5–160 $\mu\text{E}\cdot\text{m}^{-2}\cdot\text{s}^{-1}$ by fitting a light dimmer to the source. This allows for testing at higher and lower light intensities.

1.7. Mount the setup on an orbital shaker to agitate samples throughout the duration of the test. This keeps the cells in free suspension and facilitates CO₂ mass transfer from air to water (**Figure 1**, insert 6).

1.8. Place the setup in a temperature-controlled room or a thermostatic cabinet to maintain stable temperatures throughout testing (**Figure 1**, insert 7).

[Place Figure 1 here]

2. Preparation of algal growth medium

2.1. The ISO 8692 algal growth medium consists of four different stock solutions. Weigh out the appropriate amount of salts and dilute in ultrapure water according to **Table 1**.

[Place Table 1 here]

NOTE: H₃BO₃ can be dissolved by adding 0.1 M NaOH. EDTA should be removed when testing metals, to avoid complexation with metal ions. Sterilize the stock solutions by membrane filtration (mean pore diameter 0.2 μm) or by autoclaving (120 °C, 15 min). Do not autoclave stock solutions 2 and 4, but sterilize them by membrane filtration. Store the solutions in the dark at 4 °C.

2.2. To produce 1 L of algal growth medium, transfer 500 mL sterilized ultrapure water into a 1 L sterilized volumetric flask and add 10 mL of stock solution 1: Macronutrients, 1 mL of stock solution 2: Fe-EDTA, 1 mL of stock solution 3: Trace elements, and 1 mL of stock solution 4:

NaHCO₃.

2.3. Fill up to 1 L with sterilized ultrapure water, stopper the flask and shake thoroughly to homogenize the algal growth medium.

2.4. Equilibrate the solution before use by leaving it overnight in contact with air or by bubbling with sterile, filtered air for 30 min. After equilibration, adjust the pH, if necessary, to pH 8.1 ± 0.2, with either 1 M HCl or 1 M NaOH.

3. Setting up the algal test

NOTE: A flow diagram of the algal test procedure is shown in **Figure 2**.

[Place Figure 2 here]

3.1. Prepare a stock solution of the test compound at the desired highest test concentration in the algal growth medium prepared according to step 2. For preparation of stock solutions/suspensions, follow OECD 201 (for soluble compounds) or OECD 318 (for nanomaterials).

3.2. Measure the pH in the stock solution. If it deviates more than one unit from the algal growth medium, adjust the pH to 8 with either 1 M HCl or 1 M NaOH.

3.3. Calculate the inoculum volume needed to reach a final cell concentration of 1 x 10⁴ cells/mL in a 25 mL test solution.

NOTE: The inoculum should come from a culture of uncontaminated exponentially growing *Raphidocelis subcapitata* grown using the LEVITATT setup.

3.4. Calculate the amount of stock solution to add to each 25 mL volumetric flask to obtain the desired test concentrations. The factor between each concentration should not exceed 3.2.

3.5. Mark one 25 mL volumetric flask for each chosen concentration and an additional 25 mL volumetric flask marked control.

3.6. Add the amount of stock solution of the test compound needed to reach the desired concentrations to the 25 mL volumetric flask. Do **not** add stock solution to the control.

3.7. Add the medium to each 25 mL volumetric flask to reach a volume of approximately 20 mL.

3.8. Add the volume of inoculum calculated in step 3.3 to each 25 mL volumetric flask. Add the medium to each 25 mL volumetric flask to a final total volume of 25 mL.

3.9. Stopper the flasks and mix thoroughly by turning the flasks two times vertically.

3.10. Transfer 0.4 mL from each flask into individual screw cap vials and add 1.6 mL of acetone (saturated with MgCO_3): one sample for each test concentration and the control. Close the lids tightly and store in the dark at room temperature until fluorescence measurements (section 4).

3.11. Pipet 4 mL of each test solution into 20 mL scintillation vials (3 replicates per concentration and 5 replicates for the control). Screw lids on the scintillation vials. **Remember** that the lids must have a drilled hole (approximately 1 mm in diameter) to allow for CO_2 exchange.

3.12. After 24 h, 48 h, and 72 h, pipet 0.4 mL from each vial into screw cap vials and add 1.6 mL of acetone (saturated with MgCO_3). Close the lids tightly and store in the dark at room temperature until fluorescence measurements (section 4).

3.13. After the last sample is taken at 72 h, gently pool the three replicates for a given concentration in one vial and measure the pH. Repeat for all concentrations and the control. The pH should not deviate more than 1.5 units from the initial pH for any of the samples measured.

3.14. Discharge the remaining liquids into a waste container following your institutional rules and regulations.

4. Analyzing algal test samples

4.1. Use a fluorescence spectrophotometer to measure the algal biomass (here expressed as chlorophyll A). The peak emission for chlorophyll A is 420 nm for the excitation wavelength and 671 nm for the emission wavelength.

4.2. Measure the fluorescence of each individual sample three times and calculate the average value for each sample.

4.3. Use equation 1 to calculate the growth rate. The measured fluorescence (relative units) can be used directly as the biomass parameter in equation 1.

Equation 1: $\mu = (\ln N_t - \ln N_0) / t$

where μ is the growth rate (d^{-1}), N_0 is the initial biomass, N_t is the biomass at time t , and t is the length of the test period (d). Note, N_0 and N_t should be expressed in the same unit.

4.4. Use a statistical software to fit a non-linear regression curve (e.g., a log-logistic or Weibull function) to the growth rate data to obtain effective concentration values at 10%, 20%, and 50% inhibition. In the supplementary information an example of code for fitting in the statistical software R using the DRC package¹¹ is given.

REPRESENTATIVE RESULTS:

An initial test with a reference substance is carried out to determine the sensitivity of the algal

strain. Reference substances regularly used for *R. subcapitata* are potassium dichromate and 3,5-Dichlorophenol^{7,8}. **Figure 3** and **Table 2** show a representative result of an algal test including curve fitting and statistical outputs when the DRC package in R is applied to the growth rates.

A successful test will have growth rates above 0.9 d⁻¹ to comply with the OECD guideline and 1.5 d⁻¹ to comply with ISO 8692 guideline and should contain at least one concentration between 0% and 100% inhibition. Low growth rates may occur as a result of various issues such as bacterial contamination or inoculum not being in the exponential growth phase at the beginning of the test. Microscopic investigation of the replicates should only show uniform sickle-shaped green algae (*R. subcapitata*) with dimensions of approximately 2 µm width and 8 µm length. If a single replicate is contaminated, it can be omitted and the analysis can be carried out without this data. However, if multiple replicates are contaminated, repeat the experiment with uncontaminated exponentially growing inoculum. To evaluate whether the inoculum was in the exponential growth phase at the beginning of the test, calculate the growth rate of the control replicates at 24 h intervals and use only the time interval at which the algal growth of the control is exponential for statistical analysis.

To test the robustness of the setup, a toxicity test using two reference substances (K₂Cr₂O₇ and 3,5-Dichlorophenol) and three nanomaterials was repeated three times (3,5-Dichlorophenol, BaSO₄ nanoparticles (NM-220), and ZnO nanoparticles (NM-111)) and four times (K₂Cr₂O₇ and CeO₂ nanoparticles (NM-212)). The results showed a coefficient of variation of the EC₅₀-values between 11% and 39%, with the lowest coefficient of variation observed for ZnO nanoparticles (NM-111) and the highest coefficient of variation for CeO₂ nanoparticles (NM-212) (**Table 3**).

[Place Table 3 here]

FIGURE AND TABLE LEGENDS:

Figure 1: Picture of LED Vertical Illumination Table for Algal Toxicity Tests (LEVITATT). 1) 20 mL glass scintillation vials for incubation, 2) 4 mL sample for analysis, 3) lid with drilled hole for CO₂ exchange, 4) casing for defined light conditions, 5) LED light source located in the center of the casing, 6) orbital shaker for agitation during the experiment, and 7) a thermostatic cabinet.

Figure 2: Flow diagram of the algal test setup.

Figure 3: Representative concentration-response curve for 72 h exposure of a chemical compound to algae (*R. subcapitata*). The solid line represents the log-logistic fit and the shaded area is the 95% confidence interval for the fit. The open circles represent the calculated growth rate for each replicate.

Table 1: Concentrations of nutrients in stock solutions for algal growth medium

Table 2: Representative effective concentrations for 10%, 20%, and 50% inhibition of growth rate for a chemical compound using algae (*R. subcapitata*). The value in brackets represents the

95% confidence interval of a log-logistic fitting.

Table 3: Results of an internal laboratory toxicity test with *R. subcapitata* exposed for 72 h to two reference substances and three nanomaterials from the JRC repository

DISCUSSION:

Phytoplankton converts solar energy and carbon dioxide to organic matter and thus holds a pivotal role in the aquatic ecosystem. For this reason, algal growth rate inhibition tests are included as one of three mandatory aquatic toxicity tests required for regulatory risk assessment of chemicals. The ability to perform a reliable and reproducible algal toxicity test is key in this regard. Test setups using Erlenmeyer flasks introduces a range of variabilities and inconveniences as described in the introduction. To circumvent this issue, microtiter plates have been proposed³. While the microtiter plates minimize the volume and space required for testing, concerns have been raised in literature with regard to the compliance of such setups with the test validity criteria of test guidelines⁶. For example, significant loss of semivolatile chemicals as well as cross-over to other wells in microtiter plates at 37 °C in cellular growth media (DMEM GluteMAX, Opti-MEM, and Hams F12 GlutaMAX) was recently demonstrated by Birch et al.¹². Testing of volatile substances may be successfully conducted with the LEVITATT setup using 1) closed vials with CO₂ enriched headspace⁹, 2) directly dosing the volatile compound through the headspace¹³ or in a filled test vial¹⁰. In terms of space requirements, LEVITATT provides a test setup that fills the gap between microtiter plates and Erlenmeyer flask setups while still providing benefits from both setups, e.g., maintaining a concise and compact test environment and sufficient test volume for destructive sampling (e.g., for characterization of nanomaterials during the test).

The inter-sample variability for the LEVITATT test system ranged from 3.4% (3,5-Dichlorophenol and ZnO NP) to 5.6% (BaSO₄ NP). This is within the requirement of coefficient of variation of average growth in replicate control cultures of 15% indicated by the OECD 201 guideline⁷ (for the LEVITATT inter-sample variability all exposures were also included).

The reproducibility with regards to EC₅₀-values of the test setup for the reference substances showed a coefficient of variance of 13% for K₂Cr₂O₇ (n = 4) and 21% for 3,5-Dichlorophenol (n = 3). This is comparable to tests carried out with conventional 250 mL Erlenmeyer flask bioassays for the reference substance K₂Cr₂O₇ showing 16.8%¹⁴ and 25.4%¹⁵ coefficient of variation for EC₅₀-values. Microtiter plates have shown lower variation coefficient for some reference substances (e.g., K₂Cr₂O₇ (9%^{14,15}), while higher coefficients of variation have been observed for phenol (34.9%¹⁶) and Dichlorophenol (38%¹⁷). Limited information is available with regard to reproducibility of studies with nanomaterials. However, comparing the inter-sample coefficient of variation for ZnO NPs using the LEVITATT system (3.4%) with microtiter plates (67%¹⁸) or Erlenmeyer flasks (13%¹⁹ and 35%²⁰) it has less variation. To further test the robustness of the LEVITATT system, a round-robin study of two test materials (one reference substance and one difficult to test substance) have been initiated.

Maintaining an uncontaminated algal culture can be difficult if not handled in sterile conditions. Exponential algal growth is a key prerequisite for performing guideline algal testing. Measuring

the growth at multiple time points (e.g., 24 h, 48 h, 72 h) can identify whether exponential growth is occurring throughout the test period. Fluctuations in temperature and pH can influence the algal growth; thus, these parameters must be stable throughout the test period. In small volumes of test sample, fluctuations in temperature and pH occur more rapidly compared to larger volumes and the practical issues of measuring these parameters are increasingly difficult with decreasing test volume. Parameters such as pH and temperature using 4 mL test volume was stable throughout a 72 h testing period in the LEVITATT both in a temperature-controlled room at 20 °C ± 2 °C and in an incubator at similar conditions.

Analytical methods for quantification of algal growth are many: cell counting in a haemocytometer, coulter counter, or fluorescence of pigment extracts. For difficult substances, considerations should be made with regard to the most suitable method for biomass quantification. For metal oxide nanoparticles, fluorescence of pigment extracts has been found to perform best due to interference of agglomerates when counting algae by haemocytometer or coulter counter²¹. In contrast, Farkas and Booth²² found that quantification of biomass by fluorescence was not a suitable method for ecotoxicity testing of carbon-based nanomaterials due to autofluorescence and absorbance of pigments to the nanomaterials. For colored substances, there may also be interference of the color with the fluorescence emission signal, thus, requiring additional controls or dilution to a level where this interference is negligible.

In the guidance document for aquatic toxicity testing of difficult substances², one of the recommendations for testing colored materials is to increase the light intensity. Similarly, increased light intensity has been mentioned to circumvent shading issues when testing nanomaterials^{23,24}. However, such modifications are often associated with increased temperatures, thus, requiring additional cooling or ventilation of the samples. In the LEVITATT setup, this is solved using LED light that produces little heat compared to conventional light bulbs or fluorescent tubes. Additionally, choosing an LED with a sufficiently high light intensity output and the installation of a dimmer allow for increasing the light intensity to test colored substances or nanomaterials and regular chemicals without altering the overall setup between tests. Furthermore, the placement of the light source below the samples and in separate casings allows for a consistent and homogenous light field.

In conclusion, the LEVITATT provides a compact platform for algal toxicity testing of regular chemicals compliant with international standardized guidelines. Furthermore, the setup provides a robust platform for testing of difficult substances that interfere with the passage of light toward the algal, e.g., nanomaterials.

ACKNOWLEDGMENTS:

This research was funded by PATROLS – Advanced Tools for NanoSafety Testing, Grant agreement 760813 under Horizon 2020 research and innovation program.

DISCLOSURES:

The authors have nothing to disclose.

REFERENCES:

1. European Chemicals Agency, *Guidance on Registration*. Helsinki, Finland (2016).
2. Organisation for Economic Cooperation and Development, *Guidance Document on Aquatic Toxicity Testing of Difficult Substances and Mixtures* (2019).
3. Blaise, C., Legault, R., Bermingham, N., Van Coillie, R., Vasseur, P. A simple microplate algal assay technique for aquatic toxicity assessment. *Toxicity Assessment*. **1** (3), 261–281 (1986).
4. Hjorth, R., Sorensen, S. N., Olsson, M. E., Baun, A., Hartmann, N. B. A certain shade of green: can algal pigments reveal shading effects of nanoparticles? *Integrated Environmental Assessment and Management*. **12** (1), 200–202 (2016).
5. Chen, F. et al. Algae response to engineered nanoparticles: current understanding{,} mechanisms and implications. *Environmental Science: Nano*. **6** (4), 1026–1042 (2019).
6. Arensberg, P., Hemmingsen, V. H., Nyholm, N. A miniscale algal toxicity test. *Chemosphere*. **30** (11), 2103–2115 (1995).
7. Organisation for Economic Cooperation and Development, *Test No. 201: Freshwater Alga and Cyanobacteria, Growth Inhibition Test* (2011).
8. International Organization for Standardization (ISO), *Water Quality - Fresh Water Algal Growth Inhibition Test with Unicellular Green Algae* (2012).
9. Halling-Sørensen, B., Nyhohn, N., Baun, A. Algal toxicity tests with volatile and hazardous compounds in air-tight test flasks with CO₂ enriched headspace. *Chemosphere*. **32** (8), 1513–1526 (1996).
10. Mayer, P., Nyholm, N., Verbruggen, E. M. J., Hermens, J. L. M., Tolls, J. Algal growth inhibition test in filled, closed bottles for volatile and sorptive materials. *Environmental Toxicology and Chemistry*. **19** (10), 2551–2556 (2000).
11. Ritz, C., Baty, F., Streibig, J. C., Gerhard, D. Dose-response analysis using R. *PloS One*. **10** (12), e0146021–e0146021 (2015).
12. Birch, H., Kramer, N. I., Mayer, P. Time-resolved freely dissolved concentrations of semivolatile and hydrophobic test chemicals in in vitro assays—measuring high losses and crossover by headspace solid-phase microextraction. *Chemical Research in Toxicology*. **32** (9), 1780–1790 (2019).
13. Trac, L. N., Schmidt, S. N., Mayer, P. Headspace passive dosing of volatile hydrophobic chemicals – Aquatic toxicity testing exactly at the saturation level. *Chemosphere*. **211**, 694–700 (2018).
14. Eisentraeger, A., Dott, W., Klein, J., Hahn, S. Comparative studies on algal toxicity testing using fluorometric microplate and Erlenmeyer flask growth-inhibition assays. *Ecotoxicology and Environmental Safety*. **54** (3), 346–354 (2003).
15. Paixao, S. M., Silva, L., Fernandes, A., O'Rourke, K., Mendonca, E., Picado, A. Performance of a miniaturized algal bioassay in phytotoxicity screening. *Ecotoxicology*. **17** (3), 165–171 (2008).
16. Thellen, C., Blaise, C., Roy, Y., Hickey, C. Round-robin testing with the selenastrum--capricornutum microplate toxicity assay. *Hydrobiologia*. **188**, 259–268 (1989).
17. Nagai, T., Taya, K., Annoh, H., Ishihara, S. Application of a fluorometric microplate algal toxicity assay for riverine periphytic algal species. *Ecotoxicology and Environmental Safety*. **94**, 37–44 (2013).
18. Lee, W.-M., An, Y.-J. Effects of zinc oxide and titanium dioxide nanoparticles on green algae under visible, UVA, and UVB irradiations: no evidence of enhanced algal toxicity under UV

pre-irradiation. *Chemosphere*. **91** (4), 536–544 (2013).

19. Samei, M., Sarrafzadeh, M.-H., Faramarzi, M. A. The impact of morphology and size of zinc oxide nanoparticles on its toxicity to the freshwater microalga, *Raphidocelis subcapitata*. *Environmental Science and Pollution Research*. **26** (3), 2409–2420 (2019).

20. Neale, P. A., Jaemting, A. K., O'Malley, E., Herrmann, J., Escher, B. I. Behaviour of titanium dioxide and zinc oxide nanoparticles in the presence of wastewater-derived organic matter and implications for algal toxicity. *Environmental Science: Nano*. **2** (1), 86–93 (2015).

21. Hartmann, N. B. et al. The challenges of testing metal and metal oxide nanoparticles in algal bioassays: titanium dioxide and gold nanoparticles as case studies. *Nanotoxicology*. **7** (6), 1082–1094 (2013).

22. Farkas, J., Booth, A. M. Are fluorescence-based chlorophyll quantification methods suitable for algae toxicity assessment of carbon nanomaterials? *Nanotoxicology*. **11** (4), 569–577 (2017).

23. Handy, R. D. et al. Practical considerations for conducting ecotoxicity test methods with manufactured nanomaterials: what have we learnt so far? *Ecotoxicology*. **21** (4), 933–972 (2012).

24. Handy, R. D. et al. Ecotoxicity test methods for engineered nanomaterials: practical experiences and recommendations from the bench. *Environmental Toxicology and Chemistry*. **31** (1), 15–31 (2012).