

# Exploring barriers for the use of FEA-based variation simulation in industrial development practice

Nerenst, Tim Brix; Ebro, Martin; Nielsen, Morten; Eifler, Tobias; Nielsen, Kim Lau

Published in: Design Science

Link to article, DOI: 10.1017/dsj.2021.21

Publication date: 2021

Document Version Publisher's PDF, also known as Version of record

#### Link back to DTU Orbit

*Citation (APA):* Nerenst, T. B., Ebro, M., Nielsen, M., Eifler, T., & Nielsen, K. L. (2021). Exploring barriers for the use of FEAbased variation simulation in industrial development practice. *Design Science*, *7*, Article e21. https://doi.org/10.1017/dsj.2021.21

#### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

• Users may download and print one copy of any publication from the public portal for the purpose of private study or research.

- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Exploring barriers for the use of FEA-based variation simulation in industrial development practice

Tim Brix Nerenst<sup>1</sup>, Martin Ebro<sup>2</sup>, Morten Nielsen<sup>2</sup>, Tobias Eifler<sup>1</sup> and Kim Lau Nielsen<sup>1</sup>

<sup>1</sup> Department of Mechanical Engineering, Technical University of Denmark, Kongens Lyngby, Denmark

<sup>2</sup> Modelling & Simulation, Novo Nordisk A/S, Hillerød, Denmark

#### Abstract

Over the last decades, finite element analysis (FEA) has become a standard tool in industrial product development, allowing for virtual analysis of designs, quick turnaround times and prompt implementation of results. Although academic research also provides numerous approaches for evaluating a product's robustness towards geometrical, material and load variations based on FEA analyses, this, however, stands in striking contrast to the limited use of these FEA-based variation simulations in industry. In order to bridge the existing gap between academic research and industrial application, this paper explores the barriers that limit the adoption of FEA-based variation simulation. The investigation is based on interviews with five lead engineers, followed by a case study that details the underlying technical challenges and allows for some initial suggestions for future solutions. The case study involves a sterile canister with seven geometrical variables. The design objective is to ensure sufficient sealing within the range of expected probabilistic variation. The combined study details the identified main barriers for a wider application, that is, the lack of robust CAD, practical guidelines to select an efficient design of experiments for design purposes, and the complexity of the automated processes. From a technical perspective, the case study results in estimations for main and interaction effects, an accurate metamodel and Monte Carlo simulations of 100,000 samples providing the design engineer with more detailed and actionable insights on the performance of the product compared with the traditional nominal or best/worst case simulations.

Received 31 May 2021 Revised 08 September 2021 Accepted 10 September 2021

Corresponding author T. B. Nerenst tbne@mek.dtu.dk

© The Author(s), 2021. Published by Cambridge University Press. This is an Open Access article, distributed under the terms of the Creative Commons Attribution licence (http:// creativecommons.org/licenses/by/ 4.0), which permits unrestricted re-use, distribution and reproduction, provided the original article is properly cited.

Des. Sci., vol. 7, e21 journals.cambridge.org/dsj DOI: 10.1017/dsj.2021.21





Key words: FEA variation simulation, DOE, Meta-model, Monte-Carlo, Industrial barriers

### 1. Introduction

The key responsibility of a mechanical design engineer is to embody the overall product and all individual components, such that the product fulfils all the technical and customer requirements (Pahl *et al.* 2007). This task usually includes the definition of suitable product configurations, geometries, dimensions, materials, manufacturing information (type and tolerances) and assembly instructions. In this process, robust design (RD) offers a development approach that aims at improving safety economically by solving variation-related issues upstream by an improved product design (Taguchi, Chowdhury, & Wu 2007), instead of relying on the widespread, and costly use of design margins and overengineering (Eckert, Isaksson, & Earl 2019) or excessive quality control. The goal is to choose optimal parameter

1/22

combinations in order to achieve consistently high product quality and performance despite variation related to production or assembly tolerances, varying load scenarios or ambient conditions of use (Taguchi, Chowdhury, & Wu 2007). In general, RD is a well-researched field, and fundamental ideas are widely accepted among researchers and practitioners. At the same time, many companies struggle with implementing a consistent RD strategy in practice (Gremyr, Arvidsson, & Johansson 2003; Krogstie, Ebro, & Howard 2015), particularly in light of the ever-increasing possibilities for simulation-driven design. Despite the opportunities of commercially available, highend software for finite element analysis (FEA), there remains a gap in most engineering industries when it comes to the systematic application of FEA to evaluate the effect of geometrical, material and load variations (Coleman 2012; Will 2015), hereinafter referred to as FEA-based variation simulation. Instead, FEA is used mainly on nominal designs and often in late development phases, leading to products with a high safety factor or overly optimistic designs prone to failure as variation occurs. The latter is typically not discovered before production ramp-up or after launch when the true distribution of variation reveals itself.

The present research explores the underlying reasons and possible solutions for the low uptake of FEA-based variation simulations in industrial development practice. The corresponding aim is to address the gap between current RD research that usually focuses on the details of advanced experimental designs (Jin, Chen, & Sudjianto 2003; Lehman, Santner, & Notz 2004; Joseph *et al.* 2019) and algorithms for robustness optimization (Du & Chen 2004; Raza & Liang 2012; Xie *et al.* 2018; Kriegesmann 2020; Li, Gao, & Xiao 2020) and wider industrial implementation of these tools. The research focuses explicitly on applying FEA-based variation simulation for new designs in the early embodiment phase, rather than incremental design improvements supported by vast legacy knowledge and the reuse of existing models.

The paper is structured as follows. After Section 2, Section 3 outlines the twofold research approach based on performed interviews and an industrial case study. The interview results are briefly reviewed in Section 4, which, combined with the case study, creates the foundation for exploring and evaluating the existing industrial barriers. Finally, the *Discussion* of results is presented, before the main *Conclusions* are summarized.

#### 2. Related literature

Despite its low uptake in the industry, RD is well-researched (Göhler, Ebro, & Howard 2018). Park *et al.* (2006) provide a general overview of RD methods and suggest three categories of approaches: axiomatic design (Suh 1995), the Taguchi method (Taguchi, Chowdhury, & Wu 2007) and robust design optimization (RDO; Capiez-Lernout & Soize 2008). Although several authors have addressed the first category, that is, the evaluation of early product solutions in terms of robustness (Suh 1995; Eifler & Howard 2018), the following focuses on the two latter approaches concerning the management of variation and uncertainty in mechanical product design and its vital role for a virtual robustness assessment based on FEA.

In his seminal work, Taguchi promotes the essential idea of off-line quality, that is, the frontloading of all cost and quality control ideas to the product design stage. Based on crossed array experiments, the objective is to choose optimal parameter combinations that will minimize the variation of the product's quality characteristics, measured by the quality loss function (Taguchi, Chowdhury, & Wu 2007).

Statisticians have appreciated Taguchi's work (Logothetis & Wynn 1990; Laycock, Atkinson, & Donev 1995; Hamada, Wu, & Jeff 2000; Draper & George 2007), but it has also received critique, because the practical implications can make the experimental designs inefficient and unnecessarily complicated (Box, Bisgaard, & Fung 1988). More recent reviews have evaluated the current status of this research direction (see, e.g., the review by Robinson, Borror, & Myers (2004)) and also proposed new research areas in the field of RD and uncertainty management (Parnianifard *et al.* 2018).

Despite existing for decades and despite being well-researched from an academic perspective, there remains a gap in most engineering industries when it comes to the systematic use of FEA-based robustness analyses (Coleman 2012; Will 2015). This gap particularly holds true for industries that predominantly face the challenge of exploring new design ideas and product configurations in their development work, thus cannot benefit from using incremental design patterns such as available legacy knowledge or the reuse of simulation models. For these cases, it seems that existing research largely disregards the corresponding challenges for the implementation of the suggested tools and approaches. Instead, successful case studies from product development are typically found in industries that build on profound legacy knowledge, such as in the automotive industry (Söderberg, Lindkvist, & Dahlström 2006; Wu, Kuang, & Hou 2019; Shan *et al.* 2020; Xiong *et al.* 2020), the aerospace industry (Forslund *et al.* 2011; Sun *et al.* 2014; Pohl *et al.* 2017; Madrid *et al.* 2019) and the defence industry (Chen *et al.* 2013; Ma *et al.* 2019; Fenrich *et al.* 2020).

Against this background, Martin & Ida (2008) explore the lack of focus on the main RD principles found in most papers by mapping out the concurrent conflicts of resource efficiency, view on interactions and one-shot versus sequential experimentation. The authors emphasize that product quality will increase when engineers understand variation and the underlying principles of robustness in general. This is of particular importance today, because design practices rely to a higher degree on virtual experiments, which enable engineers to assess robustness earlier in the development process and systematically explore a wider design space of potential solutions. At the same time, the enormous opportunities come with additional challenges, because an implementation of FEA-based variation simulation in large industrial organisations will require a seamless process between design solutions, the necessary CAD models, suitable design of experiments (DOE) for the task at hand, setting up the FEA analysis and postprocessing of results. Unfortunately, these barriers are primarily neglected in existing research, and the available studies focus primarily on the simulation itself. Typical examples are: (i) traditional sampling and approximation methods of RDO; (ii) reliability-based design optimization approaches as discussed by (Chakri et al. 2018), including sampling-based techniques from crude Monte Carlo simulations (Rashki, Miri, & Moghaddam 2012) and (iii) importance sampling (Au & Beck 1999), to moment methods such as the firstorder reliability method (Rackwitz & Flessler 1978; Camuz et al. 2019) and the second-order reliability method (Breitung 1984; Zhao & Ono 1999).

### 3. Methodology

The focus of the present research is twofold, concentrating on: (i) some key results of explorative, open-ended interviews with industry practitioners (Brix Nerenst

*et al.* 2019) to identify typical challenges and barriers that prevent the widespread use of FEA-based variation simulation in mechanical product development and (ii) a case study in collaboration with a medical device manufacturer for an in-depth technical understanding of the identified challenges. In this way, the research acknowledges the importance of understanding the practical considerations while applying the methodology during real mechanical development. These are critical aspects, because the investigated barriers and suggested solutions for future research are in the cross field between fundamental research and practical applications.

#### 3.1. Exploration of potential barriers

The barriers encountered by the industry when performing FEA-based variation simulation have been investigated through semistructured elite interviews (Brix Nerenst *et al.* 2019). Five face-to-face interviews were conducted over a 6-month period with five technical lead engineers from different companies to compile a list of relevant barriers. The five companies were carefully chosen based on their use of FEA in product development, their size and their level of legacy knowledge in designing new products. Instead of small incremental changes to an existing product, all the companies face developing completely new products to fulfil new customer requirements. In addition, the companies were selected from different industries to reduce a potential bias. The selected industries represent medical, marine, and industrial equipment, and all employ more than 1000 engineers. The selection of engineers within the companies was based on their role as mechanical leads, all having more than 10 years of experience. Therefore, the interviewees are considered part of the elite in this field of knowledge (Aberbach & Rockman 2002; Hochschild 2009).

Based on the above assumptions, the barriers identified by the interviewees are assumed to also have relevance for other companies, even more so in the case of lower maturity in the field of FEA analyses. The open interview format was chosen to investigate the complex challenges of exploring different design solutions in an industry environment, going beyond the duration of a single case study, and to allow for retrospectively exploring the interviewees' deep knowledge and impressions of today's utilization of FEA in product development. Confidentially agreements were prepared before the interviews to ensure that the actual industrial cases could be discussed in enough detail to represent their genuinely experienced barriers. The focal points of the interviews are outlined in Table 1. Parts (a) and (b) of the interviews were controlled by a 20-minute window to ensure that all topics were covered. In closing, the discussion focused on where FEA-based variation simulation would create the most significant impact in a general product development process.

#### 3.2. Evaluation of potential technical solutions: a case study

A live case study was conducted in collaboration with a participating medical device company to further analyse the experienced barriers from an industry case perspective, fully understand the mentioned barriers' underlying details and evaluate potential solutions. The case study was carried out 2 months after the interviews, allowing time to ideate, select and develop the methods, tools and

Table 1. Interview format of the two parts				
Part A	Investigate the strengths and weaknesses of the decision-making tools, expert statements, physical tests, analytical calculations and nominal FEA in order to create a baseline of the product development and map out how FEA-based variation simulation compares to alternative methods that are also used to assess the robustness of a design			
Part B	Explore the lead engineers' view on the benefits of utilizing FEA-based variation simulation and the experienced industrial barriers when applying the method			

Abbreviation: FEA, finite element analysis.

scripts for the suggested process. The purpose of the case study is to explore the identified barriers for applying FEA-based variation simulation in an industrial setting and represents the general complexity of day-to-day challenges. The technical outcome of the case study is a better understanding of the sealing process of a sterile canister when geometrical variation occurs.

The case study follows a commonly accepted approach (Prajapati 2017; Madrid *et al.* 2019) to reduce FEA-based variation simulation's computational expenses through surrogate modelling (see Figure 1). The product considered in the case study is a cylindrical glass canister on top of which a rubber layer must be held in place by an aluminium cap (see Figure 2). One of the primary functional requirements is that the holding force of the aluminium cap is sufficiently high to ensure proper sealing when exposed to external forces during transport and handling. The three parametric CAD components were modelled in full 3D in the commercial software package 3DX/CATIA (Dassault Systems 2020), with the key parametric design parameters: membrane (height, H, and width, W), cap (thickness, T, length and inner radius, R) and cartridge (inner radius, r and height, h; see Figure 3).

The material properties for the rubber membrane are viscoelastic and exposed to large compression, whereas the cap is elastic-plastic and exposed to plastic deformation. A global contact is defined with a Coulomb friction coefficient of 0.1. The cap is fixated on the top side. The translation (*d*) is applied in the negative *y*-direction on the cartridge. In order to minimize the computational time, only 10 degrees of the model are included in the FEA (Dassault Systems 2013, 2020).<sup>1</sup> An explicit solver was used to increase the robustness of the simulations, since an implicit solver can result in convergence issues when variation is applied and the amount of deformation and contact changes.

The DOE chosen is a two-level fractional factorial design  $I^{K-P}$ , where *I* is the number of levels, *K* is the number of parameters and *P* is the fraction of the full



**Figure 1.** The idealized process for performing finite element analysis-based variation simulation.

<sup>&</sup>lt;sup>1</sup>Axis-symmetric modelling was not available in 3DX version 2019.



**Figure 2.** Example of the finite element analysis results with component names and boundary conditions during deformation. The cap is fixed on the upper corner, whereas the displacement, d, is applied to the bottom of the cartridge.



**Figure 3.** Overview of the variable geometrical parameters in the undeformed state: membrane (height, H, and width, W), cap (thickness, T, length and inner radius, R) and cartridge (inner radius, r, and height, h).

design. The experimental design resulted in a total of 64 simulations required for the seven geometrical parameters. The DOE is executed using the 3DX/Process Composer, which automatically generates the geometrical changes, re-meshes,

Downloaded from https://www.cambridge.org/core. DTU Library - Technical University of Denmark, on 21 Oct 2021 at 11:06:29, subject to the Cambridge Core terms of use, available at https://www.cambridge.org/core/terms. https://doi.org/10.1017/dsj.2021.21

Table 2. Overview of key results from interviews with five lead engineers				
Outcome A	A mapping of how decision-making tools, competing with FEA-based variation simulation, are utilized today in the product development process			
Outcome B	A mapping of the barriers preventing efficient industrial use of FEA-based variation simulation			

Abbreviation: FEA, finite element analysis.

performs the FEA and stores the force curve for each simulation. An in-house python script is created to postprocess the DOE results: (i) analyse the parameter effects, (ii) create a metamodel (linear approximation) based on the significant main and interaction effects and (iii) perform a Monte Carlo simulation where each effect term is generated randomly with a normal distribution. All model parameters in Figure 3 are considered independent with a standard deviation of 7% of the mean (an approximation of the expected variation).

#### 4. Results

The following section provides a summary of the results generated from the industrial interviews and the case study. Overall, the interviews resulted in the outcomes presented in Table 2. The three most critical barriers were further explored in the industrial case study.

#### 4.1. Interview results

The interviews aimed to consider the use of FEA-based variation simulation in a general design context to understand the barriers preventing the widespread use of FEA-based variation simulation. For this purpose, Part A of the interviews focused on the question of alternative decision-making approaches and presented the interviewees with a generic design process as illustrated in the top and the middle of Figure 4. On this basis, alternative decision-making tools were discussed to clarify both the importance of different development phases and the corresponding time and resource constraints.

The bottom of Figure 4 presents Outcome A of the interviews, where the result is a mapping of the decision-making tools used, on average, by the interviewed lead engineers. Not surprisingly, Figure 4 shows that, in the early phase of a design process '*Find principle solutions*', expert knowledge is utilized to make 50% of all design decisions. Furthermore, all interviews unanimously underlined the role of innovative solutions and the task of exploring not only product concepts but also different product embodiments, which indicates that decision time is crucial during the early development phase where rapid design changes occur and explain why decisions based on numerical simulations are low during this phase.

On this basis, the discussion of Part B of the interviews resulted in a list of all commonly experienced industrial barriers across the different companies (see Brix Nerenst *et al.* 2019 and Table A1 in Appendix A). Based on the discussions with the lead engineers, an extensive list of barriers was reduced to three barriers for further investigation. These three barriers are deemed most critical in preventing the



**Figure 4.** Currently used product development methods and decision-making approaches along a generic development process.

widespread use of FEA-based variation simulation while being solvable with academic research.

All lead engineers agreed that the most relevant barrier is: (i) *a lack of CAD model maturity and robustness*, that is, limited definition of essential details and parametric modelling in the early embodiment phase. While firstly related to the time and resource aspects of parametric CAD, The lack of more useful parametric CAD methodologies leads to limited 'tuning' of existing parameters in the finalization of the design. Optimization of the robustness is therefore often limited to a highly constrained solution space.

Further complicating the matter were the software setups to achieve FEA-based variation simulation. All companies develop the CAD models in one software and perform FEA in another. The geometry is transferred from the CAD application to the FEA application in a neutral format, for example, Standard for the Exchange of Product Data STEP, whereby the CAD parametric is lost. The existing approach typically leads to an inefficient manual process where multiple new CAD models are created repeatedly to bring out the effect of changing specific design parameters. As a result of the manual process, only a few parameters (max. 1–3) are included in the DOE. In contrast, the lead engineers deemed a screening of more than 10 parameters necessary to effectively use FEA-based variation simulation when exploring different embodiments.

This desire leads to the second barrier of performing FEA-based variation simulation: (ii) *Selection of an effective DOE and postprocessing of the results require specialist knowledge*. Because the parameters increased, selecting effective designs, that is, a feasibly low number of simulations aligned with the corresponding design decisions, became increasingly difficult. Although Simpson *et al.* (2001) provide a comprehensive overview of DOEs and metamodels, industrial utilization combined

with FEA remains limited. The lead engineers explained that generating efficiently small experimental designs, postprocessing the data and trusting the results require specialized knowledge, which generally does not exist in the design teams.

The third barrier experienced is purely technical: (iii) *To date, the FEA software is found to be inadequate in supporting the automatic execution of multiple simulations.* With the time aspect in mind, the tedious manual setup and execution of each simulation require too much effort, resulting in other decision-making tools being used instead (see Figure 4).

#### 4.2. Case study results

The case study presented in Section 3 considers the sealing of a sterile canister. The case study is primarily used to detail the found barriers from a technical perspective and explore possible solutions for improving the adoption rate of FEA-based variation simulation. Due to the case of company's intellectual property, specific design details have been omitted.

The case study results in 64 successful simulations executed automatically based on a two-level fractional factorial design,  $I^{K-P} = 2^{7-1} = 64$ . The total runtime was 32 hours (Intel(R) Xeon(R) CPU E5-2690 v4 @ 2.60 GHz). Figure 5 shows the 64 force-displacement curves with a Butterworth filter applied to reduce the numerical noise (Butterworth 1930). The filtering of the raw FEA signal is performed in Python3 utilizing the Scipy package (Scipy.signal.filtfilt(); see the supplementary material of The SciPy Community 2020). The pull-off force is measured at the bottom of the glass cartridge, whereas the displacement is measured as the vertical displacement of the rigid glass cartridge. When the force is above the zero line (dotted red line), only the membrane exerts a force onto the cartridge. Because the force drops below the zero line, an additional pull force on the cartridge is required to pull the cap off, that is, the holding force. The simulations show that the holding force is above the zero line throughout the deformation for some geometrical configurations. Potentially, this results in caps being pressed off by the internal forces from the compressed membrane. For other configurations of the geometry, the holding force is below the zero line and by far exceeds the required holding force (see Figure 5). The dotted green line indicates the specified nominal force, which lies close to the average of the simulated



**Figure 5.** Filtered (Butterworth) history output of the holding force of all 64 simulations. The internal force being the force exerted by the compressed membrane. The external force being the cap's holding force.



**Figure 6.** Comparing the metamodel with the finite element analysis results to evaluate the metamodel accuracy and to check for outliers.

configurations. However, the applied geometrical variance has a large impact on the holding force. The maximum holding force is defined for each simulation and used as the functional response in the statistical analysis of the DOE. An ANOVA test is performed for the statistical analysis.

Based on the 15 main and interaction effects, a metamodel is constructed, shown in Eq. (1) with  $C_1 - C_{16}$  being parameter coefficients determined by the fractional factorial design. The metamodel achieved an accurate fit with an *R*-squared value of 0.99792.

$$\widehat{y} = C_1 - C_2 R + C_3 T + C_4 L - C_5 h + C_6 r - C_7 H - C_8 W - C_9 R T - C_{10} R r + C_{11} T L - C_{12} T h + C_{13} T r + C_{14} L r - C_{15} h r + C_{16} T L h.$$
(1)

A comparison between the FEA results and the metamodel is shown in Figure 6 to check for potential outliers, for example, avoid a missed second-order effect. The scale of the corresponding parameter effects is shown in Figure 7. The figure shows how the different geometrical parameters can increase or decrease the holding force. In this case study, the three most impactful parameters are the thickness of the cap (T), the radius of the cartridge (r) and the radius of the cap (R). A geometrical increase of T and r results in an increased holding force, whereas an increase of R reduces the holding force. Following these parameters, a number of interactions are presented, which can be challenging to predict as a designer in the case of complex geometry, whereas the DOE naturally brings out the information.

By exploiting the cost-efficient (in terms of computing resources) evaluation of the metamodel in Eq. (1), the estimated holding force of 100,000 samples is presented in Figure 8. The seven parameters included in Eq. (1) are all varied with a normal distribution with a standard deviation of 7% of the mean (an approximation of the expected variation). From Figure 8, it is seen that the mean,  $\mu$ , aligns with the product specification, and that in this example, a margin of six standard deviations exists between the mean and a holding force of zero, that is, an expected failure rate very close to 0%. However, if the standard deviation is increased to 17% of the mean, the expected failure rate is increased to 3.2%.

The results from the metamodel provide a statistical foundation to evaluate the suitability of the holding force, which in this case shows that proper sealing of the



**Figure 7.** Main and interaction effects sorted by the impact on the holding force. An overview of possible parameters to adjust the design performance.



**Figure 8.** The estimated distribution of the holding force for 100,000 produced samples. The nominal holding force is denoted  $\mu$  and one standard deviation as  $\sigma$ .

cap is ensured within the allowed variation. The metamodel demonstrates that a cap can only be pushed off in sporadic cases, because the probability of all parameters contributing to a low holding force is very low. The probabilistic evaluation can provide greater insight into the design performance than just relying on the direct DOE data visualized in Figure 5. FEA-based variation simulation can be used to calculate the cost of a given tolerance specification versus the expected production scrape rate, because such tolerance calculations have an enormous potential to reduce production costs across industries. Overall, the DOE approach provides a much more detailed design understanding compared with the safety-factor approach.

#### Results of barrier mitigation

The following explores how the three main barriers were investigated and suggests future research and improvements. A summary of the derived results is provided in Table 4.

A lack of CAD model maturity and robustness. In the case study, the CAD assembly of an existing product was used, so that the question of CAD model maturity played a minor role in the investigation. However, while only containing

**Table 3.** Resilient modelling increases the CAD model robustness by creating features in a specific sequence. This removes wrongful links between 'parent' and 'child' features which can disrupt the regeneration

Group	Description	Typical features
1. Ref	Reference entities, no solids are allowed	Ref bodies, layouts, sketches, planes, coordinate systems and images
2. Construction	Construction features, such as surfaces and 3D curves used to define complex solid features	Surfaces, project, extend, split, trim and 3D curves
3. Core	Core solids that determine the overall shape of the structure	Extrude, revolve, sweep, loft, thin wall and shell
4. Detail	Detailed feature to refine the shape. Can only link to the core group	Extrude, revolve, sweep, loft and hole thread
5. Modify	Modify and replicate existing features	Draft, pattern and mirror
6. Quarantine	Volatile features which should under no circumstances be 'parent' features	Chamfer, round and blend

two components and seven parameters, the original company CAD models were shown to be poorly configured and had no parametric controls. The result was regeneration issues due to unrobust modelling. Figure 9 shows an example of the original sketch constraints for one key parameter (masked other specifications). The red highlight in Figure 10 shows how parameter configurations can result in unsuccessful regeneration of sketches. Another experienced issue with the regeneration of CAD models was that one feature refers to another feature not yet generated. Creating a model which disregards the 'parent–child'<sup>2</sup> relationships can become very sensitive.

For addressing-related issues, and based on existing work on CAD methodologies (Camba, Contero, & Company 2016), the case study subsequently implemented a resilient modelling strategy to mitigate feature regeneration issues. Resilient modelling (Gebhard 2013) suggests organizing the feature tree in six standardized groups, as shown in Table 3. In the case study, it was possible to increase the CAD models' ability to regenerate to 100% when combining resilient modelling and stacking of sketch constraints. Figure 11 shows a simple example of an improved configuration, where the constraints ensure a successful regeneration for positive dimensions of L1–L3 (no fold-over as seen in Figure 10).

Surprisingly, based on the interviews and the professional experience by the authors, CAD modelling methodologies are, however, not widely accepted as standard industry practice. The lack of use is in line with previous research, for example, the work of Aranburu, Justel, & Angulo (2020), who clearly highlight the need for increased focus on robust CAD models. Although some DOE techniques (Latin hypercube sampling) can cope with data loss, that is, some of the simulations are allowed to fail, it often comes at the cost of a more significant number of simulations. The latter is particularly critical from a design perspective, where the

Downloaded from https://www.cambridge.org/core. DTU Library - Technical University of Denmark, on 21 Oct 2021 at 11:06:29, subject to the Cambridge Core terms of use, available at https://www.cambridge.org/core/terms. https://doi.org/10.1017/dsj.2021.21

<sup>&</sup>lt;sup>2</sup>A 'parent' is a stand-alone feature and does not refer to others. A 'child' feature refers to another feature to exist.









Table 4. Necessary design support for early finite element analysis-based variation assessment				
General barrier	Required methodical or technical support			
	Review and implementation of available CAD methodologies			
	Complement existing methodologies by developing practical guidelines for applying sketch constraints to ensure robust CAD models			
Maturity/robustness of CAD models	Ruleset for control of assembly constraints in variation simulations, that is, standardized rules for applying variation to assemblies and avoid interferences (e.g., in case of tilt or misalignment between components)			
	Ruleset for systematic consideration of project and technology constraints, for example, product's overall size or manufacturing constraints such as moulding requirements (minimum thickness, gate position, etc.)			
	Development of a DOE selection tool for engineers working with FEA (without statistical background), including archetypical design decisions/ tasks such as parameter screening, comparison of several design solutions, metamodelling, design space exploration and robustness verification			
Selection of effective DOE strategy	Guidelines for DOE augmentation for a suitable two-step procedure, for example, (i) design comparison and (ii) detailed exploration of optimal designs			
	Development and implementation of targeted DOE education for FEA engineers (without statistical background)			
	Improvement of software interfaces or direct integration of CAD and FEA modelling			
	Development of suitable information visualization techniques for communication of results			
Automatic execution	Guidelines for node/element set selection for robust and correct positioning including uncertainty assessment			
	Possibilities for customized result extraction, for example, by company standard scripts (will require improved possibilities for scripting within the software)			

Abbreviations: DOE, design of experiments; FEA, finite element analysis.

task is not necessarily a fully validated simulation but an efficient and sufficiently accurate estimation of parameter effects.

Selection of an effective DOE and postprocessing of the results require specialist knowledge. The options for different DOEs were experienced to be vast in the commercial software, either as a built-in option or as an upload possibility for pregenerated design matrices. However, specialized guidance, particularly on options for augmentation, and suitability for metamodelling, is experienced to be nonexistent. Instead, only general descriptions of the experimental designs are provided. Although some guidance does exist in literature (Simpson *et al.* 2001), the complexity and fundamental understanding of how to choose a suitable DOE for a variety of design decisions will require additional education of industrial FEA



Figure 11. Alternative sketch constraints to increase robustness.

specialists. Without this knowledge, experimental designs can promise similar capabilities, while the number of required runs can vary significantly or contain other limitations. For example, the case study utilized 64 runs to explore all possible interaction effects. However, a subsequent investigation proved this unnecessary and that 32 runs would have been sufficient for exploring factor relevance from a design perspective. However, none of the companies had standard DOE procedures for the wide variety of design decisions and tasks, such as parameter screening, metamodelling or probabilistic evaluation, in place.

To date, the FEA software is found to be inadequate in supporting the automatic execution of multiple simulations. In this case study, the FEA-based variation simulation resulted in the process shown in Figure 12. Due to the requirements experienced for robust CAD, data extraction and postprocessing, the depicted process differs from the more straightforward process described in the literature



**Figure 12.** Illustration of the data flow used in the finite element analysis (FEA)-based variation simulation study. The process highlights the need for robust CAD and shows how the design of experiments and FEA is executed in 3DEXPERIENCE, while further postprocessing of the raw data is performed in Python.



**Figure 13.** Example of proximity selection. This method includes all nodes/elements within a defined range of a reference line or surface.

(see Figure 1). The case study shows how commercial FEA software can execute 64 simulations without interruptions, making the process significantly more efficient and less prone to human error by omitting manual CAD configuration and STEP format. Although the software provides some automatic postprocessing capabilities, the case study also shows that programming knowledge is required to enable flexibility. In conventional FEA, the results of deformation and stress/strain contours are interpreted manually by the specialist in an interactive viewer environment. However, when FEA is combined with an automated DOE process, the result of interest must be predefined, and a scheme to extract the results must be made automatic. In this case study, the holding force on the cartridge is stored as a history output within an additional process step scripted in Visual Basic for Applications VBA. In other cases, the strain or stress in a specific region of the structure might be of interest. The pitfall is that the size and position of the node/ element set can be affected by the selection options combined with changing geometry due to the applied variation. Although commercial software provides multiple methods for node/element set selection (see the example in Figures 13-15), the robust and correct positioning will be essential, because the automated process makes it difficult to trace back the corresponding influences.

#### 5. Discussion and conclusion

A combined investigation of interviews and a case study with well-established companies utilizing FEA for product development is performed to explore the barriers preventing the widespread use of FEA-based variation simulation. Based on five interviews, the corresponding lead engineers from different industry sectors acknowledged the potential of improving the current development by achieving more RDs at a lower cost and unanimously underlining that the current state-of-the-art commercial software does not yet provide integrated and seamless solutions



**Figure 14.** Example of spatial selection. This method includes all nodes/elements within a sphere or box placed in the global coordinate system.



**Figure 15.** Example of partitioning selection. This method includes all nodes/elements within a volume controlled by partitioning.

to overcome the barriers to making FEA-based variation simulation a daily exercise in an industry environment.

Against this background, the subsequent case study shows how FEA-based variation simulation provides the potential to explore and understand variation. The method enables engineers to identify significant design parameters, virtually investigate the performance of 100,000 designs and finally evaluate tolerance specifications versus scrap rate.

The present work sets itself apart from existing research by focusing on industries where entirely new concepts are developed, explored and compared continuously. Therefore, some of the derived methodical and technical support measures might very well be less relevant in industries with profound legacy knowledge and more incremental design changes, that is, where the used models have received significantly more attention over the years.

Although the case study underlines that performing simpler forms of FEAbased variation simulation for design purposes is achievable, the critical difference between the industry projects and the case study is still the time aspect. The work laid out is essentially unbounded in time. Thus, the case study allowed multiple iterations to set up a proper CAD model for subsequent use in the FEA-based variation simulation and investigate potential DOEs. Although the presented work should therefore be considered a first step to a more systematic implementation of FEA-based variation simulation in industry, it also clearly shows a discrepancy between the advanced developments being made in literature and the utilization of FEA-based variation simulation in the broader field of mechanical engineering. Although research primarily focuses on more sophisticated algorithms for multiobjective RDO, the broader engineering industry struggles with more fundamental parts of the process. For this reason, the present study provides new research directions to enhance the uptake of FEA-based variation simulation and support a wider range of mechanical design companies on the transition from safety factors to a probabilistic design approach.

#### References

- Aberbach, J. & Rockman, B. 2002 Conducting and coding elite interviews. PS: Political Science and Politics 35, 673–676.
- Aranburu, A., Justel, D. & Angulo, I. 2020 Reusability and flexibility in parametric surfacebased models: a review of modelling strategies. *Computer-Aided Design and Applications* 18 (4), 864–874; doi:10.14733/cadaps.2021.864-874. URL: http://cad-journal.net/ files/vol\_18/Vol18No4.html.
- Au, S. K. & Beck, J. L. 1999 A new adaptive importance sampling scheme for reliability calculations. *Structural Safety* 21 (2), 135–158; doi:10.1016/S0167-4730(99)00014-4.
- Box, G., Bisgaard, S. & Fung, C. 1988 An explanation and critique of Taguchi's contributions to quality engineering. *Quality and Reliability Engineering International* 4 (2), 123–131; doi:10.1002/qre.4680040207.
- Breitung, K. 1984 Asymptotic approximations for multinormal integrals. *Journal of Engineering Mechanics* 110 (3), 357–366.
- Brix Nerenst, T., Ebro, M., Nielsen, M., Eifler, T. & Nielsen, K. L. 2019 Barriers for virtual assessment of structural robustness. In *Volume 2B: Advanced Manufacturing (Vol.* 2B-2019), p. 10. American Society of Mechanical Engineers; doi:10.1115/IMECE2019-11251. URL: https://asmedigitalcollection.asme.org/IMECE/proceedings/IMECE2019/ 59384/SaltLakeCity,Utah,USA/1072920.
- Butterworth, S. 1930 "On the theory of filter amplifiers," *Experimental Wireless and the Wireless Engineer*, Vol. 7, 1930, pp. 536–541. https://www.scirp.org/(S(oyulxb452aln t1aej1nfow45))/reference/ReferencesPapers.aspx?ReferenceID=635334.
- Camba, J. D., Contero, M. & Company, P. 2016 Parametric CAD modeling: an analysis of strategies for design reusability. *Computer-Aided Design* 74, 18–31; doi:10.1016/j. cad.2016.01.003.

- Camuz, S., Bengtsson, M., Söderberg, R. & Wärmefjord, K. 2019 Reliability-based design optimization of surface-to-surface contact for cutting tool interface designs. *Journal of Manufacturing Science and Engineering, Transactions of the ASME* 141 (4), 1–7; doi: 10.1115/1.4042787.
- Capiez-Lernout, E. & Soize, C. 2008 Robust design optimization in computational mechanics. *Journal of Applied Mechanics* 75 (2), 021001; doi:10.1115/1.2775493.
- Chakri, A., Yang, X. S., Khelif, R. & Benouaret, M. 2018 Reliability-based design optimization using the directional bat algorithm. *Neural Computing and Applications* 30 (8), 2381–2402; doi:10.1007/s00521-016-2797-3.
- Chen, J., Tang, Y., Ge, R., An, Q. & Guo, X. 2013 Reliability design optimization of composite structures based on PSO together with FEA. *Chinese Journal of Aeronautics* 26 (2), 343–349; doi:10.1016/j.cja.2013.02.011.
- Coleman, P. 2012 CRESCENDO Collaborative and Robust Engineering using Simulation Capability Enabling Next Design Optimisation. TRIMIS – Transport Research and Innovation Monitoring and Information System. URL: https://trimis.ec.europa.eu/pro ject/collaborative-robust-engineering-using-simulation-capability-enabling-nextdesign#tab-partners.

Dassault Systems 2013 ABAQUS 6.9 User Documentation.

- Dassault Systems 2020 3DEXPERIENCE. URL: https://www.3ds.com/.
- Draper, B. N. R. & George, E. P. 2007 Response Surfaces, Mixtures and Ridge Analyses (Vol. 49). John Wiley & Sons, Inc.; doi:10.1198/tech.2007.s698.
- Du, X. & Chen, W. 2004 Sequential optimization and reliability assessment method for efficient probabilistic design. *Journal of Mechanical Design, Transactions of the ASME* 126 (2), 225–233; doi:10.1115/1.1649968.
- Eckert, C., Isaksson, O. & Earl, C. 2019 Design margins: a hidden issue in industry. *Design Science* 5, 1–24; doi:10.1017/dsj.2019.7.
- Eifler, T. & Howard, T. J. 2018 The importance of robust design methodology: case study of the infamous GM ignition switch recall. *Research in Engineering Design* 29 (1), 39–53; doi:10.1007/s00163-017-0251-x.
- Fenrich, R. W., Menier, V., Avery, P. & Alonso, J. J. 2020 Reliability-based design optimization of a supersonic nozzle. In Proceedings of the 6th European Conference on Computational Mechanics: Solids, Structures and Coupled Problems, ECCM 2018 and 7th European Conference on Computational Fluid Dynamics, ECFD 2018, pp. 2783–2794.
- Forslund, A., Söderberg, R., Isaksson, O. & Lööf, J. 2011 Multidisciplinary robustness evaluations of aero engine structures. In 20th International Symposium on Air Breathing Engines 2011 (ISABE 2011), pp. 1–9. URL: http://publications.lib.chalmers.se/records/ fulltext/local 153540.pdf.
- Gebhard, R. 2013 A Resilient Modeling Strategy. Technical Presentation, p. 36.
- Göhler, S. M., Ebro, M. & Howard, T. J. 2018 Mechanisms and coherences of robust design methodology: a robust design process proposal. *Total Quality Management and Business Excellence* 29 (3–4), 239–259; doi:10.1080/14783363.2016.1180952.
- Gremyr, I., Arvidsson, M. & Johansson, P. 2003 Robust design methodology: status in the Swedish manufacturing industry. *Quality and Reliability Engineering International* 19 (4), 285–293; doi:10.1002/qre.584.
- Hamada, M., Wu, C.-F. & Jeff, W. C.-F. 2000 Experiments: Planning, Analysis, and Parameter Design Optimization. Wiley.
- Hochschild, J. L. 2009 Conducting Intensive Interviews and Elite Interviews. URL: http:// www.nsf.gov/sbe/ses/soc/ISSQR\_workshop\_rpt.pdf.

- Jin, R., Chen, W. & Sudjianto, A. 2003 An efficient algorithm for constructing optimal design of computer experiments. In *Volume 2: 29th Design Automation Conference*, *Parts A and B*, pp. 545–554. ASMEDC; doi:10.1115/DETC2003/DAC-48760. URL: https://asmedigitalcollection.asme.org/IDETC-CIE/proceedings/IDETC-CIE2003/ 37009/545/297602.
- Joseph, V. R., Gu, L., Ba, S. & Myers, W. R. 2019 Space-filling designs for robustness experiments. *Technometrics* **61** (1), 24–37; doi:10.1080/00401706.2018.1451390.
- Kriegesmann, B. 2020 Robust design optimization with design-dependent random input variables. *Structural and Multidisciplinary Optimization* 61 (2), 661–674; doi:10.1007/ s00158-019-02388-3.
- Krogstie, L., Ebro, M. & Howard, T. J. 2015. How to implement and apply robust design: insights from industrial practice. *Total Quality Management and Business Excellence* 26 (11–12), 1387–1405; doi:10.1080/14783363.2014.934520.
- Laycock, P. J., Atkinson, A. C. & Donev, A. N. 1995 Optimum experimental designs. Biometrics 51 (1), 397; doi:10.2307/2533349.
- Lehman, J. S., Santner, T. J. & Notz, W. I. 2004 Designing computer experiments to determine robust control variables. *Statistica Sinica* 14 (2), 571–590.
- Li, W., Gao, L. & Xiao, M. 2020 Multidisciplinary robust design optimization under parameter and model uncertainties. *Engineering Optimization* 52 (3), 426–445; doi: 10.1080/0305215X.2019.1590564.
- Logothetis, H. P. & Wynn, N. 1990. Quality Through Design: Experimental Design, Off-Line Quality Control, and Taguchi's Contributions, p. 464. Oxford University Press and Oxford Science Publications; doi:10.2307/2348237.
- Ma, Y., Wang, X., Shi, Q. & Ren, Q. 2019. Coordinative optimization method of composite laminated structures based on system reliability. *Structural and Multidisciplinary Optimization* 59 (5), 1483–1501; doi:10.1007/s00158-018-2141-x.
- Madrid, J., Lorin, S., Söderberg, R., Hammersberg, P., Wärmefjord, K. & Lööf, J. 2019 A virtual design of experiments method to evaluate the effect of design and welding parameters on weld quality in aerospace applications. *Aerospace* 6 (6), 74; doi:10.3390/ AEROSPACE6060074.
- Martin, A. & Ida, G. 2008 Principles of robust design methodology. *Quality and Reliability* Engineering International 24 (1), 23–35; doi:10.1002/qre.
- Pahl, G., Beitz, W., Feldhusen, J. & Grote, K.-H. 2007 Engineering Design, 3rd edn. Springer.
- Park, G. J., Lee, T. H., Lee, K. H. & Hwang, K. H. 2006 Robust design: an overview. AIAA Journal 44 (1), 181–191; doi:10.2514/1.13639.
- Parnianifard, A., Azfanizam, A. S., Ariffin, M. K. & Ismail, M. I. 2018 An overview on robust design hybrid metamodeling: advanced methodology in process optimization under uncertainty. *International Journal of Industrial Engineering Computations* 9 (1), 1–32; doi:10.5267/j.ijiec.2017.5.003.
- Pohl, J., Thompson, H. M., Schlaps, R. C., Shahpar, S., Fico, V. & Clayton, G. A. 2017 Innovative turbine stator well design using a kriging-assisted optimization method. *Journal of Engineering for Gas Turbines and Power* 139 (7), 1–9; doi:10.1115/1.4035288.
- Prajapati, V. S. 2017 Topology optimization of automotive disc brake using FEA–DOE hybrid modeling. *IOSR Journal of Mechanical and Civil Engineering* 14 (2), 72–80; doi: 10.9790/1684-1402037280.
- Rackwitz, R. & Flessler, B. 1978 Structural reliability under combined random load sequences. Computers and Structures 9 (5), 489–494; doi:10.1016/0045-7949(78)90046-9.

- Rashki, M., Miri, M. & Moghaddam, M. A. 2012 A new efficient simulation method to approximate the probability of failure and most probable point. *Structural Safety* 39, 22–29; doi:10.1016/j.strusafe.2012.06.003.
- Raza, M. A. & Liang, W. 2012 Uncertainty-based computational robust design optimisation of dual-thrust propulsion system. *Journal of Engineering Design* 23 (8), 618–634; doi:10.1080/09544828.2011.636011.
- Robinson, T. J., Borror, C. M. & Myers, R. H. 2004 Robust parameter design: a review. Quality and Reliability Engineering International 20 (1), 81–101; doi:10.1002/qre.602.
- Shan, Z., Long, J., Yu, P., Shao, L. & Liao, Y. 2020 Lightweight optimization of passenger car seat frame based on grey relational analysis and optimized coefficient of variation. *Structural and Multidisciplinary Optimization* 62, 3429–3455; doi:10.1007/s00158-020-02647-8.
- Simpson, T. W., Peplinski, J. D., Koch, P. N. & Allen, J. K. 2001 Metamodels for computer-based engineering design: survey and recommendations. *Engineering With Computers* 17 (92), 129–150.
- Söderberg, R., Lindkvist, L. & Dahlström, S. 2006 Computer-aided robustness analysis for compliant assemblies. *Journal of Engineering Design* 17 (5), 411–428; doi: 10.1080/09544820500275800.
- Suh, N. P. 1995 Axiomatic design of mechanical systems. Journal of Mechanical Design, Transactions of the ASME 117 (B), 2–10; doi:10.1115/1.2836467.
- Sun, G., Song, X., Baek, S. & Li, Q. 2014 Robust optimization of foam-filled thin-walled structure based on sequential Kriging metamodel. *Structural and Multidisciplinary Optimization* 49 (6), 897–913; doi:10.1007/s00158-013-1017-3.
- Taguchi, G., Chowdhury, S. & Wu, Y. 2007 Taguchi's Quality Engineering Handbook. Wiley Blackwell; doi:10.1002/9780470258354.
- The SciPy Community 2020 Scipy. URL: https://docs.scipy.org/doc/scipy/reference/gener ated/scipy.signal.filtfilt.html.
- Will, J. 2015 Robust design optimization in virtual prototyping promises and challenges. In NAFEMS - International Association Engineering Modelling. https://www.dynardo. de/en/library/methodology/robust-design-optimization.html
- Wu, H., Kuang, S. & Hou, H. 2019 Research on application of electric vehicle collision based on reliability optimization design method. *International Journal of Computational Methods* 16 (7), 1–16; doi:10.1142/S0219876219500348.
- Xie, T., Jiang, P., Zhou, Q., Shu, L., Zhang, Y., Meng, X. & Wei, H. 2018 Advanced multiobjective robust optimization under interval uncertainty using kriging model and support vector machine. *Journal of Computing and Information Science in Engineering* 18 (4), 1–14; doi:10.1115/1.4040710.
- Xiong, F., Zou, X., Zhang, Z. & Shi, X. 2020 A systematic approach for multi-objective lightweight and stiffness optimization of a car body. *Structural and Multidisciplinary Optimization* 62, 3229–3248; doi:10.1007/s00158-020-02674-5.
- Zhao, Y. G. and Ono, T. 1999 A general procedure for first/second-order reliability method (FORM/SORM). Structural Safety 21 (2), 95–112; doi:10.1016/S0167-4730(99)00008-9.

## Appendix A. Extensive barrier list

 Table A1. Overview of discussed barriers with the five interviewed lead engineers (Brix Nerenst et al. 2019)

Barrier description and type				
Limited commercial software for FEA-based variation simulation	Technical			
FEA-based variation simulation is complex compared with other decision tools	Technical			
DOE selection is complex and requires trial and error	Technical			
FEA-based variation simulation requires a data exchange between software	Technical			
Difficulty working with model design and simulation in parallel	Technical			
Difficulty automating analysis and postprocessing of the results	Technical			
Limited knowledge of FEA-based variation simulation in the industry	Knowledge			
Limited vision from management on implementing advanced methodology	Knowledge			
The tradition of working with safety factors – difficulty with change	Knowledge			
Simulations can exceed the project time constrains	Practical			
FEA-based variation simulation increases cost (software license and specialists)	Practical			
Difficult ensuring traceability between models and results	Practical			
Traceability of why for design changes were implemented	Practical			
Steep learning curve which lowers the willingness to implement	Practical			
Limited specialists are available in the industry	Practical			
Parameterization of CAD models is complicated and expensive	Practical			
Advanced simulations can increase potential mistrust in the results	Practical			
The simulation output is difficult to convert into design changes for the designer	Practical			
Difficult to convey advanced probabilistic results in short management meetings	Practical			

Abbreviations: DOE, design of experiments; FEA, finite element analysis.