



State-of-the-art Quantum Dot-based Single-photon Sources for Quantum Key Distribution in Silica Fiber Networks at 1550 nm

Holewa, Pawel; Ostój-Zięba, Emilia; Vajner, Daniel A. ; Gao, Timm ; Lach, Mareike; Wasiluk, Maja; Gaal, Benedek; Sakanas, Aurimas; Burakowski, Marek; Mrowiński, Paweł

Total number of authors:
19

Publication date:
2023

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Holewa, P., Ostój-Zięba, E., Vajner, D. A., Gao, T., Lach, M., Wasiluk, M., Gaal, B., Sakanas, A., Burakowski, M., Mrowiński, P., Krajnik, B., Xiong, M., Huck, A., Yvind, K., Gregersen, N., Musial, A., Heindel, T., Semenova, E., & Syperek, M. (2023). *State-of-the-art Quantum Dot-based Single-photon Sources for Quantum Key Distribution in Silica Fiber Networks at 1550 nm*. Abstract from 51st International School & Conference on the Physics of Semiconductors, Szczyrk, Poland.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

State-of-the-art Quantum Dot-based Single-photon Sources for Quantum Key Distribution in Silica Fiber Networks at 1550 nm

Paweł Holewa^{1,2,3}, Emilia Ostój-Zięba¹, Daniel A. Vajner⁴, Timm Gao⁴, Mareike Lach⁴, Maja Wasiluk¹, Benedek Gaal², Aurimas Sakansas², Marek Burakowski¹, Paweł Mrowiński¹, Bartosz Krajnik¹, Meng Xiong^{2,3}, Aleksander Huck⁵, Kresten Yvind^{2,3}, Niels Gregersen², Anna Musiał¹, Tobias Heindel⁴, Elizaveta Semenova^{2,3} and Marcin Syperek¹

¹ *Department of Experimental Physics, Faculty of Fundamental Problems of Technology, Wrocław University of Science and Technology, 50-370 Wrocław, Poland*

² *DTU Electro, Technical University of Denmark, Kongens Lyngby 2800, Denmark*

³ *NanoPhoton-Center for Nanophotonics, Technical University of Denmark, 2800 Kongens Lyngby, Denmark*

⁴ *Institute of Solid State Physics, Technical University of Berlin, 10623 Berlin, German*

⁵ *Center for Macroscopic Quantum States (bigQ), Department of Physics, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark*

Optical fiber-based quantum network connecting remote nodes forms the backbone to implement ultra-secure data exchange protocols and schemes, utilizing a quantum state of a single photon. Notably, for such quantum networks existing silica-fiber-based infrastructure can be used, where the spectral window around 1550 nm provides a low-loss photon transmission channel for long-haul communication. Moreover, one can benefit from existing devices and classical signal management protocols, simplifying the preparation, encoding and transfer of quantum states. Devices producing single photon states on demand are considered key building blocks of future quantum networks. While several single-photon sources (SPS) operating in the telecom C-band, including sources based on non-linear frequency conversion or emerging materials, have been demonstrated to date, semiconductor quantum dots (QDs) are among the most promising candidates, enabling exceptional performance and engineered photonic devices.

In this presentation, we show a deterministically-fabricated optically-triggered SPS emitting in the telecom spectral range near 1550 nm. The SPS consists of a single pre-selected self-assembled InAs/InP QD embedded in a circular Bragg grating cavity for Purcell-enhanced emission of the embedded quantum emitter. The applied deterministic fabrication technique results in a high device yield in combination with excellent quantum-optical properties, paving the way for scalable applications in photonic quantum information technologies. The high Purcell enhancement with $F_p = 5$ realized in our device, shows potential for single photon generation at GHz rates. Moreover, the cavity's far-field emission pattern allows for efficient photon extraction close to 17% at the numerical aperture 0.4, which can be further optimized for the coupling to single-mode fibers. The device provides high single photon emission purity with $g^{(2)}(0) = 3.2 \times 10^{-3}$ at $T = 4.2$ K, while still supporting a good performance ($g^{(2)}(0) = 0.2$) at elevated temperatures ($T = 50$ K) accessible with compact Stirling-type cryocoolers. Finally, Hong-Ou-Mandel-type two-photon interference (TPI) experiments reveal record-high photon indistinguishabilities of 19% in the as-measured case and 99.8% with temporal post-selection.

Finally, we evaluated our SPS in a test environment for its potential implementation in polarization-encoded BB84 quantum key distribution (QKD) in silica fiber networks. A careful benchmarking of the performance of our source compared with previous single-photon QKD experiments reveals that transmission distances in excess of 100 km can be expected in full implementations.