



Dynamic SEM in-situ studies: A tool to investigate microstructural evolution during metal additive manufacturing?

König, C.; Sneppen, T.B.; Bastos da Silva Fanta, A.; Jinschek, J.

Publication date:
2023

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
König, C., Sneppen, T. B., Bastos da Silva Fanta, A., & Jinschek, J. (2023). *Dynamic SEM in-situ studies: A tool to investigate microstructural evolution during metal additive manufacturing?*. Abstract from 3rd Asia-Pacific International Conference on Additive Manufacturing, Sydney, New South Wales, Australia.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Dynamic SEM in-situ studies: A tool to investigate microstructural evolution during metal additive manufacturing?

Koenig C.¹, Sneppen, T.B.¹, Bastos da Silva A.¹, Jinschek J.¹

¹DTU Nanolab, Technical University of Denmark, Kgs. Lyngby, Denmark

An anisotropic microstructure is typical of metal components fabricated by plasma arc additive manufacturing (PLAAM) with a site-specific microstructure, due to non-equilibrium cooling conditions and the unique process parameters. Additionally, previously deposited layers are subjected to cyclic heat inputs during the manufacturing process, which can result in element diffusion, phase transitions, or changes in grain morphology.

In this study, in-situ scanning electron microscopy (SEM) methods are developed to better understand the complex spatial-temporal thermal transients that AM components are subjected to during fabrication. Our emphasis is on developing microscopy techniques required to simulate such a temperature profile on a sufficiently large sample compared to a typical grain size in AM components. The temperature distribution in bulk samples on the MEMS-SEM microheaters is predicted using COMSOL simulations. The dynamic changes in the microstructure are analyzed using electron backscatter diffraction (EBSD) and SEM imaging during a cyclic heating experiment. This study will allow to draw conclusions on the feasibility of using SEM-based heating studies to develop a fundamental understanding of microstructure formation during PLAAM processes.