



## Monolithic Selenium/Silicon Tandem Solar Cells

Nielsen, Rasmus; Crovetto, Andrea; Assar, Alireza; Hansen, Ole; Chorkendorff, Ib; Vesborg, Peter

*Publication date:*  
2024

*Document Version*  
Peer reviewed version

[Link back to DTU Orbit](#)

*Citation (APA):*

Nielsen, R., Crovetto, A., Assar, A., Hansen, O., Chorkendorff, I., & Vesborg, P. (2024). *Monolithic Selenium/Silicon Tandem Solar Cells*. Abstract from 2024 MRS Spring Meeting & Exhibit, Seattle, Washington, United States.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Monolithic selenium/silicon tandem solar cells

Rasmus Nielsen

Elemental selenium, the world's oldest photovoltaic material, is reemerging as a promising inorganic thin-film PV absorber. With a direct bandgap of 1.95 eV in its trigonal phase and a high absorption coefficient ( $>10^5 \text{ cm}^{-1}$ ) in the visible region, it is a promising candidate for the top cell in tandem devices. Furthermore, its long-term air stability, monoatomic composition, and low melting point of 220°C makes processing simple, low-cost, and compatible with most bottom cells.

We present the first monolithically integrated selenium/silicon tandem solar cell, demonstrating a highly encouraging open-circuit voltage of 1.68 V. Guided by device simulations, we identify critical energy barriers restricting the flow of charge carriers and investigate the potential of using other carrier-selective contact materials, resulting in a tenfold increase in the overall power conversion efficiency. In parallel with the tandem devices, we fabricate and characterize bifacial single junction selenium solar cells to gain insights into the polarity-dependent PV performance. In view of these results, we set forth strategies for further improving the device performance to realize higher efficiency selenium/silicon tandem solar cells.