Analysis of bit-stuffing codes and lower bounds on capacity for 2-D constrained arrays using quasistationary measures

Forchhammer, Søren

Published in:

Proceedings. International Symposium on Information Theory, 2004. ISIT 2004.

Link to article, DOI:

[10.1109/ISIT.2004.1365199](https://doi.org/10.1109/ISIT.2004.1365199)

Publication date:

2004

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Forchhammer, S. (2004). Analysis of bit-stuffing codes and lower bounds on capacity for 2-D constrained arrays using quasistationary measures. In *Proceedings. International Symposium on Information Theory, 2004. ISIT 2004*. IEEE. <https://doi.org/10.1109/ISIT.2004.1365199>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Analysis of Bit-Stuffing Codes and Lower Bounds on Capacity for 2-D Constrained Arrays using Quasi-Stationary Measures

Søren Forchhammer
Research Center COM, 345v
Technical University of Denmark
DK-2800 Lyngby, Denmark
e-mail: sf@com.dtu.dk

Abstract — A method for designing quasi-stationary probability measures for two-dimensional (2-D) constraints is presented. This measure is derived from a modified bit-stuff coding scheme and it gives the capacity of the coding scheme. This provides a constructive lower bound on the capacity of the 2-D constraint. The main examples are checkerboard codes with binary elements. The capacity for one instance of the modified bit-stuffing for the 2-D runlength-limited RLL(2, ∞) constraint is calculated to be 0.4414 bits/symbol. For the constraint given by a minimum (1-norm) distance of 3 between 1s a code with capacity 0.3497 bits/symbol is given.

I. INTRODUCTION

We present a method for designing two-dimensional (2-D) constrained codes based on bit-stuffing. We consider 2-D arrays with elements taken from a finite alphabet. The constraint is specified by the set of admissible configurations on an N by M rectangle. For 2-D RLL(1, ∞), bit-stuffing provides efficient coding [1]. In [2] bit-stuffing for 2-D RLL(d , ∞), $d \geq 2$ were considered. We shall take a slightly different approach to bit-stuffing in order to facilitate analysis e.g. providing a constructive lower bound on the capacity of the constraint. The method is generally applicable to checkerboard constraints, where a 1 must be surrounded by a certain pattern of 0s, meaning that a 0 is always admissible.

II. QUASI-STATIONARY MEASURES

A quasi stationary measure may be introduced by concatenating arrays. Given a constraint, let $\mathbf{W}$ denote a stochastic variable defined on an n by m array, which may take on any configuration admissible by the constraint. Let $\mathbf{X}$ and $\mathbf{Z}$ denote variables representing the first and last $M - 1$ columns (with n elements). Let $\mathbf{Y}$ denote a variable representing the middle $m - 2M + 2$ columns. We assume that the measures on the boundaries, $\mathbf{X}$ and $\mathbf{Z}$ are identical for the measures, $\mathbf{W}$ to be considered. Thus, starting with $\mathbf{X}_0 \mathbf{Y}_0 \mathbf{Z}_0$, arrays $\mathbf{Y}_i \mathbf{Z}_i$ may repeatedly be added to form $\mathbf{X}_0 \{\mathbf{Y}_j \mathbf{Z}_j\}_0^K$, such that $\mathbf{Z}_{i-1} \mathbf{Y}_i \mathbf{Z}_i$ has the same measure as $\mathbf{W}$. The entropy (per symbol) is given by the conditional entropy of $\mathbf{Y}_i \mathbf{Z}_i$ given $\mathbf{Z}_{i-1}$ which is

$$\frac{H_W(m) - H_X(M-1)}{m - M + 1}. \quad (1)$$

where $H_W(m)$ is the entropy of $\mathbf{W}$ (per row) and $H_X(M-1)$ is the entropy of $\mathbf{X}$ (per row). A simple way to specify $\mathbf{W}$ in (1) is to assign probabilities to the bit-stuffing scheme below. The boundaries $\mathbf{X}$ and $\mathbf{Z}$ are specified by identical but independent bit-stuffing schemes. The middle columns $\mathbf{Y}$ are specified by bit-stuffing conditional on the boundaries $\mathbf{X}$ and $\mathbf{Z}$.

III. NUMERICAL RESULTS

Two examples with binary elements and constraint size $N = M = 3$ are considered. For the RLL(2, ∞) constraint, analysis of the modified bit-stuffing was carried out calculating capacities, C for $m = 12$. The transition probabilities for a new row of $\mathbf{W}$ were determined by the products of (conditional) probabilities addressing and bit-stuffing the elements of the new line of $\mathbf{X}$ and $\mathbf{Z}$ before $\mathbf{Y}$ and using the same conditional probabilities for the corresponding elements of $\mathbf{X}$ and $\mathbf{Z}$. Thus the prerequisites for (1) is satisfied. Let p_1 denote the probabilities of writing a 1 when this is admissible. Simple bit-stuffing writing an unbiased sequence with $p_1 = 1/2$ gave $C = 0.388$. Using a single biased sequence gave $C = 0.437$ for optimal choice of p_1 . Finally the values of p_1 may be chosen independently for each column of $\mathbf{X}$ and $\mathbf{Y}$. (The p_1 values of $\mathbf{Z}$ are given by $\mathbf{X}$.) This gave a best value of $C = 0.44149$, also providing a lower bound for the constraint. This is a fair improvement on the lower bound of 0.4267 on the capacity of (diagonal) bit-stuffing in [2].

Capacities were also calculated for applying the modified bit-stuffing scheme to the constraint given by a min. (1-norm) distance of 3 between 1s. The results obtained for $m = 15$ were $C = 0.276$ when writing an unbiased sequence, $C = 0.344$ for a single biased sequence and $C = 0.3477$ choosing different biased sequences for each column of $\mathbf{X}$ and $\mathbf{Y}$. For this constraint the boundaries, $\mathbf{Z}_{i-1}$ and $\mathbf{Z}_i$ must be at least an additional row ahead in order to bit-stuff the elements of $\mathbf{X}$ and $\mathbf{Z}$ independently of past elements of $\mathbf{Y}$. A more elaborate scheme for specifying $\mathbf{W}$ in (1) was also devised. The probabilities p_1 were made dependent on the other elements on the $(N - 1) = 2$ previous rows. The next row of $\mathbf{X}$ (and $\mathbf{Z}$) is specified by probabilities conditioned on the two previous rows. The new row of $\mathbf{Y}$ is specified by probabilities conditioned on 3 rows of $\mathbf{X}$ and $\mathbf{Z}$ and 2 rows of $\mathbf{Y}$. These conditional probabilities were obtained from the maxentropic solution [3] for $\mathbf{W}$ (with two rows forming the states). This gave a capacity of $C = 0.3497$, which also provides a new lower bound for the constraint.

REFERENCES

- [1] R.M. Roth, P.H. Siegel and J.K. Wolf, "Efficient coding schemes for the hard-square model," *IEEE Trans. Inform. Theory*, vol. 47, pp. 1166-76, March, 2001.
- [2] S. Halevy, J. Chen, R.M. Roth, P.H. Siegel, J.K. Wolf, "Improved bit-stuffing bounds on two-dimensional constraints," *Proc. ISIT'02*, Lausanne, Switzerland, p. 385, 2002.
- [3] S. Forchhammer and J. Justesen, "Entropy bounds for constrained two-dimensional random fields," *IEEE Trans. Inform. Theory*, vol. 45, no. 1, pp. 118-127, Jan. 1999.