Measurement and calculation of the critical pulsewidth for gain saturation in semiconductor optical amplifiers

Borri, Paola; Mørk, Jesper; Hvam, Jørn Märcher; Merozzi, A.

Published in:

Lasers and Electro-Optics Europe, 1998. 1998 CLEO/Europe. Conference on

Publication date:

1998

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Borri, P., Mørk, J., Hvam, J. M., & Merozzi, A. (1998). Measurement and calculation of the critical pulsewidth for gain saturation in semiconductor optical amplifiers. In *Lasers and Electro-Optics Europe, 1998. 1998 CLEO/Europe. Conference on IEEE*.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

CTu160

Nonlinear compression of tilted light pulses

R. Danielius, A. Dubietis, G. Valiulis, G. Tamošauskas, A. Piskarskas
 Vilnius University Laser Research Center, Sauletekio Avenue 9, building 3,
 2040 Vilnius, Lithuania
 tel: +370-2 769477, fax: +370-2 775623
 e-mail: audrius.dubietis@ff.vu.lt

Summary

Nonlinear pulse compression under special conditions of large group-velocity mismatch (GVM) and strong energy exchange suggested for the first time 8 years ago [1,2], was demonstrated to be a simple and efficient method to generate powerful femtosecond pulses via frequency doubling of picosecond Nd-laser pulses in KDP crystal. However, the direct transfer of this technique to other wavelengths or other well-developed laser sources (Ti:sapphire, for instance) encounters serious problems related to the lack of nonlinear crystals with suitable dispersive properties. To this regard, the use of tilted pulses offers unique possibility to adjust the GVM in a nonlinear crystal for a particular wavelength [3,4].

In this Contribution we present the experimental results on second-harmonic pulse (at 527.5 nm) compression in BBO and third-harmonic pulse (at 351.7 nm) compression in KDP crystal. In case of type II BBO the tilt angle was calculated to introduce symmetrical GVM of the incident e and o polarized pulses in respect to the second-harmonic one. In type I KDP the GVM between the incident pulses was provided by dispersion whereas the pulse tilting ensured sum-frequency to have the GV equal to the average of the incident ones. A combination of telescopes and gratings was used to tilt the incident pulses as well as to restore the front of the output pulses. In both cases compressed pulses with durations well below 200 fs (what corresponds to ~9-fold compression factor) were measured. The simulation shows that proper GVM conditions can be found for a variety of wavelengths (Fig.1).

References:

1. Y. Wang and R. Dragila, Phys. Rev. A **41** (1990) 5645.
2. A. Stabinis, G. Valiulis, and E. A. Ibragimov, Opt. Comm. **86** (1991) 301.
3. A. Dubietis, G. Valiulis, G. Tamošauskas, R. Danielius, and A. Piskarskas, Opt. Lett. **22**, 1071 (1997).
4. A. Dubietis, G. Valiulis, G. Tamošauskas, R. Danielius, and A. Piskarskas, Opt. Comm. **144**, 55 (1997).

CTu161

Measurement and calculation of the critical pulsewidth for gain saturation in semiconductor optical amplifiers

P. Borri, J. Mørk, and J. M. Hvam,

Mikroelektronik Centret, The Technical University of Denmark, DK-2800 Lyngby, Denmark. Tel: +45 4525 5745; Fax: +45 4588 7762; e-mail: paola@mic.dtu.dk
 A. Mecozzi,

Fondazione Ugo Bordoni, via B. Castiglione 59, 00142 Roma, Italy.

Active semiconductor optical waveguides are essential components in many recently proposed devices for high-speed optical signal processing. It is well known that ultrafast carrier dynamics, like carrier heating and spectral holeburning, lead to gain non-linearities, which restrict the modulation bandwidth of semiconductor lasers. In the case of pulse amplification, these non-linearities lead to a pulsewidth dependence of the gain saturation [1]. A critical pulsewidth can be defined [2], which separates two qualitatively different regimes: a long-pulse regime, where the gain is determined by the pulse energy only, and a short-pulse regime, where the gain also depends on the pulsewidth. Calculated critical pulsewidths are on the order of several picoseconds [1], which is getting in the range of pulses being explored for ultrafast optical signal processing. Experiments that we are aware of, however, do not investigate the detailed dependence of the saturation energy versus pulse duration, and subsequently do not allow extraction of the critical pulsewidth.

We have measured the gain saturation of a 250 μm -long InGaAsP optical amplifier operating at 1.55 μm , for pulse durations from 200 fs to 10 ps. Infrared pulses of 200 fs are generated using the idler of an optical parametric amplifier. Longer pulsewidths and linear chirp compensation are achieved using a pulse-shaper in the beam path. Cross correlation measurements show that the pulses are background-free.

The measured amplifier gain as a function of output energy (in the range from 5 fJ to 5 pJ) clearly shows that the onset of gain saturation is pulsewidth dependent. By plotting the corresponding 3dB output energy as a function of the pulse duration we deduce a critical pulsewidth, for which the saturation induced by depletion of the carrier density (sometimes denoted linear gain saturation) equals the saturation due to ultrafast carrier dynamics. We obtain critical pulsewidths in the range from 2 to 7 ps, depending on the optical wavelength and bias current. Note that these values are significantly larger than the relaxation time of the carrier plasma temperature ($\tau_T \approx 700$ fs). However, as the pulsewidth becomes comparable to and shorter than τ_T , the variation of saturation energy with pulsewidth changes qualitatively, depending on whether the main saturation mechanism comes from spectral holeburning or carrier heating. In agreement with calculations based on density matrix equations [2], we find a larger role of carrier heating at shorter wavelengths.

- [1] Y. Lai, K. L. Hall, E. P. Ippen, and G. Eisenstein, IEEE Photon. Technol. Lett. **2**, 711 (1990); R. S. Grant and W. Sibbett, Appl. Phys. Lett. **58**, 1119 (1991).
- [2] A. Mecozzi and J. Mørk, IEEE J. Select. Topics in Quant. Electron., Oct. 1998.