Analyzing the Relationship Between Car Generation and Severity of Motor-Vehicle Crashes in Denmark

Rich, Jeppe; Prato, Carlo Giacomo; Hels, Tove; Lyckegaard, Allan; Kristensen, Niels Buus

Publication date:
2013

[Link back to DTU Orbit](#)

Citation (APA):

Rich, J., Prato, C. G., Hels, T., Lyckegaard, A., & Kristensen, N. B. (2013). *Analyzing the Relationship Between Car Generation and Severity of Motor-Vehicle Crashes in Denmark*. Poster session presented at Transportation Research Board 92nd Annual Meeting, Washington DC, District of Columbia, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

ANALYZING THE RELATIONSHIP BETWEEN CAR GENERATION AND SEVERITY OF MOTOR-VEHICLE CRASHES IN DENMARK

JEPPE H. RICH, CARLO G. PRATO, TOVE HELS, ALLAN LYCKEGAARD, NIELS B. KRISTENSEN
DTU – TECHNICAL UNIVERSITY OF DENMARK

TRANSPORTATION RESEARCH BOARD ANNUAL MEETING – POSTER SESSION 724 – JANUARY 16, 2013

Background

In Denmark, road fatalities are on the decrease. This is due to legislation changes, enforcement measures, technological enhancements, infrastructural improvements and human factors. However, research has not investigated the contribution of each factor to the significant road safety improvement.

Aim

To assess the relationship between car generation and conditional accident severity of drivers in car crashes in Denmark.

Method

Crash severity is recorded in four naturally ordered categories:

- No injury/material damage (1)
- Light injury of driver (2)
- Severe injury of driver (3)
- Death of driver (4)

Because of the ordered response discrete variable, an ordered logit-model approach was chosen with a relaxation of the proportional odds assumption:

$$P(y_i > j) = \frac{\exp[\alpha_j - (X_i' \beta + T_i' \gamma_j)]}{1 + \exp[\alpha_j - (X_i' \beta + T_i' \gamma_j)]} \quad j = 1, \dots, J$$

Where P is the probability of having an accident with a driver injury greater than j given that the accident has happened. The probability of occurrence of severity category j (1,2,3,4) relates to a vector T_i of observed explanatory variables for which the proportional odds assumption **does not** hold and to a vector X_i for which the proportional odds assumption **does** hold. A Brant test investigated whether the variables violated the proportional odds assumption. α_j , β_j and γ_j were estimated by maximum likelihood in Stata.

Data

In the analysis we included drivers of passenger cars and vans in police-recorded accidents in Denmark in the period 2004-2010. Thus we included:

- 80,502 observations of drivers in 49,405 accidents (single + multiple vehicle accidents)
- Driver injury as the response variable
- The following explanatory variables:

Car characteristics carmaker-specific cargen04, ..., cargen10 Logownweight Relativeweight	Dummies for the 20 most sold car makes in Denmark 2004, ..., 2010 minus year of 1 st registration Logarithm of the own weight of the car (kg) Own weight relative to (average) weight of other car(s) involved in the accident
Driver characteristics Male age26 age43 age65 age99 Legallicense alcohol_male1 alcohol_male2 alcohol_male3 Seatbeltmiss seatbelt21 seatbelt26 seatbelt43 seatbelt65 seatbelt99	Dummy for male driver Piece-wise linear function for driver age (22sages26) Piece-wise linear function for driver age (27sages43) Piece-wise linear function for driver age (44sages65) Piece-wise linear function for driver age (66sage) Dummy for valid license of the driver at the time of accident Piece-wise linear function of BAC for male drivers (0s BAC ≤50) Piece-wise linear function of BAC for male drivers (50< BAC ≤100) Piece-wise linear function of BAC for male drivers (100< BAC) Dummy for seatbelt not used by driver Dummy for seatbelt use and 18sages21 Dummy for seatbelt use and 22sages26 Dummy for seatbelt use and 26sages43 Dummy for seatbelt use and 44sages65 Dummy for seatbelt use and 66sage
Crash characteristics d04, ..., d10 Leftback Rightback Front Rear Alone Motorway road_2track road_1track Urban Logspeedlimit	Dummy for year of accident Dummy for "left back" point of collision Dummy for "right back" point of collision Dummy for "front" point of collision Dummy for "rear" point of collision Dummy for single-vehicle accident Dummy for accident occurring on a motorway Dummy for accident occurring on a two-lane road Dummy for accident occurring on a one-lane road Dummy for accident occurring in an urban area Log transformed speed limit (km/h)

The explanatory variable of main interest was car generation; the rest of the variables correct for conditions related to the driver, the vehicle and the accident.

Results

Associated with the most severe driver injuries were:

- Older cars, lighter cars.
- Higher car speed proxied by the speed limit.
- Older drivers and female drivers.
- A blood alcohol concentration above 1.0 (male drivers).
- Single-vehicle accidents.
- Accident on rural roads as opposed to motorways (freeways) and urban roads.
- Frontal collisions.

The effect on driver injury severity of the vehicle's generation

- Newer cars: lower probability of driver injury or death
- Newer cars: higher probability of material damage only accidents (not shown).

Elasticities for speed limit, curb weight and weight ratio

- Higher speed (limit) in accident: higher probability of driver injury or death (red bars).
- Heavier car: lower probability of driver injury or death (grey bars).
- Heavier car relative to the other car in accident: lower probability of driver injury or death (yellow bars).

Scenarios

To illustrate the relations found we calculated the lives and injuries saved if older cars were removed and hypothetically redistributed proportionately among younger cars:

Driver injury severities, accidents from 2004 to 2010, N=80,502.				
	Fatalities	Severely injured	Slightly injured	Material Damage
Basis model calculation (real life)	642	4,659	7,168	68,032
Scenario 1: # cars > 10 years reduced by half	571	4,401	6,980	68,550
<i>Difference</i>	-71	-258	-188	518
<i>Difference in percentage</i>	-11.1%	-5.5%	-2.6%	0.8%
Scenario 2: # cars > 15 years reduced by half	607	4,537	7,083	68,275
<i>Difference</i>	-36	-122	-85	243
<i>Difference in percentage</i>	-5.5%	-2.6%	-1.2%	0.4%
Scenario 3: # cars > 20 years reduced by half	631	4,624	7,146	68,100
<i>Difference</i>	-11	-35	-22	68
<i>Difference in percentage</i>	-1.8%	-0.8%	-0.3%	0.1%

The results indicate that when correcting for a number of variables relating to the driver, the vehicle and the accident, a clear safety potential by renewing the car fleet remains. The potential is probably even larger than indicated here, since this study only analyzed potential in injury reduction given that the accident had happened (conditional severity). Renewal of the car fleet will most likely reduce the number of accidents as well, since newer cars are more likely to have more active safety equipment than older cars. Moreover, by including the effect of newer cars on passenger injury, the safety potential would be even larger.