



## Nanostructured Thermoelectric Oxide Materials for Effective Power Generation from Waste Heat

Van Nong, Ngo; Pryds, Nini

*Publication date:*  
2012

[Link back to DTU Orbit](#)

*Citation (APA):*

Van Nong, N., & Pryds, N. (2012). *Nanostructured Thermoelectric Oxide Materials for Effective Power Generation from Waste Heat*. Abstract from 6th International Workshop on Advanced Materials Science and Nanotechnology, Ha Long City, Viet Nam.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal


If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Nanostructured Thermoelectric Oxide Materials for Effective Power Generation from Waste Heat

Ngo Van Nong and Nini Pryds

Department of Energy Conversion and Storage, Technical University of Denmark, Risø Campus, Frederiksborgvej 399, 4000 Roskilde, Denmark

A large amount of thermal energy that emitted from many industrial processes is available as waste heat. It is difficult to reclaim this heat due to the dispersed nature and relative smallness of its sources. Thermoelectric conversion can offer a very promising method to overcome these difficulties by converting heat directly into electricity. However, the requirements for this task place in the materials are not easily satisfied by the conventional thermoelectric materials. Not only they must possess a high thermoelectric performance, they should also be stable at high temperatures and be composed of nontoxic and low-cost elements, and must be able to be processed and shaped cheaply. Oxides are among the strongest candidate materials for this purpose, and recently they have been intensively investigated and developed [1-5]. In this report, the development progress of two state-of-the-art *p*-type  $\text{Ca}_3\text{Co}_4\text{O}_{9+\delta}$  and *n*-type doped-ZnO oxide systems is presented. The thermoelectric generator (TEG) devices based on these oxide materials were fabricated, examined, and demonstrated with various output applications. At a  $\Delta T = 500$  K, the maximum output power of our TEG composed of 32 *p-n* couples reached 1W, which is among the best one so far and is enough for a practical application such as phone charge or GPS device (see Fig. 1).



**Fig. 1.** a) The historical progress of achievements for the typical *n*- and *p*-type oxide thermoelectric materials over the years and b) demonstration of high temperature oxide thermoelectric generators.

## References:

1. N. V. Nong et al., *Adv. Mater.* (2011) 23 [21], 2484.
2. N. V. Nong et al., *J. Electron. Mater.* (2011) 40 [5], 716.
3. N. V. Nong et al., *J. Alloys Compd.*, (2011) 509, 977.
4. N. V. Nong et al., *J. Alloys Compd.* (2010) 491, 53.
5. M. Ohtaki et al., *J. Electron. Mater.* (2009) 38, 1234.