SiC JFET Cascode Loss Dependency on the MOSFET Output Capacitance and Performance Comparison with Trench IGBTs

Pittini, Riccardo; Zhang, Zhe; Andersen, Michael A. E.

Published in:
2013 IEEE Applied Power Electronics Conference and Exposition

Link to article, DOI:
[10.1109/APEC.2013.6520465](https://doi.org/10.1109/APEC.2013.6520465)

Publication date:
2013

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Pittini, R., Zhang, Z., & Andersen, M. A. E. (2013). SiC JFET Cascode Loss Dependency on the MOSFET Output Capacitance and Performance Comparison with Trench IGBTs. In *2013 IEEE Applied Power Electronics Conference and Exposition* (pp. 1287-1293). IEEE. <https://doi.org/10.1109/APEC.2013.6520465>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

SiC JFET Cascode Loss Dependency on the MOSFET Output Capacitance and Performance Comparison with Trench IGBTs

Riccardo Pittini

Technical University of Denmark
Dept. of Electrical Engineering
Kgs. Lyngby, 2800, Denmark
ripit@elektro.dtu.dk

Zhe Zhang

Technical University of Denmark
Dept. of Electrical Engineering
Kgs. Lyngby, 2800, Denmark
zz@elektro.dtu.dk

Michael A.E. Andersen

Technical University of Denmark
Dept. of Electrical Engineering
Kgs. Lyngby, 2800, Denmark
ma@elektro.dtu.dk

Abstract— In power electronics there is a general trend to increase converters efficiencies and power densities; for this reason new power semiconductors based on materials such as Silicon Carbide (SiC) and Gallium Nitride (GaN) are becoming more popular. This is especially valid for renewable energies applications where the generated energy has a higher cost than with conventional energy sources. This paper proposes an experimental analysis of the switching performance of a high voltage SiC JFET connected in cascade connection with a low voltage MOSFET. The analysis focuses on the influence of the MOSFET output capacitance on the switching performance of the SiC Cascode connection in terms of switching energy loss, dV/dt and dI/dt stresses. The Cascode connection switching performances are compared with the switching performance latest Trench IGBTs. The analysis is based on a set of several laboratory measurements and data post-processing in order to properly characterize the devices and quantify whether the SiC JFET Cascode connection can provide good performances with a simple MOSFET gate driver.

I. INTRODUCTION

In the last years a large growth of power electronics has been experienced mainly driven by the huge interest in renewable energy sources and smarter energy use. Moreover, in many applications there is an increasing trend to improve systems efficiencies supported by state policies and by economical benefits.

Silicon Carbide (SiC) together with Gallium Nitride (GaN) have been known to be attractive wide band gap semiconductors especially suited for increasing the efficiency and power density of switch mode power supplies (SMPS) compared to silicon (Si) based SMPS [1]. They have the potential of providing power semiconductors characterized by high band-gap, higher mobility and higher thermal conductivity than Si, leading to lower conduction and switching losses, higher breakdown voltage, possibility to operate at high temperatures, increased switching frequency and power density.

The recent improvements in the crystal fabrication, fabrication yield increases and availability of new low-cost power devices based on SiC have made SiC-based power semiconductors more competitive [2][3]. However, there are still a limited number of power semiconductors available in SiC; they are limited to SiC Schottky barrier diodes, SiC Junction Effect Field Transistors (JFETs) available in both normally-on and normally-off variants, SiC Bipolar Junction Transistors (BJTs) [4] and recently SiC Metal Oxide Semiconductor Field Effect Transistors (MOSFETs) [5][6].

SiC-diodes have become price competitive as Si-diodes; SiC-diodes are often used as replacement of Si-diodes in applications characterized by high efficiency and high voltage due to their almost zero-recovery losses at device turn-off [7]. SiC JFETs have really become price competitive and they can provide very low switching losses and low on-state resistance [8]. The main drawbacks related to the use of SiC JFETs are related to the driving circuitry: SiC JFETs are voltage driven devices with threshold and driving voltages that differ from Si-MOSFETs. Moreover, SiC JFETs require a low continuous power from the driver (high leakage current) and therefore they do not represent a direct and easy replacement for Si-MOSFETs or Silicon Insulated Gate Bipolar transistors (Si-IGBTs). The driver complexity [9] and the limited the availability of commercial drivers suited for Si-JFETs also contribute to limit the device diffusion in different applications. The driver issue in terms of continuous power from the driver is even worse for SiC-BJTs moreover, the limited availability of SiC-BJTs have also reduced their success. During 2011, SiC-based MOSFETs has been released thorough commercial channels [5]; the devices have with similar ratings as SiC JFETs promising good performance making the devices suited for significantly increase the switching frequency and the power density of power electronics converters. However, also in this case to properly take advantage of the new device a custom designed driver is required and it will probably limit the device diffusion due to the lack of commercial available drivers.

TABLE I
TESTED DEVICE CHARACTERISTICS

JFET	MOSFET	IGBT no.1	IGBT no.2
SJDP120R085	IPB017N06N3	IGW15N120H3	IRG7PH30K10
1200 V	60 V	1200 V	1200 V
85 mOhm	1.7 mOhm	2.05 Vce	2.05 Vce
27 A *	180 A *	30 A *	33 A *
17 A **	180 A **	15 A **	23 A **

*Parameter at 25 ° C

**Parameter at 100 ° C

device off-time is sufficiently low, the inductor current decay is small (the inductor discharges slightly through its resistance and through the freewheeling diode) and allows turning on the DUT for measuring a turn-on event at the same current level as the turn-off event. After this second turn-on event the device is switched off permanently and kept in off state until the inductor is completely discharged. After that it is possible to vary the first pulse width to increase or reduce the desired current and at which the measurement should be performed.

The test setup (Fig. 4) characteristics are summarized:

- DC voltage source: 700 V
- Capacitor bank: 1000 V 300 μ F
- Load inductor: 285 μ H
- Freewheeling diode: SiC 1200 V 20 A

A. Tested Devices

The paper focused on analyzing devices with similar characteristics in order to establish references for converters with DC voltages of 700-800 V. At this voltage levels CoolMOS provide a limited voltage margin (available up to 900 V) and their on state resistance is significantly high compared to SiC devices or Si IGBTs. Since for the candidate application efficiency is one of the most important factors, 1200 V SiC JFETs (SJDP120R085) were one of the first candidates for achieving high efficiency. Alternatively, 1200 V SiC MOSFETs could have been used however, the price performance ratio of the SiC JFET looked well application-suited. The low voltage MOSFET was selected due its very low on resistance (IPB017N06N3) that would give a minimum impact on the total on state resistance of the Cascode connection. The large availability of IGBT devices in the 1200 V range made the selection of IGBTs more

complex. However, among all, trench IGBTs can provide both fast switching with limited tail current and low $V_{CE,on}$. The selected devices have similar current ratings as the selected SiC JFET and are produced by two different manufacturers identified as IGBT no.1 (IGW15N120H3) and IGBT no.2 (IRG7PH30K10) in the measurements and in the comparison plots. A summary of the main device characteristics is presented on Table I.

B. Instrumentation and Measurements

All measurements were performed with the comparable test conditions in terms of voltage, current, time intervals and temperature. The power connection from the DC-link capacitor to the power components was realized with flat copper conductor to obtain as low inductance as possible as visible on Fig. 4. The gate driver was placed close to the DUT, the wires were twisted in order to reduce the loop inductance and it was connected to a digital control card used to generate test pulses. The minimum resolution of the pulses is 1 μ s with a basic accuracy of 0.25 μ s. The digital control card ensured test repeatability having well defined pulses width for each current level. All measurements were performed with the same probe configuration with an exception for the IGBT measurements where there was no MOSFET's drain-source voltage measurement.

The oscilloscope features allow saving measurements directly in Matlab format for post-processing. The oscilloscope configuration was the following (examples of measured switching transients on Fig. 5):

- Ch.1: DUT source/emitter current. Current probe is a ultra miniature Rogowsky coil with a bandwidth of 20 MHz (20mV/A) measuring the Cascode source current excluding the gate driving current.
- Ch.2: Gate-source/gate-emitter voltage of the Cascode configuration/IGBTs; 100 MHz 1X voltage probe.
- Ch.3: DUT drain-source/collector-emitter voltage. High voltage probe 100X (LeCroy PPE 4 kV) measuring the Cascode drain-source voltage.
- Ch.4: drain-source voltage of the low voltage MOSFET in the Cascode configuration; 100 MHz 1X voltage probe. Not used with IGBT's.

Fig. 5 Cascode JFET measured turn-on (left) and turn-off (right) detail 700 V 9 A, MOSFET gate resistance 2.5 ohm. Ch.1: 5 A/div, Ch.2: 5 V/div, Ch.3: 200 V/div and Ch.4: 10 V/div, time: 100 ns/div.

Fig. 6 Cascode switching loss dependency on MOSFET's output capacitance.

The Rogowsky coil delay was measured in a reference comparison measurement with a shunt resistor where it was quantified in 24 ns; this value is verified also in probe manual. The oscilloscope features de-skew compensation, however, this was not used but implemented digitally during data post-processing. Measurements were performed at different current levels (from 5 A to up to 20 A) for the selected DC voltage (700 V).

C. Methodology and Data Post-Processing

The first set of measurements focused on analyzing the effect of the MOSFET output capacitance on the switching performance of the Cascode configuration. The main focus was to observe if it is possible vary the switching performance with simple low voltage components instead of using components rated at high voltage [11]. To simulate a large MOSFET's output capacitance, additional capacitors of different values (0-100 nF range) were added in parallel to the low voltage MOSFET used in the Cascode connection. The capacitors were connected directly on the MOSFET's leads in order to reduce the leakage inductance to the minimum and to avoid possible unwanted oscillations. In the second step, the switching performance of the Cascode valve were measured at different current levels and as last phase the Cascode valve was replaced with the selected IGBTs for characterizing their switching performance.

All measured waveforms were stored in MATLAB format in order to allow post-processing of the measurements and create adequate plots. Light filtering was applied to the measurements for reducing the measurement noise; after filtering the waveforms were verified to ensure that the filtering process did not change the measurement information. MATLAB functions were developed for extracting the desired information from the measurement files, such as switching energy loss, the transition intervals (turn-on and turn-off times), the voltage and current stresses in terms of dV/dt and dI/dt and instantaneous peak power loss.

Fig. 7 Cascode dV/dt stress dependency on MOSFET's output

IV. CASCODE SWITCHING LOSS DEPENDENCY ON MOSFET'S OUTPUT CAPACITANCE

In the first set of measurements the switching losses of the Cascoded devices are measured by varying the MOSFET's output capacitance for a fixed current (9 A). For reasonably low additional capacitances (0-100 nF range) the turn-on losses have a minimal dependency on the MOSFET's output capacitance as observed in Fig. 6. In this case, at the Cascode turn-on the MOSFET's delay and switching speed determine the turn-on instant of the JFETs. The turn-off losses on Fig. 6 increase more than the turn-on losses, in fact as the MOSFET's output capacitance increases, the turn-off losses increase with a linear trend. This could be explained by analyzing the Cascode configuration a bit more in detail.

At device turn-on the MOSFET's output capacitance discharges through the low ohmic low voltage MOSFET and the voltage change across the JFET's gate-source (also output capacitance terminals) varies as in a capacitor discharge through a resistor with the RC-time constant defined by the MOSFET's output capacitance and the MOSFET's on-state resistance.

Vice versa, at device turn-off the MOSFET's output capacitance is slowly charged through the JFET's on-state resistance; at the start of the JFET's turn-off process the

Fig. 8 Cascode turn-on (left) and turn-off (right) transients. Highlighting charge/discharge of MOSFET's output capacitance.

Fig. 9 Cascode dI/dt stress dependency on MOSFET's output capacitance.

voltage rises over the MOSFET with an initial RC time constant defined by the JFET's on state resistance and the total output capacitance. As soon as the voltage over the MOSFET's start to increase, the JFET's on resistance increases giving an additional contribute to the JFET's turn-off losses until the JFET becomes completely pinched off. For this reason, an increase of the MOSFET's output capacitance slightly influences the Cascode turn-on performance and will strongly influence the turn-off performance.

This effect is also observed in the dV/dt stress at device turn-on and turn-off on Fig. 7. The dV/dt stress at turn-on is slightly influenced by the MOSFET's output capacitance while the dV/dt stress at turn-off is significantly reduced with a large MOSFET's output capacitance. The dV/dt stress reduction at turn-off is large, in fact the dV/dt stress is reduced from 38 kV/us down to 10 kV/us with the largest tested capacitance value. According to the measurement a small capacitor can be placed on parallel to the low voltage MOSFET to reduced the turn-off dV/dt and balance it with the turn-on dV/dt reducing the immunity requirements for the

Fig. 11 Cascode turn-off switching loss and dV/dt dependency on MOSFET's output capacitance.

Fig. 10 Cascode turn-on and turn-off times dependency on MOSFET's output capacitance.

gate driver. However, it is also necessary to observe how other parameters are affected by a large MOSFET output capacitance.

It is also interesting to observe how the dI/dt stress varies as a function of the MOSFET's output capacitance. On Fig. 9 it can be observed that the turn-on dI/dt has a light variation (small reduction), however, large output capacitance mainly influences the turn-off dI/dt . This stress can be reduced down to about 33% or the initial value. Therefore, it can be deduced that a large MOSFET's output capacitance can reduce both dV/dt and dI/dt at turn-off. This result is also confirmed by taking a look at the transition times (turn-on and turn-off times) of the Cascode configuration on Fig. 9.

It was observed that in the Cascode configuration, the turn-on losses are dominating over the turn-off losses (Fig. 6 700 V 9 A); by increasing the MOSFET's output capacitance the Cascode turn-off time increase as seen in Fig. 11. Therefore, it is possible to find a balance between the turn-on dV/dt and the turn-off dV/dt with a slight increase of switching losses (Fig. 11). Depending on the application and on the desired performances in terms of switching losses and maximum dV/dt and dI/dt stresses, this could be advantageous for reducing the immunity requirements of the gate driver which are normally very high (recommended immunity for SiC gate drivers is about ~ 50 kV/us).

V. COMPARISON OF THE SWITCHING LOSSES OF SiC CASCODE WITH Si IGBTs

In multi-kW applications with DC-link voltage level of 700-800 V SiC normally-on JFET in Cascode connection with a low voltage MOSFET has to be compared with newly developed high speed trench IGBTs which, especially for the latest series (3rd generation); these devices can provide very low $V_{CE,sat}$ and low switching losses (or operation up to ~ 100 kHz). The IGBTs switching performance were measured with different gate resistors values; starting with a large values as used in their datasheets (e.g. 35-22 Ohm), down to a very low values (2.5 Ohm). To analyze the switching performance, the turn-on and turn-off losses are analyzed independently for IGBT no.1 and IGBT no.2. Subsequently, the total switching

Fig. 12 IGBT no.1 and Cascode turn-on energy loss.

Fig. 13 IGBT no.1 and Cascode turn-off energy loss.

losses are analyzed in comparison with the Cascode configuration.

IGBT no.1 is a fast switching IGBT (IGW15N120H3) rated for operation up to 100 kHz; its turn-on and turn-off switching losses are presented on Fig.12 and Fig.13 respectively. When the IGBT is operated with large gate resistors as characterized in the datasheet, the switching losses are significantly higher than the SiC Cascode configuration. However, by reducing the gate resistor the turn-on losses are significantly reduced. With a minimum gate resistor the reduction can be down to 33% of the losses specified in the datasheet. The performance achieved in terms of turn-on losses are also better than the ones obtained with the SiC Cascode. Vice versa, the IGBT turn-off losses are independent from the gate resistance and vary linearly with the device current (Fig. 13). The turn-off losses are always larger than the SiC Cascode turn-off due to the IGBT tail current.

In a similar way the switching losses of IGBT no.2 are compared with the switching losses of the SiC Cascode on Fig. 14 and Fig. 15. The measured turn-on losses of IGBT no.2 are significantly lower than the ones measured for

IGBT no.1 (Fig. 12 and Fig. 14) for large gate resistor values. Also in this case, with reduced gate resistors compared to the value specified in the datasheet, it is possible to reduce the IGBT turn-on losses even lower than the turn-on losses of the SiC Cascode. The turn-on losses with low gate resistors become lower than the SiC Cascode for all measured current levels. As observed in the previous case, the IGBT no.2 turn-off losses are almost not influenced by the reduction of the gate resistance and, also for this case, their value is significantly larger than the SiC Cascode turn-off losses for the entire range of tested currents. Therefore, it is observed that even though latest generation of trench IGBT have very low switching losses, the tail current is still one of the main sources of turn-off losses in IGBTs.

As observed until now is clear that when IGBTs are used up to their boundaries in terms of switching speed, they can provide good performances even in comparison to the new power semiconductors based on SiC. It is required to analyze the total switching losses (both turn-on and turn-off energy loss) to evaluate the overall performance of the devices. To achieve a complete comparison the total losses (turn-on and

Fig. 14 IGBT no.2 and Cascode turn-on energy loss.

Fig. 15 IGBT no.2 and Cascode turn-off energy loss.

Fig. 16 IGBT no.1 and Cascode total switching energy loss.

Fig. 17 IGBT no.2 and Cascode total switching energy loss.

turn-off) have to be evaluated.

A comparison of the total switching losses of IGBT no.1 with SiC Cascode and IGBT no.2 with SiC Cascode are presented on Fig. 16 and Fig. 17 respectively. Both IGBTs types are rated for high-speed (IGBT no.1 up to 100 kHz and IGBT no.2 up to 30 kHz), however, it is observed that IGBT no.1 has higher switching losses compared to IGBT no.2 when this ones are used with the gate resistors specified in the datasheet, this is observed especially at high current values (above 10 A). In both IGBTs it is possible to significantly reduce the total losses by decreasing their gate resistor to a very low value. In this case the energy loss reduction in IGBT no.1 is larger compared to IGBT no.2. The IGBTs switching performance can be increased to a level where the energy loss during the switching transient is very close to the one observed for the SiC Cascode (Fig. 16).

VI. CONCLUSIONS

The paper presented the effects of increased MOSFET's output capacitance on the switching behavior of the Cascode configuration.

It was observed that in the Cascode configuration the turn-off dV/dt stress can be significantly reduced with a limited increase of the switching losses by a larger MOSFET's output capacitance; e.g. by adding an additional capacitor in parallel to the MOSFET. The additional capacitor influences mainly the turn-off losses with little influence on the turn-on losses.

The Cascode configuration was characterized in terms of switching losses and compared with newly 3rd generation trench IGBTs. This latest IGBTs proved to be very competitive also towards SiC devices in the multi-kW power range. In fact, when IGBTs are switched very fast the measured switching losses are very close to the switching losses of a SiC Cascode configuration. Undoubtedly, pure SiC power devices provide lower losses, however, there is still a big lack of available integrated gate-driver solutions for these devices. For this reason, the Cascode configuration or latest IGBT generations are still very appealing for many applications.

REFERENCES

- [1] Elasser, A.; Chow, T.P.; , "Silicon carbide benefits and advantages for power electronics circuits and systems", *Proceedings of the IEEE* , vol.90, no.6, pp. 969- 986, Jun 2002.
- [2] Ostling, M.; Ghandi, R.; Zetterling, C.; , "SiC power devices — Present status, applications and future perspective", *IEEE 23rd International Symposium on Power Semiconductor Devices and ICs (ISPSD 2011)*, pp.10-15, 23-26 May 2011.
- [3] Khan, M.A.; Simin, G.; Pytel, S.G.; Monti, A.; Santi, E.; Hudgins, J.L.; "New Developments in Gallium Nitride and the Impact on Power Electronics", *IEEE 36th Power Electronics Specialists Conference (PESC '05)*, pp.15-26, 16-16 June 2005.
- [4] Franke, W.-T.; Fuchs, F.W.; , "Comparison of switching and conducting performance of SiC-JFET and SiC-BJT with a state of the art IGBT", *13th European Conference on Power Electronics and Applications (EPE '09)*, pp.1-10, 8-10 Sept. 2009.
- [5] <http://www.cree.com/>
- [6] Fan Xu; Ben Guo; Tolbert, L.M.; Wang, F.; Blalock, B.J.; , "Evaluation of SiC MOSFETs for a high efficiency three-phase buck rectifier," *Twenty-Seventh Annual IEEE Applied Power Electronics Conference and Exposition (APEC 2012)*, pp.1762-1769, 5-9 Feb. 2012.
- [7] Ho, C.N.M.; Breuninger, H.; Pettersson, S.; Escobar, G.; Serpa, L.; Coccia, A.; , "Practical implementation of an interleaved boost converter using SiC diodes for PV applications," *IEEE 8th International Conference on Power Electronics and ECCE Asia (ICPE & ECCE Asia 2011)*, pp.372-379, May 30 2011-June 3 2011.
- [8] Wilhelm, C.; Kranzer, D.; Burger, B.; , "Development of a highly compact and efficient solar inverter with Silicon Carbide transistors," *6th International Conference on Integrated Power Electronics Systems (CIPS 2010)*, pp.1-6, 16-18 March 2010.
- [9] Kelley, R.; Ritenour, A.; Sheridan, D.; Casady, J.; , "Improved two-stage DC-coupled gate driver for enhancement-mode SiC JFET," *Twenty-Fifth Annual IEEE Applied Power Electronics Conference and Exposition (APEC 2010)*, pp.1838-1841, 21-25 Feb. 2010.
- [10] Mihaila, A.; Udrea, F.; Azar, R.; Brezeanu, G.; , "Analysis of static and dynamic behaviour of SiC and Si devices connected in cascode configuration," *Proceedings International Semiconductor Conference (CAS 2011)*, vol.2, pp.333-336 vol.2, Oct 2011.
- [11] Biela, J.; Aggeler, D.; Bortis, D.; Kolar, J.W.; , "5kV/200ns Pulsed Power Switch based on a SiC-JFET Super Cascode," *Proceedings of the IEEE International Power Modulators and High Voltage Conference*, pp.358-361, 27-31 May 2008.