Upper Bound for Energy Efficiency in Multi-Cell Fibre-Wireless Access Systems

Koonen, A. M. J.; Popov, M.; Wessing, Henrik

Publication date:
2013

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Koonen, A. M. J., Popov, M., & Wessing, H. (2013). *Upper Bound for Energy Efficiency in Multi-Cell Fibre-Wireless Access Systems*. Poster session presented at 39th European Conference and Exhibition on Optical Communication (ECOC 2013), London, United Kingdom.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Upper Bound for Energy Efficiency in Multi-Cell Fibre-Wireless Access Systems

A.M.J. Koonen¹, M. Popov², H. Wessing³

¹COBRA Institute, Eindhoven Univ. of Technology, Eindhoven, The Netherlands; a.m.j.koonen@tue.nl

²ACREO Swedish ICT AB, Kista, Sweden; mikhael.popov@acreo.se

³DTU Fotonik, Techn. Univ. of Denmark, Lyngby, Denmark; hewe@fotonik.dtu.dk

Abstract Bringing radio access points closer to the end-users improves radio energy efficiency. However, taking into account both the radio and the optical parts of a fibre-wireless access system, the overall system energy efficiency has an upper bound determined by the relation between the energy consumption of the optical and wireless parts.

Fibre-fed LTE access

Fibre-fed radio pico-cells

Total power consumed:

$$P_{tot, \text{pico-cells}} = P_{radio} + P_{optical}$$

$$= c \cdot K \cdot \left(\frac{R}{\sqrt{K}} \right)^{\gamma} \cdot A_1^{\sqrt{N/K}-1} \cdot P_{mob} + 2 \cdot K \cdot P_{trx}$$

number of rooms N
≥ number of pico-cells K

Wired/wireless converged indoor network

Single large radio cell

Free-space radio channel:

$$P_{rec} = P_{trans} \cdot \left(\frac{\lambda}{4\pi R} \right)^2 \cdot G_{AT} \cdot G_{AR}$$

Total power consumed:

$$P_{tot, \text{single cell}} = P_{radio} + P_{optical} = c \cdot R^{\gamma} \cdot A_1^{\sqrt{N}-1} \cdot P_{mob} + 2 \cdot P_{trx}$$

where

- c includes antenna gains and OE signal conversion efficiency
- N is number of rooms
- A_1 is attenuation factor per wall crossing
- γ is path loss exponent ($\gamma=2$ in free space, γ may be up to 4 or more inside buildings)
- P_{mob} is received radio power needed at mobile device
- P_{trx} is power needed in optical transceiver

Total power consumption: pico-cells vs. single cell

$$\frac{P_{tot, \text{pico-cells}}}{P_{tot, \text{single cell}}} = \frac{K^{1-\gamma/2}}{A_1^{\sqrt{N}-\sqrt{N/K}}} + \frac{2K \cdot P_{trx}}{P_{tot, \text{single cell}}} \left(1 - \frac{K^{-\gamma/2}}{A_1^{\sqrt{N}-\sqrt{N/K}}} \right)$$

is dependent on number K of pico-cells, must be <1 for total power saving.
For $A_1=1$ (no walls), total power consumption is minimum for

$$K = \left[\frac{\gamma-2}{2} \left(\frac{P_s}{2P_{trx}} - 1 \right) \right]^{2/\gamma}$$

Energy savings by pico-cells

- $N=25$ rooms

Concluding remarks

- Radio-over-fiber based pico-cell techniques can improve not only the capacity but also the energy efficiency of wireless networks.
- As long as the number of pico-cells stays below an upper bound, the total power consumption of the network is less than that of a single-cell network
- Total power consumption is minimized by optimizing the number of pico-cells.
- The optimum number of picocells increases and the attainable minimum power consumption decreases when radio path loss exponent increases, wall losses increase, and/or RoF transceiver power consumption decreases.

Financial support from the European Commission in the ERC project BROWSE is gratefully acknowledged, as well as valuable discussions with Fred Snijders.