



## Light extraction efficiency enhancement for fluorescent SiC based white light-emitting diodes

Ou, Haiyan; Ou, Yiyu; Argyraki, Aikaterini; Kamiyama, S.; Grivickas, V.; Schimmel, S.; Kaiser, M.; Wellmann, P.; Linnarsson, M. K.; Jokubavicius, V.

Total number of authors:  
12

Publication date:  
2013

[Link back to DTU Orbit](#)

### Citation (APA):

Ou, H., Ou, Y., Argyraki, A., Kamiyama, S., Grivickas, V., Schimmel, S., Kaiser, M., Wellmann, P., Linnarsson, M. K., Jokubavicius, V., Yakimova, R., & Syväjärvi, M. (2013). *Light extraction efficiency enhancement for fluorescent SiC based white light-emitting diodes*. Abstract from 2nd Asian symposium on electromagnetic and photonics engineering (ASEPE 2013), Tabriz, Iran, Islamic Republic of.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Light extraction efficiency enhancement for fluorescent SiC based white light-emitting diodes

H. Ou<sup>1</sup>, Y. Ou<sup>1</sup>, A. Argyraki<sup>1</sup>, S. Kamiyama<sup>2</sup>, V. Grivickas<sup>3</sup>, S. Schimmel<sup>4</sup>, M. Kaiser<sup>4</sup>, P. Wellmann<sup>4</sup>, M. K. Linnarsson<sup>5</sup>, V. Jokubavicius<sup>6</sup>, R. Yakimova<sup>6</sup>, M. Syväjärvi<sup>6</sup>

<sup>1</sup>Department of Photonics Engineering, Technical University of Denmark, DK-2800, Lyngby, Denmark

<sup>2</sup>Department of Materials Science and Engineering, Meijo University, 1-501 Shiogamaguchi, Tenpaku-ku, Nagoya 468-8502, Japan

<sup>3</sup>Institute of Applied Research, Vilnius University, Vilnius, Lithuania

<sup>4</sup>Materials of Electronics Energy Technology, University of Erlangen-Nuremberg, D-91058, Erlangen, Germany

<sup>5</sup>School of Information and Communication Technology, KTH Royal Institute of Technology, SE-16440, Kista, Sweden

<sup>6</sup>Department of Physics, Chemistry and Biology, Linköping University, SE-58183, Linköping, Sweden  
[haou@fotonik.dtu.dk](mailto:haou@fotonik.dtu.dk)

## Abstract

Fluorescent SiC based white light-emitting diodes(LEDs) light source, as an innovative energy-efficient light source, would even have longer lifetime, better light quality and eliminated blue-tone effect, compared to the current phosphor based white LED light source. In this paper, the yellow fluorescent Boron-Nitrogen co-doped 6H SiC is optimized in terms of source material, growth condition, dopant concentration, and carrier lifetime by using photoluminescence, pump-probe spectroscopy etc. The internal quantum efficiency is measured and the methods to increase the efficiency have been explored. At a device level, the focus is on improving the light extraction efficiency due to the rather high refractive index of SiC by nanostructuring the surface of SiC. Both periodic nanostructures made by e-beam lithography and nanosphere lithography and random nanostructures made by self-assembled Au nanosphere mask and a thin layer of Al film have been investigated and all of them showed much enhanced extraction efficiency. All these good results pave the way to a very promising fluorescent SiC based white LED light source.