



Phase Behavior in EOR Surfactant Flooding

Sandersen, Sara Bülow; von Solms, Nicolas; Stenby, Erling Halfdan

Publication date:
2011

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Sandersen, S. B., von Solms, N., & Stenby, E. H. (2011). *Phase Behavior in EOR Surfactant Flooding*. Poster session presented at Thermodynamics 2011, Athens, Greece.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Phase Behavior in EOR Surfactant Flooding

¹Sara Bülow Sandersen, ²Erling H. Stenby & ¹Nicolas von Solms


Center for Energy Resources Engineering (CERE), ¹Department of Chemical & Biochemical Engineering, ²Department of Chemistry
 Technical University of Denmark (DTU)

Contact: sbs@kt.dtu.dk

Introduction

Worldwide there are an increasing demand for improved enhanced oil recovery techniques as significant amounts of oil is left in the swept zone after primary and secondary recovery techniques are applied. To keep an efficient oil production Enhanced Oil Recovery (EOR) is introduced, where the main target is to displace the crude oil trapped in the reservoir, often due to capillary and viscous forces. Among several techniques, surfactant flooding is one way to apply tertiary oil recovery, which is the injection of water mixed with appropriate surfactants (and co-surfactants) to control the phase behavior properties inside the reservoir.

Surfactant systems are typically considered as the so-called Winsor type systems as pictured. The aim of this process is to lower the interfacial tension (IFT) to ultra low by forming a microemulsion phase as is shown as Winsor III, which will mobilize the crude oil.




Facts generally accepted in literature

- An increase in temperature entails an increase in optimal salinity.
- Effect of pressure is debatable.
- Surfactant systems are sensitive to salinity.
- Surfactant compositions in the system are challenged by chromatographic separation.

Surfactant systems are sensitive to the salinity and the temperature, [1]. An increase in temperature increases the optimal salinity and therefore it is a demand that the surfactant systems can resist the present physical reservoir conditions. Note that both high temperatures and pressures will be reservoir conditions.

It is crucial that the Winsor III type system is formed (thus achieving the ultra low IFT when the microemulsion is formed) and as this can be correlated to the salinity, the salinity of the injection water must be designed to match the single reservoir.


High Pressure Equipment



This project is concerned about the effect from increased pressures and temperatures on the phase behavior of surfactant systems, hopefully to get a better understanding of the underlying mechanisms. Pressures are varied from 1 to 400 bar at 40 to 60 °C. Experiments are conducted on a DBR JEFRI PVT cell, allowing volume measurements and visual observations when the surfactant systems is equilibrating.

Emulsions

Formed in mixtures of liquids as droplets either as macroscopic or microscopic size. In surfactant flooding either water/oil or oil/water microemulsions are required, as the microemulsion reduces the IFT between oil and water.




Experimental Work

Surfactant system tested

Sodium Dodecyl Sulphate/ 1-Butanol/Heptane/ Water/ NaCl [2].


> II(+) is microemulsion and aqueous phase
 > III is the three phase-region.
 > II(-) is the oleic phase and microemulsion



The composition of the examined systems who resulted in a change in phase behavior dependent on pressure effect


Exp #	Water	SDS	Butanol	Heptane	NaCl
Composition in wt%					
1	0,423	0,023	0,046	0,478	0,030
2	0,441	0,044	0,089	0,396	0,031
3	0,711	0,028	0,055	0,157	0,050
4	0,532	0,022	0,044	0,365	0,037

Results



Overview of the shift in number of phases dependent on change in pressure

Experiment No.	Phase shift	Temp. [°C]	Pressure at beginning [Bar]	Pressure at phase shift [Bar]
#1	3 to 2	37	1	156
#2	2 to 3	37	1	302
#3	2 to 3	40	1	100-200
#4	3 to 2	40	1	160



References

- [1] D.W. Green and G.P. Willhite, 'Enhanced Oil Recovery', SPE Textbook Series, vol 6, 7, (1998)
 [2] J. Van Nieuwkoop and G. Snoei, Journal of Colloid and Interface Science, (1985), 103, 400-41