A Miniature Membrane Reactor for Evaluation of Process Design Options on the Enzymatic Degradation of Pectin

Zainal Alam, Muhd Nazrul Hisham; Pinelo, Manuel; Arnous, Anis; Jonsson, Gunnar Eigil; Meyer, Anne S.; Gernaey, Krist

Published in:
Industrial & Engineering Chemistry Research

Link to article, DOI:
[10.1021/ie200338k](https://doi.org/10.1021/ie200338k)

Publication date:
2011

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Zainal Alam, M. N. H., Pinelo, M., Arnous, A., Jonsson, G. E., Meyer, A. S., & Gernaey, K. (2011). A Miniature Membrane Reactor for Evaluation of Process Design Options on the Enzymatic Degradation of Pectin. *Industrial & Engineering Chemistry Research*, 50, 11252-11258. <https://doi.org/10.1021/ie200338k>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

A Miniature Membrane Reactor for Evaluation of Process Design Options on the Enzymatic Degradation of Pectin

Muhd Nazrul Hisham Zainal Alam*

Department of Bioprocess Engineering, Faculty of Chemical Engineering, Universiti Teknologi Malaysia, Malaysia

Manuel Pinelo, Anis Arnous, Gunnar Jonsson, Anne S. Meyer, and Krist V. Gernaey

Department of Chemical and Biochemical Engineering, Technical University of Denmark, Denmark

ABSTRACT: The objective of this paper is to assess if a membrane microreactor system could potentially be used to diagnose consequences of different process design and reactor operation options relevant for larger-scale enzymatic degradation of pectin reactions. The membrane microreactor prototype was fabricated from poly(methylmethacrylate) (PMMA) and poly-(dimethylsiloxane) (PDMS) with a working volume of $\sim 190 \mu\text{L}$. The prototype also contained the necessary sensors and actuators, i.e., pressure transducer, mixing via magnetic stirrer bar and a temperature controller. The functionality of the prototype was demonstrated by performing a continuous enzymatic degradation of pectin experiment for a range of reactor conditions: different membrane molecular weight cutoff (MWCO) values, enzyme-to-substrate ratios (E/S), and substrate feeding rates (F) were assessed. Based on the experimental data, it was found that the apparent reaction rate increased from $0.11 \mu\text{mol/h}$ to $0.13 \mu\text{mol/h}$ when the E/S ratio was doubled from 0.2% (g/g) to 0.4% (g/g). In contrast, when the substrate feeding rate was reduced from $200 \mu\text{L/h}$ to $100 \mu\text{L/h}$ (i.e., longer residence time), a higher yield was achieved (producing a pectin fragment concentration of 0.82 mM in the permeate) and the apparent reaction rate increased by $\sim 50\%$ (i.e., from $0.11 \mu\text{mol/h}$ to $0.17 \mu\text{mol/h}$). Clearly, this signifies that the substrate feeding rate is a critical variable that influences the conversion rate and the process yield. The data also showed that the process design affected the membrane rejection profile. The results obtained thus underlined the suitability of a miniature membrane reactor system for evaluating different process design options that are relevant for larger-scale reactions of enzymatic pectin degradation.

INTRODUCTION

Pectic substances can be found in fruits and vegetables, and they are abundant in many different agro-industrial waste streams. Agro-industries are highly interested in converting these low-value waste streams into useful high-value products (for example, into biofunctional oligosaccharides (carbohydrates containing between 2 and ~ 20 monomers^{1,2}). Such a conversion of pectin is possible through enzymatic reactions catalyzed by pectinolytic enzymes (typically of fungal origin), such as the pectin lyase (PL) (EC 4.2.1.10), pectin methylesterase (PME) (EC 3.2.1.11), endopolygalacturonase (PG) (EC 3.2.1.15), etc.^{3,4}

A number of studies have convincingly shown that enzymatic modification of pectin can benefit from the application of membrane bioreactors.^{5–10} With the use of membrane bioreactors, enzymes are retained in the reaction system while, at the same time, allowing for (continuous) product removal and substrate feeding. It is indeed a rational processing option, as the high viscosity of pectin in solution prevents batch processing of high initial substrate levels, which, in turn, is a barrier to obtaining high enzyme efficiencies. Moreover, potentially inhibitory low-molecular-weight compounds—produced from the continuous degradation of the pectin polymer—can be continuously removed from the reaction mixture and, thus, the reaction rates increase. An increase by 40% in volumetric productivity ($\text{kg}_{\text{product}} (\text{m}^{-3} \text{ reactor volume h}^{-1})$)—compared to the productivity in a traditional batch reactor—has been reported when low-molecular-weight substances (e.g., D-galacturonic acid) produced from the depolymerization of pectin were continuously

removed from the system.⁶ It has also been demonstrated that a membrane reactor may run stably for up to 15 days of continuous operation with the possibility of achieving a pectin substrate conversion as high as 90%.⁷ In addition, proper selection of the membrane molecular weight cutoff (MWCO), coupled with a feasible operation strategy (i.e., batch, fed-batch or continuous operation) and appropriate reactor residence time, offer the possibility of controlling the molecular weight size distribution of the end-product mixture, which is an outcome that cannot be achieved with conventional batch reactors.^{5,8,11}

To date, academia relies mostly on bench-scale membrane bioreactors to conduct studies on continuous enzyme-catalyzed pectin hydrolysis reactions.^{5–10} Considering the huge number of experiments usually needed to elucidate novel enzyme-catalyzed production processes and the large amount of enzymes and substrates consumed per experiment (i.e., bench-scale reactors normally operate with a volume from a few hundred milliliters and upward), performing experiments in bench-scale membrane bioreactors can be very costly, especially when multiple parallel experiments are needed.

In this respect, miniature-sized bioreactors (i.e., microfabricated reactors with working volumes of $< 1 \text{ mL}$ ^{12,13}) with integrated

Received: February 20, 2011

Accepted: August 15, 2011

Revised: August 4, 2011

Published: August 15, 2011

Figure 1. Two-dimensional (2-D) schematic of the membrane microbio reactor experimental setup.

sensors and actuators are better-suited for research and process development studies. This is because, at such a small scale of operation, enzyme and substrate consumption are significantly reduced (normally in the range of micrograms or microliters per experiment) while heat- and mass-transfer rates are notably increased.^{12,13} Muller et al.¹⁴ compared the running cost of similar experiments performed in a different scale of operation and reported that the running cost for continuous reactions in a microreactor—relative to the bench-scale reactor—decreases by a factor of 50. Delattre et al.¹⁵ proposed the use of a convective interactive media (CIM) disk as a support for immobilization of pectin lyase (PL) in a microreactor and demonstrated the usefulness of such a microsystem in investigating the optimum temperature, optimum pH, and thermal stability of the enzyme. In a previous study,¹⁶ we developed a disposable membrane microbio reactor system and showed that the kinetic profiles achieved in microscale were congruent with those obtained in a bench-scale setup (i.e., a reproducible result is obtained in a miniature-scale membrane reactor while only requiring a fraction of the resources typically needed to operate a bench-scale membrane bio reactor).

In this paper, we aim to further examine the functionality of the membrane microbio reactor prototype and assess if such a miniature membrane reactor can be applied to evaluate consequences of process operation choices relevant for larger-scale enzymatic degradation of pectin reactions. Different reactor design options—namely, membrane molecular weight cutoff (MWCO), enzyme-to-substrate ratio (E/S), and substrate feeding rate (F)—were tested to assess their influence on the reaction yield and productivity. The MWCO, E/S ratio, and feeding rate (i.e., reactor residence time) all are important reactor variables that have direct influence on the enzymatic degradation of pectin reaction rates/yield and selectivity toward the production of desired oligomers.^{2,8,9}

MATERIALS AND METHODS

Microbio reactor Design and Fabrication. The scheme of the experimental setup for the membrane microbio reactor is

illustrated in Figure 1. Prototyping of the microbio reactor was done with three-dimensional (3D) computer-aided design (CAD) software, SolidWorks 2006, and micromachining in which poly(methylmethacrylate) (PMMA) (Plexiglas GS, Klar 233, Nordisk Plast, Auning, Denmark) and poly(dimethylsiloxane) (PDMS) were used as the materials for fabrication. Development of the prototype also encompassed setting up the necessary measurement apparatus and machinery to drive the microbio reactor systems. Mixing of the reactor content was achieved by means of a magnetic stirrer bar and the recirculation pump. Both the magnetic stirrer and the recirculation pump were set to operate at a rotational speed (N) of 500 rpm and at a recirculation rate (R_p) of 2700 $\mu\text{L/h}$, respectively. These operating conditions remained unchanged in each experimental run to provide a consistent mixing performance.

Programs for measurement and control routines were written in LabVIEW v8.5 software (National Instruments, Austin, TX, USA), and were implemented by interfacing LabVIEW with a data acquisition (DAQ) card (NI USB-6229, National Instruments) for data logging and sending signals to actuators. Further analysis of *online* measurement data (temperature and pressure) was done using Matlab v7.0 software (The Mathworks, Natick, MA, USA). Details for the design and fabrication of the membrane microbio reactor prototype have been described elsewhere.¹⁶

Startup and Reactor Operation. The startup of the reaction in the membrane microbio reactor first involved filling the reactor with enzyme solution. The enzyme solution was loaded into the reactor by disconnecting one of the inflow/outflow interconnects at the side of the bottom PMMA layer. While the enzyme solution filled the reactor, air that was trapped inside the PFA tubes, the microchannels, and the reaction chamber was pushed out of the reactor simultaneously through one of the already-opened side ports. Since the PFA tubes and the microbio reactor were both transparent, bubble-free conditions were assessed visually before starting the reaction. Once the reactor was completely filled, the loop was reconnected. The reactor temperature then was set and the reaction was initiated by starting

the feeding of the substrate solution. Substrate solution was continuously fed into the reactor using a syringe pump (Model MA1 70-2211, Harvard Apparatus, Holliston, MA, USA) and circulated by means of a micro gear pump (Model mzt 2905, HNP Mikrosysteme GmbH, Parchim, Germany).

During the course of reaction (which occurred in both the reactor chamber and the recirculation line), enzyme and unreacted substrate solutions were retained in the system by the membrane while low-molecular-weight products (less than the membrane MWCO) were continuously separated from the system. Regenerated cellulose membranes with MWCO = 1 and 10 kDa, respectively (Model PLGC06210, Millipore, Billerica, MA, USA) were used for separation.

Enzymatic Depolymerization of Sugar Beet Pectin by Pectin Lyase. Sugar beet pectin with a degree of methoxylation of ~60% and a degree of acetylation of ~19% (Danisco A/S, Brabrand, Denmark) was used as a substrate. The pectin lyase used in this study was supplied by Novozymes A/S (Bagsværd, Denmark). It was a cloned monocomponent enzyme from *Aspergillus aculeatus* with an enzyme activity on citrus pectin of 0.0085 U/mg. (One unit of activity (U) is defined as the production of 1 μ mol of double bonds per minute at pH 4.5 and 50 °C.) A 0.1 M sodium acetate buffer solution (pH 4.5) was used to prepare both the substrate and the enzyme solutions.

Continuous enzymatic pectin degradation experiments were performed for a limited range of different reactor variables, namely, membrane MWCO (1 kDa and 10 kDa), E/S (0.2% (g/g) and 0.4% (g/g)), and F (100 and 200 μ L/h). For every experimental condition, the reaction was performed with an initial substrate concentration ($[S]_0$) of 10 g/L, at pH 4.5, and the temperature was controlled at 50 °C. Duplicates were made for every experiment to check data reproducibility, and the reaction was carried out until a steady state was reached.

Ultraviolet (UV) Absorption at 235 nm. Similarly to the analytical method applied in our previous work,¹⁶ the UV absorption analysis was performed in order to monitor the progress of the depolymerization reaction. This was done by measuring sample absorbance via a microtiter plate reader at 235 nm. Beer–Lamberts law ($A_{235} = \epsilon c$) was used to estimate the concentration of product fragments (c) generated from the depolymerization reaction. A molar absorption coefficient (ϵ) of 5500 $M^{-1} cm^{-1}$ was used.¹⁷

Monogalacturonic and Oligogalacturonic Acid Electrochemical Measurement via HPAEC-PAD. Identification and quantification of monogalacturonic and oligogalacturonic acids in hydrolysates were performed using an ICS-3000 system coupled to an AS50 autosampler (Dionex Corp., Sunnyvale, CA). Separations were performed using a CarboPac PA20 (3 mm $\times$ 150 mm) analytical column (Dionex Corp.), according to the method described previously.¹⁸ A two-eluent system comprised of deionized water (18.2 mS/cm at 25 °C) and 500 mM NaOH aqueous solution was used. Monosaccharides and oligosaccharides were eluted isocratically with 2.5 mM NaOH for 20 min, followed by a second isocratic elution at high NaOH concentration (500 mM) for 10 min to elute any present acidic species. The eluent flow rate was always kept at 0.5 mL/min. All eluents were prepared from high-performance liquid chromatography (HPLC)-grade chemicals. The quantification of monogalacturonic and digalacturonic acids was carried out using external standards. Trigalacturonic acids were quantified using the response factor of galacturonic acid. Data were collected and analyzed on computers equipped with Chromeleon 6.80 Sp8 software (Dionex Corp.).

Figure 2. Pectin fragment concentration dynamics in the permeate (mM): comparison between membranes with molecular weight cutoff (MWCO) values of 1 and 10 kDa run at a feeding rate (F) of 200 μ L/h with an enzyme-to-substrate ratio (E/S) = 0.2% (g/g). The data points are averages of two experimental runs, shown $\pm$ standard deviation ($\sigma_{\max} < 0.04$ mM).

RESULTS AND DISCUSSION

The kinetic profiles of the enzymatic pectin degradation experiments followed a general trend where the concentration of the pectin fragments in the permeate increased progressively with time until a steady state was reached. In each case, a steady-state product formation level was reached when a balance between the feed flow rate (F , in units of μ L/h), the kinetic conversion rate (i.e., the overall rate of the enzymatic reaction, as measured from the product formation rate), and the membrane flux of the system was reached.¹⁶ Based on the experimental data with two different membranes, i.e., MWCO = 1 and 10 kDa (Figure 2), it was found that the membrane with MWCO = 1 kDa showed a higher membrane rejection at the beginning of the reaction, compared to the membrane with MWCO = 10 kDa, resulting in an apparently lower product formation rate of pectin fragments (Figure 2). Theoretically, the membrane rejection coefficient (R) is defined as a function of the ratio between the solute concentration in the permeate (C_p) and the solute concentration on the surface of the membrane (C_M) (i.e., $R = 1 - C_p/C_M$). Thus, C_M is a function of the solute concentration in the reactor.¹⁹ From this relation, a lower permeate concentration (C_p) indicates a higher membrane rejection characteristic when C_M is constant. Hence, the results obtained are as expected for a membrane with smaller pore size (i.e., 1 kDa vs 10 kDa) as the membrane with the lower MWCO will reject pectin fragments with molecular weights of >1 kDa.

Interestingly, when the enzymatic reaction came to steady state (Figure 2), the final concentrations of pectin fragments in the permeate were comparable (yield ≈ 0.55 mM) for both membranes (i.e., 1 and 10 kDa). This result indicated that, as the reaction proceeded to steady state, the membrane pore size was no longer influencing the membrane rejection, despite the fact that the pore size of the membranes differed by a factor of 10. This observation may be due to increased viscosity and/or fouling resulting from the buildup of unreacted substrate in the reactor as well as at the membrane surface (i.e., concentration polarization effects). Such effects lead to an increase of C_M and, hence, the rejection R of the 10 kDa membrane. It was

Figure 3. Concentration profiles of the pectin oligomers for membranes with different molecular weight cutoff (MWCO) values ((a) MWCO = 1 kDa and (b) MWCO = 10 kDa), run at a feeding rate (F) of 200 $\mu\text{L/h}$ with an enzyme-to-substrate ratio (E/S) of 0.2% (g/g). (Legend: ($\square$) GalA monomers, ($\diamond$) GalA dimers, and ($\circ$) GalA trimers.)

anticipated that the membrane with the lowest MWCO value would have the highest membrane selectivity while removing pectin fragments from the reactor system, i.e., shorter fragments were to be expected in the permeate mixture when using a membrane with smaller pore size (e.g., 1 kDa). Size-exclusion chromatography (SEC) profiles confirmed the presence of different sizes of pectin oligomers in the reactor permeate (data not shown), but, as shown in Figure 3, it was also found that similar types and relatively similar levels of the very-low-molecular-weight pectin oligomers, i.e., galacturonic acid (GalA) monomers, dimers, and trimers, were recovered in the permeate for both membranes (the molecular weights of the dehydrated, methylated forms of the monogalacturonic, digalacturonic, and trigalacturonic acids are ~ 190 , 380, and 570 D, respectively). The oligomer concentration profiles for both membrane systems indicated a sharp increase of the oligomer concentration during the first 2–4 h of reaction, before reaching a steady state after a reaction time of ~ 4 h (Figure 3). Although the concentrations of the recovered low-molecular-weight pectin oligomers in the permeate were slightly higher for the 10 kDa membrane system, compared to the 1 kDa system, suggesting that the enzymatic rates could be slightly higher on pectin oligomers than on the native polysaccharides, it can be concluded that the concentrations of the low-molecular-weight pectin oligomers were within the same order of magnitude for both membranes.

In our previous work,¹⁶ it was observed that the system pressure gradually increased after the initiation of the enzymatic reaction (i.e., a relative pressure increase as high as 1.5 bar was registered). The increase of the system pressure was believed to be caused by the accumulation of the unreacted substrate molecules in the system. This was confirmed, since the system pressure no longer increased when the substrate feeding was stopped and the system was flushed with buffer solution (i.e., solution without the presence of any pectin substrates).¹⁶ Under a pressurized state—due to continuous feeding—the unreacted substrates will tend to deposit on the surface of the membrane, which leads to the formation of a gel layer on the membrane surface.²⁰ Hence, it creates a concentration gradient between the substrate concentration in the bulk solution and the concentration on the membrane surface (i.e., concentration polarization effects). Considering the typical diffusivity (D) values of pectin

Table 1. Concentration of Oligomers (Monomers, Dimers, and Trimers) in the Retentate and in the Permeate at Steady State for the Membranes Used in the Experimental Work: (a) MWCO = 1 kDa and (b) MWCO = 10 kDa

(a) 1 kDa of MWCO			
at steady state, $t = 12$ h	GalA monomers	GalA dimers	GalA trimers
[retentate], C_b (mg/L)	8.03	4.5	2.2
[permeate], C_p (mg/L)	10	8	2.9
(b) 10 kDa of MWCO			
at steady state, $t = 8$ h	GalA monomers	GalA dimers	GalA trimers
[retentate], C_b (mg/L)	8.5	4.6	2.3
[permeate], C_p (mg/L)	10.7	9.3	3.38

molecules (i.e., $\sim 10^{-11}$ m^2/s)²⁰ and a standard membrane boundary layer thickness, δ ($\sim 15 \times 10^{-6}$ m for 1% (w/v) of pectin²¹); it is possible to deduce that, under a constant feeding rate of 200 $\mu\text{L/h}$, the concentration of pectin close to the membrane surface, C_M could be ~ 7 –10 times higher (~ 70 –100 g pectin/L) than the concentration of pectin in the bulk solution (C_b , i.e., in accordance to $C_M/C_b = \exp(J_v/k)$).¹⁹ The rejection capacity of the system can be greatly influenced by this additional gel layer on the membrane surface.⁹

Since the substrate feeding rate (F) is equivalent to the permeate flux (J_p), because the microreactor volume does not change with time (i.e., $dV/dt = 0$ and no headspace), the pectin oligomer concentration in the bulk solution (C_b) can be assumed to be the same as the concentration of the pectin oligomers in the permeate (C_p). The results from the HPLC analysis also supported the hypothesis of identical concentrations of small pectin fractions in the bulk solution and in the permeate (see Table 1). In the steady state, comparable concentrations of GalA monomers, dimers, and trimers were detected at both sides of the membrane (i.e., retentate and permeate) for both 1 and 10 kDa membranes. Hence, based on this analysis, the apparent higher production rate of pectin fragments observed for the 10 kDa membrane as assessed by the amount of dehydrated

Figure 4. Concentration profiles of pectin fragments in the permeate (given in units of mM) for a membrane with a molecular weight cutoff (MWCO) of 1 kDa, operated under different enzyme-to-substrate (E/S) ratio (i.e., 0.2% or 0.4% (g/g)) at a feeding rate (F) of 200 $\mu\text{L}/\text{h}$. The data points are averages of two experimental runs, shown $\pm$ standard deviation ($\sigma_{\text{max}} < 0.04$ mM).

Figure 5. Concentration profile of pectin fragments in the permeate (given in units of mM) for a membrane with MWCO = 10 kDa, operated at different feeding rates (i.e., 100 or 200 $\mu\text{L}/\text{h}$) at an E/S ratio of 0.2% (g/g). The data points are averages of two experimental runs, shown $\pm$ standard deviation ($\sigma_{\text{max}} < 0.04$ mM).

reducing ends by UV absorbance (Figure 2), indicated that a higher amount of larger-molecular-weight pectin fragments (i.e., larger than trigalacturonic acid) passed through the 10 kDa membrane than through the 1 kDa membrane during the first 8 h of the reaction.

To further evaluate the ability of the microbio reactor prototype to assess consequences of process operation choices, we tested the system by varying the E/S ratio as well as F . When the E/S ratio was increased, both the steady-state concentration of pectin fragments in the permeate and the apparent steady-state reaction rate increased; with the 1 kDa MWCO membrane at a residence time of 1 h, the steady-state rates, which were established after ~ 8 h of reaction, were calculated to be 0.11 and 0.13 $\mu\text{mol}/\text{h}$ for E/S dosages of 0.2% and 0.4% (g/g), respectively. This is presented in Figure 4. In contrast, when the substrate feeding rate (F) was reduced from 200 $\mu\text{L}/\text{h}$ to 100 $\mu\text{L}/\text{h}$, a significant increase in the steady-state product concentration, from 0.55 mM to ~ 0.82 mM was achieved (Figure 5). The apparent steady-state reaction rate increased

Figure 6. Concentration profile of pectin fragments in the permeate (given in units of mM) for membranes with MWCO = 1 kDa and 10 kDa, respectively, operated at a feeding rate of $F = 100$ $\mu\text{L}/\text{h}$ with an E/S ratio of 0.2% (g/g). The data points are averages of two experimental runs, shown $\pm$ standard deviation ($\sigma_{\text{max}} < 0.04$ mM).

by $\sim 50\%$ (i.e., from 0.11 $\mu\text{mol}/\text{h}$ to 0.17 $\mu\text{mol}/\text{h}$) at increased residence times from 1 h to 2 h for a membrane with MWCO = 10 kDa at an E/S ratio of 0.2% (g/g) (calculated from data shown in Figure 5). This result was expected since reducing the substrate feeding rate (F) by 50%, in effect, increased the reactor residence time from ~ 1 h to ~ 2 h. Theoretically, the residence time (τ) is defined as the reactor volume divided by the reactor feeding flow rate (F). The residence time can also be translated as the time period that the enzyme has to catalyze the degradation of the pectin (i.e., substrate) before the degraded fragments were removed from the system, as signified by Lin et al.²² In addition, reducing the system flux apparently decreased the accumulation rate of the unreacted substrates on the membrane surface. In turn, this resulted in a higher product recovery rate as the concentration polarization effect was considerably reduced (and a less thick gel layer was formed on the membrane, because of the lower flux rate). Olano-Martin et al.⁸ also reported that an increase of residence time led to a higher product conversion of high methylated pectin into pectic-oligosaccharides in a continuous dead-end membrane reactor.

Similarly, when the enzymatic reaction was performed under the same conditions as those reported in Figure 2, but with a lower feeding rate (i.e., system flux ≈ 100 $\mu\text{L}/\text{h}$ and residence time of $\tau = 2$ h), a significantly higher product yield and recovery rate were observed (see Figure 6). The apparent steady-state product formation level increased with longer residence time (i.e., up to ~ 0.82 mM and 0.65 mM for the 10 kDa and 1 kDa membranes, respectively (Figure 6)). Hence, the reactor residence time of 1 h limited the apparent steady-state product formation levels (i.e., yield ≈ 0.55 mM) when different membrane MWCO values were evaluated (refer to Figure 2). The recorded effect of reactor residence time on the steady-state product formation level indicated that the apparent steady-state product level could be controlled (at least within certain boundaries) by adjusting the feed rate, which influenced both the substrate supply and the residence time. There was apparently plenty of substrate, even at the low feed rate, which, in turn, must signify that the enzymatic rate in the reactor (i.e., at the apparent steady state) was running near maximum.

In the present work, we demonstrated that the impact of important process operation design choices—namely, the substrate

feeding rate (F) (i.e., reactor residence time or system flux), molecular weight cutoff (MWCO) of the membrane, and the enzyme-to-substrate ratio (E/S)—could be investigated with the use of a membrane microbioreactor prototype. The results highlight that F is a critical variable that can dramatically alter the rejection profile of a membrane bioreactor system. Obviously, there was a serious accumulation of unreacted substrates in our system. We deliberately operated our microbioreactor system under the chosen experimental conditions (i.e., at relatively low E/S ratios of 0.2% (g/g)), because we wanted to closely monitor the progress and the dynamic changes of continuous degradation of pectin polymer kinetic profiles. We also set the reactor to work at a residence time of 1–2 h, because we need to generate sufficient volume of permeate for sampling and analysis. A low standard deviation, σ (i.e., $\sigma_{\max} < 0.04$ mM and also observable from the error bars in each plot), showed that data obtained in every experiment were highly reproducible. In this respect, we believe that the usage of a fresh membrane for every experiment is crucially important for achieving high data reproducibility. Every experiment requires only low amounts of enzymes and substrates, a small piece of membrane per experiment ($A_m \approx 38.5$ mm²), and also a relatively inexpensive temperature control system (i.e., a few centimeters of wire as the heating element for temperature control²³); this allows for a large number of experiments to be tested against a relatively low cost. Finally, another aspect worth mentioning here is the potential for parallel reactor operation. This is indeed a challenging task as fluidic handling (e.g., feeding strategy) and local reactor monitoring and control become increasingly complex when the number of microbioreactors increases from one to many units. Nevertheless, parallel reactor operation is essential and it would definitely be useful for screening novel processes, in a process optimization step or in predicting effects of various operation variables on the reaction rates/yield. The membrane microbioreactor presented here—in its current state—may still require some modifications before parallel operation becomes feasible. First, integration of on board micropumps and microvalves²⁴ would be required as substitutes for the large and expensive pumps used in the current version of this setup. Second, the permeate stream should be interfaced with a microfluidic detection chip such that the progress of the experiment performed in the prototype can be monitored *online*, i.e., via a fully automated system, thus eliminating the need for sampling, which, in practice, can be very laborious and demanding for lengthy reactor operation.

CONCLUSIONS

A continuous β -elimination of sugar beet pectin catalyzed by pectin lyase has been successfully performed in a membrane microbioreactor prototype under various experimental conditions of membrane molecular weight cutoff (MWCO), substrate feeding rate (F , given in units of $\mu\text{L/h}$), and enzyme-to-substrate (i.e., pectin) ratio (E/S). The experimental data indicated that the concentration polarization phenomenon—which is an effect that is typically encountered in a membrane separation system—has a strong influence on the product removal rate of the reactor system. While higher enzyme load increases reaction rates, the product recovery rate is highly governed by the system flux (i.e., feeding rate). Moreover, the membrane MWCO was also found to have little or no significant impact on membrane selectivity when concentration polarization became a limiting factor for

product separation. From the practical point of view, we developed a disposable microbioreactor system that allows for inexpensive experimentation in a laboratory environment. Summarizing, the results demonstrate the potential use of the membrane microbioreactor prototype as a supporting tool for assessing novel “biorefining”-type processes (e.g., enzyme-catalyzed degradation of pectin) and especially allowing prediction of the consequences of reactor design choices, notably the membrane MWCO and the substrate feeding rate F .

AUTHOR INFORMATION

Corresponding Author

*Tel.: +607 5535541. Fax: +607 5581463. E-mail: nazrul@cheme.utm.my.

ACKNOWLEDGMENT

The financial support of Muhd Nazrul Hisham Zainal Alam, for his Ph.D. project, by Universiti Teknologi Malaysia and the Malaysia Ministry of High Education is acknowledged.

LIST OF SYMBOLS

MWCO = membrane molecular weight cutoff (kDa)

E/S = enzyme to substrate ratio % (g/g)

$[S]_0$ = initial substrate concentration (g/L)

F = substrate feeding rate ($\mu\text{L/h}$)

A_{235} = absorbance at 235 nm

c = concentration of product fragments (M or mM)

ε = molar absorption coefficient ($\text{M}^{-1} \text{cm}^{-1}$)

R_p = recirculation rate ($\mu\text{L h}^{-1}$)

N = rotational speed (rpm)

C_b = concentration of oligomers in bulk solution/retentate (g/L or mg/L)

C_p = concentration of oligomers in permeate (g/L or mg/L)

C_M = concentration of oligomers in surface of membrane (g/L or mg/L)

D = molecule diffusivity (m^2/s)

δ = boundary layer (i.e., gel layer) thickness (m)

k = mass-transfer coefficient; $k = D/\delta$ (m/h)

J_v = system flux (m/h)

J_p = permeate flux (m/h)

R = membrane rejection coefficient (dimensionless)

A_m = membrane surface area (mm²)

τ = residence time (h)

REFERENCES

- (1) Ovodov, Y. S. Current views on pectin substances. *Russ. J. Bioorg. Chem.* **2009**, *35*, 269–284.
- (2) Pinelo, M.; Jonsson, G.; Meyer, A. S. Membrane technology for purification of enzymatically produced oligosaccharides: Molecular and operational features affecting performance. *Sep. Purif. Technol.* **2009**, *70*, 1–11.
- (3) Nikolic, M. V.; Mojovic, L. Hydrolysis of apple pectin by coordinated activity of pectic enzymes. *Food Chem.* **2007**, *101*, 1–9.
- (4) Holck, J.; Hjerno, K.; Lorentzen, A.; Vignæs, L. K.; Hemmingsen, L.; Licht, T. R.; Mikkelsen, J. D.; Meyer, A. S. Tailored enzymatic production of oligosaccharides from sugar beet pectin and evidence of differential effects of a single DP chain length difference on human faecal microbiota composition after *in vitro* fermentation. *Process Biochem.* **2011**, *46*, 1039–1049.
- (5) Gallifuoco, A.; Cantarella, M.; Marucci, M. Investigating the kinetics of the enzymatic depolymerization of polygalacturonic acid in

continuous UF-membrane reactors. *Biotechnol. Prog.* **2007**, *23*, 1111–1117.

(6) Belafi-Bako, K.; Eszterle, M.; Kiss, K.; Nemestothy, N.; Gubicza, L. Hydrolysis of pectin by *Aspergillus niger* polygalacturonase in a membrane bioreactor. *Food Eng.* **2007**, *78*, 438–442.

(7) Rodriguez-Nogales, J. M.; Ortega, N.; Perez-Mateos, M.; Busto, M. D. Pectin hydrolysis in free enzyme membrane reactor: An approach to the wine and juice clarification. *Food Chem.* **2008**, *107*, 112–119.

(8) Olano-Martin, E.; Mountzouris, K. C.; Gibson, G. R.; Rastall, R. A. Continuous production of pectic oligosaccharides in an enzyme membrane reactor. *J. Food Sci.* **2001**, *66*, 966–971.

(9) Rodriguez-Nogales, J. M.; Ortega, N.; Perez-Mateos, M.; Busto, M. D. Operational stability and kinetic study of a membrane reactor with pectinases from *Aspergillus niger*. *Food Sci.* **2008**, *70*, 104–108.

(10) Gallifuoco, A.; Alfani, F.; Cantarella, M.; Viparelli, P. New experimental procedure for monitoring molecular weight breakdown during enzymatic degradation of polygalacturonic acid in continuous membrane reactors. *Ind. Eng. Chem. Res.* **2003**, *42*, 3937–3942.

(11) Martin-Orue, C.; Henry, G.; Bouhallab, S. Tryptic hydrolysis of κ -caseinomacropeptide: Control of the enzymatic reaction in a continuous membrane reactor. *Enzyme Microb. Technol.* **1999**, *24*, 173–180.

(12) Betts, J. I.; Baganz, F. Miniature bioreactors: current practices and future opportunities. *Microb. Cell Fact.* **2006**, *5*, 1–14.

(13) Schapper, D.; Zainal Alam, M. N. H.; Szita, N.; Lantz, A. E.; Gernaey, K. V. Application of microbioreactors in fermentation process development: A review. *Anal. Bioanal. Chem.* **2009**, *395*, 679–695.

(14) Muller, D. H.; Liauw, M. A.; Greiner, L. Microreaction technology in education: Miniaturized enzyme membrane reactor. *Chem. Eng. Technol.* **2005**, *28* (12), 1569–1571.

(15) Delattre, C.; Michaud, P.; Vijayalakshmi, M. A. New monolithic enzymatic micro-reactor for the fast production and purification of oligogalacturonides. *J. Chromatogr. B* **2008**, *861*, 203–208.

(16) Zainal Alam, M. N. H.; Pinelo, M.; Samantha, K.; Jonsson, G.; Meyer, A.; Gernaey, K. V. Continuous membrane microbioreactors for development of integrated pectin modification and separation processes. *Chem. Eng. J.* **2010**, *167*, 418–426.

(17) van den Broek, L. A. M.; den Aantrekker, E. D.; Voragen, A. G. J.; Beldman, G.; Vincken, J. P. Pectin lyase is a key enzyme in the maceration of potato tuber. *J. Sci. Food Agric.* **1997**, *75*, 167–172.

(18) Arnous, A.; Meyer, A. S. Comparison of methods for compositional characterization of grape (*Vitis vinifera* L.) and apple (*Malus domestica*) skins. *Food Bioprod. Process.* **2008**, *86*, 79–86.

(19) Mulder, M. *Basic Principles of Membrane Technology*; Kluwer Academic Publishers: London, 1996.

(20) Sarkar, B.; Dasgupta, S.; De, S. Effect of electric field during gel-layer controlled ultrafiltration of synthetic and fruit juice. *J. Membr. Sci.* **2008**, *307*, 268–276.

(21) Sarkar, B.; Pal, S.; Ghosh, T. B.; Dea, S.; DasGupta, S. A study of electric field enhanced ultrafiltration of synthetic fruit juice and optical quantification of gel deposition. *J. Membr. Sci.* **2008**, *311*, 112–120.

(22) Lin, Y.-W.; Hsiao, Y.-C.; Chiang, B.-H. Production of high degree polymerized chitooligosaccharides in a membrane reactor using purified chitosanase from *Bacillus cereus*. *Food Res. Int.* **2009**, *42*, 1355–1361.

(23) Zainal Alam, M. N. H.; Schapper, D.; Gernaey, K. V. Embedded resistance wire as heating element for temperature control in micro-bioreactors, *Microeng.* **2010**, *20*, 055014. (DOI: 10.1088/0960-1317/20/5/055014.)

(24) Wu, M.-H.; Huang, S.-B.; Cui, Z.; Cui, Z.; Lee, G.-B. A high throughput perfusion-based microbioreactor platform integrated with pneumatic micropumps for three-dimensional cell culture. *Biomed. Microdevices* **2008**, *10*, 309–319.