



Suppression of vibration in bounded structures subjected to action of a distributed load by continuous spatial modulations of their parameters

Sorokin, Vladislav

Published in:

Proceedings of the 11th World Congress on Computational Mechanics (WCCM XI)

Publication date:

2014

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Sorokin, V. (2014). Suppression of vibration in bounded structures subjected to action of a distributed load by continuous spatial modulations of their parameters. In *Proceedings of the 11th World Congress on Computational Mechanics (WCCM XI)*

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

SUPPRESSION OF VIBRATION IN BOUNDED STRUCTURES SUBJECTED TO ACTION OF A DISTRIBUTED LOAD BY CONTINUOUS SPATIAL MODULATIONS OF THEIR PARAMETERS

Vladislav S. Sorokin¹

¹ Department of Mechanical Engineering, Technical University of Denmark, Nils Koppels Allé,
Building 404, 2800 Kgs. Lyngby, Denmark, vladsor@mek.dtu.dk

Key Words: *Vibration Suppression, Bounded Structures, Distributed Load, Spatial Modulations, Inhomogeneous String.*

The paper is concerned with a problem of vibration suppression in any preassigned region of a bounded structure subjected to action of an external load which is distributed over its entire area. Continuous spatial modulations of structure parameters, particularly of its material, are proposed to be used as a means for vibration suppression. The considered problem is relevant, in particular, for the task of sound and vibration isolation which gained much attention in the recent years (see, e.g. [1-4]). Usually, behaviour of unbounded structures in presence of a point load or an excitation source is considered within this task [1,2]. So, the problem reduces to identification of frequency stop and pass bands and their subsequent tailoring by spatial/temporal modulations of system parameters. In the present paper the problem of vibration suppression is considered in a different formulation: behaviour of a bounded structure under action of a distributed load is studied. Similar cases were analyzed, in particular, in the monograph [3]. We note that the problem under study is close to those solved by the method of topology optimization [4], which is a popular method for obtaining the optimal layout of one or several material constituents in structures and materials.

As a simple illustrative example, consider oscillations of a string under action of an external distributed time-periodic load. The suppression of vibration in predefined areas of the string is carried by continuous spatial modulation of its cross-section. So, the following equation is studied:

$$\rho S \frac{\partial^2 u}{\partial t^2} - \frac{\partial}{\partial x} \left(T \frac{\partial u}{\partial x} \right) = f(x, t), \quad (1)$$

here ρ is density of the string material, T is tension force, $u(x, t)$ is lateral deflection of the string, $S(x)$ is the variable cross-sectional area, $f(x, t) = f_0(x) \sin \omega t$ is density of the external load. The boundary conditions are set to be homogeneous: $u|_{x=0} = u|_{x=l} = 0$. To solve the considered problem a novel approach based on the method of direct separation of motions [5] is employed. First, the case of harmonic in the spatial coordinate x external load $f_0(x) = F_0 \cos kx$ was studied. As the result, it is shown that the optimal characteristics of vibration suppression will be achieved when cross-section is modulated in the following way:

$$S(x) = S_0 (1 + \chi \cos(2kx + \theta)), \quad (2)$$

here $\theta = \pi$ if $\delta = \omega^2 \rho S_0 / (Tk^2) < 1$, and $\theta = 0$ if $\delta > 1$. For example, it is possible to completely suppress vibration near one of the string ends. Also a considerable reduction of vibration near any preassigned point of the string can be achieved. The corresponding dependencies of the string deflection on the spatial coordinate x are presented in Figure 1 (a)-(c) for various χ and the following values of other parameters $\rho S_0 / T = 1(\text{s/sm})^2$, $l = 5 \text{ sm}$, $k = 10 \text{ 1/sm}$, $F_0 = -10 \text{ kg/s}^2$, $\omega = 9.51/\text{s}$. We note that it is possible to suppress vibration considerably in the whole string when χ is comparatively large (see Figure 1 (d)).




Figure 1. Dependencies of the string deflection on the spatial coordinate x .

The case of arbitrarily distributed external load was also studied. Expanding function $f_0(x)$ in the Fourier series, an optimal modulation of the string cross-sectional area is determined.

The work is financed by the Danish Council for Independent Research and FP7 Marie Curie Actions – COFUND: DFF – 1337-00026.



REFERENCES

- [1] D.J. Mead, Wave propagation in continuous periodic structures: research contributions from Southampton. *Journal of Sound and Vibration*, Vol. **190** (3), pp. 495-524, 1996.
- [2] B.R. Mace, D. Duhamel, M.J. Brennan, L. Hinke, Finite element prediction of wave motion in structural waveguides. *Journal of the Acoustical Society of America*, Vol. **117**, 2835–2843, 2005.
- [3] N.S. Bakhvalov, G.P. Panasenko, *Homogenization: averaging processes in periodic media*, Kluwer, 1989.
- [4] M.P. Bendsøe, O. Sigmund, *Topology optimization - theory, methods and applications*, Springer-Verlag, 2003.
- [5] I.I. Blekhman, *Vibrational mechanics*, World Scientific, 2000.