



Transmittance enhancement in 6H-SiC with nanocone structures

Lu, Weifang; Ou, Yiyu; Ou, Haiyan

Publication date:
2015

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Lu, W., Ou, Y., & Ou, H. (2015). *Transmittance enhancement in 6H-SiC with nanocone structures*. Abstract from 3rd European-Asian workshop on Light-Emitting Diodes, Lyngby, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Transmittance enhancement in 6H-SiC with nanocone structures

Weifang Lu^{1,*}, Yiyu Ou^{1,2}, and Haiyan Ou¹

¹Department of Photonics Engineering, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark

²Light Extraction ApS, 2800, Kgs. Lyngby, Denmark

*E-mail: weilu@fotonik.dtu.dk

Abstract — Enhanced transmittance of 6H-SiC with nanocone structures were achieved by using self-assembled Au nanoparticles as etching mask. HF passivation process of nanocone structures was investigated to further improve the transmittance. The max transmittance of structured SiC is significantly improved by 10%.

Keywords—nanocone; transmittance; HF passivation

I. INTRODUCTION

The light extraction efficiency is one of the most important parameters for high-performance light-emitting diodes, which is usually low due to the refractive index mismatch at the interface of SiC and air^[1]. To enhance the extraction efficiency, nanostructures could be implemented at the SiC surface using e-beam lithography^[2], nanosphere lithography^[3], self-assembled metal nanoparticles^[4], or Al thin film^[5]. But the surface nanostructures also lead to the enhanced recombination rate due to surface defects and dangling bond, introduced during the fabrication process. To date, hydrogenation, and deposition of SiO₂, SiN_x, Al₂O₃ or TiO₂ are effective ways to improve the surface passivation^[6]. In this work, nanocone structures on 6H-SiC were achieved by self-assembled Au nanoparticles. We used 5% HF solution to clean and passivate the surface.

II. RESULTS AND DISCUSSIONS




Fig1. (a) SEM cross-section view of the sample and (b) the transmittance curves of the sample after different process.

To improve the uniformity of Au nanoparticles, 20nm SiO₂ layer were deposited on the surface of original 6H-SiC samples. Then, a 6nm Au film layer was deposited on the surface. After treated by rapid thermal annealing at 650 °C for 3min, Au nanoparticles were formed. The nanocone structures were fabricated by utilizing RIE etching for 5 min, followed by 15min oxygen plasma cleaning to remove the residual polymer. The residual Au was removed by iodine based solution. The samples were passivated for different time (5min, 10min, 20min and 30min) to improve transmittance. It is found that the nanocone structures are approximately

400nm high and 100nm wide, as shown in Fig.1 (a). Fig1 (b) shows the transmittance curves of the sample after different process, which was measured by a calibrated goniometer system. The transmittance of nanocone structured SiC was enhanced by 6%. After HF passivation for 30min, the transmittance was improved by 10 %.




Fig2.XPS survey scans before and after RIE etching, removing Au, HF etching for different time.

The analysis of the surface was carried out with XPS using Al $K\alpha$ radiation with energy resolution of 0.1eV. The corresponding O1s peak was refer to nature oxidation layer of nanocone surface in room temperature as shown in Fig2. It is apparent that RIE processing generated fluoride contamination on the structures, which was practically removed by the oxygen plasma cleaning and HF solution. However, the residual Au couldn't be cleared away after oxygen plasma process, which may suppress the enhancement of transmittance.

III. SUMMARY

In conclusion, we have shown that the nanocone structures created by using Au particles as etching mask, give rise to the enhancement of transmittance. The HF passivation process was introduced to further improve the light extraction.

ACKNOWLEDGMENT

This work was supported by the Danish councils for strategic research funding (no.0603-00494B).

REFERENCES

- [1] X. Zhu, Y. Ou, V. Jokubavicius, M. Syv ää rvi, O. Hansen, H. Ou, N.A. Mortensen, S. Xiao, Applied Physics Letters 101 (2012) 241108.
- [2] Y. Ou, V. Jokubavicius, P. Hens, M. Kaiser, P. Wellmann, R. Yakimova, M. Syv ää rvi, H. Ou, Optics express 20 (2012) 7575.
- [3] Y. Ou, X. Zhu, V. Jokubavicius, R. Yakimova, N.A. Mortensen, M. Syv ää rvi, S. Xiao, H. Ou, Scientific reports 4 (2014).
- [4] Y. Ou, I. Aijaz, V. Jokubavicius, R. Yakimova, M. Syv ää rvi, H. Ou, Optical Materials Express 3 (2013) 86.
- [5] A. Argyraki, Y. Ou, H. Ou, Optical Materials Express 3 (2013) 1119.
- [6] M. Otto, M. Kroll, T. Käsebieber, R. Salzer, J. Ziegler, A.N. Sprafke, R. Wehrspohn, Optical Society of America, 2012, p. PW1B. 3.