



## The universal influence of contact resistance on TEG efficiency

**Bjørk, Rasmus**

*Published in:*

Book of Abstracts. International Conference on Thermoelectrics (ICT) 2015

*Publication date:*

2015

*Document Version*

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*

Bjørk, R. (2015). The universal influence of contact resistance on TEG efficiency. In *Book of Abstracts. International Conference on Thermoelectrics (ICT) 2015*

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.


## 15C.1

### The universal influence of contact resistance on TEG efficiency

R. Bjørk<sup>1</sup>

<sup>1</sup> Department of Energy Conversion and Storage, Technical University of Denmark - DTU,  
Frederiksborgvej 399, DK-4000, Roskilde, Denmark  
\*e-mail of presenting author: rabj@dtu.dk

We present an investigation of the influence of both electrical and thermal contact resistance on the efficiency of a segmented thermoelectric generator [1]. For the study, 12 different segmented *p*-legs and 12 different segmented *n*-legs are considered, using 8 different *p*-type and 8 different *n*-type thermoelectric materials. For all systems, a universal influence of both the electrical and thermal contact resistance is observed on the leg's efficiency. The universal behaviour allows the maximum tolerable contact resistance for a segmented system to be found, i.e. the resistance at which a leg of only the high temperature thermoelectric material has equal efficiency as a segmented leg with contact resistance at the interface, as shown in Fig. 1.



**Figure 35:** The maximum tolerable pure electrical or thermal contact resistance for a segmented TE leg as function of the gain in efficiency due to the segmentation.

The author would like to thank the European Commission for sponsoring the NanoCaTe (FP7-NMP Project No. 604647) project.

#### References:

[1] R. Bjørk, The universal influence of contact resistance on the efficiency of a thermoelectric generator, Accepted Journal of Electronic Materials (2015)