



## Multiangular observations of vegetation indices from UAV cameras

**Sobejano Paz, Veronica; Wang, Sheng; Jakobsen, Jakob; Bandini, Filippo; Bauer-Gottwein, Peter; Garcia, Monica**

*Publication date:*  
2016

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*  
Sobejano Paz, V., Wang, S., Jakobsen, J., Bandini, F., Bauer-Gottwein, P., & Garcia, M. (2016). *Multiangular observations of vegetation indices from UAV cameras*. Abstract from Sustain-ATV Conference 2016, Kgs. Lyngby, Denmark.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

## **Multi-angular observations of vegetation indices from UAV cameras**

Veronica Sobejano- Paz<sup>1</sup>, Sheng Wang<sup>1</sup>, Jakob Jakobsen<sup>2</sup>, Filippo Bandini<sup>1</sup>, Peter Bauer-Gottwein<sup>1</sup>, Monica Garcia\*<sup>1</sup>

1: Department of Environmental Engineering, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark

\*Corresponding author email: [mgarc@env.dtu.dk](mailto:mgarc@env.dtu.dk)

2. DTU-Space. Technical University of Denmark, 2800 Kgs. Lyngby, Denmark.

### **Abstract**

Unmanned aerial vehicles (UAVs) are found as an alternative to the classical manned aerial photogrammetry, which can be used to obtain environmental data or as a complementary solution to other methods (Nex and Remondino, 2014). Although UAVs have coverage limitations, they have better resolution compared to satellites and aircrafts, they are cheaper and easy to handle, providing data in a short period of time (Matese *et al.*, 2015; Uysal, Toprak and Polat, 2015). Furthermore, they can be equipped with different types of payloads carrying various sensors such as a thermal and multispectral cameras (Berni *et al.*, 2009), hyper spectral camera (Burkart *et al.*, 2015) and photometric elevation mapping sensor (Shahbazi *et al.*, 2015) among others. Therefore, UAVs can be used in many fields such as agriculture, forestry, archeology, architecture, environment and traffic monitoring (Nex and Remondino, 2014).

In this study, the UAV used is a hexacopter s900 equipped with a Global Positioning System (GPS) and two cameras; a digital RGB photo camera and a multispectral camera (MCA), with a resolution of 5472 x 3648 pixels and 1280 x 1024 pixels, respectively. In terms of applications, traditional methods using vegetation indices from reflectance often assume Lambertian models (de Moura *et al.*, 2015), where the light is reflected equally in all the directions (Mobley, 2014) and, therefore, multi-angular reflectance is not considered. However, differences in directional scattering (anisotropy) can provide important data about biophysical behavior in vegetation such as leaf area index (LAI), leaf angular distribution (LAD), vegetation water content, nitrogen and chlorophyll content (Tagesson *et al.*, 2015), canopy roughness and others (de Moura *et al.*, 2015). The Bidirectional Reflectance Distribution Function (BRDF) describes the surface reflectance changes depending on viewing geometry, usually used to analyze remote sensing data from satellite, airborne and surface platforms. (Singh *et al.*, 2016). BRDF observations can also be obtained with the MCA camera located in the UAV. Thus, the aim of this study is to capture multi-angular observations in different forest locations (Sorø and Risø) in Denmark by flying the UAV over the area of interest. Since the payload has a fix position, the viewing angles obtained due to the Field of view (FOV) of the MCA camera can be exploited and the flight pattern simulates some goniometer positions. This approach allows to measure different azimuth and zenith angles according to the sun position and to acquire different characteristics of vegetation depending on a specific time and amount of light.

### **References**

Berni, J. A. J., Member, S., Zarco-tejada, P. J., Suárez, L. and Fereres, E. (2009) 'Thermal and Narrowband

---



Multispectral Remote Sensing for Vegetation Monitoring From an Unmanned Aerial Vehicle', 47(3), pp. 722–738.

Burkart, A., Aasen, H., Alonso, L., Menz, G., Bareth, G. and Rascher, U. (2015) 'Angular dependency of hyperspectral measurements over wheat characterized by a novel UAV based goniometer', *Remote Sensing*, 7(1), pp. 725–746. doi: 10.3390/rs70100725.

Matese, A., Toscano, P., Di Gennaro, S. F., Genesio, L., Vaccari, F. P., Primicerio, J., Belli, C., Zaldei, A., Bianconi, R. and Gioli, B. (2015) 'Intercomparison of UAV, aircraft and satellite remote sensing platforms for precision viticulture', *Remote Sensing*, 7(3), pp. 2971–2990. doi: 10.3390/rs70302971.

Mobley, C. (2014) *Ocean Optics. Web Book. Surfaces. Lambertian BRDFs*. Available at: [http://www.oceanopticsbook.info/view/surfaces/lambertian\\_brdfs](http://www.oceanopticsbook.info/view/surfaces/lambertian_brdfs) (Accessed: 15 November 2016).

de Moura, Y. M., Hilker, T., Lyapustin, A. I., Galvão, L. S., dos Santos, J. R., Anderson, L. O., de Sousa, C. H. R. and Arai, E. (2015) 'Seasonality and drought effects of Amazonian forests observed from multi-angle satellite data', *Remote Sensing of Environment*. Elsevier Inc., 171, pp. 278–290. doi: 10.1016/j.rse.2015.10.015.

Nex, F. and Remondino, F. (2014) 'UAV for 3D mapping applications: A review', *Applied Geomatics*, 6(1), pp. 1–15. doi: 10.1007/s12518-013-0120-x.

Shahbazi, M., Sohn, G., Théau, J. and Menard, P. (2015) 'Development and evaluation of a UAV-photogrammetry system for precise 3D environmental modeling', *Sensors (Switzerland)*, 15(11), pp. 27493–27524. doi: 10.3390/s151127493.

Singh, M. K., Gautam, R., Gatebe, C. K. and Poudyal, R. (2016) 'PolarBRDF: A general purpose Python package for visualization and quantitative analysis of multi-angular remote sensing measurements', *Computers & Geosciences*. Elsevier, 96, pp. 173–180. doi: 10.1016/j.cageo.2016.08.015.

Tagesson, T., Fensholt, R., Huber, S., Horion, S., Guiro, I., Ehammer, A. and Ardö, J. (2015) 'Deriving seasonal dynamics in ecosystem properties of semi-arid savanna grasslands from in situ-based hyperspectral reflectance', *Biogeosciences*, 12(15), pp. 4621–4635. doi: 10.5194/bg-12-4621-2015.

Uysal, M., Toprak, A. S. and Polat, N. (2015) 'Dem generation with uav photogrammetry and accuracy analysis in sahitler hill'. Elsevier Ltd, (June). doi: 10.1016/j.measurement.2015.06.010.

---