



## TRA Visions 2016

Idea Number: L1-81

PILLAR / TRANSPORT MODE			
ROAD <input type="checkbox"/>	RAIL <input checked="" type="checkbox"/>	MARINE <input type="checkbox"/>	CROSS MODAL <input type="checkbox"/>
Project	<input type="checkbox"/> RA1: Environment – Decarb., Sustainability & Energy Efficiency		
Related	<input type="checkbox"/> RA2: Vehicle & Vessels Technology, Design & Production		
to:	<input checked="" type="checkbox"/> RA3: Urban and Long-Distance People Mobility – Systems and Services		
	<input type="checkbox"/> RA4: Freight Transport & Logistics		
	<input type="checkbox"/> RA5: Safe, Secure and Resilient Transport Systems		
	<input type="checkbox"/> RA6: Transport Infrastructures		
	<input type="checkbox"/> RA7: Human Factors, Socio-Economics and Foresights		
	<input type="checkbox"/> RA8: Automation and Connectivity		
	<input type="checkbox"/> RA9: Enabling Environment for Innovation Implementation		

Project Title:

A Cubic Function Model for Railway Line Delay



TRA VISIONS 2016  
is funded by



## 1. Introduction

One of the most important factors for passengers' perception of railway transport is the reliability and punctuality of the service, strictly connected to operation stability. In order to measure and evaluate this, several indices and evaluation methods have been proposed in scientific research (f. i. [1], [2], [3]). The present paper reveals these methods, and present a new closed-form analytic expression that can be used for fast analyses in the initial strategic planning phases of railway operations.

Stability of railway operation is defined as the ability of a plan to withstand unexpected events that generate delays. It can be described by different comparisons between the magnitude of the disruptive events and the disturbance that they generate. For this reason, it is necessary to introduce a classification for delays. In the literature [4], train delays are usually classified into *primary* and *secondary delays*.

The *primary delays* are unexpected extensions of the planned times of the individual processes included in the scheduled. Rolling stock and infrastructure failures can be the causes of primary delay, as well as large passenger flows at the platform that require longer dwelling times than scheduled. Causes can also be operations related, e.g. a train driver arriving too late after a break.

The *secondary delays*, on the other hand, are delays generated by operation conflicts, which are themselves due to primary delays. When a train is delayed, it needs to use infrastructure elements like switches, crossovers, track sections, and platforms at different times than planned. A conflict arises when two or more trains request to use the same element at the same time: they will be queued by dispatching decisions, since each item can only be used by one train at a time. The delay that is generated because of the queuing is called secondary delay. The secondary delays include the delays that propagate from one train to the following ones on railway lines, because each blocking section of the line can only be occupied by one train at a time. This effect is called

propagation of delays and is the subject of several scientific studies ( [5], [6], [7]).

The *stability* of a timetable can be addressed by comparing some given primary delays with their effect on the whole operation [8]. The total delay is then the sum of the delays of all the trains on a line and it is used as an overall measure of the disruption. The timetable stability is described by the comparison between the amount of primary delays and the total delay generated because of the propagation and other conflicts in operation. The timetable robustness is the ability to withstand variations in design parameters, and changes in operational conditions. It is meant to minimize primary and secondary delays, and can be studied by means of the time needed to absorb given disruptions [4]. This time is called recovery time or settling time [3].

The relation between primary and total delays is one of the key characteristics of a timetable that planners take it into account when creating the schedules. This is why methods for the estimation of the total delay are important for railway timetabling. Stability and robustness analysis of timetables can be conducted, studying the total delay on railway lines as a function of the primary delay.

The present paper derives the total delay as a polynomial function of the primary delay, under a set of assumptions. The relation is derived from a theoretical formulation of the delay propagation between consecutive trains. The individual delay of trains is computed at each station of a railway line, as a function of the primary delay assigned to a train at a station. The individual delays of the train sum up to the total delay on the line. We used the micro-simulation of a suburban railway line in Denmark to validate the model proposed.

The importance and contribution of this finding is, that costly and time consuming simulation model runs can be fitted with a close-formed analytic expression in the initial planning phases of railway projects, making it possible to proceed faster and evaluate more alternatives. The formulation can also be

used for “backward engineering, e.g. to assess what level of time table supplements you need to obtain a desired reliability of the service.

### 1.1. Reading guideline and notation

The paper is organized as follows: previous approaches are listed in the literature in section 3. A delay propagation model is proposed in section 4, followed by the mathematical formulation of the individual and total delay as functions of the primary delay. A micro-simulation model of a suburban railway line north of Copenhagen was used to validate the model, and the results are presented alongside a numerical example in section 5. A discussion is presented, finally, in section 6. A table of abbreviations is presented here below to summarize the terms used in the mathematical formulation.

Table 1 - Table of abbreviations

$d$	Total delay measured on the line
$i$	Train index
$s$	Station index
$d_{i,s}$	Individual delay of train $i$ at station $s$
$t_d$	Delay threshold
$a_{i,s}$	Running time supplement of train $i$ between stations $s-1$ and $s$
$a$	Running time supplement of every train between any pair of stations
$b_{i,s}$	Buffer time at station $s$ between trains $i-1$ and $i$
$b$	Buffer time at any station between any pair trains
$p$	Primary delay
$n_s$	Number of stations of a railway line
$v$	Traffic volume, number of trains in a timetable
$s^*_i$	Recovery station for train $i$
$i^*_s$	First train on-time at station $s$

## 2. Categorization of railway simulation models

Simulation models are used to simulate real processes in a computer environment in order to understand and predict the phenomenon in focus. Rail traffic simulation represents the complex railway system with the interaction between trains, infrastructure, plans of operation and complex operational rules. Train movements are constrained by the infrastructure since trains can only overtake each other at designated points in the network, that usually require one of the two trains to stop, waiting to be passed. Such a highly constrained operation generates the phenomenon of delay propagation, due to the peculiar interaction between different trains, and between the infrastructure and the trains. Railway simulation models can thus be used to understand and predict the railway operation. The models can be classified by scale, approach and process.

*Scale-wise*, a simulator can be classified into microscopic, mesoscopic, or macroscopic, according to the amount of detail included in the model. Macroscopic models only include aggregate information about the topology of the network, representing the stations as nodes and the lines as edges in between. Only few details are incorporated, including the minimum headways between trains at stations and fixed running time on the edges. Microscopic models, on the other hand, represent the railway system in much more detail, including the topology of each track section represented, together with the signaling system and the blocking sections. The train running times are computed by means of integration of the motion equations of the trains, given the tractive effort, the resistances and the instructions from the signaling system at every instant of time. Mesoscopic models are a compromise between Micro- and Macroscopic models, and contain selected details, like the tracks schemes without the single blocking sections. Macroscopic models are lean, fast and not detailed, whereas microscopic models usually require hard computation and give detailed results. This makes the first suitable for large network simulation, while the latter fit better with the simulation of short lines or stations.

*Approach-wise*, simulation models can be stochastic or deterministic, according to the analysis to perform. Deterministic simulation is used to study the timetables as they are or with determined operational conditions. A conflict-free timetable is the result of a deterministic design with no stochasticity in process times. Stochastic models include delay distributions, variations in process times and are used to design stable timetables.

*Process-wise*, the simulation models can be classified into Asynchronous and Synchronous. The difference is the processing order of train paths. An asynchronous model typically elaborates entire train paths and computes the interactions between trains after a priority order. Trains that are elaborated first have the highest priority and are not affected by trains that are elaborated later. Synchronous models, on the contrary, elaborate all the train paths at the same time, following time steps at which each path is computed according to the operation conditions.

The model introduced in this paper an estimation method of the total delay on a railway line as a function of the primary delay given to a train. It can be seen as a macroscopic model, with no detail on the tracks layout and only information about buffer times between trains and running time supplements available. It may be used on simple railway lines to overcome the high computational load typical of microsimulation models and hence as a fast tool for the purpose of initial strategic analyses. This paper characterizes a clear relation between primary delay given to trains and the resulting total delay on a line as a cubic parabola. The model is validated by analyzing the results of a complete micro-simulation of delay propagation on a suburban railway line in Denmark.

### **3. Literature Survey**

Traffic density and occurrence of disturbances in railway operation are often positive correlated [9], and the extent of disruptions is also strongly affected by the traffic intensity relative to capacity consumption. The planned operation (published time-table) needs some buffer times to be capable to absorb disturbances. A timetable and railway system that can cope with disruptions

and unexpected events without significant modifications to the operation is referred to as robust [10]. Some of the tools to gain stability in timetables are the running time supplements and the buffer times in headways between trains; the reduction of heterogeneity in trains' characteristics is also indicated as a method to increase robustness [3].

Many techniques to evaluate railway stability and robustness have been proposed in the last ten years, some of them based on analytical approaches, others based on empirical models and what-if analysis. Vroman, Dekker, & Kroon [1] propose the relation between timetable homogeneity and the propagation of delays due to interdependencies between trains, while the inequality of headway time dispersion is investigated by Carey & Carville [11]. Salido, Barber, & Ingolotti [3] assess robustness in terms of average delay per train and settling time, to evaluate different solutions of their rescheduling model.

Mattson [2] studies the interferences between trains under different capacity utilization values through a micro-simulation tool: Mattson finds this to be the most precise way to analyze secondary delays, but it needed very detailed input and is a time consuming process. The detailed input and output give flexibility to the method, making it adaptable to different contexts: signaling systems, operation rules, rolling stocks, and infrastructure alignments can be modelled through the micro-simulation of any guided transport system. Pellegrini, Marlière, & Rodriguez [12] concluded that the simulation of speed variation dynamics is too hard to compute in re-scheduling problems, compared to the accuracy gain. Nevertheless, it is effective for estimation of actual train interactions through the signaling system: the robustness increment given by better acceleration and braking performance can be investigated through micro-simulation to compare different kinds of rolling stock.

Several delay propagation models for railway networks have been presented in the literature. Goverde [5] represents the timetables in timed event graphs to model the delay propagation in a macroscopic algorithm based on max-plus algebra. Hasegawa et al. [6] uses a hydrodynamic model to train traffic: they

modelled the delay propagation as a shock wave in a compressible fluid and appraised the total delay as a cubic function of the primary delays by means of propagative velocity. Stochastic models have also been introduced to predict the total expected delay from the passenger point of view [13]. Meester and Muns [7] derive the distributions of secondary delays from the primary delay distributions using phase-type distribution, to formulate a model between a general queuing model and a very detailed simulation model.

## 4. Model derivation

The purpose of the model development is to derive a close-form analytical expression that explains the total delay on a railway line, as a function of the primary delay of a train. The total delay is computed as the sum of the delays of individual trains at each station, which is the result of the propagation of the delay from the previous train to the following ones. The development of the delay of a train throughout the line and between consecutive trains is studied by means of buffer times and timetable allowance. The summation of the individual delays is developed under different hypothesis in this paragraph and two different polynomial relations are presented between the primary delays and the total delay.

### 4.1. Total delay and individual delay

The total delay  $d$  represents the magnitude of the disruption impact on the line: it is the total deviation from the scheduled timetable and can be calculated as the sum of every train's delay

$$d = \sum_{i,s} (d_{i,s} | d_{i,s} \geq t_d), \quad (1)$$

with  $d_{i,s}$  being the delay of train  $i$  registered at station or timing point  $s$  (difference between real and scheduled time), and  $t_d$  being the delay threshold, under which we considered the train punctual. It is important to emphasize that every train's delay is recorded at all the timing points: this means that the same delay record is repeated several times for every train, reduced by the supplement of running time included in the schedule between two consecutive timing points



(timetable allowance). For a simpler formulation, the delay threshold will be omitted in the rest of the paper.

The delay of a train at one station is the result of the propagation of the delay from previous trains and the recovery of its own delay in the previous segment of line. The timetables include two different elements to reduce the delay propagation between trains and to increase each train's ability to recover delays along their paths, both of which have impact on punctuality, capacity and total travel time. 1) The *timetable allowance*, also called slack or running time supplement, is the difference between the minimum running time of a train on a given railway segment and the scheduled time. This supplementary time can be used to recover train runs from delays. The distribution of the supplement times along the train paths often follows the guidelines from the International Union of Railways (UIC) or by the national Railway Infrastructure Managers rule-of-the-thumb guidelines. A large amount of supplement time improve the overall punctuality of trains, but it also increases the scheduled travel times, reducing the attractiveness of the railway system. 2) Another element to cope with delays is the *buffer time between trains*, defined as the difference between the minimum time headway between trains at a given timing point and the scheduled interval. This prevents small delays from spreading to the following trains and increases the punctuality as well, but it also consumes capacity, as it decreases the number of trains that can be run in a given time interval [4].

## **4.2. Notation and problem formulation**

The notation to describe the propagation of delays among trains is described in the following.  $a_{i,s}$  is the timetable allowance, also called running time supplement, of train  $i$  between stations  $s-1$  and  $s$ .  $b_{i,s}$  is the buffer time at station  $s$  between trains  $i-1$  and  $i$ . These introduced variables are useful to describe how the delay is propagating to consecutive trains and how every train recovers over the stations.

The individual train delay  $d_{i,s}$  can be either the result of hindrance from previous trains or residual delays that have only partially been recovered after its

generation. In the first case, the delay of the previous train exceeds the buffer time and the exceeding part is transfer to the following train. In the latter case, the delay of a train at a station exceeds the amount of delay that a train could recover. Both the cases can be modelled in the following equation, where  $d_{i,s-1}$  is the delay of the same train at previous stations and  $d_{i-1,s}$  is the delay of previous trains at the same measuring station:

$$d_{i,s} = \max\{(d_{i,s-1} - a_{i,s}), (d_{i-1,s} - b_{i,s}), 0\} \quad (2)$$

$a_{i,s}$  represents the timetable allowance scheduled for train  $i$  from station  $s-1$  to station  $s$ ;  $b_{i,s}$  is the buffer time scheduled between trains  $i-1$  and  $i$  at station  $s$ .

The total delay is the sum of the individual train delays over the stations. The individual train delays, formulated as above, are non-linear functions of previous delays. A delayed train that is recovering its delay along the way could be hindered by the previous train at any station, depending on the different timetable allowance and buffer times of both trains at every station. For this reason, we introduce two assumptions here, with the aim to formulate the individual delay of any train  $i$  at any station  $s$ , as a function of the primary delay given to the first train.

The model assumes that the timetable allowance is equally spread over the train paths and that all the paths are identical. This simplified assumption is reasonable in suburban railway lines, if trains run with the same stop pattern, the train paths are the same for each train run, and the train paths are repeated over time at a given frequency. It is further assumed that the buffer times between trains are equal between any given pair of train at every point along the line. With these two assumptions, both the timetable allowance and the buffer time can be written as train- and station-independent, and the indices  $i$  and  $s$  can be omitted. Therefore,  $a$  is the timetable allowance of every train between any pair of stations and  $b$  is the buffer time at every point between any pair of trains.

We define  $p$  the primary delay of the first train at the first station, that means that  $d_{1,1}=p$ . This delay will propagate to the following trains through the

expression of individual delay given in (2). The expression can be rewritten as follows, based on the primary delay and the unique values of  $a$  and  $b$ :

$$d_{i,s} = p - (s - 1)a - (i - 1)b, \quad (3)$$

Subject to  $d_{i,s} \geq 0 \forall i, s$ .

For a better comprehension, the table below summarizes the modelled individual train delay at the stations. The table includes a finite line with a given number of stations  $n_s$  and a finite number of train, namely the traffic volume  $v$ .

*Table 2 - Individual train delay at each station under the hypothesis of equal running time supplements and buffer times.*

Station \ Train	1	2	...	s	...	$n_s$
1	$p$	$p-a$	...	$p-(s-1)a$	...	$p-(n_s-1)a$
2	$p-b$	$p-a-b$	...	$p-(s-1)a-b$	...	$p-(n_s-1)a-b$
...	...	...	...	...	...	...
i	$p-(i-1)b$	$p-a-(i-1)b$	...	$p-(s-1)a-(i-1)b$	...	$p-(n_s-1)a-(i-1)b$
...	...	...	...	...	...	...
v	$p-(v-1)b$	$p-a-(v-1)b$	...	$p-(s-1)a-(v-1)b$	...	$p-(n_s-1)a-(v-1)b$

In the following two situations, the total delay is modelled as the summation of the individual train delays under the separate hypotheses of no recovery or total recovery of the delay on the line. The two situations differ with regard to the domain of summation of the individual elements.

### **4.3. The total delay without recovery**

Table 2 shows a linear relation between the primary delay  $p$  and any non-negative individual train delay. If the primary delay is big enough, no train will completely recover its delay before the last station  $n_s$  is reached. The total delay under this assumption can be computed summing the individual train delays, with the summation extended to all the trains and all the stations:

$$\begin{aligned}
 d &= \sum_{i,s} d_{i,s} = \sum_{i=1}^v \sum_{s=1}^{n_s} (p - (s-1)a - (i-1)b) = \\
 &= p n_s v + \frac{1}{2} (+n_s v (a+b) - a v n_s^2 - b n_s v^2).
 \end{aligned} \tag{4}$$

This equation expresses the total delay as a linear function of the primary delay, given the number of trains and stations, the timetable allowance and the buffer time.

#### **4.4. The total delay with recovery**

The formulation becomes more complicated when trains are able to recover from their delay before the end of the line. As opposite to the previous case, the primary delay is small enough to allow even the first train to recover completely before the end of the line; it can also be so small that it does not propagate to the last train at the first station, where the primary delay occurs. In this case, there will be at least one train that is not subject to secondary delays.

The summation domain should be, therefore, limited to the train and stations with non-negative delay, as follows:

$$d = \sum_{i,s|d_{i,s}>0} d_{i,s} = \sum_{i,s|d_{i,s}>0} p - (s-1)a - (i-1)b. \tag{5}$$

We can approach the summation in two different ways. The first consists of finding the total delay at each station, and summing the individual delays from the first train to the last train delayed at the station. The general total delay is the sum of the total delays at stations, from the first station to the last station with at least one train delayed, which is the last station where the first train is delayed. The opposite approach sums first the total delay of individual trains at all the stations, from the first station to the last station where that train is delayed. In this case, the general total delay results from the summation of the individual trains total delay, from the first train to the last train that is delayed at the first station. For this reason, the *recovery station* and the *first train on time* are defined hereunder.

We define the recovery station of each train, the first station where the train recovers completely its delay. The recovery station of the first train results from its timetable allowance that reduces the initial delay at every section between stations.

$$s^*_1 = \frac{p}{a} + 1, \quad (6)$$

For each train  $i$ , the recovery station  $s^*_i$  can be found by rounding up to the next unit the result of the generic equation

$$s^*_i = \frac{p-(i-1)b}{a} + 1. \quad (7)$$

At the same way, the first train running on time at the first station is the result of only the initial delay propagation to the following trains, reduced by the buffer time at every step. It is expressed by the equation

$$i^*_1 = \frac{p}{b} + 1. \quad (8)$$

For any given station  $s$ , the first train on time  $i^*_s$  can be calculated by the generic equation below

$$i^*_s = \frac{p-(s-1)a}{b} + 1 \quad (9)$$

and rounding up the result to the next unit.

These values set the new boundary of the summation to find the total delay: the individual delay should only sum trains at stations which individual delay is not negative. The grand total delay can be computed either summing the total delay at individual stations or summing the total delay of individual trains. The two approaches described above will provide the same result. We give hereunder only the formulation of the first approach, which first takes into account the delayed trains at every station, and then sums the total delays at every station. The summations should only be extended to the last delayed train at each station, and to the last station where the first train is delayed with non-negative delay, i.e.  $(i^*_s - 1) = \frac{p-(s-1)a}{b}$  and  $(s^*_1 - 1) = \frac{p}{a}$ .

Equation (5) can be written as

$$\begin{aligned}
 d &= \sum_{i,s|d_{i,s}>0} d_{i,s} = \sum_{s=1}^{\frac{p}{a}} \sum_{i=1}^{\frac{p-(s-1)a}{b}} p - (s-1)a - (i-1)b = \\
 &= \frac{1}{12ab} (a^2p + 3abp + 3ap^2 + 3bp^2 + 2p^3).
 \end{aligned} \tag{10}$$

The result is a polynomial relation of third degree between the primary delay and the total delay. The total delay can hence be expressed as a cubic parabola function of the primary delay. Contrary to the previous formulation, the total delay in the case with recovery does not depend either on the number of stations on the line or on the traffic volume. This characteristic is intuitively understandable: the delay does not propagate to the last train, so additional trains would not be included in the summation of the total delay; similarly, the delay is recovered by all the trains before the last station, so additional stations would not be included in the summation.

This formulation introduces an approximation given by the discrete nature of the quantities. Both the upper limits of the summations are given by a ratio and should be rounded up to the unit. The summation is solved considering the upper limits as continuous, assuming that the error is small enough. The error can be computed numerically comparing the actual summation of the individual delays and the modelled summation, as presented in the numerical example in section 5.1, case with recovery.

Intermediate cases between the two presented bounds are also possible. In particular, the combination of primary delay, timetable allowance and buffer time can be so that the first train is able to recover before the last station, but the delay is anyway propagated to the last train at the first station. Similarly, a situation can occur in which the first train is not able to recover before the last station, but the delay at the first station is not transmitted to the last train, so that there is still at list one train that is not delayed at all.

#### 4.5. The total delay in the general case

The two cases above describe the total delay in the boundary cases of no recovery or total recovery before the end of the line. They can also be seen as two different sections of the same curve; if we fix the buffer time and the timetable allowance, the total delay as a function of the primary delay becomes a composite curve that builds up from polynomials of different degree. A third degree function describes the first section of the curve, while a linear function characterizes the last segment. The borders of the first section are the null primary delay and such a value corresponding to either the first train not being able to recover completely its delay before the end of the line, or the last train being delayed at the first station. The more restrictive value is given by the ratios between the timetable allowance and the buffer time, and between the number of stations and the traffic volume.

The conditions mentioned above can be written as

$$(s^*_1 - 1) \leq n_s \rightarrow p \leq a n_s, \quad (11)$$

$$(i^*_1 - 1) \leq v \rightarrow p \leq b v. \quad (12)$$

Therefore, the total delay is a cubic function of the primary delay in the interval  $p \in [0, \min(a n_s, b v)]$ .

On the other hand, the total delay becomes a linear function of the primary delay when no train is able to recover the delay before the end of the line. This condition is formalized by the inequality

$$d_{v,n_s} = p - (n_s - 1)a - (v - 1)b > 0, \quad (13)$$

where  $d_{v,n_s}$  is the individual delay of train  $v$  at station  $n_s$ . The inequality is respected for values of primary delay greater than

$$p > (n_s - 1)a + (v - 1)b, \quad (14)$$

It is reasonable to state that within the segment between the cubic and the linear sections there is a sub-segment with a quadratic dependency between the total delay and the primary delay. In the first segment both  $i^*_s$  and  $s^*_i$  depend on the

primary delays, whereas in the linear segment they are fixed at  $i_s^* = v$  and  $s_{i=ns}^* = n_s$ . In the section in between, either of the two is fixed and the other still depend on the primary delay.

## 5. Case studies

In this section, we present numerical examples of the cases formulated above and the simulation of a real suburban railway in Denmark to show the relation between the primary delay given to a train and the total delay generated on the line.

### 5.1. Numerical examples on a short corridor

#### A case without recovery

A timetable with  $v=6$  trains is operated on a railway line with  $n_s=8$  stations. The timetable includes the same supplementary time between all stations  $a=2$  minutes, while the buffer time between consecutive trains is  $b=6$  minutes everywhere. With primary delays over  $p=44$  minutes (14), all the individual delays of every train at each station of the line will be non-negative, as shown in the table below. The total delay on the line is computed numerically by means of the summation of all the individual delays on the line. All the individual delays are computed by equation (3), subject to non-negativity.

*Table 3 - Individual delays [min] on a railway line, given a primary delay [min]. Positive delays are bolded; colour intensity proportional to cell values. Stations are also given a letter ID.*

		STATION							
		1	2	3	4	5	6	7	8
		A	B	C	D	E	F	G	H
TRAIN	1	<b>44</b>	<b>42</b>	<b>40</b>	<b>38</b>	<b>36</b>	<b>34</b>	<b>32</b>	<b>30</b>
	2	<b>38</b>	<b>36</b>	<b>34</b>	<b>32</b>	<b>30</b>	<b>28</b>	<b>26</b>	<b>24</b>
	3	<b>32</b>	<b>30</b>	<b>28</b>	<b>26</b>	<b>24</b>	<b>22</b>	<b>20</b>	<b>18</b>
	4	<b>26</b>	<b>24</b>	<b>22</b>	<b>20</b>	<b>18</b>	<b>16</b>	<b>14</b>	<b>12</b>
	5	<b>20</b>	<b>18</b>	<b>16</b>	<b>14</b>	<b>12</b>	<b>10</b>	<b>8</b>	<b>6</b>
	6	<b>14</b>	<b>12</b>	<b>10</b>	<b>8</b>	<b>6</b>	<b>4</b>	<b>2</b>	<b>0</b>

The total delay measured at different values of primary delay is reported in the following chart: it represents a linear relation, with the specific formulation.






Figure 1 - Total delay measured on the line as a function of the primary delay given to the first train at the first station

### A case with recovery

The same example as before can represent the case with complete recovery for primary delays up to  $p=14$  minutes. This case is represented in the table below.

Table 4 - Individual delays [min] on a railway line, given a primary delay [min]. Positive delays are bolded; colour intensity proportional to cell values. Stations are also given a letter ID.

		STATION							
		1	2	3	4	5	6	7	8
		A	B	C	D	E	F	G	H
TRAIN	1	<b>14</b>	<b>12</b>	<b>10</b>	<b>8</b>	<b>6</b>	<b>4</b>	<b>2</b>	0
	2	<b>8</b>	<b>6</b>	<b>4</b>	<b>2</b>	0	0	0	0
	3	<b>2</b>	0	0	0	0	0	0	0
	4	0	0	0	0	0	0	0	0
	5	0	0	0	0	0	0	0	0
	6	0	0	0	0	0	0	0	0

The following chart represents the total delay computed both as the numerical summation of the individual delays and through the analytical formulation (10).




Figure 2 - Total delay measured as the numerical summation and estimated through the analytical formulation.

The numerically computed total delay is regressed to a cubic polynomial expression, given in the chart, along with the  $R^2$  index, which shows a high quality regression. The equation of the analytical total delay is given as well.

### The general case

The results of previous examples are part of a composite function, which borders are be defined here below.

The cubic section extends in the range of primary delay  $p \in [0,16]$ . The linear range, on the opposite side, starts at the value  $p > 44$  minutes.

It is worth to notice that the intermediate range can be regressed perfectly to a quadratic parabola, consistently with the assumed shape in the theoretical explanation. The regression is shown in the picture below.




Figure 3 - The total delay numerically summed in the example. Partial recovery range.

The chart below shows the three segments of the total delay as a function of the primary delay with the equations and coefficients of the regressed polynomial functions.




Figure 4 - Total delay summed in the numerical example.

---

## ***5.2. A real large scale case: the Nordbane in Copenhagen***

The numerical examples above were subject to a number of assumptions that could be too strong in some cases. The assumption of uniform timetable allowance and buffer time, in particular, could be unrealistic for some railway lines. This is compared with a real case in the following, where measurements of the total delay on a simulated railway line, with no information about the supplement times and the buffer between trains.

To validate the polynomial shape of the total delay against the primary delay we simulated the operation of a suburban railway line in Denmark. The suburban railway network in Copenhagen is a very densely occupied network with 2 minutes headway in the busiest section. Six different lines operate on the network, five out of which run through the same central section. The suburban line is operated by uniform rolling stock in cyclic timetable. The selected section of the suburban network is the line from Hellerup to Hillerød. Overtakes in this section are prevented. Though it is theoretically possible at selected stations, it hardly occurs in real operation, due to the very high frequency of the train service.

The micro-simulation software RailSys by Rail Management Consultants GmbH (RMCon) was used for the simulation. This micro-simulation uses continuous computation of train motion equations and simulates the interaction between trains through discrete processing of signal box states. Given user defined infrastructure, rolling stock, and timetable databases, it is possible to calibrate the train paths defining the running time supplements; moreover, different driving behaviors can be modelled for on time trains and delayed ones.

The model formulated in the paper can, on the other hand, be interpreted as a macroscopic simulation tool, which only has basic information on the link between two stations and the constraints in operation. The only pieces of information required in this model are the buffer times and the timetable allowance. We used a microsimulation tool to validate this in a more detailed model, which includes details about the geometry of the infrastructure and the actual separation of trains through the signaling system.

Two different train paths run every ten minutes on the line between Hellerup and Lyngby with two different stopping patterns:

- Line A: runs throughout the entire line, skipping 5 stops in the first stretch
- Line E: only runs the first stretch, stopping at all the stations.

The line stationing and stopping patterns are summarized below:

*Table 5 - Stopping patterns of each train path. X = Stop, | = pass*

<b>Station</b>	<b>Code</b>	<b>km</b>	<b>A</b>	<b>E</b>
<i>Hellerup</i>	Hl	7,8	X	X
<i>Bernstorffsvej</i>	Btf	9,3		X
<i>Gentofte</i>	Gj	10,9		X
<i>Jægersborg</i>	Jæt	12,6		X
<i>Lyngby</i>	Ly	13,9	X	X
<i>Sorgenfri</i>	Stf	15,9		X
<i>Virum</i>	VG	17,7		X
<i>Holte</i>	Hot	19,0	X	X
<i>Birkerød</i>	BG	23,8	X	
<i>Allerød</i>	LG	29,3	X	
<i>Hillerød</i>	HG	36,5	X	

We Monte Carlo sampled of  $n=100$  values of primary delay from a uniform distribution between 0 and 10 minutes and measured the related total delay developed on the line. Delays up to ten minutes were completely recovered by all the trains before the end of the line, meaning that this case is with complete recovery. The resulting shape of the total delay against the primary delay is a cubic parabola.

The same primary delay given to trains from different lines resulted in different values of total delay. The graph below collects the total delay values for primary delays given to either line A or E. The graph shows that there is not a unique curve that represents the total delay for any train delayed in the timetable. The total delay keeps cubic against primary delay given to individual lines, and two different regressions are applied to the results.




Figure 5 - Measured total delay on the suburban railway line Hellerup - Hillerød, as a function of the primary delay. Each curve represents the total delay generated delaying either railway line of the timetable.

### 5.3 Discussion

The numerical examples revealed a high accuracy of the model for both the linear segment and the cubic one. The estimation of the total delay in the case with no recovery is exact, and shows the linear relation with the primary delay. The estimation of the total delay presents, on the other hand, an approximation in the range with total recovery. This is due to the upper bound of the summation, which is integer by nature but is approximated continuous in the summation solution.

The microsimulation of a suburban railway line revealed that the proposed model is not limited to simplified theoretical lines. The simulated railway line is characterized by non-uniform timetable allowance and stations not equally spread along the line. Moreover, we simulated heterogeneous stopping pattern and non-uniform buffer time between trains on the line. The trains also had different scheduled running times in the segments Hellerup-Lyngby and Lyngby-Holte. Nevertheless, the total delay shape against the primary delay is still close to a cubic parabola. Delays up to 10 minutes were completely

recovered by all the trains before the end of the line, in accordance with the model developed. This shape validates the polynomial expression of the total delay as a function of the primary delay for small primary delays.

It is worth to notice that the graph also shows some phenomenon that is not fully explained by this paper. The total delay generated by the same amount of primary delay is different, depending on the first train delayed. This is due to the different interactions that are generated. The primary delay is generated at the first station. When the delay is given to a train from line A, it propagates to both the following stations and the following train. The A line is faster than the E line, so the buffer time between a train A and a train E is minimum at the first station and increases on the way. The opposite is valid in the opposite sequence: the buffer time between a train E and a train A is maximum at the first station and decreases to the minimum at Holte, which is the last station of line E. Delays given to a train A do not propagate to the following train until a value that is big enough, so that the train A hinders the following train E at Holte station. This value equals the total timetable allowance of train E from Hellerup to Holte, increased by the buffer time between line E and line A at Holte. This phenomenon is the reason why the total delay values related to primary delays given to line E are smaller than line A.

## **6. Conclusions and contributions**

The paper presented a model of the total delay on railway lines as a composite polynomial function of the primary delay given to one train. The function can be divided into three sections, which boundaries are specific values of the primary delay. The values can be computed under the assumption of uniform timetable allowance and buffer time, and given the number of stations on the line and the traffic volume of the timetable.

The estimation method presents an approximation, due to the discrete nature of the upper boundaries in the summations. This approximation leads to a small underestimation of the total delay in the cubic section, and further research development is needed to estimate an expression for the error. The

approximation expires in the linear section of the total delay, which is computed exactly.

The paper validates the theoretical model through a numerical example with ideal conditions: equal train paths, uniform timetable allowance and buffer times over trains and station. The case study demonstrated that even in real conditions that differ from the hypothesis of the model, the total delay is still a cubic function of the primary delay.

This model lays the basis for future development of stability analysis of suburban railway line without micro-simulation, as well as metro-like systems, which typically have homogenous timetables and rolling stock. The estimation of the total delay, given the value of primary delay gives a measure of the effect related to a disruption, which is namely the stability. The model can be extended to railway networks, linking different suburban railway lines together. The linkage should be the objective of studies to set the validity limits of the extension from lines to networks.

The advantage of such a model in railway networks and hence the contribution of this paper is in its simplicity and analytic formulation and closed form expression, compared to micro-simulation models, yet giving an accurate estimation of the total delay. Stability analyses typically deal with small amount of primary delays, so only the cubic section of the model is needed, as shown in the case study Hellerup – Hillerød. Nevertheless, the intermediate segment could still be formulated from a theoretical point of view: a quadratic polynomial regression resulted in the numerical example. This will make it possible to make much faster initial analyses of punctuality of timetable in the initial strategic planning phases when designing new timetables.

The average timetable allowance and buffer time can also be computed by reversing the total delay formulation, due to the close-form expression of the model. This means that with a given desired punctuality of the railway line, the needed timetable supplement can be estimated by the function. This would also



ease the planning process compared to a try-and-correct approach using microsimulation.

## 7. Bibliography

- [1] J. C. M. Vroman, R. Dekker and L. G. Kroon, "Reliability and heterogeneity of railway services," *European Journal of Operational Research*, vol. 172, pp. 647-665, 2006.
- [2] L. G. Mattsson, "Railway Capacity and Train Delay," in *Critical Infrastructure*, Berlin, Springer Heidelberg, 2007, pp. 129-150.
- [3] M. A. Salido, F. Barber and L. Ingolotti, "Robustness in Railway Transportation Scheduling," in *World Congress on Intelligent Control and Automation*, Chongqing, China., 2008.
- [4] R. M. P. Goverde and I. A. Hansen, "Performance indicators for railway timetables," in *IEEE International Conference on Intelligent Rail Transportation Proceedings*, 2013.
- [5] R. Goverde, "A delay propagation algorithm for large-scale railway traffic networks," *Transportation Research Part C: Emerging Technologies*, vol. 18, no. 3, pp. 269-287, 2010.
- [6] Y. Hasegawa, H. Konya and S. Shinohara, "Macro-Model On Propagation-Disappearance Process Of Train Delays," *Railway Technical Research Institute, Quarterly Reports*, vol. 22, no. 2, pp. 78-82, 1981.
- [7] L. E. Meester and S. Muns, "Stochastic delay propagation in railway networks and phase-type distributions," *Transportation Research Part B-methodological*, vol. 42, no. 2, pp. 218-230, 2007.
- [8] F. Cerreto, "Micro-simulation based analysis of railway lines robustness," in *6th International Conference on Railway Operations Modelling and Analysis*, Tokyo, 2015.
- [9] M. Wiklund, Järnvägstransportsystemets sårbarhet – struktur för modellformulering och metodutveckling, VTI-meddelande 932-2002, 2002.
- [10] Y. Takeuchi and N. Tomii, "Robustness Indices for Train Rescheduling," in *1st International Conference on Railway Operations Modelling and Analysis RailDelft2005*, Delft, 2005.
- [11] M. Carey and S. Carville, "Exact heuristic measures of schedule reliability," *Journal of Operational Research Society*, vol. 51, pp. 666-682, 2000.
- [12] P. Pellegrini, G. Marlière and J. Rodriguez, "Optimal train routing and scheduling for managing traffic perturbations in complex junctions," *Transportation Research Part B*, pp. 58-80, 2014.
- [13] F. Kirchhoff, "Modelling Delay Propagation in Railway Networks," *Operations Research Proceedings*, pp. 237-242, 2014.
- [14] ON-TIME Consortium, "ONTIME," 2011. [Online]. Available: <http://www.ontime-project.eu/description.aspx>.
- [15] Shift2Rail Joint Undertaking, "Mission and Objectives," 2009. [Online]. Available: <http://www.shift2rail.org/about-shift2rail/mission-and-objectives/>.
- [16] Technical University of Denmark, "RobustRailS Research Project," 2012. [Online]. Available: <http://www.robustrails.man.dtu.dk/About-the-project>.
- [17] Technical University of Denmark, "IPTOP," 2014. [Online]. Available: [http://www.iptop.transport.dtu.dk/Project\\_description](http://www.iptop.transport.dtu.dk/Project_description).