



Studying fatigue damage evolution in uni-directional composites using x-ray computed tomography

Mikkelsen, Lars Pilgaard

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Mikkelsen, L. P. (2017). *Studying fatigue damage evolution in uni-directional composites using x-ray computed tomography*. Abstract from Seminar im Rahmen des GRK 2078 , Karlsruhe, Baden-Württemberg, Germany.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Seminar im Rahmen des GRK 2078

Referent: **Assoc. Prof. Lars P. Mikkelsen**
Composites and Materials Mechanics, DTU Wind Energy,
Technical University of Denmark

Datum: 23.05.2017
Uhrzeit: 14:30-15:30 Uhr

Ort: Geb. 10.23, 3. OG, Raum 308.1

Titel: **Studying fatigue damage evolution in uni-directional composites using x-ray computed tomography**

Abstract

Understanding fatigue damage evolution in the load carrying laminates of wind turbine blade plays an important role for designing longer and lighter turbine blades which will make it possible to increase the size of wind turbines or to upgrade existing turbines for lower wind classes. Thereby, it will be possible to lower the costs of energy for wind energy based electricity.

In the present work, a lab-source x-ray computed tomography equipment (Zeiss Xradia 520 Versa) has been used in connection with ex-situ fatigue testing of uni-directional composites in order to identify fibre failure during the fatigue loading. The load carrying laminates in wind turbine blades is typically based on a number of non-crimp fabrics in which the load carrying fibres are oriented in the axial direction of the blades. In order to ease the handling of the fabric during the dry fabric layup and to ensure a good alignment of the final laminates, approximately 10% of the fibres are oriented in secondary directions as so-called backing bundles and stitched to the uni-directionally oriented bundles. Due to the coarse structure of the non-crimp fabric, test samples with a larger cross-section (compared to other comparable x-ray studies) have been used in order to ensure a representative test volume during the ex-situ fatigue testing. Using the ability of the x-ray computed tomography to zoom into regions of interest, non-destructive, the fatigue damage evolution in a repeating ex-situ fatigue loaded test sample has been explored. Thereby, the fatigue failure mechanism has been uncovered showing fibre breakage regions growing from cross-over regions of the backing bundles. Based on those observations, more realistic micromechanically based fatigue damage models as well as suggestions on bundle arrangement improving the fatigue resistance of non-crimp fabric used in the wind turbine industry can be made.

Alle Interessenten sind herzlich eingeladen.

Prof. (apl.) Dr.-Ing. habil. Kay A. Weidenmann