



A Failure Locus for Hydrogen Assisted Failure

Fuentes-Alonso, Sandra; Harris, Zach D.; Burns, James T.; Martínez Pañeda, Emilio

Published in:

Proceedings of the 30th Nordic Seminar on Computational Mechanics (NSCM-30)

Publication date:

2017

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Fuentes-Alonso, S., Harris, Z. D., Burns, J. T., & Martínez Pañeda, E. (2017). A Failure Locus for Hydrogen Assisted Failure. In J. Hørsberg, & N. L. Pedersen (Eds.), *Proceedings of the 30th Nordic Seminar on Computational Mechanics (NSCM-30)* (pp. 225)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

A FAILURE LOCUS FOR HYDROGEN ASSISTED FAILURE

SANDRA FUENTES-ALONSO*, ZACH D. HARRIS†, JAMES T. BURNS†
AND EMILIO MARTÍNEZ-PAÑEDA††

*Department of Construction and Manufacturing Engineering
Universidad de Oviedo
Campus de Viesques, 33203 Gijón, Spain

†Center for Electrochemical Science and Engineering
Department of Materials Science and Engineering, University of Virginia
395 McCormick Road, Charlottesville, VA 22904, USA

††Department of Mechanical Engineering
Technical University of Denmark
2800 Kgs. Lyngby, Denmark
e-mail: mail@empaneda.com - Web page: <http://www.empaneda.com>

Abstract. We investigate cracking in the presence of hydrogen by means of a hybrid experimental-numerical approach. Slow strain rate tests are conducted in a Nickel superalloy under different environmental conditions. Finite element analysis of crack initiation and subsequent growth is modeled by means of a hydrogen-dependent traction separation law. A special control algorithm is employed to overcome numerical instabilities intrinsically associated with cohesive zone formulations. The fracture energy is degraded by means of an experimentally-motivated hydrogen degradation relation. Numerical results provide important insight into the failure process, enabling to identify critical values of hydrogen concentration and remote stresses that trigger cracking. The work builds upon previous works by the authors^{1,2} and brings important insight into the technologically important problem of hydrogen assisted cracking.

Keywords: Hydrogen embrittlement, Cohesive zone models, Fracture, Finite element analysis.

REFERENCES

- [1] E. Martínez-Pañeda, C.F. Niordson and R.P. Gangloff. Strain gradient plasticity-based modeling of hydrogen environment assisted cracking. *Acta Mater.*, **117**, 321–322, (2016).
- [2] B.C. Rincon Troconis, Z.D. Harris, H. Ha, J.T. Burns and J.R. Scully. The effect of heat-to-heat variations in metallurgy and hydrogen-metal interactions on the hydrogen embrittlement of Monel K-500. *Mater. Sci. Eng., A*, **703**, 533–550, (2017).