



Hydrogen assisted catalytic biomass pyrolysis for green fuels

Stummann, Magnus Zingler; Høj, Martin; Schandel, Christian Bækthøj; Hansen, A. B. ; Wiwel, P.; Jensen, Peter Arendt; Gabrielsen, J.; Jensen, Anker Degn

Publication date:
2017

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Stummann, M. Z., Høj, M., Schandel, C. B., Hansen, A. B., Wiwel, P., Jensen, P. A., Gabrielsen, J., & Jensen, A. D. (2017). *Hydrogen assisted catalytic biomass pyrolysis for green fuels*. Abstract from TCbiomass 2017, Chicago, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Hydrogen assisted catalytic biomass pyrolysis for green fuels

M. Z. Stummann^a, M. Høja, C. Schandel^a, A. B. Hansen^b, P. Wiwel^b, P. A. Jensen^a, J. Gabrielsen^b, A. D. Jensen^{a*}

^a DTU Chemical Engineering, Technical University of Denmark (DTU), Kgs. Lyngby, DK-2800, Denmark,

^b Haldor Topsøe A/S, Kgs. Lyngby, DK-2800, Denmark.

*aj@kt.dtu.dk

Fast pyrolysis of biomass is a well-known technology for producing bio-oil, however in order to use the oil as transportation fuel the oxygen content must be decreased from approximately 30 wt.% to below 1 wt.%. This can be achieved by catalytic hydrodeoxygenation (HDO). Unfortunately, deactivation due to coking of the catalyst is an inhibitive problem for this technology. The objective of the present work is to produce oxygen free gasoline and diesel from biomass by hydrogen assisted catalytic fast pyrolysis. Fast pyrolysis of beech wood has been performed in high-pressure hydrogen atmosphere in a fluid bed reactor with a commercial CoMoS/MgAl₂O₄ catalyst as bed medium followed by an additional vapor phase, fixed bed HDO reactor using a commercial NiMoS/Al₂O₃ catalyst. The obtained bio-oil is essentially oxygen free. Oxygen specific GC-AED showed only traces of phenols, benzofurans and naphthols (< few ppm) as the remaining oxygenates. The temperature in the fluid bed reactor has been varied between 365 and 470 °C and pressure has been varied between 15 and 35 barg in order to investigate the impact on yields and oil composition. The char yield decreased with increasing temperature and decreasing pressure. Increasing the pressure also increased the water yield and decreased the CO/CO₂ yield, indicating that the reaction pathway for the oxygen removal is highly pressure dependent. GCxGC-FID analysis of the condensed oil product showed a chromatic area up to 79 % for aromatics, indicating that the aromatic content in the oil is equilibrium controlled. Elemental analysis showed that the oxygen content in the char decreased with increasing temperature in the fluid bed reactor. Oil yields of up to 21.6 wt.% were obtained, corresponding to an energy recovery of 51 %. An experiment without the HDO reactor showed that most oxygen is removed in the fluid bed reactor.