



Multiphase oxygen electrodes for solid oxide electrolysis cells

Tripkovic, Dordije; Hendriksen, Peter Vang; Mogensen, Mogens Bjerg

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Tripkovic, D., Hendriksen, P. V., & Mogensen, M. B. (2017). *Multiphase oxygen electrodes for solid oxide electrolysis cells*. Abstract from 21st International Conference on Solid State Ionics, Padova, Italy.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Multiphase oxygen electrodes for solid oxide electrolysis cells

*Dordžije Tripković**, Peter Vang Hendriksen, Mogens Bjerg Mogensen

^(a) Technical University of Denmark, DTU Energy, Frederiksborgvej 399, Roskilde, Denmark

*E-mail of the Corresponding Author: djtri@dtu.dk

Solid oxide electrolysis has the potential to become the most efficient way to convert electrical into chemical energy. Solid oxide electrolysis cells (SOEC) are thus an attractive solution for converting the occasional surplus amount of electricity produced by renewable energy sources to hydrogen or syngas. This promising technology requires further maturation to become economically competitive. Among other problems, the sluggish reaction at the oxygen electrode limits maximum fuel production rate, which directly affects overall process efficiency. Recent studies published by several groups highlight the importance of dissimilar interfaces and surface chemistry in promoting oxygen electrode reaction rate, opening a new route to enhance the electrode performance. Particularly, perovskite (113)/Ruddlesden-Popper (214) interface has been reported as highly beneficial for strontium doped lanthanum cobaltite (LSC) electrodes.[1–3]

The aim of this study is to investigate the potential of 113/214 interface to improve cobalt-free electrodes such as strontium doped lanthanum ferrite (LSF). The performance of LSF₁₁₃/LSF₂₁₄ couples is assessed by electrical conductivity relaxation (ECR) of geometrically well-defined electrodes, as well as by electrochemical impedance spectroscopy (EIS) of thin film electrodes prepared by PLD. The surface of the model electrodes is deliberately modified in a controlled manner by addition of secondary phases and examined by SEM and surface-sensitive characterization techniques.

Acknowledgements

- SYNFUEL project, 4106-00006B, Innovationsfonden, for financial support;
- Bilge Yildiz (MIT) and Rainer Küngas (Haldor Topsøe A/S) for fruitful discussions.

References

- [1] M. Sase, F. Hermes, K. Yashiro, K. Sato, J. Mizusaki, T. Kawada, N. Sakai, H. Yokokawa, (La,Sr)CoO₃/(La,Sr)₂CoO₄ with PLD-layered films, J Electrochem Soc. 155 (2008) B793-B797.
- [2] E.J. Crumlin, E. Mutoro, S.-J. Ahn, G.J. la O', D.N. Leonard, A. Borisevich, M.D. Biegalski, H.M. Christen, Y. Shao-Horn, J. Phys. Chem. Lett. 1 (2010) 3149–3155.
- [3] Y. Chen, Z. Cai, Y. Kuru, W. Ma, H.L. Tuller, B. Yildiz, Adv. Energy Mater. 3 (2013) 1221–1229.