



## Wood waste in a circular economy - dynamic accounting of greenhouse gas emissions from resource cascading

Faraca, Giorgia; Tonini, Davide; Astrup, Thomas Fruergaard

*Publication date:*  
2018

*Document Version*  
Version created as part of publication process; publisher's layout; not normally made publicly available

[Link back to DTU Orbit](#)

*Citation (APA):*  
Faraca, G., Tonini, D., & Astrup, T. F. (2018). *Wood waste in a circular economy - dynamic accounting of greenhouse gas emissions from resource cascading*. Abstract from 2nd Conference on Life Cycle Assessment of Waste, Snekkersten, Denmark.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Wood waste in a circular economy - dynamic accounting of greenhouse gas emissions from resource cascading

G. Faraca\*, D. Tonini\*\*, T. F. Astrup\*

\* Department of Environmental Engineering, Technical University of Denmark, Miljøvej, Building 115, 2800 Kgs. Lyngby, Denmark

\*\* European Commission, Joint Research Center, Edificio Expo, Calle Inca Garcilaso 3, 41092 Seville, Spain

**Keywords:** wood waste management, global warming potential, dynamic LCA, cascading utilization

## Introduction

Wood waste is a valuable material with a potential for both energy and material utilization. However the circular economy approach adopted by the European Union clearly favours material recycling over energy recovery, aiming for a society where resource utilization is optimized through sequential applications, i.e. increasing the overall lifetime of the resource and minimizing the quality loss per application (“resource cascading”). The main recycling applications for wood waste are, depending on its quality, production of particleboard, floor boards, insulation materials, wood-composite materials, and pellets. The environmental performance of wood waste recycling alternatives has been previously assessed by the scientific community in terms of Global Warming Potential (GWP), although the quality of the resource and temporal aspects of the recycling systems are generally overlooked. The aim of this study is: i) to dynamically assess the GWP of greenhouse gas (GHG) emissions of alternative wood waste cascading use systems; and ii) to discuss the role of the quality of wood waste with respect to the environmental savings that can be achieved.

## Material and Methods

The functional unit is the management of 1 tonne of wood waste from Danish recycling centres. Fifteen scenarios were grouped into two sets reflecting whether different quality grades of the wood waste were kept together (WWmix) or separate (WWquality) during management. Four WWmix scenarios covered recycling to particleboard with one, two, three or four cascading cycles. Eleven WWquality scenarios covered the following recycling applications: particleboard, flooring, wood insulation board (WIB), wood plastic composites, and pellets; up to four recycling to particleboard iterations were included in the scenarios when possible. For the dynamic GWP, biogenic and fossil CO<sub>2</sub> emission profiles were calculated according to Cherubini et al. (2013); accounting of other GHGs followed the approach explained in Levasseur et al. (2011).

## Results and Conclusions

The results showed that WWquality scenarios provided larger savings than WWmix scenarios except for the pellet case; recycling to flooring and to WIB achieved the largest savings. This demonstrates that savings can be larger if i) quality-oriented recycling is chosen instead of maximizing the mass sent to recycling, ii) the recycling application is characterized by longer lifetime and/or iii) it substitutes energy-intensive materials.

## References

- Cherubini, F., Peters, G.P., Berntsen, T., Strømman, A.H., Hertwich, E. (2011). CO<sub>2</sub> emissions from biomass combustion for bioenergy: atmospheric decay and contribution to global warming. *GCB Bioenergy* 3, 413–426.
- Levasseur, A., Lesage, P., Margni, M., Deschênes, L., Samson, R. (2010). Considering time in LCA: Dynamic LCA and its application to global warming impact assessments. *Environ. Sci. Technol.* 44, 3169–3174.