



Robust Identification

Friis, Tobias; Krautwald Vesterholm, Karsten; Katsanos, Evangelos; Brincker, Rune

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Friis, T., Krautwald Vesterholm, K., Katsanos, E., & Brincker, R. (2017). *Robust Identification*. Abstract from Danish Hydrocarbon Research and Technology Centre Technology Conference 2017, Lyngby, Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Danish Hydrocarbon Research and Technology Centre Technology Conference 2017

Robust Identification

Tobias Friis, Karsten Krautwald Vesterholm, Evangelos Katsanos, Rune Brincker

Current methods for identification of dynamic behavior have certain limitations in relation to the actual behavior of offshore platforms. The limitations are mainly related to the basic assumptions of linearity and stationarity when Operational Modal Analysis (OMA) is applied. However, the majority of the structures are highly non-linear and time varying, e.g. in cases of non-linearities from friction and in case of time varying systems when emptying and filling tanks on the topside. The research project is focused at adjusting existing OMA procedures so that the mechanical characteristics of the platform can be identified under the mentioned real conditions. With the ability to identify the real dynamic behavior, the life time prediction and structural health monitoring can be carried out with far greater precision.