



Dynamic Effects of Diabatization in Distillation Columns

Bisgaard, Thomas

Publication date:
2012

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Bisgaard, T. (Author). (2012). Dynamic Effects of Diabatization in Distillation Columns. Sound/Visual production (digital), DTU Chemical Engineering.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.


Dynamic Effects of Diabatization in Distillation Columns

Paper 24, ACD 2012, Session no. 5, Thursday, 8 November 2012

Thomas Bisgaard (thbis@kt.dtu.dk)

CAPEC, Department of Chemical and Biochemical Engineering

Technical University of Denmark



Presentation Outline

Motivation

Introduction

Methodology

Dynamic Modeling

Simulation Study

Results

Conclusion

Future Work

Motivation

- Increasing focus on environmental issues and resource management
- Distillation is a widely used separation process in the industry, but it is highly energy intensive. Some key numbers for USA in 1988:
 - Distillation accounted for 4% of the total energy consumption ¹
 - Roughly 40% of the processing energy used in refining and continuous chemical processes was used for distillation
- Conventional distillation columns operate at low efficiencies ²
- Diabatic distillation columns **can** provide:
 - Higher efficiencies ³
 - Less utilities and thus less operation cost ⁴

¹ Humphrey, J.L. et al., Separation process technology, McGraw-Hill, 1997

² de Koeijer, G. et al., 2000, Int. J. Applied Thermodynamics 3(3):105–110


³ Nakaiwa, M. et al., 1998, Appl. Therm. Eng., 18(11), 1077–1087

⁴ Olujic, Z. et al., 2003, J. Chem. Technol. Biotechnol. 78(2-3):241–248


Introduction

(1/3)


- **Adiabatic operation:** Heat is added at the highest temperature (reboiler) and heat is removed at the lowest temperature (condenser), thereby preventing integration (e.g. conventional,...)
- **Diabatic operation:** Heat required to perform the separation is added and/or removed throughout the column (e.g. HIDiC, DSHE, ...)



CDiC



General HIDiC



DSHE

Introduction

(2/3)

- **Research example:** Verification of high heat transfer performance and enhanced mass transfer performance in a pilot scale (0,8 m diameter) test unit at TU Delft ⁵




⁵<http://www.ecn.nl>

Introduction

(3/3)

The Heat-Integrated Distillation Column (HIDiC)



CT: Composition Transmitter

LT: Level Transmitter

PT: Pressure Transmitter

Methodology

- Formulate generic, dynamic first-principle model describing:
 - Adiabatic distillation columns (Conventional)
 - Diabatic distillation columns (HIDiC)
- Implement model in simulator (Matlab[®])
- Formulate realistic case-studies and perform numerical simulations
- Dynamic controllability analysis and compare distillation control configurations on decentralized 2×2 system (remaining perfectly controlled)
- Perform closed-loop simulations based on single-loop control strategies

Dynamic Modeling

- Model features:
 - Binary separation of benzene-toluene with **equally sized** rectifying and stripping section
 - **Mass balances**
 - **Energy balances**
 - Liquid tray hydraulics (variable liquid tray holdups)
 - One mathematical term distinguishes configuration (adiabatic, diabatic)
- Major assumptions:
 - Equilibrium stage model
 - Lewis/Randall ideal mixture
 - **Constant pressure** in each section
 - Negligible vapor holdup compared to liquid holdup
 - Negligible changes in sensible heat
 - Homogeneous stages (ideally mixed)

Simulation Study

- Considered distillation column configurations:
 - Conventional distillation column (CDiC)
 - Heat-Integrated Distillation Column (HIDiC)

Selected model parameters:

Parameter	Value
Top purity	99% benzene
Bottom purity	95% toluene
Number of stages	20
Feed stage location	11
Feed flow	100 $\frac{\text{kmol}}{\text{h}}$
Feed benzene content	0.50
Stripping section pressure	0.1013 MPa
Hydraulic time constant	0.0042 h
Heat of vaporization	30,001.1 $\frac{\text{kJ}}{\text{kmol}}$
Relative volatility	2.317
Heat transfer rate	9,803 $\frac{\text{kJ}}{\text{h}\cdot\text{K}}$

Results - Open-loop

(1/2)

Dynamic responses to step-changes in disturbance variables.

Black curves: +5%

Gray curves: -5%


Legends:

Dashed lines: HiDiC


Dotted lines: CDiC

(Solid lines: HiDiC without condenser and reboiler)

Feed flow rate





Feed composition



Results - Open-loop

(2/2)



Controllability Analysis
 Dynamic RGA Analysis and
 SVA applied on a
 decentralized 2×2 :
HIDiC (black lines)
 and a
CDiC (gray lines).

Legends:

- (○): *LV*
- (*) : *DV*
- (□): *(L/D)V*
- (△): *LB* ←
- (▽): *L(V/B)*
- (▷): *DB*
- (◁): *D(V/B)*
- (*) : *(L/D)B*
- (◇): *(L/D)(V/B)*


Results - Closed-loop

(1/2)

- SISO controller based on an approximated First-order-Plus-Time-Delay model


- Transfer function:

$$\begin{bmatrix} dY \\ dX \end{bmatrix} = \begin{bmatrix} \frac{-0.04972}{0.1336s + 1} \\ \frac{-0.009427}{0.055465s + 1} e^{-0.0897s} \end{bmatrix} \begin{bmatrix} \frac{-0.2566}{0.5070s + 1} e^{-0.0545s} \\ \frac{0.3144}{0.4357s + 1} \end{bmatrix} \begin{bmatrix} dL \\ dB \end{bmatrix}$$



Results - Closed-loop

(2/2)



Closed-loop responses for the
HIDiC to:

$t = 0$ h: +10% step-change in
feed flow rate

$t = 15$ h: -10% step-change in
feed composition


Tuning parameters (From S-IMC):

$dL \rightarrow dY_D$:

$K_C = -0.0790$, $\tau_I = 0.5158$ h

$dB \rightarrow X_B$:

$K_C = 8.3147$, $\tau_I = 0.4357$ h



Conclusion

- A flexible and generic model have been developed to describe various diabatic distillation column configurations
- Various feasible pairings exist for the HIDiC
- Diabatization causes increased coupling between input-output variables
- In this study, among others an *LB*-structure seemed to be a promising control structure for a HIDiC

Future Work

- PhD Project initiated with the title **Operation and Design of Diabatic Distillation Processes**
- Develop detailed model framework for adiabatic and diabatic distillation processes
- Investigations, including:
 - Thermodynamics: Impact on complex thermodynamic modeling on e.g. dynamics
 - Operability: Abnormal operation, e.g. steady-state multiplicity
 - Control: Development of regulatory and multivariable control strategies

End

Thank you for your attention