



Pumping at low Reynolds numbers - the leucon sponge pump

Walther, Jens Honore; Asadzadeh, Saeed Sayed ; Larsen, Poul Scheel; Riisgård, Hans Ulrik

Publication date:
2019

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):

Walther, J. H., Asadzadeh, S. S., Larsen, P. S., & Riisgård, H. U. (2019). *Pumping at low Reynolds numbers - the leucon sponge pump*. Abstract from 72nd Annual Meeting of the APS Division of Fluid Dynamics, Seattle, United States.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Abstract Submitted
for the DFD19 Meeting of
The American Physical Society

Sorting Category: 4. (C)

Pumping at low Reynolds numbers - the leucon sponge pump¹ JENS HONORE WALTHER, SAYED SAEED ASADZADEH, POUL SCHEEL LARSEN, Technical University of Denmark, HANS ULRIK RIISGRD, University of Southern Denmark — Leuconoid sponges are filter-feeders with a complex system of branching inhalant and exhalant canals leading to and from the close-packed choanocyte chambers. Each of these choanocyte chambers holds many choanocytes that act as pumping units delivering the relatively high pressure rise needed to overcome the system pressure losses in canals and constrictions. We study these pumping units by solving the Navier-Stokes equations using computational fluid dynamics simulations. We find that each choanocyte operates as a leaky, positive displacement-type pump owing to the interaction between its beating flagellar vane and the collar, open at the base for inflow but sealed above. The leaking backflow is caused by small gaps between the vaned flagellum and the collar. The choanocyte pumps act in parallel, each delivering the same high pressure, because low-pressure and high-pressure zones in the choanocyte chamber are separated by a seal – secondary reticulum. The mechanical pump power expended by the beating flagellum is compared with the useful (reversible) pumping power received by the water flow to arrive at a typical mechanical pump efficiency of about 70 %.

¹This work was supported by a research grant no. (9278) from VILLUM FONDEN.

Prefer Oral Session
 Prefer Poster Session

Jens Honore Walther
jhw@mek.dtu.dk
No Company Provided

Date submitted: 12 Jul 2019

Electronic form version 1.4