



## Effects of zinc borate on the properties of hydrocarbon intumescent coating chars

Zeng, Ying; Erik Weinell, Claus; Dam-Johansen, Kim; Ring, Louise ; Kiil, Søren

*Publication date:*  
2019

*Document Version*  
Peer reviewed version

[Link back to DTU Orbit](#)

*Citation (APA):*

Zeng, Y., Erik Weinell, C., Dam-Johansen, K., Ring, L., & Kiil, S. (2019). *Effects of zinc borate on the properties of hydrocarbon intumescent coating chars*. 1. Abstract from Bring on the Heat China 2019 (BOTH 2019), Suzhou, China.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Effects of zinc borate on the properties of hydrocarbon intumescent coating chars

Ying Zeng\*, Claus Erik Weinell\*, Kim Dam-Johansen\*, Louise Ring‡, Søren Kiil\*,<sup>a</sup>

<sup>a</sup>: Corresponding author, email address: sk@kt.dtu.dk

\*: Department of Chemical and Biochemical Engineering, Technical University of Denmark, DTU, Building 229, 2800 Kgs. Lyngby, Denmark

‡: Hempel A/S Fire Protection-Group R&D, Carretera de Sentmenat 108, 08213 Polinyà, Spain

## Abstract

The protection of structural steel on exposure to a fire has become paramount to prevent the loss of lives and assets with increasing use of structural steel as a material to create the shape of construction projects. Structural steel loses bearing ability when its temperature exceeds 500 °C (critical temperature), and an efficient way to prolong the time before the critical temperature is reached is to use intumescent coatings. At elevated temperature, intumescent coatings swell, via a complex chemical mechanism, to a porous multicellular char layer that acts as a thermal shield protecting the underlying substrate.

The focus of the present work is the so-called hydrocarbon intumescent coatings, as it is the most challenging type used for fire scenarios in high-risk environments such as petrochemical complexes and offshore platforms. Zinc borate, an effective but suspiciously toxic compound in hydrocarbon intumescent formulations, was investigated with respect to its effects on the performance parameters (e.g. fire-resistance performance, thermal degradation, dynamic viscosity of incipient char, and char expansion and structure) of the coatings. With the understanding of the mechanism behind the positive effects of zinc borate, one can get a scientific basis for the replacement of zinc borate.